

API Testing Project – GoRest Public API (Postman + REST Assured)

1. Project Overview

Objective:

Test REST APIs provided by GoRest using **Postman** and **REST Assured (Java)**.

Learning Outcomes:

- Understanding CRUD operations on REST APIs
 - Implementing API authentication
 - Validating API responses using Postman scripts and REST Assured assertions
 - Automating API tests in Java using Maven
-

2. Base URL

<https://gorest.co.in/public/v2>

3. Authentication

Method: Bearer Token

Steps to get token:

1. Register or log in at <https://gorest.co.in/consumer/login>
2. Generate a Personal Access Token.
3. In this document two types of APIs are available Users and Posts
4. Include it in headers:

Authorization: Bearer <your_access_token>

Content-Type: application/json

Accept: application/json

Note add All these headers in every test case of postman and rest-Assured

Users API

1. Get number of users

Make get call to below API

<https://gorest.co.in/public/v2/users>

Tests to be added

Verify response code to 200

Verify number of Users are above 0

2. Create a new user

Make get post to below API

<https://gorest.co.in/public/v2/users>

Add a new header with key as Authorization value as Value as Bearer TokenValue

Body as json

```
{  
  "name": "John",  
  "gender": "male",  
  "email": "john@gmail.com",  
  "status": "active"
```

```
}
```

Note - Email id is unique so please send new email in each call.

Tests to be added

Verify response code to 201

Store generate id from response and store as a environment variable called "userid"

3. Update existing user

<https://gorest.co.in/public/v2/users/userid>

Replace url and userid from environment variables

Use put or patch to update existing user with below payload

```
{
```

```
"name": "Tom",
```

```
"gender": "male",
```

```
"email": "tom@gmail.com",
```

```
"status": "active"
```

```
}
```

Tests to be added

Verify response code to 200

Verify response contains "tom"

4. Delete Existing User

<https://gorest.co.in/public/v2/users/userid>

Replace url and userid from environment variables Use

delete for user deletion

Tests to be added

Verify response code to 204

Verify response contains message "No Content"

Posts API

Base Endpoint: <http://gorest.co.in/public/v2/posts>

5) Get All Posts

GET <http://gorest.co.in/public/v2/posts>

Tests to be added

Verify response code to 200

Get the user id and use it next api like "user_id": 8229751

6) Create Post

POST <https://gorest.co.in/public/v2/posts>

Body:

```
{  
  "user_id": 8229751,  
  "title": "My First Post",  
  "body": "This is a test post"  
}
```

Response:

```
{  
  "id": 258283,  
  "user_id": 8229751,  
  "title": "My New Post",  
  "body": "This is a test post2"  
}
```

Tests to be added

Verify response code to 200

Get the id of post and use it in further APIs

7) Update Post

PUT <https://gorest.co.in/public/v2/posts/id>

Request Payload

```
{
```

```
"user_id": 8229751,  
"title": "My New Post",  
"body": "This is a test post3"  
}
```

Response

```
{  
  "user_id": 8229751,  
  "title": "My New Post",  
  "body": "This is a test post3",  
  "id": 258283  
}
```

8) Delete Post

DELETE <https://gorest.co.in/public/v2/posts/id>

Test for 204 No Content