```xml
<?xml version="1.0" encoding="UTF-8" ?>

<Form version="1.3" maxVersion="1.9" type="org.netbeans.modules.form.forminfo.JFrameFormInfo">
  <Properties>
    <Property name="defaultCloseOperation" type="int" value="3"/>
  </Properties>
  <SyntheticProperties>
    <SyntheticProperty name="formSizePolicy" type="int" value="1"/>
    <SyntheticProperty name="generateCenter" type="boolean" value="false"/>
  </SyntheticProperties>
  <AuxValues>
    <AuxValue name="FormSettings_autoResourcing" type="java.lang.Integer" value="0"/>
    <AuxValue name="FormSettings_autoSetComponentName" type="java.lang.Boolean" value="false"/>
    <AuxValue name="FormSettings_generateFQN" type="java.lang.Boolean" value="true"/>
    <AuxValue name="FormSettings_generateMnemonicsCode" type="java.lang.Boolean" value="false"/>
    <AuxValue name="FormSettings_i18nAutoMode" type="java.lang.Boolean" value="false"/>
    <AuxValue name="FormSettings_layoutCodeTarget" type="java.lang.Integer" value="1"/>
    <AuxValue name="FormSettings_listenerGenerationStyle" type="java.lang.Integer" value="0"/>
    <AuxValue name="FormSettings_variablesLocal" type="java.lang.Boolean" value="false"/>
```

```xml
    <AuxValue name="FormSettings_variablesModifier"
type="java.lang.Integer" value="2"/>

  </AuxValues>


  <Layout>

    <DimensionLayout dim="0">

      <Group type="103" groupAlignment="0" attributes="0">

        <Group type="102" attributes="0">

            <EmptySpace min="-2" pref="56" max="-2" attributes="0"/>

            <Group type="103" groupAlignment="0" attributes="0">

                <Component id="jLabel1" min="-2" max="-2"
attributes="0"/>

                <Group type="102" alignment="0" attributes="0">

                    <Group type="103" groupAlignment="0" attributes="0">

                        <Component id="jLabel2" alignment="0" min="-2"
pref="86" max="-2" attributes="0"/>

                        <Component id="jLabel4" alignment="0" min="-2"
pref="96" max="-2" attributes="0"/>

                    </Group>

                    <EmptySpace min="-2" pref="24" max="-2"
attributes="0"/>

                    <Group type="103" groupAlignment="0" max="-2"
attributes="0">

                        <Component id="jLabel3" max="32767"
attributes="0"/>

                        <Component id="jTextField1" pref="186"
max="32767" attributes="0"/>

                        <Component id="jLabel5" alignment="0"
max="32767" attributes="0"/>

                    </Group>

                </Group>
```

```xml
                </Group>

                <EmptySpace pref="38" max="32767" attributes="0"/>

            </Group>

            <Group type="102" alignment="1" attributes="0">

                <EmptySpace max="32767" attributes="0"/>

                <Group type="103" groupAlignment="0" attributes="0">

                    <Group type="102" alignment="1" attributes="0">

                        <Component id="jButton1" min="-2" max="-2"
attributes="0"/>

                        <EmptySpace min="-2" pref="62" max="-2"
attributes="0"/>

                        <Component id="jButton2" min="-2" max="-2"
attributes="0"/>

                        <EmptySpace min="-2" pref="70" max="-2"
attributes="0"/>

                    </Group>

                    <Group type="102" alignment="1" attributes="0">

                        <Component id="jLabel6" min="-2" pref="162" max="-2"
attributes="0"/>

                        <EmptySpace min="-2" pref="51" max="-2"
attributes="0"/>

                    </Group>

                </Group>

            </Group>

        </Group>

    </DimensionLayout>

    <DimensionLayout dim="1">

      <Group type="103" groupAlignment="0" attributes="0">

        <Group type="102" alignment="0" attributes="0">

          <EmptySpace max="-2" attributes="0"/>
```

```xml
                <Component id="jLabel1" min="-2" max="-2" attributes="0"/>

                <EmptySpace min="-2" pref="40" max="-2" attributes="0"/>

                <Group type="103" groupAlignment="3" attributes="0">

                    <Component id="jLabel2" alignment="3" min="-2" max="-2"
attributes="0"/>

                    <Component id="jLabel3" alignment="3" min="-2" max="-2"
attributes="0"/>

                    <Component id="jLabel5" alignment="3" min="-2" pref="23"
max="-2" attributes="0"/>

                </Group>

                <EmptySpace min="-2" pref="34" max="-2" attributes="0"/>

                <Group type="103" groupAlignment="3" attributes="0">

                    <Component id="jLabel4" alignment="3" min="-2" max="-2"
attributes="0"/>

                    <Component id="jTextField1" alignment="3" min="-2"
max="-2" attributes="0"/>

                </Group>

                <EmptySpace type="separate" max="-2" attributes="0"/>

                <Component id="jLabel6" min="-2" max="-2" attributes="0"/>

                <EmptySpace pref="27" max="32767" attributes="0"/>

                <Group type="103" groupAlignment="3" attributes="0">

                    <Component id="jButton2" alignment="3" min="-2" max="-2"
attributes="0"/>

                    <Component id="jButton1" alignment="3" min="-2" max="-2"
attributes="0"/>

                </Group>

                <EmptySpace min="-2" pref="30" max="-2" attributes="0"/>

            </Group>

        </Group>

    </DimensionLayout>
```

```xml
        </Layout>

    <SubComponents>

      <Component class="javax.swing.JLabel" name="jLabel1">

        <Properties>

          <Property name="font" type="java.awt.Font"
editor="org.netbeans.beaninfo.editors.FontEditor">

            <Font name="Arial Unicode MS" size="18" style="0"/>

          </Property>

          <Property name="text" type="java.lang.String" value="Account
Number &amp; ATM Generate"/>

        </Properties>

      </Component>

      <Component class="javax.swing.JLabel" name="jLabel2">

        <Properties>

          <Property name="font" type="java.awt.Font"
editor="org.netbeans.beaninfo.editors.FontEditor">

            <Font name="Arial Unicode MS" size="14" style="0"/>

          </Property>

          <Property name="text" type="java.lang.String" value="Account No"/>

        </Properties>

      </Component>

      <Component class="javax.swing.JLabel" name="jLabel3">

        <Properties>

          <Property name="font" type="java.awt.Font"
editor="org.netbeans.beaninfo.editors.FontEditor">

            <Font name="Arial Unicode MS" size="14" style="1"/>

          </Property>

        </Properties>

      </Component>
```

```xml
<Component class="javax.swing.JLabel" name="jLabel4">

  <Properties>

    <Property name="font" type="java.awt.Font"
editor="org.netbeans.beaninfo.editors.FontEditor">

      <Font name="Arial Unicode MS" size="14" style="0"/>

    </Property>

    <Property name="text" type="java.lang.String" value="ATM Card
No"/>

  </Properties>

</Component>

<Component class="javax.swing.JTextField" name="jTextField1">

  <Properties>

    <Property name="font" type="java.awt.Font"
editor="org.netbeans.beaninfo.editors.FontEditor">

      <Font name="Arial Unicode MS" size="14" style="0"/>

    </Property>

  </Properties>

</Component>

<Component class="javax.swing.JButton" name="jButton1">

  <Properties>

    <Property name="font" type="java.awt.Font"
editor="org.netbeans.beaninfo.editors.FontEditor">

      <Font name="Arial Unicode MS" size="18" style="0"/>

    </Property>

    <Property name="text" type="java.lang.String" value="Home"/>

  </Properties>

  <Events>

    <EventHandler event="actionPerformed"
listener="java.awt.event.ActionListener"
```

```xml
                    parameters="java.awt.event.ActionEvent"
                    handler="jButton1ActionPerformed"/>

              </Events>

        </Component>

        <Component class="javax.swing.JButton" name="jButton2">

          <Properties>

            <Property name="font" type="java.awt.Font"
            editor="org.netbeans.beaninfo.editors.FontEditor">

                <Font name="Arial Unicode MS" size="18" style="0"/>

            </Property>

            <Property name="text" type="java.lang.String" value="UPDATE"/>

          </Properties>

          <Events>

            <EventHandler event="actionPerformed"
            listener="java.awt.event.ActionListener"
            parameters="java.awt.event.ActionEvent"
            handler="jButton2ActionPerformed"/>

          </Events>

        </Component>

        <Component class="javax.swing.JLabel" name="jLabel5">

          <Properties>

            <Property name="font" type="java.awt.Font"
            editor="org.netbeans.beaninfo.editors.FontEditor">

                <Font name="Arial Unicode MS" size="18" style="0"/>

            </Property>

          </Properties>

        </Component>

        <Component class="javax.swing.JLabel" name="jLabel6">

        </Component>

      </SubComponents>
```

```
        </Form>
```