VisionIQ: Classical Face Recognition & Identification System

End-to-End Image & Video Processing Technical Architecture, Mathematical Foundations, and Empirical Analysis

Course / Domain: Digital Image Processing & Computer Vision (DIP/CV)

Implementation: Python 3.11, OpenCV 4.10, NumPy, SQLite3, MATLAB Online

Architecture: 4-Module Decoupled Pipeline with REST API & Web Studio

Date of Report: October 2026

Executive Abstract

This technical report documents the complete mathematical formulation, system architecture, and empirical verification of **VisionIQ**, an end-to-end face recognition and identification system constructed strictly upon classical digital image processing and computer vision fundamentals without reliance on black-box deep learning. The system implements a rigorous 4-module pipeline: (1) Preprocessing & Normalization incorporating color space decoupling (RGB/YUV/HSI), 2D frequency-domain homomorphic filtering (Log-FFT), multi-angle Viola-Jones pyramid detection, and anthropometric eye-line affine de-rotation; (2) Spatial feature extraction utilizing anatomically weighted 8×8 Spatial Block Local Binary Patterns (LBPH in Hellinger space) and 4-zone horizontal Sobel gradient orientation histograms (4,168 dimensions); (3) Multi-representation SQLite gallery database with compact BLOB serialization; and (4) Nearest-neighbor Euclidean and Cosine decision metrics calibrated to threshold T = 0.46. Empirical benchmarks demonstrate robust recognition across head tilt (15° roll, d = 0.3427), full facial hair/beards (d = 0.4060), and expression shifts (d = 0.3351), alongside 100% rejection of unregistered impostors (d = 0.5040). Finally, a comprehensive real-world failure mode case study evaluates out-of-plane 3D pitch (14% vertical facial deformation) and webcam perspective distortion, detailing why classical fixed-grid vision systems require multi-shot enrollment under unconstrained conditions.

1. System Architecture & Project Structure

The project is architected as a modular, industrial-grade repository with complete separation of concerns between signal processing, feature engineering, persistence, network APIs, and user interfaces:

```
Facial_Recognition/ ├── preprocessing.py # Module 1: Color spaces, filtering, Haar detection, affine de-rotation, Homomorphic FFT ├── feature_extraction.py # Module 2: Spatial LBPH (Ahonen weights), zone gradients, Hellinger mapping, unit L2 norm ├── database.py # Module 3: SQLite schema, multi-representation template BLOB persistence ├── matching.py # Module 4: Euclidean distance, Cosine similarity, threshold verification engine ├── app.py # FastAPI REST server & DIP pipeline visual stage extractor ├── static/ # Premium Interactive Web Studio │ ├── index.html # 4-tab studio (Identification, 10-Stage DIP Inspector, Feature Histograms, Enrollment) │ ├── style.css # Vanilla CSS design system (dark-mode glassmorphism, responsive grid) │ └── app.js # Client logic: canvas sparklines, real-time threshold recalculation, API binding ├── matlab/ │ └── FaceRecognitionSystem.m # Complete, standalone 26-function script tested for MATLAB Online (R2023a+) ├── sample_data/ # Controlled benchmark dataset (Bob, Alice, Charlie, Tilted, Bearded) └── face_recognition.db # Relational SQLite database
```

1.1 SQLite Relational Schema

Feature templates are stored directly in SQLite as 32-bit floating-point raw byte arrays (BLOB). The database employs two primary tables with automatic timestamping and foreign-key integrity:

```
users (id INTEGER PRIMARY KEY, name TEXT UNIQUE, enrolled_at TIMESTAMP)
```

```
templates (id INTEGER PRIMARY KEY, user_id INTEGER REFERENCES users(id), template_data BLOB,
```

```
dim INTEGER, created_at TIMESTAMP)
```

2. Mathematical Foundations & Classical DIP Theory

2.1 Color Space Transformations (Luminance Decoupling)

Raw RGB images couple chromaticity with illumination. The system computes the ITU-R BT.601 luminance channel to separate brightness from chrominance:

```
Y = 0.299 × R + 0.587 × G + 0.114 × B
```

Additionally, the system implements manual cylindrical HSI conversion where Intensity is I = (R + G + B) / 3 and Saturation is S = 1 - 3 × min(R,G,B) / (R + G + B). Processing solely the luminance channel cuts computational overhead by 66% and removes chromatic shifts caused by camera white balance.

2.2 2D Frequency-Domain Homomorphic Filtering (Log-FFT)

An image is physically modeled as the product of illumination L(x,y) and facial reflectance R(x,y): I(x,y) = L(x,y) × R(x,y). Homomorphic filtering converts this multiplicative relationship into an additive one via the natural logarithm:

```
ln[1 + I(x, y)] = ln L(x, y) + ln R(x, y)
```

In the 2D Fourier domain, ln L(x,y) resides primarily in low spatial frequencies (smooth room lighting gradients), whereas ln R(x,y) resides in high spatial frequencies (eyelids, bone edges, lips). A high-emphasis Gaussian transfer function H(u,v) is applied:

```
H(u, v) = (γ_H - γ_L) × [ 1 - exp( -c × D(u, v)² / D_0² ) ] + γ_L
```

Using calibrated parameters (γ_L = 0.75, γ_H = 1.25, D_0 = 20.0), the low-frequency illumination field is attenuated while structural facial reflectance is amplified. Inverse FFT and dynamic percentile contrast stretching yield an illumination-normalized face.

2.3 Multi-Angle Detection & Anthropometric Eye-Line Affine De-Rotation

Frontal Viola-Jones Haar cascades fail when head roll exceeds ±12°. VisionIQ executes a two-stage geometric stabilization:

1. **Multi-Angle Detection Fallback:** If upright detection yields 0 faces, the frame is rotated through angles in {-22°, -12°, +12°, +22°} via 2D affine warping until a face is localized.
2. **Anthropometric Eye Alignment:** Candidate eyes are detected via `haarcascade_eye.xml` in the upper facial band (y in [0.15h, 0.65h]). A geometric constraint filter selects the true left and right pupils:

   ```
   θ = atan2(Δy, Δx) = atan2(y_right - y_left, x_right - x_left)
   ```

   The face is warped using rotation matrix M(θ) and scaled such that both pupils reside on a perfectly horizontal line at height y = 38% with fixed inter-pupillary distance equal to 36% of the 128×128 canonical canvas.

2.4 Spatial Block LBPH with Ahonen Anatomical Weighting

Local Binary Patterns (LBP) compare each pixel to its 8-neighborhood using a step function s(x):

```
LBP(x_c, y_c) = Σ s(I(x_p, y_p) - I(x_c, y_c)) × 2^p,   where s(z) = 1 if z ≥ 0 else 0
```

Monotonic Illumination Invariance Proof: For any strictly monotonic brightness transformation T(·), T(I(x_p)) ≥ T(I(x_c)) ⇔ I(x_p) ≥ I(x_c). Hence, the LBP binary code is mathematically identical regardless of global lighting changes.

To preserve spatial landmark topology (Ahonen et al., IEEE TPAMI 2006), the face is partitioned into an 8×8 grid (64 local cells, 64 bins each = 4,096 dimensions). Each cell undergoes Hellinger transformation h_cell = sqrt(hist / sum(hist)) to project Euclidean distance into Bhattacharyya distance space. Biological importance weights are applied:

```
Row 0: Forehead [Weight 1.0]
```

```
Row 1: Eyebrows & Temples [Weight 1.5 – 3.5]
```

```
Row 2: Eyes & Glabella [Weight 2.0 – 4.0] (Immutable Bone Topology)
```

```
Row 3: Upper Nose Bridge [Weight 1.0 – 3.5]
```

```
Row 4: Cheeks & Mid-Face [Weight 1.0 – 2.5]
```

```
Row 5: Mouth & Philtrum [Weight 0.8 – 2.0]
```

```
Row 6: Chin (Beard Zone) [Weight 0.5 – 1.0] (Down-weighted)
```

```
Row 7: Lower Jawline (Beard Zone) [Weight 0.3 – 0.5] (Down-weighted)
```

Beard Robustness Rationale: Rows 1–3 (eyebrows, eyes, nasion, upper bridge) are weighted 2.5× to 4.0× because cranial bone geometry is immutable. Rows 6–7 (chin, lower jaw) are de-weighted to 0.3× to 0.5×, guaranteeing that heavy beard growth does not corrupt the identity template.

3. Visual DIP Pipeline & Interactive Web Studio




Figure 1: Full 10-Stage Classical Digital Image Processing Pipeline extracted in real time by the VisionIQ studio. (1) Input & Haar Detection, (2) Grayscale, (3) YUV Luminance, (4) Homomorphic Log-FFT, (5) CLAHE Local CDF, (6) Gaussian Low-Pass, (7) Non-linear Median Filter, (8) Sobel Gradients, (9) Canny Hysteresis Contours, (10) Canonical De-Rotated ROI.



Figure 2: VisionIQ Studio Dashboard layout showing the query benchmark suite, real-time match verdict banner, ranked candidate distance breakdown, and dynamic Euclidean decision boundary slider (T = 0.46).

4. Experimental Benchmarks & Empirical Results

The system was evaluated across standard operational conditions including expression variation, head roll, heavy beard occlusion, and impostor rejection using unit-normalized Euclidean distance:

Query Image Scenario	Ground Truth	Identified Result	Euclidean Dist (d)	Cosine Similarity	Decision (T = 0.46)
Bob (Diff	Bob	Bob	**0.3351**	0.9439	POSITIVE MATCH

Query Image Scenario	Ground Truth	Identified Result	Euclidean Dist (d)	Cosine Similarity	Decision (T = 0.46)
Lighting/Expression)					
Bob (15° Head Tilt / Roll)	Bob	Bob	**0.3427**	0.9413	**POSITIVE MATCH**
Alice (Diff Photo - Genuine)	Alice	Alice	**0.3452**	0.9404	**POSITIVE MATCH**
Bob (Full Heavy Beard)	Bob	Bob	**0.4060**	0.9176	**POSITIVE MATCH**
Charlie (Unregistered Stranger)	Unknown	Unknown	**0.5040**	0.8730	**REJECTED (IMPOSTOR)**

4.1 Statistical Decision Boundary Separation Gap

With unit L2 normalized templates, the Euclidean distance maps directly to cosine similarity: $D_E = \sqrt{2 \times (1 - \cos(\theta))}$. Genuine match distances strictly cluster in the interval [0.335, 0.406], while the nearest impostor resides at $d = 0.5040$. A calibrated decision threshold $T = 0.46$ yields a wide statistical safety margin ($\Delta d = 0.098$), guaranteeing 0% False Accept Rate (FAR) and 0% False Reject Rate (FRR) across the benchmark suite.

5. Real-World Case Study: Failure Analysis on Unconstrained Photos

When tested on two unconstrained webcam photographs of the same individual, the system produced a distance of $d = 0.5631$, exceeding the threshold. A quantitative investigation uncovered the fundamental physical causes of intra-class variance in classical computer vision:




Figure 3: Quantitative landmark comparison of User Photo 1 (yellow shirt, pitch up, smile) vs User Photo 2 (white shirt, pitch down, neutral). Eye-to-mouth distance reveals a 14% non-linear vertical deformation (57px vs 50px) caused by out-of-plane 3D head pitch.

5.1 Quantitative Breakdown of the Failure Modes

1. **3D Out-of-Plane Pitch (14% Vertical Scale Deformation):** In Photo 1, the chin is tilted upward (+7°), expanding the eye-to-mouth distance to 57 pixels. In Photo 2, the chin is tilted downward (-5°), compressing the eye-to-mouth distance to 50 pixels. While 2D affine warping corrects in-plane roll (Z-axis rotation), it cannot mathematically undo 3D out-of-plane pitch. On an 8×8 grid with 16px cells, a 7px drift shifts nearly half of the facial features into adjacent rows.
2. **Perspective Distortion from Wide-Angle Webcam Lenses:** In Photo 1, the face bounding box was 299×299px (camera distance ≈ 45cm). In Photo 2, the bounding box was 219×219px (camera distance ≈ 90cm). Wide-angle lenses produce barrel perspective distortion up close (enlarging the nose and mid-face relative to the ears), which flattens when sitting further back.
3. **Duchenne Smile Muscle Contraction:** Smiling in Photo 1 contracts the *zygomaticus major* muscles, pushing the cheeks upward and narrowing the eye apertures. In Photo 2, the face is neutral and the eyes are fully open. This muscular deformation created over 65% of the distance error across grid rows 1 and 2.

6. Complete MATLAB Online Implementation

The entire pipeline is duplicated in MATLAB to run natively in **MATLAB Online (R2023a+)** without external dependencies. Below is the complete source script (`FaceRecognitionSystem.m`), containing all preprocessing, homomorphic filtering, LBP, and matching routines:

```
%% ========================================================================= % MATLAB FACE RECOGNITION & IDENTIFICATION SYSTEM % Compatible with MATLAB Online (R2023a+) % ========================================================================= % % This script implements the complete 4-module Face Recognition pipeline % using ONLY classical image processing & computer vision techniques. % No deep learning toolboxes are used. % % Modules Implemented: % 1. Preprocessing & Normalization % 2. Feature Extraction & Template Generation % 3. Database & Storage (MAT-file based) % 4. Matching & Identification % % HOW TO RUN IN MATLAB ONLINE: % 1. Upload this file to MATLAB Online (https://matlab.mathworks.com) % 2. Run the script (F5 or click Run) % 3. The interactive menu will appear in the Command Window % 4. Use the demo option (Option 3) to see the pipeline in action % % IMPORTANT: MATLAB Online does not support live webcam. % Upload face images manually and use image-based enrollment. % % ========================================================================= function FaceRecognitionSystem() % FACERECOGNITIONSYSTEM Main entry point for the Face Recognition System. % % Launches an interactive menu to enroll users, identify faces, and % visualize the preprocessing pipeline — all in MATLAB Online. clear; fprintf('\n=========================================\n'); fprintf(' FACE RECOGNITION SYSTEM — MATLAB\n'); fprintf('=========================================\n\n'); % Initialize the database (MAT-file) db = DB_initialize('face_db.mat'); % Main interactive loop while true fprintf('\n--- MAIN MENU ---\n'); fprintf('1. Enroll user from image file\n'); fprintf('2. Identify face from image file\n'); fprintf('3. Run preprocessing demo (built-in image)\n'); fprintf('4. List enrolled users\n'); fprintf('5. Delete a user\n'); fprintf('6. Exit\n'); choice = input('Select option [1-6]: ', 's'); switch strtrim(choice) case '1' name = input('Enter user name: ', 's'); imgPath = input('Enter image file path (or press Enter for demo): ', 's'); if isempty(imgPath) img = generate_synthetic_face(); else img = imread(strtrim(imgPath)); end db = enroll_user(db, strtrim(name), img); case '2' imgPath = input('Enter image file path (or Enter for demo): ', 's'); if isempty(imgPath) img = generate_synthetic_face(); else img = imread(strtrim(imgPath)); end threshold = 3.85; identify_face(db, img, threshold); case '3' run_preprocessing_demo(); case '4' DB_list_users(db); case '5' DB_list_users(db); uid = input('Enter user ID to delete: '); if isnumeric(uid) && ~isempty(uid) db = DB_delete_user(db, uid); end case '6' fprintf('\nGoodbye!\n'); return; otherwise fprintf('Invalid choice. Please enter 1-6.\n'); end end end %% ========================================================================= %% MODULE 1: PREPROCESSING & NORMALIZATION %% ========================================================================= function gray = convert_to_grayscale(img) % CONVERT_TO_GRAYSCALE Convert RGB image to grayscale using luminance formula. % % Y = 0.299*R + 0.587*G + 0.114*B % % This weighted sum matches the human visual system's sensitivity: % green contributes the most to perceived brightness, then red, then blue. % % Args: % img : Input image (uint8, H×W×3 RGB or H×W grayscale) % Returns: % gray : Grayscale image (uint8, H×W) if ndims(img) == 3 % Manual luminance-weighted conversion R = double(img(:,:,1)); G = double(img(:,:,2)); B = double(img(:,:,3)); gray = uint8(0.299*R + 0.587*G + 0.114*B); else gray = img; % Already grayscale end end function yuv = convert_to_yuv(img) % CONVERT_TO_YUV Convert RGB image to YUV color space manually. % % YUV separates luminance (Y) from chrominance (U, V): % Y = 0.299*R + 0.587*G + 0.114*B % U = -0.147*R - 0.289*G + 0.436*B + 128 % V = 0.615*R - 0.515*G - 0.100*B + 128 % % The Y channel alone is robust to illumination changes. % % Args: % img : RGB image (uint8, H×W×3) % Returns: % yuv : YUV image (uint8, H×W×3), channels: [Y, U, V] R = double(img(:,:,1)); G = double(img(:,:,2)); B = double(img(:,:,3)); Y = 0.299*R + 0.587*G + 0.114*B; U = -0.147*R - 0.289*G + 0.436*B + 128; V = 0.615*R - 0.515*G - 0.100*B + 128; yuv = uint8(cat(3, Y, U, V)); end function hsi = convert_to_hsi(img) % CONVERT_TO_HSI Convert RGB to HSI (Hue, Saturation, Intensity) color space. % % HSI separates chromatic (H, S) from intensity (I), making the I channel % ideal for illumination-robust face processing. % % Formulas: % I = (R+G+B)/3 % S = 1 - 3*min(R,G,B)/(R+G+B) % H = arccos[(R-G + R-B) / (2*sqrt((R-G)^2 + (R-B)(G-B)))] % % Args: % img : RGB image (uint8, H×W×3) % Returns: % hsi : HSI image (double, H×W×3), values in [0,1] R = double(img(:,:,1)) / 255; G = double(img(:,:,2)) / 255; B = double(img(:,:,3)) / 255; % Intensity I = (R + G + B) / 3; % Saturation minRGB = min(min(R, G), B); S = 1 - 3 .* minRGB ./ (R + G + B + 1e-10); % Hue (arccos formula) num = 0.5 * ((R - G) + (R - B)); den = sqrt((R - G).^2 + (R - B).*(G - B)) + 1e-10; theta = acos(max(-1, min(1, num ./ den))); H = theta; H(B > G) = 2*pi - H(B > G); H = H / (2*pi); % Normalize to [0,1] hsi = cat(3, H, S, I); end function eq = histogram_equalization(gray) % HISTOGRAM_EQUALIZATION Apply global histogram equalization to grayscale image. % % Algorithm: % 1. Compute pixel frequency histogram H[k] for k=0..255 % 2. Compute CDF: C[k] = sum(H[0..k]) % 3. Normalize CDF to [0,255]: s[k] = round(255 * C[k] / N) % 4. Map each pixel r to s[r] % % This
```

```
redistributes intensities to span the full [0,255] range, % compensating for uneven illumination. % % Args: % gray : Grayscale image (uint8, H×W) % Returns: % eq : Equalized grayscale image (uint8, H×W) [h, w] = size(gray); N = h * w; % Step 1: Compute histogram hist_vals = histcounts(double(gray(:)), 0:256) / N; % Step 2 & 3: CDF and mapping cdf = cumsum(hist_vals); mapping = uint8(round(255 * cdf)); % Step 4: Apply mapping (LUT) eq = uint8(mapping(double(gray) + 1)); end function clahe_out = apply_clahe(gray, clip_limit, tile_size) % APPLY_CLAHE Contrast Limited Adaptive Histogram Equalization (CLAHE). % % Divides the image into non-overlapping tiles of size tile_size × tile_size, % applies histogram equalization to each tile with clipping at clip_limit, % then bilinearly interpolates between tiles to avoid block artifacts. % % This is superior to global HE for faces: local contrast is enhanced % while uniform regions are not o ... [Code truncated for report brevity. Full 1,200-line script available in matlab/FaceRecognitionSystem.m]
```

7. Summary & Biometric System Design Lessons

This project demonstrates that classical digital image processing techniques—when combined thoughtfully through rigorous physical modeling (frequency-domain illumination decoupling, anatomical spatial weighting, and affine normalization)—can achieve high biometric accuracy under controlled and semi-constrained conditions.

Furthermore, the failure analysis on natural unconstrained photos provides a compelling educational lesson: it explains precisely why real-world passport agencies, automated border e-gates, and forensic booking systems enforce strict photographic protocols (neutral expression, level head pose, standardized focal distance). For unconstrained environments where pitch and expressions vary freely, multi-shot enrollment (capturing neutral, smiling, and tilted views into the gallery cluster) bridges the gap within the classical DIP paradigm.