



Dynamic programming



•Longest Common Subsequence

Dynamic programming

- It is used, when the solution can be recursively described in terms of solutions to subproblems (*optimal substructure*)
- Algorithm finds solutions to subproblems and stores them in memory for later use
- More efficient than “*brute-force methods*”, which solve the same subproblems over and over again



The longest common subsequence(LCS) problem

- The longest common subsequence(LCS) problem is a classic and well studied problem in computer science with extensive applications in diverse areas ranging from spelling error corrections to molecular biology.
- A subsequence of a string is obtained by deleting zero or more symbols of that string.
- The longest common subsequence problem for two strings, is to find a common subsequence in both strings, having maximum possible length.
- Problem “LCS”. LCS Problem for 2 Strings. Given strings X and Y , compute the Longest Common Subsequence of X and Y .

Longest Common Subsequence (LCS)

Application: comparison of two DNA strings

Ex: $X = \{A B C B D A B\}$, $Y = \{B D C A B A\}$

Longest Common Subsequence:

$X = A \text{ **B** } \text{ **C** } \text{ **B** } D \text{ **A** } B$

$Y = \text{ **B** } D \text{ **C** } A \text{ **B** } \text{ **A** }$

- Brute force algorithm would compare each subsequence of X with the symbols in Y

LCS Algorithm

- if $|X| = m$, $|Y| = n$, then there are 2^m subsequences of x ; we must compare each with Y (n comparisons)
- So the running time of the brute-force algorithm is $O(n 2^m)$
- Notice that the LCS problem has *optimal substructure*: solutions of subproblems are parts of the final solution.
- Subproblems: “find LCS of pairs of *prefixes* of X and Y ”

LCS Algorithm

- First we'll find the length of LCS. Later we'll modify the algorithm to find LCS itself.
- Define X_i , Y_j to be the prefixes of X and Y of length i and j respectively
- Define $c[i,j]$ to be the length of LCS of X_i and Y_j
- Then the length of LCS of X and Y will be $c[m,n]$

$$c[i, j] = \begin{cases} c[i-1, j-1] + 1 & \text{if } x[i] = y[j], \\ \max(c[i, j-1], c[i-1, j]) & \text{otherwise} \end{cases}$$

LCS recursive solution

$$c[i, j] = \begin{cases} c[i-1, j-1] + 1 & \text{if } x[i] = y[j], \\ \max(c[i, j-1], c[i-1, j]) & \text{otherwise} \end{cases}$$

- We start with $i = j = 0$ (empty substrings of x and y)
- Since X_0 and Y_0 are empty strings, their LCS is always empty (i.e. $c[0, 0] = 0$)
- LCS of empty string and any other string is empty, so for every i and j : $c[0, j] = c[i, 0] = 0$

LCS recursive solution

$$c[i, j] = \begin{cases} c[i-1, j-1] + 1 & \text{if } x[i] = y[j], \\ \max(c[i, j-1], c[i-1, j]) & \text{otherwise} \end{cases}$$

- When we calculate $c[i, j]$, we consider two cases:
- **First case:** $x[i] = y[j]$: one more symbol in strings X and Y matches, so the length of LCS X_i and Y_j equals to the length of LCS of smaller strings X_{i-1} and Y_{j-1} , plus 1

LCS recursive solution

$$c[i, j] = \begin{cases} c[i-1, j-1] + 1 & \text{if } x[i] = y[j], \\ \max(c[i, j-1], c[i-1, j]) & \text{otherwise} \end{cases}$$

- **Second case:** $x[i] \neq y[j]$
- As symbols don't match, our solution is not improved, and the length of $\text{LCS}(X_i, Y_j)$ is the same as before (i.e. maximum of $\text{LCS}(X_i, Y_{j-1})$ and $\text{LCS}(X_{i-1}, Y_j)$)

Why not just take the length of $\text{LCS}(X_{i-1}, Y_{j-1})$?

LCS Length Algorithm

LCS-Length(X, Y)

1. $m = \text{length}(X)$ // get the # of symbols in X
2. $n = \text{length}(Y)$ // get the # of symbols in Y
3. for $i = 1$ to m $c[i,0] = 0$ // special case: Y_0
4. for $j = 1$ to n $c[0,j] = 0$ // special case: X_0
5. for $i = 1$ to m // for all X_i
6. for $j = 1$ to n // for all Y_j
7. if ($X_i == Y_j$)
8. $c[i,j] = c[i-1,j-1] + 1$
9. else $c[i,j] = \max(c[i-1,j], c[i,j-1])$
10. return c

LCS Example

- We'll see how LCS algorithm works on the following example:
- $X = \text{A B C B}$
- $Y = \text{B D C A B}$

What is the Longest Common Subsequence of X and Y?

$\text{LCS}(X, Y) = \text{B C B}$

$X = \text{A } \mathbf{B} \quad \mathbf{C} \quad \mathbf{B}$

$Y = \quad \mathbf{B} \text{ D } \mathbf{C} \text{ A } \mathbf{B}$

LCS Example (0)

ABCB
BDCAB

		j	0	1	2	3	4	5
			Y _j	B	D	C	A	B
i								
0	X _i							
1	A							
2	B							
3	C							
4	B							

$X = \text{ABCB}; \quad m = |X| = 4$

$Y = \text{BDCAB}; \quad n = |Y| = 5$

Allocate array $c[5,4]$

LCS Example (1)

ABCB
BDCAB

		j	0	1	2	3	4	5
			Y _j	B	D	C	A	B
i	X _i							
0			0	0	0	0	0	0
1	A		0					
2	B		0					
3	C		0					
4	B		0					

for i = 1 to m c[i,0] = 0
for j = 1 to n c[0,j] = 0

LCS Example (2)

ABCB
BDCAB

		j	0	1	2	3	4	5
		Yj		B	D	C	A	B
i	Xi							
0			0	0	0	0	0	0
1	A	0	0	0				
2	B	0						
3	C	0						
4	B	0						

if ($X_i == Y_j$)
 $c[i,j] = c[i-1,j-1] + 1$
 else $c[i,j] = \max(c[i-1,j], c[i,j-1])$

LCS Example (3)

ABCB
BDCAB

		j	0	1	2	3	4	5
			Y _j	B	D	C	A	B
i	X _i	0	0	0	0	0	0	0
1	A	0	0	0	0			
2	B	0						
3	C	0						
4	B	0						

if ($X_i == Y_j$)
 $c[i,j] = c[i-1,j-1] + 1$
 else $c[i,j] = \max(c[i-1,j], c[i,j-1])$

LCS Example (4)

ABCB
BDCAB

		j	0	1	2	3	4	5
			Y _j	B	D	C	A	B
i	X _i	0	0	0	0	0	0	0
1	A	0	0	0	0	0	1	
2	B	0						
3	C	0						
4	B	0						

if ($X_i == Y_j$)
 $c[i,j] = c[i-1,j-1] + 1$
 else $c[i,j] = \max(c[i-1,j], c[i,j-1])$

LCS Example (5)

ABCB
BDCAB

		j	0	1	2	3	4	5
			Y _j	B	D	C	A	B
i								
0	X _i		0	0	0	0	0	0
1	A		0	0	0	0	1	1
2	B		0					
3	C		0					
4	B		0					

if ($X_i == Y_j$)
 $c[i,j] = c[i-1,j-1] + 1$
 else $c[i,j] = \max(c[i-1,j], c[i,j-1])$

LCS Example (6)

ABCB
BDCAB

i	j	Y _j	0	1	2	3	4	5
				B	D	C	A	B
0	X _i		0	0	0	0	0	0
1	A		0	0	0	0	1	1
2	B		0	1				
3	C		0					
4	B		0					

if ($X_i == Y_j$)
 $c[i,j] = c[i-1,j-1] + 1$
 else $c[i,j] = \max(c[i-1,j], c[i,j-1])$

LCS Example (7)

ABCB
BD CAB

		j	0	1	2	3	4	5
i		Y _j		B	D	C	A	B
	0	X _i	0	0	0	0	0	0
	1	A	0	0	0	0	1	1
	2	B	0	1	1	1	1	
	3	C	0					
	4	B	0					

if ($X_i == Y_j$)
 $c[i,j] = c[i-1,j-1] + 1$
 else $c[i,j] = \max(c[i-1,j], c[i,j-1])$

LCS Example (8)

ABCB
BDCAB

i	j	Y _j						
			0	1	2	3	4	5
				B	D	C	A	B
0	X _i		0	0	0	0	0	0
1	A		0	0	0	0	1	1
2	B		0	1	1	1	1	2
3	C		0					
4	B		0					

if ($X_i == Y_j$)
 $c[i,j] = c[i-1,j-1] + 1$
 else $c[i,j] = \max(c[i-1,j], c[i,j-1])$

LCS Example (10)

ABCB

BD CAB

i	j						
		0	1	2	3	4	5
	Y _j		B	D	C	A	B
0	X _i	0	0	0	0	0	0
1	A	0	0	0	0	1	1
2	B	0	1	1	1	1	2
3	C	0	↓	↓			
			1	→ 1			
4	B	0					

if ($X_i == Y_j$)
 $c[i,j] = c[i-1,j-1] + 1$
 else $c[i,j] = \max(c[i-1,j], c[i,j-1])$

LCS Example (11)

ABCB
BD CAB

i	j	Y _j	0	1	2	3	4	5
				B	D	C	A	B
0	X _i		0	0	0	0	0	0
1	A		0	0	0	0	1	1
2	B		0	1	1	1	1	2
3	C		0	1	1	2		
4	B		0					

if ($X_i == Y_j$)
 $c[i,j] = c[i-1,j-1] + 1$
 else $c[i,j] = \max(c[i-1,j], c[i,j-1])$

LCS Example (12)

ABCB
BDCAB

		j	0	1	2	3	4	5
i		Yj	B	D	C	A	B	
		Xi						
0			0	0	0	0	0	
1	A		0	0	0	1	1	
2	B		0	1	1	1	2	
3	C		0	1	1	2	2	
4	B		0					

if ($X_i == Y_j$)
 $c[i,j] = c[i-1,j-1] + 1$
 else $c[i,j] = \max(c[i-1,j], c[i,j-1])$

LCS Example (13)

ABCB

BDCAB

i	j	Y _j	0	1	2	3	4	5
				B	D	C	A	B
0	X _i		0	0	0	0	0	0
1	A		0	0	0	0	1	1
2	B		0	1	1	1	1	2
3	C		0	1	1	2	2	2
4	B		0	1				

$\text{if } (X_i == Y_j)$
 $\quad c[i,j] = c[i-1,j-1] + 1$
 $\text{else } c[i,j] = \max(c[i-1,j], c[i,j-1])$

LCS Example (14)

ABCB
BD CAB

i	j	Y _j	0	1	2	3	4	5
				B	D	C	A	B
0	X _i		0	0	0	0	0	0
1	A		0	0	0	0	1	1
2	B		0	1	1	1	1	2
3	C		0	1	1	2	2	2
4	B		0	1	1	2	2	


if ($X_i == Y_j$)
 $c[i,j] = c[i-1,j-1] + 1$
 else $c[i,j] = \max(c[i-1,j], c[i,j-1])$

LCS Example (15)

ABCB
BDCAB

i	j	Y _j	0	1	2	3	4	5
				B	D	C	A	B
0	X _i		0	0	0	0	0	0
1	A		0	0	0	0	1	1
2	B		0	1	1	1	1	2
3	C		0	1	1	2	2	2
4	B		0	1	1	2	2	3

if ($X_i == Y_j$)
 $c[i,j] = c[i-1,j-1] + 1$
 else $c[i,j] = \max(c[i-1,j], c[i,j-1])$



LCS Algorithm Running Time

- LCS algorithm calculates the values of each entry of the array $c[m,n]$
- So what is the running time?
- $O(m*n)$
- since each $c[i,j]$ is calculated in constant time, and there are $m*n$ elements in the array

LCS Algorithm Running Time

- LCS algorithm calculates the values of each entry of the array $c[m,n]$
- So what is the running time?

$O(m*n)$

since each $c[i,j]$ is calculated in constant time, and there are $m*n$ elements in the array

How to find actual LCS

- So far, we have just found the *length* of LCS, but not LCS itself.
- We want to modify this algorithm to make it output Longest Common Subsequence of X and Y


Each $c[i,j]$ depends on $c[i-1,j]$ and $c[i,j-1]$
or $c[i-1,j-1]$

For each $c[i,j]$ we can say how it was acquired:

For example, here

$$c[i,j] = c[i-1,j-1] + 1 = 2 + 1 = 3$$

2	2
2	3



How to find actual LCS - continued

- Remember that

$$c[i, j] = \begin{cases} c[i-1, j-1] + 1 & \text{if } x[i] = y[j], \\ \max(c[i, j-1], c[i-1, j]) & \text{otherwise} \end{cases}$$

- So we can start from $c[m, n]$ and go backwards
- Whenever $c[i, j] = c[i-1, j-1] + 1$, remember $x[i]$ (because $x[i]$ is a part of LCS)
- When $i=0$ or $j=0$ (i.e. we reached the beginning), output remembered letters in reverse order

Finding LCS

		j	0	1	2	3	4	5
i		Yj						
			B	D	C	A	B	
0	Xi		0	0	0	0	0	0
1	A		0	0	0	0	1	1
2	B		0	1	1	1	1	2
3	C		0	1	1	2	2	2
4	B		0	1	1	2	2	3


Finding LCS (2)

		j	0	1	2	3	4	5
		Yj		B	D	C	A	B
i	Xi							
0			0	0	0	0	0	0
1	A		0	0	0	0	1	1
2	B		0	1	1	1	1	2
3	C		0	1	1	2	2	2
4	B		0	1	1	2	2	3

LCS (reversed order): **B C B**


LCS (straight order): **B C B**

(this string turned out to be a palindrome)




When are Dynamic Programming Algorithms Efficient?

- The running time of any dynamic programming algorithm is a function of two things:
 - (1) number of partial solutions we must keep track of
 - (2) how long it take to evaluate each partial solution.



Conclusion

- LCS problem for more than two strings have extensive applications e.g. in molecular biology.
- It would be interesting to see whether our techniques can be extended for LCS problems involving more than two strings or variants thereof (e.g. constrained LCS, rigid LCS), motivated by practical applications in molecular biology.




Problem statement

- Given 3 strings **X**, **Y** and **Z**, the task is to find the longest common sub-sequence in all three given sequences.



Thank You






Question

[Q] How many subsequences of X are there? What would be the complexity of a LCS algorithm that checks for every subsequence of X if it is a subsequence of Y ?


[Sol] If m is the length of X , there are 2^m subsequences as, for each element, you can choose whether to include it or not (note that the empty sequence and X itself are also subsequences).

If n is the length of Y , then a brute-force algorithm would run in $O(n \times 2^m)$ complexity.



Question

1. We want to characterize a LCS in terms of LCS of subproblems. Given a solution Z , state the conditions under which Z is a LCS of X and Y (based on the relations between Z and subproblems of LCS (X, Y)).
2. Prove the LCS has an optimal sub-structure?
3. Using the characterization of question, what would be the complexity of a direct recursive implementation for finding the LCS of X and Y ? Prove that the LCS problem has sub-problem superposition.
4. Does every sub-problem needs to be computed? Propose a solution to compute only the required sub-problems. Does it change the complexity?



Question

5. Propose a way to store the length of the LCS of sub-problems so that we do not need to re-compute them. In which order do you need to solve the sub-problems? Test it by computing the LCS of $\langle 1, 0, 1, 0, 0, 1, 0, 1 \rangle$ and $\langle 0, 1, 1, 1, 1, 0, 1, 0 \rangle$.
6. Write the corresponding algorithm for finding the LCS of two sequences. The algorithm with the previous question, we only know the maximum length of a common subsequence of X and Y . What else do you need to store in order to actually exhibit a LCS? Modify your algorithm so that it returns a LCS of X and Y .