Experiment-6

Aim: Exercise on updating records in table. Create Client_master with the following fields (ClientNO, Name, Address, City, State, bal_due)

- Create database and use database

Code:

```
CREATE DATABASE ASSIGNMENT_6;

USE ASSIGNMENT_6;
```

➢ **Explanation:**

- This command creates a new database named ASSIGNMENT_6 where tables and records will be stored.
- This command selects the ASSIGNMENT_6 database so that all further operations will be performed inside this database.

- **Create table**

Code:

```
CREATE TABLE Client_master (
ClientNO VARCHAR(10) PRIMARY KEY,
Name VARCHAR(50),
Address VARCHAR(100),
City VARCHAR(50),
State VARCHAR(50),
bal_due INT
);
```

➢ **Explanation:**

- This command creates a table named Client_master with fields like client number, name, address, city, state, and balance due.

(a) Insert five records

Code:

```
INSERT INTO Client_master VALUES ('C101','Amit','Street 1','Delhi','Delhi',6000);

INSERT INTO Client_master VALUES ('C102','Ravi','Street 2','Mumbai','Maharashtra',3000);

INSERT INTO Client_master VALUES ('C123','Sita','Street 3','Chennai','Tamil Nadu',4500);

INSERT INTO Client_master VALUES ('C104','Neha','Street 4','Kolkata','West Bengal',7000);

INSERT INTO Client_master VALUES ('C105','Raj','Street 5','Pune','Maharashtra',2000);
```

- **Explanation:**
- The INSERT INTO statement is used to add multiple records into the table.

(b) Find the names of clients whose bal_due> 5000 .

Code:

```
SELECT Name
FROM Client_master
WHERE bal_due > 5000;
```

- **Explanation**
- The WHERE clause filters clients whose balance due is greater than 5000.

Output:

Result Grid | Filter

Name
Amit
Neha

(c) Change the bal_due of ClientNO " C123" to Rs. 5100

Code:

```
UPDATE Client_master
SET bal_due = 5100
WHERE ClientNO = 'C123';
```

- **Explanation:**
- The UPDATE statement modifies existing data. Here, it updates the balance due of client C123 to 5100.

(d) Change the name of Client_master to Client12.

Code:

```
ALTER TABLE Client_master
RENAME TO Client12;
```

- **Explanation:**
- The ALTER TABLE command is used to rename the table from Client_master to Client12.

(e) Display the bal_due heading as “BALANCE”

Code:

```
SELECT bal_due AS BALANCE
FROM Client12;
```

- **Explanation:**
- The AS keyword is used to rename the column heading temporarily. Here, bal_due is displayed as BALANCE.

Output:

Result Grid | Filter Rows:

BALANCE
6000
3000
7000
2000
5100