

EXPERIMENT – 6

AIM: To create a stored procedure `transfer_employee(emp_id, new_dept_id)` with validation and error handling, and to implement database triggers for salary validation and audit logging. The procedure and triggers are tested using normal and edge-case inputs.

SOURCE CODE:

USING EXPERIMENT – 3 DATABASE

SQL QUERIES:

STORED PROCEDURE: `transfer_employee`

The procedure will:

1. Check whether the employee exists.
2. Check whether the new department exists.
3. Check whether the employee is already in that department.
4. Transfer the employee.
5. Handle errors using `SQLEXCEPTION`.
6. Roll back the transaction if an error occurs.

DELIMITER //

```
CREATE PROCEDURE transfer_employee(
    IN p_emp_id INT,
    IN p_new_dept_id INT
)
BEGIN
    DECLARE v_employee_count INT DEFAULT 0;
    DECLARE v_department_count INT DEFAULT 0;
    DECLARE v_current_dept INT DEFAULT 0;

    -- Error handler
    DECLARE EXIT HANDLER FOR SQLEXCEPTION
    BEGIN
        ROLLBACK;
        SELECT 'Error occurred. Transaction rolled back.' AS
message;
        END;

    START TRANSACTION;
```

```

-- Check whether employee exists
SELECT COUNT(*)
  INTO v_employee_count
  FROM Employee
  WHERE emp_id = p_emp_id;

IF v_employee_count = 0 THEN
  ROLLBACK;
  SELECT 'Error: Employee does not exist.' AS message;

ELSE

  -- Check whether department exists
  SELECT COUNT(*)
    INTO v_department_count
    FROM Department
    WHERE dept_id = p_new_dept_id;

  IF v_department_count = 0 THEN
    ROLLBACK;
    SELECT 'Error: Department does not exist.' AS
message;

  ELSE

    -- Get current department
    SELECT dept_id
      INTO v_current_dept
      FROM Employee
      WHERE emp_id = p_emp_id;

    -- Check if already in requested department
    IF v_current_dept = p_new_dept_id THEN
      ROLLBACK;
      SELECT 'Error: Employee is already in this
department.'
        AS message;

    ELSE

      -- Transfer employee
      UPDATE Employee
      SET dept_id = p_new_dept_id
      WHERE emp_id = p_emp_id;

      COMMIT;

      SELECT
        'Employee transferred successfully.'
        AS message;

```

```

        END IF;

    END IF;

END IF;

END //

DELIMITER ;

```

TESTING THE STORED PROCEDURE

```

SELECT
    e.emp_id,
    e.emp_name,
    d.dept_name
FROM Employee e
JOIN Department d
    ON e.dept_id = d.dept_id
WHERE e.emp_id = 101;

```

OUTPUT:



The screenshot shows the MySQL IDE interface. The 'EXPLORER' panel on the left lists tables: demo, department, department_salary_summary, employee, employee_basic, and employee_hierarchy. The main window displays 'Query 1' with the following SQL query:

```

76 SELECT
77     e.emp_id,
78     e.emp_name,
79     d.dept_name
80 FROM Employee e
81 JOIN Department d
82     ON e.dept_id = d.dept_id
83 WHERE e.emp_id = 101;

```

The result set shows one row of data:

emp_id	emp_name	dept_name
101	Aarav Sharma	IT

```
CALL transfer_employee(101, 3);
```

OUTPUT:



The screenshot shows the MySQL IDE interface. The main window displays 'Query 1' with the following SQL query:

```

1 CALL transfer_employee(101, 3);

```

The result set shows a message:

message
Employee transferred successfully.

```

SELECT
    e.emp_id,
    e.emp_name,
    d.dept_name
FROM Employee e
JOIN Department d
    ON e.dept_id = d.dept_id
WHERE e.emp_id = 101;

```

OUTPUT:




The screenshot shows the MySQL IDE interface. The 'EXPLORER' panel on the left lists the database 'demo' and its tables: 'department', 'department_salary_summary', and 'employee'. The 'Query 1' tab is active, displaying the SQL query from the previous block. The 'Results' panel at the bottom shows a single row of data:

emp_id	emp_name	dept_name
101	Aarav Sharma	Finance

EDGE CASE – EMPLOYEE DOES NOT EXIST

```
CALL transfer_employee(999, 3);
```

OUTPUT:




The screenshot shows the MySQL IDE interface. The 'Query 1' tab is active, displaying the SQL query: `CALL transfer_employee(999, 3);`. The 'Results' panel at the bottom shows an error message:

message
Error: Employee does not exist.

EDGE CASE – DEPARTMENT DOES NOT EXIST

```
CALL transfer_employee(101, 99);
```

OUTPUT:




The screenshot shows the MySQL IDE interface. The 'Query 1' tab is active, displaying the SQL query: `CALL transfer_employee(101, 99);`. The 'Results' panel at the bottom shows an error message:

message
Error: Department does not exist.

EDGE CASE – SAME DEPARTMENT

```
CALL transfer_employee(101, 3);
```

OUTPUT:



SALARY VALIDATION TRIGGER

Let, salary must be ≥ 15000

```
DELIMITER //
```

```
CREATE TRIGGER validate_employee_salary
BEFORE INSERT ON Employee
FOR EACH ROW
BEGIN
    IF NEW.salary < 15000 THEN
        SIGNAL SQLSTATE '45000'
        SET MESSAGE_TEXT = 'Salary must be at least 15000';
    END IF;
```

```
END //
```

```
DELIMITER ;
```

TEST SALARY VALIDATION

```
INSERT INTO Employee
(emp_id, emp_name, gender, salary, hire_date, dept_id)
VALUES
(131, 'Test Employee', 'M', 10000, '2026-09-25', 1);
```

OUTPUT:




TEST VALID SALARY

```
INSERT INTO Employee
(emp_id, emp_name, gender, salary, hire_date, dept_id)
VALUES
(131, 'Test Employee', 'M', 30000, '2026-09-25', 1);

SELECT
    emp_id,
    emp_name,
    salary
FROM Employee
WHERE emp_id = 131;
```

OUTPUT:



The screenshot shows the MySQL IDE interface. On the left is the 'EXPLORER' pane with a search bar and a list of tables: 'demo', 'department', 'department_salary_summary', and 'employee'. The 'demo' table is selected. The main area displays 'Query 1' with the following SQL code:

```
6 SELECT
7     emp_id,
8     emp_name,
9     salary
10 FROM Employee
11 WHERE emp_id = 131;
```

Below the query, the results are shown in a table with three columns: 'emp_id', 'emp_name', and 'salary'. The data row shows '131', 'Test Employee', and '30000.00'.

emp_id	emp_name	salary
131	Test Employee	30000.00

SALARY VALIDATION FOR UPDATE

```
DELIMITER //
```

```
CREATE TRIGGER validate_employee_salary_update
BEFORE UPDATE ON Employee
FOR EACH ROW
BEGIN

    IF NEW.salary < 15000 THEN
        SIGNAL SQLSTATE '45000'
        SET MESSAGE_TEXT = 'Salary must be at least 15000';
    END IF;


END //
```

```
DELIMITER ;
```

TEST INVALID SALARY UPDATE

```
UPDATE Employee
SET salary = 5000
WHERE emp_id = 131;
```

OUTPUT:



```
SELECT emp_id, emp_name, salary
FROM Employee
WHERE emp_id = 131;
```

OUTPUT:

The screenshot shows the MySQL Workbench interface. On the left, the 'EXPLORER' pane lists tables: 'demo', 'department', 'department_salary_summary', and 'employee'. The main editor area shows 'Query 1' with the following SQL code:

```
1 SELECT emp_id, emp_name, salary
2 FROM Employee
3 WHERE emp_id = 131;
4
```

Below the query editor, the results of the query are displayed in a table:

emp_id	emp_name	salary
131	Test Employee	30000.00

CREATE AUDIT TABLE

```
CREATE TABLE Salary_Audit (
    audit_id INT AUTO_INCREMENT PRIMARY KEY,
    emp_id INT,
    old_salary DECIMAL(10,2),
    new_salary DECIMAL(10,2),
    changed_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
    action VARCHAR(30)
);
```

AUDIT LOGGING TRIGGER

```
DELIMITER //
```

```
CREATE TRIGGER salary_audit_trigger
AFTER UPDATE ON Employee
FOR EACH ROW
BEGIN
```

```

IF OLD.salary <> NEW.salary THEN

    INSERT INTO Salary_Audit
    (
        emp_id,
        old_salary,
        new_salary,
        action
    )
VALUES
    (
        NEW.emp_id,
        OLD.salary,
        NEW.salary,
        'SALARY UPDATED'
    );

END IF;

END //

DELIMITER ;

```

TEST AUDIT TRIGGER

```

UPDATE Employee
SET salary = 35000
WHERE emp_id = 131;


```

```

SELECT *
FROM Salary_Audit;

```

OUTPUT:



The screenshot shows a MySQL IDE window with a query editor and a results pane. The query editor contains the SQL query: `SELECT * FROM Salary_Audit;`. The results pane displays a table with 7 columns: `audit_id`, `emp_id`, `old_salary`, `new_salary`, `changed_at`, and `action`. The table contains one row of data.

audit_id	emp_id	old_salary	new_salary	changed_at	action
1	131	30000.00	35000.00	2026-09-24T21:46:41.000Z	SALARY UPDATED


TEST MULTIPLE SALARY CHANGES

```
UPDATE Employee
SET salary = 40000
WHERE emp_id = 131;
```

```
UPDATE Employee
SET salary = 45000
WHERE emp_id = 131;
```

```
SELECT
    audit_id,
    emp_id,
    old_salary,
    new_salary,
    action
FROM Salary_Audit
WHERE emp_id = 131;
```

OUTPUT:



The screenshot shows a MySQL IDE window titled 'MySQL - db_454577wwy'. On the left is an 'EXPLORER' pane with a search bar and a list of tables: 'demo', 'department', 'department_salary_summary', 'employee', 'employee_basic', 'employee_hierarchy', and 'employee_project'. The 'demo' table is selected. The main area displays 'Query 1' with the following SQL code:

```
9  SELECT
12  old_salary,
13  new_salary,
14  action
15  FROM Salary_Audit
16  WHERE emp_id = 131;
```

Below the query, the results are shown in a table with 5 columns: 'audit_id', 'emp_id', 'old_salary', 'new_salary', and 'action'. There are 3 rows of data.

audit_id	emp_id	old_salary	new_salary	action
1	131	30000.00	35000.00	SALARY UPDATED
2	131	35000.00	40000.00	SALARY UPDATED
3	131	40000.00	45000.00	SALARY UPDATED

TEST EDGE CASE – SALARY UNCHANGED

```
UPDATE Employee
SET salary = 45000
WHERE emp_id = 131;
```

No new audit record is created

TEST EDGE CASE – NULL SALARY

```
DROP TRIGGER validate_employee_salary;
```

```
DELIMITER //
```

```
CREATE TRIGGER validate_employee_salary
BEFORE INSERT ON Employee
FOR EACH ROW
BEGIN
```

```

IF NEW.salary IS NULL OR NEW.salary < 15000 THEN
    SIGNAL SQLSTATE '45000'
    SET MESSAGE_TEXT =
    'Salary cannot be NULL and must be at least 15000';
END IF;


END //

DELIMITER ;

INSERT INTO Employee
(emp_id, emp_name, gender, salary, hire_date, dept_id)
VALUES
(132, 'Null Salary', 'F', NULL, '2026-09-25', 1);

```

OUTPUT:



CHECK ALL TRIGGERS

```
SHOW TRIGGERS;
```

OUTPUT:

The screenshot shows the MySQL Workbench interface with the 'SHOW TRIGGERS;' command executed in Query 1. The output is displayed in a table format with the following columns: Trigger, Event, Table, and Statement.

Trigger	Event	Table	Statement
validate_employee_salary	INSERT	employee	BEGIN IF NEW.salary IS NULL OR NEW.salary < 15000 THEN SIGNAL SQLSTATE '45000' SET MESSAGE_TEXT = 'Salary cannot be NULL and must be at
validate_employee_salary_update	UPDATE	employee	BEGIN IF NEW.salary < 15000 THEN SIGNAL SQLSTATE '45000' SET MESSAGE_TEXT = 'Salary must be at least 15000'; END IF; END
salary_audit_trigger	UPDATE	employee	BEGIN IF OLD.salary <> NEW.salary THEN INSERT INTO Salary_Audit (emp_id, old_salary, new_salary, action) VALUES (NEW.emp_id, OLD.salary, NEW

CHECK STORED PROCEDURE

```
SHOW PROCEDURE STATUS
WHERE Db = 'db_454577wwy';
```

OUTPUT:

MySQL - db_454577wwy

Query 1Query 2Query 3

1 SHOW PROCEDURE STATUS
2 WHERE Db = 'db_454577wwy';
3

EXPLORER
Search...
TABLES
demo
department
department_salary_summary
employee

Db	Name	Type	Language	Definer	Modified	Created	Security_type	Comment	character_set_client	collati
db_454577wwy	transfer_employee	PROCEDURE	SQL	user_454577wwy@%	2026-09-24T21:39:54.000Z	2026-09-24T21:39:54.000Z	DEFINER		utf8mb4	utf8mi