EASY BUILD: CUSTOMER RETURN POLICY (v2)

Document ID: POL-OPS-044
Version: 2.0
Year: 2024
Status: SUPERSEDED

This document replaces return policy v1.0 and outlines updated windows.

Standard Return Window: 30 days

Reduced to 30 days return window. Cement packaging must be unopened and undamaged. Steel rebars cannot be cut. Restocking fee 15%.

Safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Furthermore, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

In this context, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Moreover, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Additionally, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Moreover, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Moreover, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Specifically, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Specifically, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Furthermore, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Specifically, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Furthermore, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Consequently, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Specifically, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Additionally, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Additionally, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Additionally, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Consequently, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Moreover, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Moreover, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

In this context, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Specifically, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

In this context, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Consequently, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

In this context, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Moreover, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Specifically, order pick-pack workflows utilize picking lists generated by WMS.

Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Moreover, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Specifically, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Additionally, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Furthermore, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Moreover, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Furthermore, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Consequently, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Consequently, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Moreover, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Specifically, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Moreover, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Additionally, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Consequently, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

In this context, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Specifically, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Consequently, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Specifically, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Specifically, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Specifically, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Consequently, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

In this context, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

In this context, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Moreover, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Furthermore, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Consequently, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Specifically, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

In this context, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Additionally, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Consequently, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

In this context, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Consequently, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Specifically, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

In this context, stock put-away is guided by the Warehouse Management System

(WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Additionally, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Additionally, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

In this context, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Specifically, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Additionally, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Consequently, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Moreover, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.