EASY BUILD: CUSTOMER RETURN POLICY (v3) - CURRENT

Document ID: POL-OPS-044
Version: 3.0
Year: 2026
Status: ACTIVE

Standard Return Window: 21 days

Standard return window is 21 days. Custom-cut marble and custom-tinted paint are strictly non-returnable. Cement returns must show zero moisture exposure. Restocking fee is 20%. Approved by Rajesh Kumar (CEO).

Order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

In this context, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Consequently, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Consequently, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Moreover, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Consequently, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

In this context, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Moreover, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Specifically, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

In this context, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Specifically, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Specifically, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

In this context, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Moreover, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

In this context, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Additionally, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Specifically, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

In this context, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Moreover, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Moreover, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

In this context, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Moreover, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

In this context, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

In this context, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Consequently, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Additionally, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Specifically, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Furthermore, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Consequently, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Moreover, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Furthermore, order pick-pack workflows utilize picking lists generated by WMS.

Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

In this context, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Additionally, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Consequently, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Additionally, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Moreover, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Specifically, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Additionally, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Additionally, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Additionally, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Consequently, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

In this context, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Furthermore, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Consequently, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Consequently, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Specifically, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

In this context, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

In this context, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Specifically, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Moreover, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Additionally, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Moreover, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Specifically, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

In this context, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Moreover, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Specifically, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Moreover, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Moreover, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Consequently, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Moreover, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Specifically, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Furthermore, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Specifically, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Additionally, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Moreover, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Consequently, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Specifically, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Specifically, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Furthermore, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Additionally, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

In this context, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Specifically, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Moreover, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Specifically, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.