

EASY BUILD: CUSTOMER SUPPORT KNOWLEDGE BASE

Document ID: EB-CS-KB-007

Owner: Priya Sharma (VP Sales & Cust Support)

Version: 4.0

1. Complaint Categorization and SLAs

Support tickets are categorized based on priority levels: P1 (System Down/Major Order Block), P2 (Partial Damage/Delivery delay), P3 (Billing queries), P4 (General feedback). SLA responses are 2 hours for P1, 8 hours for P2, 24 hours for P3/P4.

Safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Furthermore, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Additionally, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Additionally, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Additionally, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

In this context, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Moreover, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Specifically, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Moreover, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Consequently, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

In this context, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Consequently, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Moreover, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

In this context, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

In this context, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Specifically, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Moreover, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Furthermore, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Moreover, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Furthermore, safety stock levels are calculated using historical lead time demand

variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

In this context, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Additionally, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Specifically, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Consequently, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Specifically, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Specifically, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Moreover, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

In this context, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Consequently, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in

heavy-duty wraps before dispatch staging.

Furthermore, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Additionally, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Specifically, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Furthermore, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Additionally, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

In this context, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Moreover, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

In this context, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Additionally, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Consequently, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Additionally, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Additionally, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Consequently, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Moreover, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

In this context, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Consequently, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Specifically, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

In this context, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

In this context, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Moreover, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Consequently, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Moreover, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Moreover, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Consequently, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Moreover, stock put-away is guided by the Warehouse Management System

(WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Moreover, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Specifically, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Furthermore, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Consequently, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Furthermore, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Consequently, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier

delays or sudden market surges.

Specifically, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

In this context, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Consequently, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Moreover, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Moreover, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

In this context, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Additionally, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Additionally, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Additionally, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Additionally, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Moreover, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Moreover, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

In this context, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Specifically, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

In this context, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Moreover, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Furthermore, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Moreover, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Specifically, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Moreover, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Moreover, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

In this context, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Consequently, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Additionally, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

In this context, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Specifically, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Moreover, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

In this context, order pick-pack workflows utilize picking lists generated by WMS.

Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Consequently, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Moreover, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Consequently, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Moreover, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

In this context, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Specifically, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Specifically, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Additionally, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Furthermore, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in

heavy-duty wraps before dispatch staging.

Specifically, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Specifically, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Specifically, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Additionally, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Additionally, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Consequently, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Consequently, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Specifically, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Moreover, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

2. Returns, Refunds and Policies

Customer return windows are governed by return policy POL-OPS-044. Support agents must check the purchase date and policy version before approving refunds. Currently (2026), the return window is 21 days. Non-returnable items include custom-tinted paint and cut marble.

Vendor invoices are matched against the purchase order and warehouse receiving record (three-way matching) before payment release. Discrepancies exceeding 2% trigger holding and dispute investigation.

Additionally, purchase requisitions exceeding ₹25,000,000 must undergo comprehensive cost-benefit analysis and receive Level-3 financial approval from the CFO and final sign-off from the CEO.

Additionally, vendor invoices are matched against the purchase order and warehouse receiving record (three-way matching) before payment release. Discrepancies exceeding 2% trigger holding and dispute investigation.

Moreover, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

Additionally, vendor invoices are matched against the purchase order and warehouse receiving record (three-way matching) before payment release. Discrepancies exceeding 2% trigger holding and dispute investigation.

Specifically, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Consequently, vendor invoices are matched against the purchase order and warehouse receiving record (three-way matching) before payment release.

Discrepancies exceeding 2% trigger holding and dispute investigation.

Moreover, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Furthermore, purchase requisitions exceeding ₹25,000,000 must undergo comprehensive cost-benefit analysis and receive Level-3 financial approval from the CFO and final sign-off from the CEO.

Furthermore, purchase requisitions exceeding ₹25,000,000 must undergo comprehensive cost-benefit analysis and receive Level-3 financial approval from the CFO and final sign-off from the CEO.

Furthermore, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Specifically, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

Consequently, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Furthermore, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

In this context, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

Consequently, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Specifically, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Consequently, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Additionally, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

Additionally, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

Moreover, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Additionally, purchase requisitions exceeding ₹25,000,000 must undergo comprehensive cost-benefit analysis and receive Level-3 financial approval from the CFO and final sign-off from the CEO.

Specifically, purchase requisitions exceeding ₹25,000,000 must undergo comprehensive cost-benefit analysis and receive Level-3 financial approval from the CFO and final sign-off from the CEO.

Additionally, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Additionally, vendor invoices are matched against the purchase order and warehouse receiving record (three-way matching) before payment release. Discrepancies exceeding 2% trigger holding and dispute investigation.

Additionally, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Specifically, vendor invoices are matched against the purchase order and warehouse receiving record (three-way matching) before payment release. Discrepancies exceeding 2% trigger holding and dispute investigation.

Consequently, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Moreover, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

Additionally, vendor invoices are matched against the purchase order and warehouse receiving record (three-way matching) before payment release. Discrepancies exceeding 2% trigger holding and dispute investigation.

In this context, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Moreover, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Moreover, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Additionally, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

Consequently, capital expenditure (CapEx) involves acquisitions and upgrades of

physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Additionally, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Furthermore, purchase requisitions exceeding ₹25,000,000 must undergo comprehensive cost-benefit analysis and receive Level-3 financial approval from the CFO and final sign-off from the CEO.

Additionally, purchase requisitions exceeding ₹25,000,000 must undergo comprehensive cost-benefit analysis and receive Level-3 financial approval from the CFO and final sign-off from the CEO.

Additionally, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Additionally, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Specifically, vendor invoices are matched against the purchase order and warehouse receiving record (three-way matching) before payment release. Discrepancies exceeding 2% trigger holding and dispute investigation.

Additionally, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

In this context, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Consequently, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from

budgeted departmental allocations must be reported to the Board.

Moreover, vendor invoices are matched against the purchase order and warehouse receiving record (three-way matching) before payment release. Discrepancies exceeding 2% trigger holding and dispute investigation.

Additionally, vendor invoices are matched against the purchase order and warehouse receiving record (three-way matching) before payment release. Discrepancies exceeding 2% trigger holding and dispute investigation.

Specifically, purchase requisitions exceeding ₹25,000,000 must undergo comprehensive cost-benefit analysis and receive Level-3 financial approval from the CFO and final sign-off from the CEO.

Consequently, purchase requisitions exceeding ₹25,000,000 must undergo comprehensive cost-benefit analysis and receive Level-3 financial approval from the CFO and final sign-off from the CEO.

Furthermore, purchase requisitions exceeding ₹25,000,000 must undergo comprehensive cost-benefit analysis and receive Level-3 financial approval from the CFO and final sign-off from the CEO.

Specifically, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Consequently, vendor invoices are matched against the purchase order and warehouse receiving record (three-way matching) before payment release. Discrepancies exceeding 2% trigger holding and dispute investigation.

Furthermore, purchase requisitions exceeding ₹25,000,000 must undergo comprehensive cost-benefit analysis and receive Level-3 financial approval from the CFO and final sign-off from the CEO.

Consequently, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Moreover, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Specifically, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Furthermore, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Additionally, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

Consequently, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Moreover, purchase requisitions exceeding ₹25,000,000 must undergo comprehensive cost-benefit analysis and receive Level-3 financial approval from the CFO and final sign-off from the CEO.

Additionally, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

Moreover, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Consequently, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Consequently, vendor invoices are matched against the purchase order and warehouse receiving record (three-way matching) before payment release. Discrepancies exceeding 2% trigger holding and dispute investigation.

Additionally, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

Consequently, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Furthermore, purchase requisitions exceeding ₹25,000,000 must undergo comprehensive cost-benefit analysis and receive Level-3 financial approval from the CFO and final sign-off from the CEO.

Moreover, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Additionally, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Moreover, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Additionally, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Consequently, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Specifically, monthly financial closes must verify all accounts receivable, accounts

payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

Furthermore, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Moreover, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Specifically, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

Additionally, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Specifically, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Moreover, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

In this context, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

Additionally, purchase requisitions exceeding ₹25,000,000 must undergo comprehensive cost-benefit analysis and receive Level-3 financial approval from the CFO and final sign-off from the CEO.

Consequently, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be

balanced against storage carrying costs and liquid cash flow needs.

In this context, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

In this context, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Moreover, vendor invoices are matched against the purchase order and warehouse receiving record (three-way matching) before payment release. Discrepancies exceeding 2% trigger holding and dispute investigation.

Consequently, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

In this context, vendor invoices are matched against the purchase order and warehouse receiving record (three-way matching) before payment release. Discrepancies exceeding 2% trigger holding and dispute investigation.

Moreover, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

Consequently, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Moreover, vendor invoices are matched against the purchase order and warehouse receiving record (three-way matching) before payment release. Discrepancies exceeding 2% trigger holding and dispute investigation.

Specifically, vendor invoices are matched against the purchase order and warehouse receiving record (three-way matching) before payment release. Discrepancies exceeding 2% trigger holding and dispute investigation.

Specifically, purchase requisitions exceeding ₹25,000,000 must undergo comprehensive cost-benefit analysis and receive Level-3 financial approval from the CFO and final sign-off from the CEO.

In this context, vendor invoices are matched against the purchase order and warehouse receiving record (three-way matching) before payment release. Discrepancies exceeding 2% trigger holding and dispute investigation.

In this context, vendor invoices are matched against the purchase order and warehouse receiving record (three-way matching) before payment release. Discrepancies exceeding 2% trigger holding and dispute investigation.

Consequently, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

In this context, purchase requisitions exceeding ₹25,000,000 must undergo comprehensive cost-benefit analysis and receive Level-3 financial approval from the CFO and final sign-off from the CEO.

In this context, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Moreover, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Additionally, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Furthermore, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

Furthermore, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

In this context, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

Furthermore, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

In this context, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

Moreover, monthly financial closes must verify all accounts receivable, accounts payable, ledger entries, and bank reconciliations. Deviations from budgeted departmental allocations must be reported to the Board.

In this context, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Moreover, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Moreover, working capital optimization requires balanced management of cash, accounts receivable, and inventory levels. High safety stocks must be balanced against storage carrying costs and liquid cash flow needs.

Additionally, capital expenditure (CapEx) involves acquisitions and upgrades of physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

Specifically, capital expenditure (CapEx) involves acquisitions and upgrades of

physical assets, while operating expenditure (OpEx) covers daily transaction runs. Both require distinct approval streams based on delegated authority limits.

3. Dispute Escalation Paths

If a dealer disputes an invoice or credit limit, the ticket must be escalated to the Finance accounts team. Let's refer to our escalation matrices for handling complex payment conflicts.

Standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Additionally, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Additionally, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Moreover, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Furthermore, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

In this context, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Additionally, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, fleet dispatch operations require loading verification, vehicle

roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Additionally, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Moreover, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Specifically, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Additionally, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Consequently, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Consequently, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Consequently, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Additionally, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of

building materials for quality compliance.

Consequently, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Additionally, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Additionally, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Specifically, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Furthermore, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Specifically, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Additionally, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Specifically, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Specifically, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Specifically, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Consequently, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Consequently, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

In this context, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Moreover, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Specifically, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Furthermore, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Additionally, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Moreover, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Furthermore, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Specifically, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Moreover, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

In this context, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Furthermore, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Consequently, order pick-pack workflows utilize picking lists generated by WMS.

Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Moreover, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Furthermore, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Additionally, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Specifically, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Specifically, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

In this context, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Consequently, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

In this context, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of

building materials for quality compliance.

Consequently, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Consequently, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Consequently, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Moreover, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Furthermore, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Furthermore, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Specifically, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Specifically, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Furthermore, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Additionally, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Specifically, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Additionally, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

In this context, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Moreover, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Moreover, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Furthermore, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Specifically, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Consequently, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Furthermore, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Consequently, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Moreover, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Moreover, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Consequently, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Consequently, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Moreover, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Additionally, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Consequently, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Additionally, fleet dispatch operations require loading verification, vehicle

roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Moreover, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Specifically, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

In this context, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Additionally, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Moreover, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Additionally, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Furthermore, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Moreover, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Consequently, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of

building materials for quality compliance.

Furthermore, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

In this context, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

In this context, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Furthermore, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Additionally, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Consequently, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Consequently, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Consequently, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Consequently, order pick-pack workflows utilize picking lists generated by WMS. Picked stock is placed in transit bins, double-checked for SKU codes, and packed in heavy-duty wraps before dispatch staging.

Moreover, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Moreover, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Consequently, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Specifically, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Moreover, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Consequently, safety stock levels are calculated using historical lead time demand variance and target service level variables, ensuring protection against supplier delays or sudden market surges.

Additionally, fleet dispatch operations require loading verification, vehicle roadworthiness checks, GPS tracker activation, and printouts of logistics invoices and e-way bills.

Specifically, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Moreover, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Additionally, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Consequently, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Furthermore, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Furthermore, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Specifically, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

In this context, standard warehouse receiving processes require verification of delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Moreover, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).

Moreover, standard warehouse receiving processes require verification of

delivery documents, inspection for physical damage, and sample testing of building materials for quality compliance.

Specifically, stock put-away is guided by the Warehouse Management System (WMS), which assigns specific bin locations based on item weight, safety classification, and inventory rotation rules (FIFO/FEFO).