

OOPS ka matlab kya hai?

OOPS = Object-Oriented Programming System

OOPS kya hai?

OOPS ek programming style hai jisme hum real-world cheezon ko "objects" ke roop mein represent karte hain.

Isme data (properties) aur functions (methods) ko objects ke andar organize karte hain, taaki code samajhna, likhna aur maintain karna easy ho jaye.

(

OOPS is a programming style where we model real-world things as "objects".

Each object contains data (called properties) and functions (called methods) that operate on the data.

This helps organize code better, makes it easier to understand, reuse, and maintain.

)

Class and Object –

✓ 1. What is a Class?

- **Definition:** Class ek blueprint ya template hoti hai jisme hum object banane ke liye data (properties) aur functions (methods) define karte hain.

What does a Class contain?

A class mainly contains:

1. **Properties (Attributes):** These are the data or characteristics of the object.
Example: color, model, speed for a car.
2. **Methods (Functions):** These are actions or behaviors the object can perform.
Example: start(), stop(), accelerate() for a car.

```
class ClassName {  
  
    method1() {  
  
        // code  
  
    }  
  
    method2() {  
  
        // code  
  
    }  
  
}
```

◆ Types of Inheritance in OOP (Object-Oriented Programming)

Traditionally, there are **5 types** of inheritance:

Type	Meaning
1. Single	One child class inherits from one parent
2. Multi-level	One class inherits from another, which inherits from another
3. Hierarchical	Multiple child classes inherit from one parent
4. Multiple	One class inherits from multiple parents
5. Hybrid	Combination of multiple types

1. Single →

```
JS Clas_Obj.js > Home > Add
1  class Home{
2      Add(){
3          let a=2;
4          let a1=2;
5          console.log("add "+(a+a1));
6      }
7      Mul(){
8          let a=12;
9          let a1=2;
10         console.log("Mul "+(a*a1));
11     }
12 }
13 class Home2 extends Home{
14     Add1(){
15         let a=2;
16         let a1=2;
17         console.log("add "+(a+a1));
18     }
19     Mul112(){
20         let a=12;
21         let a1=2;
22         console.log("Mul "+(a*a1));
23     }
24 }
25
26 h=new Home2();
27 h.Add();
28 h.Mul();
29 h.Mul112();
30
```

Code → [click me](#)

2 What is Multilevel Inheritance?

Multilevel Inheritance me ek class **dusri class se inherit** karti hai, aur wo class **teesri class se inherit** karti hai.

Jaise ek **chain** banti hai.

```
JS single_1.js JS Multilevel_1.js X
Inheritance > JS Multilevel_1.js > Parent > showParent
1  class Grandparent {
2      showGrandparent() {
3          console.log("I am Grandparent");
4      }
5  }
6
7  class Parent extends Grandparent {
8      showParent() {
9          console.log("I am Parent");
10     }
11 }
12
13 class Child extends Parent {
14     showChild() {
15         console.log("I am Child");
16     }
17 }
18
19 let c = new Child();
20 c.showChild();
21 c.showParent();
22 c.showGrandparent();
23
```

Code →

[Click me](#)

3. Hierarchical Inheritance

One parent class, but **multiple child classes** inherit from it.

```
← → Programme
JS single_1.js JS Multilevel_1.js JS Hierarchical_1.js
Inheritance > JS Hierarchical_1.js > ...
1  class Parent {
2      showParent() {
3          console.log("I am Parent");
4      }
5  }
6
7  class Child1 extends Parent {
8      showChild1() {
9          console.log("I am Child 1");
10     }
11 }
12
13 class Child2 extends Parent {
14     showChild2() {
15         console.log("I am Child 2");
16     }
17 }
18
19 let c1 = new Child1();
20 c1.showParent(); // I am Parent
21 c1.showChild1(); // I am Child 1
22
23 let c2 = new Child2();
24 c2.showParent(); // I am Parent
25 c2.showChild2(); // I am Child 2
26
```

Code -> [Click me](#)

Multiple Inheritance ➡

```
// ✖ ERROR: JavaScript doesn't allow extending multiple classes
```

```
file Edit Selection ... ← → Programme
JS single_1.js JS Multilevel_1.js JS Hierarchical_1.js JS MultipleInheritance_1.js 1 X
Inheritance > JS MultipleInheritance_1.js > C > showC
1 class A {
2     showA() {
3         console.log("Class A");
4     }
5 }
6 class B {
7     showB() {
8         console.log("Class B");
9     }
10 }
11
12 class C extends A, B {
13     showC() {
14         console.log("Class C");
15     }
16 }
17
18 let obj = new C();
19 obj.showA();
20 obj.showB();
21 obj.showC();
22
```

★ Why Error?

- JavaScript only allows one `extends` keyword at a time.
- You **cannot inherit from two classes directly** like `class C extends A, B`.

MIXIN METHOD ➡ :

🔥 What is a Mixin?

Mixin ek aisa technique ya object hota hai jisme hum kuch reusable methods (functions) rakhte hain, aur unhe alag-alag classes me **copy karke** use karte hain.

Why use Mixin?

- JavaScript me **multiple inheritance** nahi hoti.
- Lekin agar tumhe ek class me do ya zyada classes ke behavior chahiye, to tum **Mixin** use karte ho.
- Isse tum ek class me **bahut saare features** add kar sakte ho bina inheritance ke.

```
24
25  CanFly = {
26    fly() {
27      console.log("✈️ I can fly");
28    }
29  };
30  CanSwim = {
31    swim() {
32      console.log("🏊 I can swim");
33    }
34  };
35  CanSwim2 = {
36    swim2() {
37      console.log("I can swim2");
38    }
39  };
40  class Duck {}
41
42  Object.assign(Duck.prototype, CanFly, CanSwim, CanSwim2);
43
44
45  let d = new Duck();
46  d.fly();
47  d.swim();
48  d.swim2();
49
50
```

Code → [click me](#)

Prototypal Inheritance



Prototype का use हम तब करते हैं:

- जब हम चाहते हैं कि एक object या function के जरिए कई object बनें और सबमें एक जैसा behavior (methods) हों।
- और वो shared behavior memory efficient हों।

A screenshot of the Visual Studio Code editor. The editor window shows a file named 'Prototypal_Inheritance.js' with the following code:

```
1 const user = {  
2   name: "Rahul",  
3   greet() {  
4     console.log("Hello");  
5   }  
6 };  
7 p=new user;  
8 p.greet();  
9
```

The terminal window at the bottom shows the command `node "d:\Program\WEB\JS\OOPS\Programe\Inheritance\Prototypal_Inheritance.js"` and the resulting error:

```
TypeError: user is not a constructor  
at Object.<anonymous> (d:\Program\WEB\JS\OOPS\Programe\Inheritance\Prototypal_Inheritance.js:7:14)  
at Module._compile (node:internal/modules/cjs/loader:1688:14)  
at Object.<js> (node:internal/modules/cjs/loader:1820:10)  
at Module.load (node:internal/modules/cjs/loader:1423:32)  
at Function._load (node:internal/modules/cjs/loader:1246:12)  
at TracingChannel.traceSync (node:diagnostics_channel:322:14)
```

ये वाला कोड ES6 Classes और Inheritance वाला तरीका है।

```
1
2 class Parent {
3   greet() {
4     console.log("Hello from Parent");
5   }
6 }
7
8 class Child extends Parent {
9   greet() {
10    console.log("Hello from Pare121212nt");
11  }
12 }
13
14 const child = new Child();
15 child.greet();
```

Super method ➡

✦ **super क्या है?**

super keyword का इस्तेमाल JavaScript में parent class के constructor या methods को call करने के लिए किया जाता है।

```
✓ class Parent {
✓   greet() {
    console.log("Hello from Parent");
  }
}

✓ class Child extends Parent {
✓   greet() {
    super.greet();      // Parent का greet() कॉल कर रहा हूँ
    console.log("Hello from Child");
  }
}

const child = new Child();
child.greet();
```

o/p → ?

```
37
38 ✓ class Parent {
39   ✓ greet() {
40     console.log("Hello from Parent");
41   }
42   ✓ greet1() {
43     console.log("Hello from Parent 1");
44   }
45 }
46
47 ✓ class Child extends Parent {
48   ✓ greet1() {
49     // super.greet();
50     super.greet1();
51     console.log("Hello from Child");
52   }
53 }
54
55 const child = new Child();
56 child.greet1();
57
58
```

code → [click me](#)

● ❖ Q: Constructor ka use kya hai?

❖ Constructor ek special function hota hai class ke andar, jo **object banate hi automatically chal jaata hai**.

✦ Use:

- Jab aap chahte ho ki **har object ke andar same structure** ho (same properties ho).
- Aapko **multiple similar objects** banana ho alag-alag data ke saath.

❖ Q: Constructor kyu use karte hain? (Kya zarurat hai?)

☞ Jab aap:

1. Har object me **same properties** repeat kar rahe ho (e.g., name, age)
2. Multiple objects bana rahe ho (10, 50, 100...)
3. Future me code maintain karna easy rakhna chahte ho

W/o constructor →

```
68
69 let s1 = { name: "Aman", age: 15 };
70 let s2 = { name: "Riya", age: 16 };
71 let s3 = { name: "Anu", age: 55 };
72 let s4 = { name: "Rubi", age: 27 };
73 let s5 = { name: "Ronak", age: 37 };
74
75 console.log(s1);
76 console.log(s2);
77 console.log(s3);
78 console.log(s4);
79 console.log(s5);
80
```

ROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
node.js v22.18.0
S D:\Programming\WEB\JS\OOPS\Programe\Inheritance> node "d
e\Inheritance\constructor_function.js"
name: 'Aman', age: 15 }
name: 'Riya', age: 16 }
name: 'Anu', age: 55 }
name: 'Rubi', age: 27 }
name: 'Ronak', age: 37 }
S D:\Programming\WEB\JS\OOPS\Programe\Inheritance>
```

Code → [click me](#)

```

80
81 let s1 = { name: "Aman", age: 15, fatherName: "Ramesh", motherName: "Sita" };
82 let s2 = { name: "Riya", age: 16, fatherName: "Sanjay", motherName: "Geeta" };
83 let s3 = { name: "Anu", age: 55, fatherName: "Mahesh", motherName: "Lata" };
84 let s4 = { name: "Rubi", age: 27, fatherName: "Raj", motherName: "Meena" };
85 let s5 = { name: "Ronak", age: 37, fatherName: "Amit", motherName: "Sunita" };
86
87 console.log(s1, s2, s3, s4, s5);
88
89
90
91

```

With Constructor ➔

```

94
95 class Student {
96   constructor(name, age, fatherName, motherName) {
97     this.name = name;
98     this.age = age;
99     this.fatherName = fatherName;
100    this.motherName = motherName;
101  }
102 }
103
104 let s1 = new Student("Aman", 15, "Ramesh", "Sita");
105 let s2 = new Student("Riya", 16, "Sanjay", "Geeta");
106 let s3 = new Student("Anu", 55, "Mahesh", "Lata");
107 let s4 = new Student("Rubi", 27, "Raj", "Meena");
108 let s5 = new Student("Ronak", 37, "Amit", "Sunita");
109
110 console.log(s1, s2, s3, s4, s5);
111

```

◆ Constructor ke saath (loop se bana do 10 student):

```

113
114
115 class Student {
116     constructor(name, age, classGrade) {
117         this.name = name;
118         this.age = age;
119         this.classGrade = classGrade;
120     }
121 }
122
123 let names = ["Aman", "Riya", "Anu", "Rubi", "Ronak", "Neha", "Amit", "Tina", "Vikas", "Pooja"];
124 let students = [];
125
126 for (let i = 0; i < names.length; i++) {
127     students.push(new Student(names[i], 15 + i, "10A"));
128 }
129
130 console.log(students);
131

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```

[
  Student { name: 'Aman', age: 15, classGrade: '10A' },
  Student { name: 'Riya', age: 16, classGrade: '10A' },
  Student { name: 'Anu', age: 17, classGrade: '10A' },
  Student { name: 'Rubi', age: 18, classGrade: '10A' },
  Student { name: 'Ronak', age: 19, classGrade: '10A' },
  Student { name: 'Neha', age: 20, classGrade: '10A' },
  Student { name: 'Amit', age: 21, classGrade: '10A' },
  Student { name: 'Tina', age: 22, classGrade: '10A' },
  Student { name: 'Vikas', age: 23, classGrade: '10A' },
]

```

Click me → [code](#)