

JobsAPI Platform

Status: All Systems Operational

Active Jobs: 16,027 Postings

Date: September 28, 2026

Engineering, ATS Ingestion & API Architecture Report

TOTAL LIVE JOBS 16,027 100% verified & active	INTEGRATED SOURCES 13 ATS / Feeds 7 active high-volume	TOP SOURCE YIELD 12,829 Greenhouse (99.2% rate)	AUTOMATED TESTS 38 / 38 Passing Zero regressions
--	---	--	--

1. ATS & Job Board Performance Breakdown

JobsAPI periodically queries and parses public APIs, ATS boards, and official feeds. Postings undergo content normalization, cryptographic deduplication, and quality validation.

Source / ATS Provider	Jobs Fetched	Live in DB	Success Rate	Avg Latency	Auth Type
Greenhouse	12,984	12,829	99.17%	58.0s (75 companies)	Public REST API
Ashby	3,021	2,114	69.98%	90.2s (35 companies)	Public REST API
Lever	1,043	504	48.32%	266.7s (38 companies)	Public JSON API
Arbeitnow	250	250	100.00%	20.1s	Open Board API
TheMuse	1,000	216	21.60%	20.5s (50 pages)	Public REST API
USAJobs (US Federal)	100	82	82.00%	18.1s	API Key + User-Agent
Remotive	19	19	100.00%	3.2s	Public Dev API
Recruitee	16	13	81.25%	8.5s	Public Company API
Workday / Jobvite / BambooHR	On-demand	Active feed	Dynamic	10-18s	Public Feed / XML

2. Ingestion Pipeline & Quality Safeguards

To eliminate duplicate jobs, dead apply links, or expired listings, all fetched raw jobs flow through the centralized `SyncPipeline` engine:

Deterministic Deduplication: Every job receives a SHA-256 fingerprint generated from `title + company + normalized_location + applyUrl`. If a posting hasn't changed, the pipeline only touches `last_seen` with zero redundant

database writes.

- **Mandatory Completeness:** Rejects listings missing title, company name, apply URL, location, source, or description under 10 characters.
- **Freshness Retention (90 Days):** Rejects postings older than 90 days from the original publish date.
- **Data Normalization:** Automatically extracts salary ranges, seniority/experience levels, employment types (Full-time, Contract, Internship), and technical skills stack (e.g. Node.js, React, AWS, Python).
- **Bulk Memory Optimization:** Executes batched MongoDB `bulkWrite` operations in chunks of 1,000 records.

3. Source-by-Source Configuration & Setup Guide

Colleagues can review how each API works, where its configuration resides, and how to add companies:

1. Greenhouse Job Board API

12,829 Live Jobs

Endpoint: `https://boards-api.greenhouse.io/v1/boards/{company_token}/jobs?content=true`

Authentication: None (Public Open API).

Config File: `backend/src/config/connectors/greenhouse.json`

How to Add Companies: Append the company handle (e.g., `"stripe"`, `"airbnb"`, `"cloudflare"`, `"mongodb"`) to the JSON array.

2. Ashby Public Postings API

2,114 Live Jobs

Endpoint: `https://api.ashbyhq.com/posting-api/job-board/{company_token}?includeCompensation=true`

Authentication: None (Public API with compensation ranges).

Config File: `backend/src/config/connectors/ashby.json`

How to Add Companies: Add the Ashby company slug (e.g., `"openai"`, `"perplexity"`, `"cohere"`, `"linear"`, `"notion"`).

3. Lever Public Postings API

504 Live Jobs

Endpoint: `https://api.lever.co/v0/postings/{company_token}?mode=json`

Authentication: None (Public JSON).

Config File: `backend/src/config/connectors/lever.json`

How to Add Companies: Add company slug (e.g., `"netflix"`, `"spotify"`, `"canva"`, `"palantir"`, `"retool"`).

4. USAJobs (US Federal Government Official API)

82 Live Jobs

Endpoint: `https://data.usajobs.gov/api/search`

Authentication: API Key + User-Agent header.

Setup: Register at `developer.usajobs.gov` and add `USAJOBS_API_KEY` and `USAJOBS_EMAIL` to `backend/.env`.

5. TheMuse, Arbeitnow & Remote Tech Feeds

485 Live Jobs

Endpoints: `https://www.themuse.com/api/public/jobs`, `https://www.arbeitnow.com/api/job-board-api`, `https://remotevibe.com/api/remote-jobs`

Authentication: None. Automated scheduled sync every 6 hours.

4. Universal Candidate Profile & Multi-ATS Auto-Apply

The system decouples candidate data from any specific job board into an ATS-independent canonical profile:

- **Canonical Candidate Profile:** Stores Identity, Work Experience, Education, Documents, and Verified Application Answers in `CandidateProfile` model.
- **Zero-Hallucination Compliance:** Sensitive legal questions (Visa sponsorship, US work auth, citizenship, disability, veteran status) default to `unknown` and are **never guessed** by heuristics or LLMs.
- **Playwright ATS Adapters:** Modular adapters for `GreenhouseAdapter`, `LeverAdapter`, `AshbyAdapter`, `WorkdayAdapter`, and `GenericATSAdapter` dynamically map form inputs and submit applications safely.

- **Preflight & Idempotency:** `ApplicationPreflightValidator` screens candidate blocklists before launch; `ApplicationIdempotencyService` prevents duplicate submissions via SHA-256 fingerprinting.

5. Key API Endpoints Reference

GET /api/jobs	• List active jobs with pagination, remote & skill filters
GET /api/jobs/search	• Full-text relevance search
POST /api/jobs/sync	• Trigger on-demand sync across all ATS sources
GET /api/candidate/profile	• Fetch universal candidate profile
PUT /api/candidate/profile	• Update candidate profile
POST /api/candidate/preflight	• Verify candidate readiness against job requirements
GET /health	• Health, liveness and telemetry metadata