


Understanding of Threads

This tutorial is an attempt to help you become familiar with multi-threaded programming with the POSIX (Portable Operating System Interface) threads, or pthreads.

What are threads?

Technically, a thread is defined as an independent stream of instructions that can be scheduled to run as such by the operating system.

A thread is a semi-process that has its own stack, and executes a given piece of code. Unlike a real process, the thread normally shares its memory with other threads (where as for processes we usually have a different memory area for each one of them). A Thread Group is a set of threads all executing inside the same process. They all share the same memory, and thus can access the same global variables, same heap memory, same set of file descriptors, etc. All these threads execute in parallel (i.e. using time slices, or if the system has several processors, then really in parallel).



What are pthreads?

In order to take full advantage of the capabilities provided by threads, a standardized programming interface was required. For UNIX systems, this interface has been specified by the IEEE POSIX 1003.1c standard (1995). Implementations which adhere to this standard are referred to as POSIX threads, or Pthreads.

Threads are efficient ...

If implemented correctly, threads have some advantages over processes. Compared to the standard `fork()`, threads carry a lot *less overhead*.

Remember that `fork()` produces a second copy of the calling process. The parent and the child are ***completely independent***, each with its own address space, with its own copies of its variables, which are completely independent of the same variables in the other process.

Threads share a common address space, thereby avoiding a lot of the inefficiencies of multiple processes.

- The kernel does not need to make a new independent copy of the process memory space, file descriptors, etc. This saves a lot of CPU time, making thread creation ten to a hundred times faster than a new process creation. Because of this, you can use a whole bunch of threads and not worry about the CPU and memory overhead incurred. This means you can generally create threads whenever it makes sense in your program.
- Less time to terminate a thread than a process.
- Context switching between threads is much faster than context switching between processes (context switching means that the system switches from running one thread or process, to running another thread or process)
- Less communication overheads -- communicating between the threads of one process is simple because the threads share the address space. Data produced by one thread is immediately available to all the other threads.

On the other hand, because threads in a group all use the same memory space, if one of them corrupts the contents of its memory, other threads might suffer as well. With processes, the operating system normally protects processes from one another, and thus if one corrupts its own memory space, other processes won't suffer.

Threads are useful – Few Applications

Example 1: A responsive user interface

One area in which threads can be very helpful is in user-interface programs. These programs are usually centered around a loop of reading user input, processing it, and showing the results of the processing. The processing part may sometimes take a while to complete, and the user is made to wait during this operation. By placing such long operations in a separate thread, while having another thread to read user input, the program can be more responsive. It may allow the user to cancel the operation in the middle.

Example 2: A graphical interface

In graphical programs the problem is more severe, since the application should always be ready for a message from the windowing system telling it to repaint part of its window. If it's too busy executing some other task, its window will remain blank, which is rather ugly. In such a case, it is a good idea to have one thread handle the message loop of the windowing system and always ready to get such repaint requests (as well as user input). Whenever this thread sees a need to do an operation that might take a long time to complete (say, more than 0.2 seconds in the worse case), it will delegate the job to a separate thread.

Example 3 : A Web server

- It needs to handle several download requests over a short period
- Hence more efficient to create (and destroy) a single thread for each request

- Multiple threads can possibly be executing simultaneously on different processors

Creating and destroying threads

When a multi-threaded program starts executing, it has one thread running, which executes the `main()` function of the program. This is already a full-fledged thread, with its own thread ID. In order to create a new thread, the program should use the `pthread_create()` function.

```
#include <pthread.h>

int pthread_create(pthread_t *thread, pthread_attr_t *attr, void*(*start_routine)(void *), void *arg);
```

The first argument is a pointer to `pthread_t`. When a thread is created, an identifier is written to the memory location to which this variable points. This identifier enables you to refer to the thread. The next argument sets the thread attributes. You do not usually need any special attributes, and you can simply pass `NULL` as this argument.

The **final two arguments** tell the thread the function that it is to start executing and the arguments that are to be passed to this function

`void *(*start_routine)(void *)` □ you can pass any type of single argument and return a pointer to any type

Here is how to use it:

Program - hello.c

```
#include <stdio.h> /* standard I/O routines */ #include <pthread.h> /* pthread
functions and data structures */

/* function to be executed by the new thread */
void* PrintHello(void* data)
{
    int my_data = (int)data; /* data received by thread */

    pthread_detach(pthread_self());
    printf("Hello from new thread - got %d\n", my_data); pthread_exit(NULL); /*
terminate the thread */ }

/* like any C program, program's execution begins in main */ int main(int
argc, char* argv[])
{
    int rc; /* return value */ pthread_t thread_id; /* thread's ID (just an
integer) */ int t = 11; /* data passed to the new thread */

    /* create a new thread that will execute 'PrintHello' */ rc =
pthread_create(&thread_id, NULL, PrintHello, (void*)t); if(rc) /* could not
create thread */
    {
        printf("\n ERROR: return code from pthread_create is %d \n", rc);
        exit(1);
    }
}
```

```

}
printf("\n Created new thread (%d) ... \n", thread_id);
pthread_exit(NULL); /* terminate the thread */ }

```

Understanding the simple threaded program above:

While it does not do anything useful, it will help you understand how threads work. Let us take a step by step look at what the program does.

1. In `main()` we declare a variable called `thread_id`, which is of type `pthread_t`. This is basically an integer used to identify the thread in the system. After declaring `thread_id`, we call the `pthread_create()` function to create a real, living thread.
2. `pthread_create()` gets 4 arguments. The first argument is a pointer to `thread_id`, used by `pthread_create()` to supply the program with the thread's identifier. The second argument is used to set some attributes for the new thread. In our case we supplied a `NULL` pointer to tell `pthread_create()` to use the default values. Notice that `PrintHello()` accepts a `void *` as an argument and also returns a `void *` as a return value. This shows us that it is possible to use a `void *` to pass an arbitrary piece of data to our new thread, and that our new thread can return an arbitrary piece of data when it finishes. How do we pass our thread an arbitrary argument? Easy. We use the fourth argument to the `pthread_create()` call. If we do not want to pass any data to the new thread, we set the fourth argument to `NULL`. `pthread_create()` returns zero on success and a non-zero value on failure.
3. After `pthread_create()` successfully returns, the program will consist of **two threads**. This is because the main program is also a thread and it executes the code in the `main()` function in parallel to the thread it creates. Think of it this way: if you write a program that does not use POSIX threads at all, the program will be single-threaded (this single thread is called the "main" thread).
4. The call to `pthread_exit()` causes the current thread to exit and free any thread-specific resources it is taking.

In order to compile a multi-threaded program using `gcc`, we need to link it with the pthreads library. Assuming you have this library already installed on your system, here is how to compile our first program:

```
gcc hello.c -o hello -lpthread
```

Exercise 1. Try `hello.c` without any modification. The output would be similar as:

```

    Created new thread (4) ...
Hello from new thread - got 11

```

Exercise 2. A thread can get its own thread id by calling `pthread_self()`, which returns the thread id: `pthread_t pthread_self();`

Use it as

```
pthread_t tid;
tid = pthread_self();
```

Modify the code for `hello.c` to print out the thread id for both threads. Recompile and run the `helloexecutable`. The new output should be similar to

```

I am thread 1. Created new thread (4) ...
Hello from new thread 4 - got 11

```

Now modify the code so that the main thread passes its own thread id to the new thread it creates. Recompile and run the `hello` executable. The output should be similar to

```
I am thread 1. Created new thread (4) ...
Hello from new thread 4 - got 1
```

Exercise 3. There are several ways for threads to terminate. One way to safely terminate is to call the `pthread_exit` routine (the equivalent of `exit` for processes). In this exercise, modify the your `hello.c` program as follows. In the `PrintHello` routine, add a line before the `printf` call `sleep(1);`. This should be the first line of the function. In the `main` function, comment out the last statement line which contains the `pthread_exit` call. Recompile and run the `hello` executable.

What happens? Why?

Now, put the `pthread_exit` call back in the main program, but remove it from the `PrintHello` routine. Also add the `sleep` call to the main routine, just before the second `printf` call, and remove it from the `PrintHello` routine. Recompile and run the `hello` executable.

What happens? Why?

It is necessary to use `pthread_exit` at the end of the main program. Otherwise, when it exits, all running threads will be killed.

Exercise 4. The `pthread_join()` function for threads is the equivalent of `wait()` for processes. A call to `pthread_join` blocks the calling thread until the thread with identifier equal to the first argument terminates.

```
#include <stdio.h> /* standard I/O routines */ #include <pthread.h> /* pthread
functions and data structures */

void* PrintHello(void* data)
{
    pthread_t tid = (pthread_t)data; /* data received by thread */

    pthread_join(tid, NULL); /* wait for thread tid */ printf("Hello from new thread %d -
got %d\n", pthread_self(), data); pthread_exit(NULL); /* terminate the thread */ }

/* like any C program, program's execution begins in main */ int main(int
argc, char* argv[])
{
    int rc; /* return value */ pthread_t thread_id; /* thread's ID (just an
integer) */ int tid;

    tid = pthread_self();

    rc = pthread_create(&thread_id, NULL, PrintHello, (void*)tid); if(rc) /* could not
create thread */ {
        printf("\n ERROR: return code from pthread_create is %d \n", rc);
        exit(1);
    }
    sleep(1);
    printf("\n Created new thread (%d) ... \n", thread_id); pthread_exit(NULL);
}
```

The first argument to `pthread_join()` is the identifier of the thread to join. The second argument is a void pointer.

```
pthread_join(pthread_t tid, void * return_value);
```

If the `return_value` pointer is non-NULL, `pthread_join` will place at the memory location pointed to by `return_value`, the value passed by the thread `tid` through the `pthread_exit` call. Since we don't care about return value of the main thread, we set it to NULL.

Recompile and run the executable for the above code. Is the output what you expected?

Note. At any point in time, a thread is either joinable or detached (default state is joinable). *Joinable* threads must be reaped or killed by other threads (using `pthread_join`) in order to free memory resources.

Detached threads cannot be reaped or killed by other threads, and resources are automatically reaped on termination. So unless threads need to synchronize among themselves, it is better to call

```
pthread_detach(pthread_self());
```

instead of `pthread_join`.

Exercise 5. Write a program `hellomany.c` that will create a number `N` of threads specified in the command line, each of which prints out a hello message and its own thread ID. To see how the execution of the threads interleaves, make the main thread sleep for 1 second for every 4 or 5 threads it creates. The output of your code should be similar to:

```
I am thread 1. Created new thread (4) in iteration 0... Hello from thread 4 - I
was created in iteration 0 I am thread 1. Created new thread (6) in iteration 1...
I am thread 1. Created new thread (7) in iteration 2... I am thread 1. Created new
thread (8) in iteration 3... I am thread 1. Created new thread (9) in iteration
4... I am thread 1. Created new thread (10) in iteration 5... Hello from thread 6
- I was created in iteration 1 Hello from thread 7 - I was created in iteration 2
Hello from thread 8 - I was created in iteration 3 Hello from thread 9 - I was
created in iteration 4 Hello from thread 10 - I was created in iteration 5 I am
thread 1. Created new thread (11) in iteration 6... I am thread 1. Created new
thread (12) in iteration 7... Hello from thread 11 - I was created in iteration 6
Hello from thread 12 - I was created in iteration 7
```

Exercise 6 . Write a program to return a value from the thread using Join function call.

Exercise 7. Write a thread based program to add the elements of array. Assign different indices to child threads for performing the sum of array parallelly.

Exercise 8. Write a program to implement race condition using shared memory. Use mutex to avoid the race condition.

For More on Threads: http://en.wikipedia.org/wiki/POSIX_Threads