

B. Consider the following schema for Order Database:

SALESMAN (Salesman_id, Name, City, Commission)
CUSTOMER (Customer_id, Cust_Name, City, Grade, Salesman_id)
ORDERS (Ord_No, Purchase_Amt, Ord_Date, Customer_id, Salesman_id)

Write SQL queries to

1. Count the customers with grades above Bangalore's average.
2. Find the name and numbers of all salesmen who had more than one customer.
3. List all salesmen and indicate those who have and don't have customers in their cities (Use UNION operation.)
4. Create a view that finds the salesman who has the customer with the highest order of a day.
5. Demonstrate the DELETE operation by removing salesman with id 1000. All his orders must also

```
CREATE TABLE SALESMAN
(SALESMAN_ID NUMBER (4),
NAME VARCHAR2 (20),
CITY VARCHAR2 (20),
COMMISSION VARCHAR2 (20),
PRIMARY KEY (SALESMAN_ID));
```

```
CREATE TABLE CUSTOMER1
(CUSTOMER_ID NUMBER (4),
CUST_NAME VARCHAR2 (20),
CITY VARCHAR2 (20),
GRADE NUMBER (3),
PRIMARY KEY (CUSTOMER_ID),
SALESMAN_ID REFERENCES SALESMAN (SALESMAN_ID) ON DELETE SET NULL);
```

```
CREATE TABLE ORDERS
(ORD_NO NUMBER (5),
PURCHASE_AMT NUMBER (10, 2),
ORD_DATE DATE,
PRIMARY KEY (ORD_NO),
CUSTOMER_ID REFERENCES CUSTOMER1 (CUSTOMER_ID) ON DELETE CASCADE,
SALESMAN_ID REFERENCES SALESMAN (SALESMAN_ID) ON DELETE CASCADE);
```

```
INSERT INTO SALESMAN VALUES (1000, 'JOHN','BANGALORE','25 %');
INSERT INTO SALESMAN VALUES (2000, 'RAVI','BANGALORE','20 %');
INSERT INTO SALESMAN VALUES (3000, 'KUMAR','MYSORE','15 %');
INSERT INTO SALESMAN VALUES (4000, 'SMITH','DELHI','30 %');
INSERT INTO SALESMAN VALUES (5000, 'HARSHA','HYDRABAD','15 %');
```

```
INSERT INTO CUSTOMER1 VALUES (10, 'PREETHI','BANGALORE', 100, 1000);
INSERT INTO CUSTOMER1 VALUES (11, 'VIVEK','MANGALORE', 300, 1000);
INSERT INTO CUSTOMER1 VALUES (12, 'BHASKAR','CHENNAI', 400, 2000);
INSERT INTO CUSTOMER1 VALUES (13, 'CHETHAN','BANGALORE', 200, 2000);
INSERT INTO CUSTOMER1 VALUES (14, 'MAMATHA','BANGALORE', 400, 3000);
```



```

INSERT INTO ORDERS VALUES (50, 5000, '04-MAY-17', 10, 1000);
INSERT INTO ORDERS VALUES (51, 450, '20-JAN-17', 10, 2000);
INSERT INTO ORDERS VALUES (52, 1000, '24-FEB-17', 13, 2000);
INSERT INTO ORDERS VALUES (53, 3500, '13-APR-17', 14, 3000);
INSERT INTO ORDERS VALUES (54, 550, '09-MAR-17', 12, 2000);

```

1. Count the customers with grades above Bangalore's average.

```

SELECT GRADE, COUNT (DISTINCT CUSTOMER_ID)
FROM CUSTOMER1
GROUP BY GRADE
HAVING GRADE > (SELECT AVG(GRADE)
FROM CUSTOMER1
WHERE CITY='BANGALORE');

```

2. Find the name and numbers of all salesmen who had more than one customer.

```

SELECT SALESMAN_ID, NAME
FROM SALESMAN A
WHERE 1 < (SELECT COUNT (*)
FROM CUSTOMER1
WHERE SALESMAN_ID=A.SALESMAN_ID);

```

3. List all salesmen and indicate those who have and don't have customers in their cities (Use UNION operation.)

```

SELECT SALESMAN.SALESMAN_ID, NAME, CUST_NAME, COMMISSION
FROM SALESMAN, CUSTOMER1
WHERE SALESMAN.CITY = CUSTOMER1.CITY
UNION
SELECT SALESMAN_ID, NAME, 'NO MATCH', COMMISSION
FROM SALESMAN
WHERE NOT CITY = ANY
(SELECT CITY
FROM CUSTOMER1)
ORDER BY 2 DESC;

```

4. Create a view that finds the salesman who has the customer with the highest order of a day.

```

CREATE VIEW ELITSALESMAN AS
SELECT B.ORD_DATE, A.SALESMAN_ID, A.NAME
FROM SALESMAN A, ORDERS B
WHERE A.SALESMAN_ID = B.SALESMAN_ID
AND B.PURCHASE_AMT=(SELECT MAX (PURCHASE_AMT)
FROM ORDERS C
WHERE C.ORD_DATE = B.ORD_DATE);

```

5. Demonstrate the DELETE operation by removing salesman with id 1000. All his orders must also be deleted.

Use ON DELETE CASCADE at the end of foreign key definitions while creating child table orders and then execute the following:



Use ON DELETE SET NULL at the end of foreign key definitions while creating child table customers and then executes the following:

```
DELETE FROM SALESMAN  
WHERE SALESMAN_ID=1000;
```

