
rinoh^{type}

Reference Guide

Release 0.5.5

Contents

5	Chapter 1: rinoh
7	Chapter 2: Sphinx Builder
8	Legacy Configuration Variables
11	Chapter 3: Style Sheets
11	Included Style Sheets
11	Default Matcher
17	Element Style Classes
91	Chapter 4: Standard Document Templates
91	Article
92	Book
97	Chapter 5: API Documentation
97	Attribute (<code>rinoh.attribute</code>)
98	Color (<code>rinoh.color</code>)
98	Dimension (<code>rinoh.dimension</code>)
99	Document (<code>rinoh.document</code>)
101	Drawing Primitives (<code>rinoh.draw</code>)
101	Flowable (<code>rinoh.flowable</code>)
104	Fonts and Typefaces (<code>rinoh.font</code>)
106	Images and Figures (<code>rinoh.image</code>)
108	Index (<code>rinoh.index</code>)
108	Language (<code>rinoh.language</code>)
113	Number (<code>rinoh.number</code>)
115	Paper sizes (<code>rinoh.paper</code>)
116	Paragraph (<code>rinoh.paragraph</code>)
120	Cross-References and Fields (<code>rinoh.reference</code>)
121	Structure (<code>rinoh.structure</code>)
124	Strings (<code>rinoh.strings</code>)
124	Style (<code>rinoh.style</code>)
126	Tables (<code>rinoh.table</code>)

127	Templates (<code>rinoh.template</code>)
139	Python Module Index
141	Index

Render a structured document to PDF.

```
usage: rinoh [-h] [-f FORMAT] [-o OPTION=VALUE] [-t NAME or FILENAME]
             [-s NAME or FILENAME] [-O FILENAME or DIRECTORY] [-p PAPER] [-i]
             [--list-templates] [--list-stylesheets] [--list-fonts]
             [FILENAME]
             [--list-formats] [--list-options FRONTEND] [--version]
             [--versions] [--docs]
             [input]
```

input

the document to render

-h, --help

show this help message and exit

-f <format>, --format <format>

the format of the input file (default: autodetect)

-o <option=value>, --option <option=value>

options to be passed to the input file reader

-t <name or filename>, --template <name or filename>

the document template or template configuration file to use (default: article)

-s <name or filename>, --stylesheet <name or filename>

the style sheet used to style the document elements (default: the template's default)

-O <filename or directory>, --output <filename or directory>

write the PDF output to FILENAME or to an existing DIRECTORY with a filename derived from the input filename (default: the current working directory)

-p <paper>, --paper <paper>

the paper size to render to (default: the template's default)

-i, --install-resources

automatically install missing resources (fonts, templates, style sheets) from PyPI

--list-templates

list the installed document templates and exit

--list-stylesheets

list the installed style sheets and exit

--list-fonts <filename>
list the installed fonts or, if FILENAME is given, write a PDF file displaying all the fonts

--list-formats
list the supported input formats and exit

--list-options <frontend>
list the options supported by the given frontend and exit

--version
show program's version number and exit

--versions
list versions of rinohtype and related software (for inclusion in bug reports)

--docs
open the online documentation in the default browser

`rinoh.frontend.sphinx` is a Sphinx extension module. It provides a Sphinx builder with the name *rinoh*. The builder recognizes the following `conf.py` options. Of these, only `rinoh_documents` (or `latex_documents`) is required.

rinoh_documents

Determines which PDF documents to build. Its format is a list of dictionaries, one for each document to be generated. The supported keys for these dictionaries are listed below. Two of them are required:

doc (required)

String that specifies the name of the master document (typically `index`).

target (required)

The name of the target PDF file without the extension.

The following keys allow overriding the content included on the document's title page and page headers/footers (depending on the template and its configuration). The values for text content can be plain text or `StyledText`.

logo (no default)

Path (absolute or relative to the location of the `conf.py` file) to an image file, typically included on the title page.

title (default: "project documentation")

The title of the document.

subtitle (default: "Release release")

Subtitle of the document.

author (default: "author")

The document's author.

date (default: determined from today and today_fmt)

The document (build) date.

The remaining keys control what is included in the document and the document template (configuration) to use.

toctree_only (default: False)

Must be `True` or `False`. If `true`, the document itself is not included in the output, only the documents referenced by it via TOC trees.

domain_indices (default: True)

If `true`, generate domain-specific indices in addition to the general index. It is equivalent to the `html_domain_indices` and `latex_domain_indices` configuration variables.

template (default: Book)

Determines the template used to render the document. It takes:

- the filename of a template configuration file,
- a `TemplateConfiguration` instance,

- the name of an installed template (see `rinoh --list-templates`), or
- a `DocumentTemplate` subclass

`rinoh_documents` will also accept other keys than those listed above. These items will be available as document metadata and can be used in a custom document template.

Example:

```
rinoh_documents = [
    dict(doc='index', target='manual', toctree_only=False,
         template='manual.rtt', logo='logo.pdf'),
    dict(doc='ref', target='reference', title='Reference Manual',
         template='reference.rtt', stamp='DRAFT'),
]
```

`rinoh_targets`

Limits rendering to the specified set of targets. This variable accepts either a list of strings or a string containing comma-separated values. The target names should match those set in `rinoh_documents`.

To render only the ‘manual’ target, you can set the following in `conf.py`:

```
rinoh_targets = ['manual']
```

The same can be achieved from the command line using the by using the string form with `sphinx-build -D`:

```
sphinx-build -b rinoh -D rinoh_targets="manual" source build
```

2.1 Legacy Configuration Variables

The configuration variables below are no longer supported. Instead, their functionality can now be configured per document in `rinoh_documents`.

`rinoh_template`

This configuration variable is **no longer supported** since the document template can be specified in `rinoh_documents` entries.

`rinoh_stylesheet`

This configuration variable is **no longer supported** since it is not obvious which style sheet will be used when the template configuration also specifies a style sheet. Please specify the style sheet to use in your template configuration file:

```
[TEMPLATE_CONFIGURATION]
name = My Book
template = book
stylesheet = my_stylesheet.rts
```

`rinoh_paper_size`

This configuration variable is **no longer supported** since it was not obvious which paper size was being used when the template configuration (`rinoh_template`) also specified a paper size. Please specify the `paper_size` to use in your template configuration file:

```
[TEMPLATE_CONFIGURATION]
name = My Book
template = book

[VARIABLES]
```



```
paper_size = A5
```

rinoh_logo

This configuration variable is **no longer supported** since the logo can be specified in the `rinoh_documents` entries.

rinoh_domain_indices

This configuration variable is **no longer supported** since the domain_indices can be specified in the `rinoh_documents` entries.

rinoh_metadata

This configuration variable is **no longer supported**. Metadata entries can now be added to `rinoh_documents` entries.

3.1 Included Style Sheets

These style sheets are included with rinohtype:

`rinohtype.stylesheets.sphinx`

Mostly a copy of the LaTeX style included with Sphinx

Entry point name: `sphinx`

`rinohtype.stylesheets.sphinx_article`

The Sphinx stylesheet adjusted for the article template

Entry point name: `sphinx_article`

`rinohtype.stylesheets.sphinx_base14`

The Sphinx stylesheet, but using the fonts from the PDF core set (yielding smaller PDF files)

Entry point name: `sphinx_base14`

Additional style sheets can be installed from PyPI. The installed style sheets can be listed using `rinohtype --list-stylesheets`.

3.2 Default Matcher

The default matcher provides the selectors for the styles used in the standard style sheets.

`rinohtype.stylesheets.matcher`

The default matcher defines the following styles

- title page rule: `HorizontalRuleStyle`
- title page logo: `FlowableStyle`
- title page title: `ParagraphStyle`
- title page subtitle: `ParagraphStyle`
- title page author: `ParagraphStyle`
- title page date: `ParagraphStyle`
- title page extra: `ParagraphStyle`
- front matter section title: `ParagraphStyle`
- body matter chapter label: `ParagraphStyle`
- body matter chapter number: `TextStyle`
- body matter chapter title: `ParagraphStyle`
- fallback: `TextStyle`
- italic: `TextStyle`

- **bold:** TextStyle
- **monospaced:** TextStyle
- **emphasis:** TextStyle
- **strong:** TextStyle
- **literal emphasis:** TextStyle
- **literal strong:** TextStyle
- **inline math:** TextStyle
- **inline definition:** TextStyle
- **quote:** TextStyle
- **file path:** TextStyle
- **keystrokes:** TextStyle
- **regular expression:** TextStyle
- **code with variable:** TextStyle
- **mail header:** TextStyle
- **MIME type:** TextStyle
- **newsgroup:** TextStyle
- **command:** TextStyle
- **make variable:** TextStyle
- **program:** TextStyle
- **man page:** TextStyle
- **window title:** TextStyle
- **UI control:** TextStyle
- **UI control accelerator:** TextStyle
- **menu cascade:** TextStyle
- **draft comment:** TextStyle
- **title reference:** TextStyle
- **error:** TextStyle
- **linked reference:** ReferenceStyle
- **external hyperlink:** TextStyle
- **broken hyperlink:** TextStyle
- **glossary inline definition:** TextStyle
- **body:** ParagraphStyle
- **code block:** ParagraphStyle
- **code block caption:** CaptionStyle
- **math block:** ParagraphStyle
- **graphviz code block:** ParagraphStyle
- **attribution:** ParagraphStyle
- **centered:** ParagraphStyle
- **line block:** ParagraphStyle
- **block quote:** GroupedFlowablesStyle
- **chapter:** SectionStyle
- **content chapter:** SectionStyle
- **heading level 1:** HeadingStyle
- **heading level 1 label:** TextStyle
- **unnumbered heading level 1:** HeadingStyle
- **heading level 2:** HeadingStyle
- **heading level 2 label:** TextStyle
- **unnumbered heading level 2:** HeadingStyle
- **heading level 3:** HeadingStyle
- **heading level 3 label:** TextStyle
- **unnumbered heading level 3:** HeadingStyle
- **heading level 4:** HeadingStyle
- **heading level 4 label:** TextStyle

- unnumbered heading level 4: HeadingStyle
- heading level 5: HeadingStyle
- heading level 5 label: TextStyle
- unnumbered heading level 5: HeadingStyle
- other heading levels: HeadingStyle
- appendix: SectionStyle
- appendix heading level 1: HeadingStyle
- appendix heading level 2: HeadingStyle
- appendix heading level 3: HeadingStyle
- appendix heading level 4: HeadingStyle
- appendix heading level 5: HeadingStyle
- title: ParagraphStyle
- prerequisites: GroupedFlowablesStyle
- prerequisites title: ParagraphStyle
- post requirement: GroupedFlowablesStyle
- abstract: GroupedFlowablesStyle
- abstract paragraph: ParagraphStyle
- example: GroupedFlowablesStyle
- example title: ParagraphStyle
- topic: GroupedFlowablesStyle
- topic title: ParagraphStyle
- rubric: ParagraphStyle
- sidebar: GroupedFlowablesStyle
- sidebar title: ParagraphStyle
- sidebar subtitle: ParagraphStyle
- list item label: ListItemLabelStyle
- list item body: GroupedFlowablesStyle
- list item paragraph: ParagraphStyle
- enumerated list: ListStyle
- enumerated list item: LabeledFlowableStyle
- enumerated list item label: ListItemLabelStyle
- nested enumerated list: ListStyle
- (table) enumerated list: ListStyle
- (table) enumerated list item: LabeledFlowableStyle
- (table) enumerated list item label: ListItemLabelStyle
- bulleted list: ListStyle
- compact bulleted list: ListStyle
- bulleted list item: LabeledFlowableStyle
- bulleted list item label: ListItemLabelStyle
- nested bulleted list: ListStyle
- (table) bulleted list: ListStyle
- (table) bulleted list item: LabeledFlowableStyle
- (table) bulleted list item label: ListItemLabelStyle
- steps list: ListStyle
- steps list title: ParagraphStyle
- steps list item: LabeledFlowableStyle
- steps list item label: ListItemLabelStyle
- unordered steps list: ListStyle
- unordered steps list title: ParagraphStyle
- unordered steps list item: LabeledFlowableStyle
- unordered steps list item label: ListItemLabelStyle
- choices list: ListStyle
- choices list item: LabeledFlowableStyle

- choices list item label: ListItemLabelStyle
- definition list: GroupedFlowablesStyle
- definition list item: LabeledFlowableStyle
- definition term: GroupedFlowablesStyle
- definition term paragraph: ParagraphStyle
- definition term classifier: TextStyle
- definition: GroupedFlowablesStyle
- definition paragraph: ParagraphStyle
- related links: GroupedFlowablesStyle
- related links section title: ParagraphStyle
- related links list: ListStyle
- related links list item: LabeledFlowableStyle
- related links list item label: ListItemLabelStyle
- related links list item paragraph: ReferencingParagraphStyle
- related link title reference: ReferenceStyle
- related link page reference: ReferenceStyle
- related link number reference: ReferenceStyle
- related link reference: ReferenceStyle
- versionmodified: TextStyle
- object description: LabeledFlowableStyle
- object signatures: GroupedFlowablesStyle
- object signature: ParagraphStyle
- object name: TextStyle
- additional name part: TextStyle
- object type: TextStyle
- object returns: TextStyle
- object parentheses: TextStyle
- object parameter list: TextStyle
- object parameter: TextStyle
- object parameter (no emphasis): TextStyle
- object brackets: TextStyle
- object optional parameter: TextStyle
- object annotation: TextStyle
- object description content: GroupedFlowablesStyle
- object description content paragraph: ParagraphStyle
- production list: GroupedFlowablesStyle
- production: LabeledFlowableStyle
- token name: ParagraphStyle
- token definition: ParagraphStyle
- field list: GroupedFlowablesStyle
- field list item: LabeledFlowableStyle
- field name: ParagraphStyle
- option list: GroupedFlowablesStyle
- option list item: LabeledFlowableStyle
- option: ParagraphStyle
- option string: TextStyle
- option argument: TextStyle
- admonition: AdmonitionStyle
- admonition title: ParagraphStyle
- admonition title paragraph: ParagraphStyle
- admonition inline title: TextStyle
- attention admonition: AdmonitionStyle
- attention admonition title: ParagraphStyle

- attention admonition title paragraph: ParagraphStyle
- attention admonition inline title: TextStyle
- caution admonition: AdmonitionStyle
- caution admonition title: ParagraphStyle
- caution admonition title paragraph: ParagraphStyle
- caution admonition inline title: TextStyle
- danger admonition: AdmonitionStyle
- danger admonition title: ParagraphStyle
- danger admonition title paragraph: ParagraphStyle
- danger admonition inline title: TextStyle
- error admonition: AdmonitionStyle
- error admonition title: ParagraphStyle
- error admonition title paragraph: ParagraphStyle
- error admonition inline title: TextStyle
- hint admonition: AdmonitionStyle
- hint admonition title: ParagraphStyle
- hint admonition title paragraph: ParagraphStyle
- hint admonition inline title: TextStyle
- important admonition: AdmonitionStyle
- important admonition title: ParagraphStyle
- important admonition title paragraph: ParagraphStyle
- important admonition inline title: TextStyle
- note admonition: AdmonitionStyle
- note admonition title: ParagraphStyle
- note admonition title paragraph: ParagraphStyle
- note admonition inline title: TextStyle
- tip admonition: AdmonitionStyle
- tip admonition title: ParagraphStyle
- tip admonition title paragraph: ParagraphStyle
- tip admonition inline title: TextStyle
- warning admonition: AdmonitionStyle
- warning admonition title: ParagraphStyle
- warning admonition title paragraph: ParagraphStyle
- warning admonition inline title: TextStyle
- seealso admonition: AdmonitionStyle
- seealso admonition title: ParagraphStyle
- seealso admonition title paragraph: ParagraphStyle
- seealso admonition inline title: TextStyle
- header: ParagraphStyle
- footer: ParagraphStyle
- footnote: NoteStyle
- footnote marker: NoteMarkerStyle
- footnote paragraph: ParagraphStyle
- footnote label: ParagraphStyle
- citation: NoteStyle
- citation marker: NoteMarkerStyle
- citation paragraph: ParagraphStyle
- citation label: ParagraphStyle
- image: FlowableStyle
- inline image: InlineFlowableStyle
- figure: FigureStyle
- figure image: FlowableStyle
- figure caption: CaptionStyle

- figure legend: `GroupedFlowablesStyle`
- figure legend paragraph: `ParagraphStyle`
- table of contents section: `SectionStyle`
- table of contents title: `HeadingStyle`
- table of contents: `TableOfContentsStyle`
- local table of contents: `TableOfContentsStyle`
- toc level 1: `TableOfContentsEntryStyle`
- toc level 2: `TableOfContentsEntryStyle`
- toc level 3: `TableOfContentsEntryStyle`
- toc level 4: `TableOfContentsEntryStyle`
- toc level 5: `TableOfContentsEntryStyle`
- toc level 6: `TableOfContentsEntryStyle`
- L3 toc level 3: `TableOfContentsEntryStyle`
- toc entry number reference field: `ReferenceStyle`
- list of figures section: `SectionStyle`
- list of figures: `ListOfStyle`
- list of figures entry: `ListOfEntryStyle`
- list of tables section: `SectionStyle`
- list of tables: `ListOfStyle`
- list of tables entry: `ListOfEntryStyle`
- table: `TableStyle`
- table with caption: `TableWithCaptionStyle`
- table caption: `CaptionStyle`
- choices table: `TableStyle`
- table cell: `TableCellStyle`
- table body cell background on even row: `TableCellBackgroundStyle`
- table body cell background on odd row: `TableCellBackgroundStyle`
- table body cell paragraph: `ParagraphStyle`
- table first column paragraph: `ParagraphStyle`
- table body cell list item number: `ParagraphStyle`
- table head cell: `TableCellStyle`
- table head cell background: `TableCellBackgroundStyle`
- table head cell paragraph: `ParagraphStyle`
- table cell left border: `TableCellBorderStyle`
- table cell top border: `TableCellBorderStyle`
- table cell right border: `TableCellBorderStyle`
- table cell bottom border: `TableCellBorderStyle`
- table top border: `TableCellBorderStyle`
- table bottom border: `TableCellBorderStyle`
- table left border: `TableCellBorderStyle`
- table right border: `TableCellBorderStyle`
- table head cell left border: `TableCellBorderStyle`
- table head cell right border: `TableCellBorderStyle`
- table head bottom border: `TableCellBorderStyle`
- table head left border: `TableCellBorderStyle`
- table head right border: `TableCellBorderStyle`
- table body top border: `TableCellBorderStyle`
- table body left border: `TableCellBorderStyle`
- table body right border: `TableCellBorderStyle`
- horizontal rule: `HorizontalRuleStyle`
- index: `IndexStyle`
- index section label: `ParagraphStyle`
- level 1 index entry: `ParagraphStyle`

- level 2 index entry: ParagraphStyle
- level 3 index entry: ParagraphStyle
- level 4 index entry: ParagraphStyle
- domain index entry name: TextStyle

3.3 Element Style Classes

These are the style classes corresponding to each type of document element. For each style class, the supported style attributes are listed along with the values that can be assigned to them in a style sheet.

<code>draw.LineStyle</code>	Style class for Line
<code>draw.ShapeStyle</code>	Style class for Shape
<code>flowable.FlowableStyle</code>	Style class for Flowable
<code>flowable.LabeledFlowableStyle</code>	Style class for LabeledFlowable
<code>flowable.GroupedFlowablesStyle</code>	Style class for GroupedFlowables
<code>flowable.FloatStyle</code>	Style class for Float
<code>image.CaptionStyle</code>	Style class for Caption
<code>image.FigureStyle</code>	Style class for Figure
<code>index.IndexStyle</code>	Style class for Index
<code>paragraph.ParagraphStyle</code>	Style class for Paragraph
<code>text.TextStyle</code>	Style class for Text
<code>inline.InlineFlowableStyle</code>	Style class for InlineFlowable
<code>reference.ReferencingParagraphStyle</code>	Style class for ReferencingParagraph
<code>reference.NoteMarkerStyle</code>	Style class for NoteMarker
<code>structure.SectionStyle</code>	Style class for Section
<code>structure.HeadingStyle</code>	Style class for Heading
<code>structure.ListStyle</code>	Style class for List
<code>structure.ListItemLabelStyle</code>	Style class for ListItemLabel
<code>structure.TableOfContentsStyle</code>	Style class for TableOfContents
<code>structure.TableOfContentsEntryStyle</code>	Style class for TableOfContentsEntry
<code>structure.AdmonitionStyle</code>	Style class for Admonition
<code>structure.HorizontalRuleStyle</code>	Style class for HorizontalRule
<code>table.TableStyle</code>	Style class for Table
<code>table.TableCellStyle</code>	Style class for TableCell
<code>table.TableCellBorderStyle</code>	Style class for TableCellBorder
<code>table.TableCellBackgroundStyle</code>	Style class for TableCellBackground

3.3.1 LineStyle

```
class rinoh.draw.LineStyle ( base=None, **attributes )
```

Style class for Line

stroke

Width and color used to draw the line

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: 1pt, #000

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

3.3.2 ShapeStyle

```
class rinoh.draw.ShapeStyle ( base=None, **attributes )
```

Style class for Shape

fill_color

Color to fill the shape

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #e5e5e5

stroke

Width and color used to draw the line (inherited from `LineStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: 1pt, #000

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

3.3.3 FlowableStyle

```
class rinoh.flowable.FlowableStyle ( base=None, **attributes )
```

Style class for Flowable

width

Width to render the flowable at

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align

Horizontal alignment of the flowable

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable

Accepts Stroke: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable

Accepts Stroke: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from *Style*)

Accepts Bool: true or false

Default: false

3.3.4 LabeledFlowableStyle

```
class rinoh.flowable.LabeledFlowableStyle ( base=None, **attributes )
```

Style class for *LabeledFlowable*

label_min_width

Minimum label width

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 12pt

label_max_width

Maximum label width

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 80pt

label_spacing

Spacing between a label and the labeled flowable

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3pt

align_baselines

Line up the baselines of the label and the labeled flowable

Accepts Bool: true or false

Default: true

wrap_label

Wrap the label at *label_max_width*

Accepts Bool: true or false

Default: false

width

Width to render the flowable at (inherited from `FlowableStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts `Break`: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.5 GroupedFlowablesStyle

```
class rinoh.flowable.GroupedFlowablesStyle ( base=None, **attributes )
```

Style class for GroupedFlowables

width

Width to render the flowable at (inherited from FlowableStyle)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill (overrides FlowableStyle default)

title

Title to precede the flowables

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Spacing between flowables

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

same_page

Keep all flowables on a single page, if possible.

Accepts Bool: true or false

Default: false

horizontal_align

Horizontal alignment of the flowable (inherited from FlowableStyle)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

3.3.6 FloatStyle

```
class rinoh.flowable.FloatStyle ( base=None, **attributes )
```

Style class for Float

float

Float the flowable to the top or bottom of the current page, to a dedicated page, or sideways to a dedicated page

Accepts FloatLocation: none, here, sideways

Default: None

width

Width to render the flowable at (inherited from `FlowableStyle`)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false
Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)
Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)
Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)
Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

3.3.7 CaptionStyle

`class rinoh.image.CaptionStyle (base=None, **attributes)`

Style class for `Caption`

number_format

How numbers are formatted (inherited from `ParagraphStyle`)

Accepts NumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number (overrides `ParagraphStyle` default)

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from `ParagraphStyle`)

Accepts Integer: a natural number (positive integer)

Default: 1 (overrides `ParagraphStyle` default)

width

Width to render the flowable at (inherited from `ParagraphStyle`)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

indent_first

Indentation of the first line of text (inherited from `ParagraphStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from `ParagraphStyle`)

Accepts `LineSpacing`: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: `<spacing type>(<arg1>, <arg2>, ...)`

Default: default

text_align

Alignment of text to the margins (inherited from `ParagraphStyle`)

Accepts `TextAlign`: left, right, center, justify

Default: justify

tab_stops

List of tab positions (inherited from `ParagraphStyle`)

Accepts `TabStopList`: a comma-separated list of tab stops. A tab stop is specified as `<position> [align] [fill string]`, where `position` (`Dimension`) is required and `align` (`TabAlign`) and `fill string` (string enclosed in quotes) are optional.

Default: (no value)

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If `None`, only show this item's number label. (inherited from `ParagraphStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: `'text string' (style name)`

Default: '.'

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts Bool: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts Typeface: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts FontWeight: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts FontSlant: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts FontWidth: ultra-condensed, extra-condensed, condensed,

semi-condensed, normal, medium, semi-expanded, expanded,
extra-expanded, ultra-expanded
Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.8 FigureStyle

```
class rinoh.image.FigureStyle ( base=None, **attributes )
```

Style class for `Figure`

float

Float the flowable to the top or bottom of the current page, to a dedicated page, or sideways to a dedicated page (inherited from `FloatStyle`)

Accepts `FloatLocation`: none, here, sideways

Default: None

width

Width to render the flowable at (inherited from `FlowableStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by

a comma (,)
Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)
Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)
Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)
Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)
Accepts Break: none, any, left, right, any restart, left restart, right restart
Default: None

hide

Suppress rendering this element (inherited from `Style`)
Accepts Bool: true or false
Default: false

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

same_page

Keep all flowables on a single page, if possible. (inherited from `GroupedFlowablesStyle`)
Accepts Bool: true or false
Default: false

3.3.9 IndexStyle

class `rinoh.index.IndexStyle` (*base=None, **attributes*)
Style class for Index

initials

Group index entries based on their first letter
Accepts Bool: true or false
Default: true

width

Width to render the flowable at (inherited from `GroupedFlowablesStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

same_page

Keep all flowables on a single page, if possible. (inherited from `GroupedFlowablesStyle`)

Accepts `Bool`: true or false

Default: false

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false
Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from FlowableStyle)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from Style)

Accepts Bool: true or false

Default: false

3.3.10 ParagraphStyle

```
class rinoh.paragraph.ParagraphStyle ( base=None, **attributes )
```

Style class for Paragraph

width

Width to render the flowable at (inherited from FlowableStyle)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill (overrides FlowableStyle default)

indent_first

Indentation of the first line of text

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text

Accepts LineSpacing: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align

Alignment of text to the margins

Accepts TextAlign: left, right, center, justify

Default: justify

tab_stops

List of tab positions

Accepts TabStopList: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position (Dimension) is required and align (TabAlign) and fill string (string enclosed in quotes) are optional.

Default: (no value)

number_format

How numbers are formatted (inherited from NumberStyle)

Accepts NumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None (overrides NumberStyle default)

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If `None`, only show this item's number label.

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: ' . '

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative)

Accepts `Integer`: a natural number (positive integer)

Default: (no value)

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false
Default: false

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)
Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)
Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)
Accepts Bool: true or false
Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)
Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.
Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)
Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black
Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)
Accepts `FontSlant`: upright, oblique, italic
Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)
Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded
Default: 5

font_size

Height of characters (inherited from `TextStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)
Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

3.3.11 TextStyle

class rinoh.text.**TextStyle** (*base=None, **attributes*)

Style class for Text

typeface

Typeface to set the text in

Accepts Typeface: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height

Accepts FontWeight: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font

Accepts FontSlant: upright, oblique, italic

Default: upright

font_width

Stretch of the characters

Accepts FontWidth: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font

Accepts FontVariant: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position

Accepts TextPosition: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing

Accepts Bool: true or false

Default: true

ligatures

Run letters together where possible

Accepts Bool: true or false

Default: true

hyphenate

Allow words to be broken over two lines

Accepts Bool: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word

Accepts Integer: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US'

Accepts Locale: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words

Accepts NoBreakAfter: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

3.3.12 InlineFlowableStyle

```
class rinoh.inline.InlineFlowableStyle ( base=None, **attributes )
```

Style class for `InlineFlowable`

baseline

The location of the flowable's baseline relative to the bottom edge

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

width

Width to render the flowable at (inherited from `FlowableStyle`)

Accepts `FlowableWidth`: `auto`, `fill` or a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `auto`

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: `left`, `right`, `center`

Default: `left`

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0`

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0`

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0`

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0`

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0`

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0`

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0`

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0`

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0`

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: `true` or `false`

Default: `false`

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: `none`

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts `Break`: `none`, `any`, `left`, `right`, `any restart`, `left restart`, `right restart`

Default: `None`

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: `true` or `false`

Default: `false`

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text

string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)
Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

3.3.13 ReferencingParagraphStyle

```
class rinoh.reference.ReferencingParagraphStyle ( base=None, **attributes )
```

Style class for `ReferencingParagraph`

text

The text content of this paragraph
Accepts `ReferenceText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: '{TITLE}'

width

Width to render the flowable at (inherited from `ParagraphStyle`)
Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: fill

indent_first

Indentation of the first line of text (inherited from `ParagraphStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from `ParagraphStyle`)
Accepts `LineSpacing`: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)
Default: default

text_align

Alignment of text to the margins (inherited from `ParagraphStyle`)
Accepts `TextAlign`: left, right, center, justify
Default: justify

tab_stops

List of tab positions (inherited from `ParagraphStyle`)
Accepts `TabStopList`: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position (`Dimension`) is required and align (`TabAlign`) and fill string (string enclosed in quotes) are optional.
Default: (no value)

number_format

How numbers are formatted (inherited from `ParagraphStyle`)

Accepts `NumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from `ParagraphStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: ' . '

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from `ParagraphStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: (no value)

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts Bool: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts Typeface: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: `#000`

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: `normal`, `small capital`, `oldstyle figures`

Default: `normal`

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: `normal`, `superscript`, `subscript`

Default: `normal`

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: `true` or `false`

Default: `true`

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: `true` or `false`

Default: `true`

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: `true` or `false`

Default: `true`

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: `2`

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as `'en_US'` (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the `<language ID>_<region ID>` format

Default: `en_US`

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: `language-default`, or a space-separated list of words

Default: `language-default`

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (`'` or `"`), optionally followed by a style name enclosed in braces: `'text string' (style name)`

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.14 NoteMarkerStyle

```
class rinoh.reference.NoteMarkerStyle ( base=None, **attributes )
```

Style class for NoteMarker

type

How the reference should be displayed (inherited from `ReferenceStyle`)

Accepts `ReferenceType`: reference, number, title, page, custom

Default: number (overrides `ReferenceStyle` default)

link

Create a hyperlink to the reference target (inherited from `ReferenceStyle`)

Accepts `Bool`: true or false

Default: true

quiet

If the given reference type does not exist for the target, resolve to an empty string instead of making a fuss about it (inherited from `ReferenceStyle`)

Accepts `Bool`: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded,

extra-expanded, ultra-expanded
Default: 5

font_size

Height of characters (inherited from `TextStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)
Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)
Accepts `FontVariant`: normal, small capital, oldstyle figures
Default: normal

position

Vertical text position (inherited from `TextStyle`)
Accepts `TextPosition`: normal, superscript, subscript
Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)
Accepts `Bool`: true or false
Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)
Accepts `Bool`: true or false
Default: true

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)
Accepts `Bool`: true or false
Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)
Accepts `Integer`: a natural number (positive integer)
Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)
Accepts `Locale`: locale identifier in the <language ID>_<region ID> format
Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)
Accepts `NoBreakAfter`: language-default, or a space-separated list of words
Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

number_format

How numbers are formatted (inherited from `NumberStyle`)

Accepts `NumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts `Bool`: true or false

Default: false

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.15 SectionStyle

```
class rinoh.structure.SectionStyle ( base=None, **attributes )
```

Style class for `Section`

show_in_toc

List this section in the table of contents

Accepts `Bool`: true or false

Default: true

width

Width to render the flowable at (inherited from `GroupedFlowablesStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

same_page

Keep all flowables on a single page, if possible. (inherited from `GroupedFlowablesStyle`)

Accepts `Bool`: true or false

Default: false

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false
Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from FlowableStyle)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from Style)

Accepts Bool: true or false

Default: false

3.3.16 HeadingStyle

```
class rinoh.structure.HeadingStyle ( base=None, **attributes )
```

Style class for Heading

keep_with_next

Keep this flowable and the next on the same page (inherited from FlowableStyle)

Accepts Bool: true or false

Default: true (overrides FlowableStyle default)

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from ParagraphStyle)

Accepts Integer: a natural number (positive integer)

Default: -1 (overrides ParagraphStyle default)

width

Width to render the flowable at (inherited from ParagraphStyle)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

indent_first

Indentation of the first line of text (inherited from ParagraphStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from ParagraphStyle)

Accepts LineSpacing: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align

Alignment of text to the margins (inherited from ParagraphStyle)

Accepts TextAlign: left, right, center, justify

Default: justify

tab_stops

List of tab positions (inherited from ParagraphStyle)

Accepts `TabStopList`: a comma-separated list of tab stops. A tab stop is specified as `<position> [align] [fill string]`, where `position` (`Dimension`) is required and `align` (`TabAlign`) and `fill string` (string enclosed in quotes) are optional.

Default: (no value)

number_format

How numbers are formatted (inherited from `ParagraphStyle`)

Accepts `NumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from `ParagraphStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: ' . '

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts `Bool`: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.17 ListStyle

class `rinoh.structure.ListStyle (base=None, **attributes)`

Style class for List

ordered

This list is ordered or unordered

Accepts `Bool`: true or false

Default: false

bullet

Bullet to use in unordered lists

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: ' • '

width

Width to render the flowable at (inherited from `GroupedFlowablesStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

same_page

Keep all flowables on a single page, if possible. (inherited from `GroupedFlowablesStyle`)

Accepts `Bool`: true or false

Default: false

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

number_format

How numbers are formatted (inherited from `NumberStyle`)

Accepts NumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts `Bool`: `true` or `false`

Default: `false`

3.3.18 ListItemLabelStyle

class `rinoh.structure.ListItemLabelStyle` (*base=None, **attributes*)

Style class for `ListItemLabel`

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If `None`, only show this item's number label. (inherited from `ParagraphStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value) (overrides `ParagraphStyle` default)

width

Width to render the flowable at (inherited from `ParagraphStyle`)

Accepts `FlowableWidth`: `auto`, `fill` or a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `fill`

indent_first

Indentation of the first line of text (inherited from `ParagraphStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0pt`

line_spacing

Spacing between the baselines of two successive lines of text (inherited from `ParagraphStyle`)

Accepts `LineSpacing`: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: `<spacing type>(<arg1>, <arg2>, ...)`

Default: `default`

text_align

Alignment of text to the margins (inherited from `ParagraphStyle`)

Accepts `TextAlign`: `left`, `right`, `center`, `justify`

Default: `justify`

tab_stops

List of tab positions (inherited from `ParagraphStyle`)

Accepts `TabStopList`: a comma-separated list of tab stops. A tab stop is specified as `<position> [align] [fill string]`, where `position` (`Dimension`) is required and `align` (`TabAlign`) and `fill string` (string enclosed in quotes) are optional.

Default: (no value)

number_format

How numbers are formatted (inherited from `ParagraphStyle`)

Accepts `NumberFormat`: `none`, `number`, `symbol`, `lowercase character`, `uppercase character`, `lowercase roman`, `uppercase roman`

Default: None

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from `ParagraphStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: (no value)

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: `true` or `false`

Default: `false`

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: `none`

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts `Break`: `none`, `any`, `left`, `right`, `any restart`, `left restart`, `right restart`

Default: `None`

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: `'text string'` (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts `Bool`: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.19 TableOfContentsStyle

```
class rinoh.structure.TableOfContentsStyle ( base=None, **attributes )
    Style class for TableOfContents

    depth
        The number of section levels to include in the table of contents
        Accepts Integer: a natural number (positive integer)
        Default: 3

    width
        Width to render the flowable at (inherited from GroupedFlowablesStyle)
        Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in,
        pc, mm, cm, %, /2, /4)
        Default: fill

    title
        Title to precede the flowables (inherited from GroupedFlowablesStyle)
        Accepts StyledText: a list of styled text strings, separated by spaces. A styled text
        string is a quoted string (' or "), optionally followed by a style name enclosed in
        braces: 'text string' (style name)
        Default: (no value)

    flowable_spacing
        Spacing between flowables (inherited from GroupedFlowablesStyle)
        Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
        Default: 0

    same_page
        Keep all flowables on a single page, if possible. (inherited from
        GroupedFlowablesStyle)
        Accepts Bool: true or false
        Default: false

    horizontal_align
        Horizontal alignment of the flowable (inherited from FlowableStyle)
        Accepts HorizontalAlignment: left, right, center
        Default: left

    space_above
        Vertical space preceding the flowable (inherited from FlowableStyle)
        Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
        Default: 0

    space_below
        Vertical space following the flowable (inherited from FlowableStyle)
        Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
        Default: 0

    margin_left
        Left margin (inherited from FlowableStyle)
        Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
        Default: 0
```

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by

a comma (,)
Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)
Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)
Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)
Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)
Accepts Break: none, any, left, right, any restart, left restart, right restart
Default: None

hide

Suppress rendering this element (inherited from `Style`)
Accepts Bool: true or false
Default: false

indent_first

Indentation of the first line of text (inherited from `ParagraphStyle`)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from `ParagraphStyle`)
Accepts LineSpacing: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: `<spacing type>(<arg1>, <arg2>, ...)`
Default: default

text_align

Alignment of text to the margins (inherited from `ParagraphStyle`)
Accepts TextAlign: left, right, center, justify
Default: justify

tab_stops

List of tab positions (inherited from `ParagraphStyle`)
Accepts TabStopList: a comma-separated list of tab stops. A tab stop is specified as `<position> [align] [fill string]`, where position (`Dimension`) is required and align (`TabAlign`) and fill string (string enclosed in quotes) are optional.
Default: (no value)

number_format

How numbers are formatted (inherited from `ParagraphStyle`)
Accepts NumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from `ParagraphStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: ' . '

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from `ParagraphStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: (no value)

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts `Bool`: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed,

semi-condensed, normal, medium, semi-expanded, expanded,
extra-expanded, ultra-expanded
Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

3.3.20 TableOfContentsEntryStyle

```
class rinoh.structure.TableOfContentsEntryStyle ( base=None, **attributes )
```

Style class for `TableOfContentsEntry`

text

The text content of this paragraph (inherited from `ReferencingParagraphStyle`)

Accepts `ReferenceText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '{NUMBER}' '\t' '{TITLE}' '\t' '{PAGE}' (overrides `ReferencingParagraphStyle` default)

width

Width to render the flowable at (inherited from `ParagraphStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

indent_first

Indentation of the first line of text (inherited from `ParagraphStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from `ParagraphStyle`)

Accepts `LineSpacing`: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align

Alignment of text to the margins (inherited from `ParagraphStyle`)

Accepts `TextAlign`: left, right, center, justify

Default: justify

tab_stops

List of tab positions (inherited from `ParagraphStyle`)

Accepts `TabStopList`: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position (`Dimension`) is

required and `align` (`TabAlign`) and `fill` string (string enclosed in quotes) are optional.

Default: (no value)

number_format

How numbers are formatted (inherited from `ParagraphStyle`)

Accepts `NumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from `ParagraphStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: ' . '

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from `ParagraphStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: (no value)

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false
Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)
Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)
Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)
Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)
Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)
Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts Bool: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts Typeface: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: `#000`

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: `normal`, `small capital`, `oldstyle figures`

Default: `normal`

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: `normal`, `superscript`, `subscript`

Default: `normal`

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: `true` or `false`

Default: `true`

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: `true` or `false`

Default: `true`

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: `true` or `false`

Default: `true`

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: `2`

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as `'en_US'` (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the `<language ID>_<region ID>` format

Default: `en_US`

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: `language-default`, or a space-separated list of words

Default: `language-default`

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (`'` or `"`), optionally followed by a style name enclosed in braces: `'text string' (style name)`

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.21 AdmonitionStyle

```
class rinoh.structure.AdmonitionStyle ( base=None, **attributes )
```

Style class for `Admonition`

inline_title

Show the admonition's title inline with the body text, if possible

Accepts `Bool`: true or false

Default: true

width

Width to render the flowable at (inherited from `GroupedFlowablesStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

same_page

Keep all flowables on a single page, if possible. (inherited from `GroupedFlowablesStyle`)

Accepts `Bool`: true or false

Default: false

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

3.3.22 HorizontalRuleStyle

```
class rinoh.structure.HorizontalRuleStyle ( base=None, **attributes )
```

Style class for `HorizontalRule`

width

Width to render the flowable at (inherited from `FlowableStyle`)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

stroke

Width and color used to draw the line (inherited from `LineStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: 1pt, #000

3.3.23 TableStyle

```
class rinoh.table.TableStyle ( base=None, **attributes )
```

Style class for Table

column_widths

Absolute or relative widths of each column

Accepts ColumnWidths: a whitespace-delimited list of column widths; `Dimensions` (absolute width), integers (relative width) and/or 'auto' (automatic width)

Default: none

split_minimum_rows

The minimum number of rows to display when the table is split across pages

Accepts Integer: a natural number (positive integer)

Default: (no value)

repeat_head

Repeat the head when the table is split across pages

Accepts Bool: true or false

Default: false

width

Width to render the flowable at (inherited from `FlowableStyle`)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.24 TableCellStyle

```
class rinoh.table.TableCellStyle ( base=None, **attributes )
```

Style class for `TableCell`

vertical_align

Vertical alignment of the cell contents within the available space

Accepts `VerticalAlign`: top, middle, bottom

Default: middle

width

Width to render the flowable at (inherited from `GroupedFlowablesStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

same_page

Keep all flowables on a single page, if possible. (inherited from `GroupedFlowablesStyle`)

Accepts `Bool`: true or false

Default: false

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

3.3.25 TableCellBorderStyle

```
class rinoh.table.TableCellBorderStyle ( base=None, **attributes )
```

Style class for `TableCellBorder`

stroke

Width and color used to draw the line (inherited from `LineStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none (overrides `LineStyle` default)

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

3.3.26 TableCellBackgroundStyle

```
class rinoh.table.TableCellBackgroundStyle ( base=None, **attributes )
```

Style class for `TableCellBackground`

fill_color

Color to fill the shape (inherited from `ShapeStyle`)

Accepts `Color`: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: `none` (overrides `ShapeStyle` default)

stroke

Width and color used to draw the line (inherited from `LineStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none` (overrides `LineStyle` default)

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: `true` or `false`

Default: `false`

Rinohtype includes a number of document templates. These are configurable and therefore should cater for most documents.

4.1 Article

The article template consists of a title page, an optional table of contents and the body text. By default, it uses a single numbering style for all pages and the same template for even and odd pages.

```
class    rinohtemplates.article.Article ( document_tree, configuration=None,  
backend=None )
```

stylesheet

The stylesheet to use for styling document elements (inherited from `DocumentTemplate`)

Accepts `StyleSheet`: the name of an Section 3.1 or the filename of a stylesheet file (with the `.rts` extension)

Default: `sphinx_article` (= `rinohtemplates.stylesheets.sphinx_article`) (overrides `DocumentTemplate` default)

abstract_location

Where to place the abstract

Accepts `AbstractLocation`: title, body

Default: title

parts

The parts making up this document (inherited from `DocumentTemplate`)

Accepts `PartsList`: a space-separated list of document part template names

Default: contents (overrides `DocumentTemplate` default)

language

The main language of the document (inherited from `DocumentTemplate`)

Accepts `Language`: the code of one of the supported languages

Default: EN (English)

strings

Strings to override standard element names (inherited from `DocumentTemplate`)

Accepts `Strings`: strings need to be entered in INI sections named after the `StringCollection` subclasses

Default: none

contents

base: None

Overrides these defaults:

- `page_number_format = number`

Type

`ArticleContentsPartTemplate`**page**

base: None

Overrides these defaults:

- `page_size = $(paper_size)`
- `left_margin = 1.2cm`
- `right_margin = 1.2cm`
- `top_margin = 1.8cm`
- `bottom_margin = 1.6cm`
- `header_footer_distance = 2pt`

Type

`ArticleBodyPageTemplate`**contents_page**base: `page`

Type

`ArticleBodyPageTemplate`**Configuration**alias of `ArticleConfiguration`**ConfigurationFile**alias of `ArticleConfigurationFile`**class** `rinoh.templates.article.AbstractLocation`

Where to place the article's abstract

Accepts: `title`, `body`

4.2 Book

The book template consists of a title page, the table of contents, the body text and an index. The front matter pages are numbered using lowercase roman numerals. The template uses different templates for even and odd pages.

class `rinoh.templates.book.Book` (*document_tree*, *configuration=None*, *backend=None*)**stylesheet**The stylesheet to use for styling document elements (inherited from `DocumentTemplate`)*Accepts* `StyleSheet`: the name of an Section 3.1 or the filename of a stylesheet file (with the `.rts` extension)*Default*: `sphinx` (= `rinoh.stylesheets.sphinx`) (overrides `DocumentTemplate` default)**parts**The parts making up this document (inherited from `DocumentTemplate`)

Accepts `PartsList`: a space-separated list of document part template names
Default: `title front_matter contents back_matter` (overrides `DocumentTemplate default`)

language

The main language of the document (inherited from `DocumentTemplate`)

Accepts `Language`: the code of one of the supported languages

Default: `EN` (English)

strings

Strings to override standard element names (inherited from `DocumentTemplate`)

Accepts `Strings`: strings need to be entered in INI sections named after the `StringCollection` subclasses

Default: none

cover

base: None

Overrides these defaults:

- `drop_if_empty = False`
- `page_number_format = None`
- `end_at_page = left`

Type

`FixedDocumentPartTemplate`

title

base: None

Overrides these defaults:

- `page_number_format = number`
- `end_at_page = left`

Type

`TitlePartTemplate`

front_matter

base: None

Overrides these defaults:

- `flowables = [TableOfContentsSection(), ListOfFiguresSection(), ListOfTablesSection()]`
- `page_number_format = lowercase roman`
- `end_at_page = left`

Type

`FixedDocumentPartTemplate`

contents

base: None

Overrides these defaults:

- `page_number_format = number`
- `end_at_page = left`

Type

`ContentsPartTemplate`

back_matter

base: None

Overrides these defaults:

- page_number_format = continue
- end_at_page = left

Type

BackMatterTemplate

page

base: None

Overrides these defaults:

- page_size = \$(paper_size)
- left_margin = 1in
- right_margin = 1in
- top_margin = 1in
- bottom_margin = 1in

Type

BodyPageTemplate

cover_page

base: page

Type

BodyPageTemplate

title_page

base: page

Type

TitlePageTemplate

front_matter_page

base: page

Overrides these defaults:

- header_footer_distance = 0
- header_text = None

Type

BodyPageTemplate

front_matter_right_page

base: front_matter_page

Overrides these defaults:

- footer_text = '\t' '\t' '{PAGE_NUMBER}'
- chapter_header_text = None
- chapter_footer_text = '\t' '\t' '{PAGE_NUMBER}'
- chapter_title_height = 2.5in
- chapter_title_flowables = [<rinoh.paragraph.Paragraph object at 0x7f795884b2e0>]
- sideways = right

Type

BodyPageTemplate

front_matter_left_page

base: front_matter_page

Overrides these defaults:

- footer_text = '{PAGE_NUMBER}'
- sideways = left

Type

BodyPageTemplate

contents_page

base: page

Overrides these defaults:

- header_footer_distance = 0

Type

BodyPageTemplate

contents_right_page

base: contents_page

Overrides these defaults:

- header_text = '\t' '\t' '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- footer_text = '{SECTION_NUMBER(2)}' '. ' '{SECTION_TITLE(2)}' '\t' '\t' '{PAGE_NUMBER}'
- chapter_header_text = None
- chapter_footer_text = '\t' '\t' '{PAGE_NUMBER}'
- chapter_title_height = 2.4in
- chapter_title_flowables = [<rinoh.paragraph.Paragraph object at 0x7f795884b040>, <rinoh.paragraph.Paragraph object at 0x7f795884acb0>]
- sideways = right

Type

BodyPageTemplate

contents_left_page

base: contents_page

Overrides these defaults:

- header_text = '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- footer_text = '{PAGE_NUMBER}' '\t' '\t' '{SectionTitles.chapter}' ' ' '{SECTION_NUMBER(1)}' '. ' '{SECTION_TITLE(1)}'
- sideways = left

Type

BodyPageTemplate

back_matter_page

base: page

Overrides these defaults:

- columns = 2
- header_footer_distance = 0

Type

BodyPageTemplate

back_matter_right_page

base: back_matter_page

Overrides these defaults:

- header_text = '\t' '\t' '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- footer_text = '{SECTION_TITLE(1)}' '\t' '\t' '{PAGE_NUMBER}'
- chapter_header_text = None
- chapter_footer_text = '\t' '\t' '{PAGE_NUMBER}'
- chapter_title_height = 2.5in
- chapter_title_flowables = [<rinoh.paragraph.Paragraph object at 0x7f795884b2e0>]
- sideways = right

Type

BodyPageTemplate

back_matter_left_page

base: back_matter_page

Overrides these defaults:

- header_text = '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- footer_text = '{PAGE_NUMBER}' '\t' '\t' '{SECTION_TITLE(1)}'
- sideways = left

Type

BodyPageTemplate

Configuration

alias of BookConfiguration

ConfigurationFile

alias of BookConfigurationFile

Note

The API documentation is still incomplete.

5.1 Attribute (`rinoh.attribute`)

class `rinoh.attribute.AcceptNoneAttributeType`

Accepts 'none' (besides other values)

class `rinoh.attribute.OptionSet`

Accepts the values listed in values

Accepts:

class `rinoh.attribute.Attribute (accepted_type, default_value, description)`

Descriptor used to describe a style attribute

class `rinoh.attribute.OverrideDefault (default_value)`

Overrides the default value of an attribute defined in a superclass

class `rinoh.attribute.AttributesDictionary (base=None, **attributes)`

class `rinoh.attribute.RuleSet (name, base=None, source=None, **kwargs)`

find_source (*name*)

Find top-most ruleset where configuration *name* is defined

class `rinoh.attribute.RuleSetFile (filename, base=None, source=None, **kwargs)`

property location

Textual representation of this source

property root

Directory path for resolving paths relative to this source

class `rinoh.attribute.Bool`

Expresses a binary choice

class `rinoh.attribute.Integer`

Accepts natural numbers

exception `rinoh.attribute.ParseError`

5.2 Color (`rinoh.color`)

class `rinoh.color.Color` (*red, green, blue, alpha=1*)

Color defined by component values

Parameters

red : float

red component (0 .. 1)

blue : float

blue component (0 .. 1)

green : float

green component (0 .. 1)

alpha : float

opacity (0 .. 1)

property **rgba**

classmethod **parse_string** (*string, source*)

classmethod **doc_format** ()

class `rinoh.color.HexColor` (*string*)

Color defined as a hexadecimal string

Parameters

string : str

#RGBA or #RRGGBBAA (# and A are optional)

class `rinoh.color.Gray` (*luminance, alpha=1*)

Shade of gray

Parameters

luminance : float

brightness (0 .. 1)

alpha : float

opacity (0 .. 1)

5.3 Dimension (`rinoh.dimension`)

Classes for expressing dimensions: lengths, widths, line thickness, etc.

Each dimension is expressed in terms of a unit. Several common units are defined here as constants. To create a new dimension, multiply number with a unit:

```
height = 100*PT
width = 50*PERCENT
```

Fractional dimensions are evaluated within the context they are defined in. For example, the width of a `Flowable` is evaluated with respect to the total width available to it.

class `rinoh.dimension.Dimension` (*value=0, unit=None*)

A simple dimension

Parameters

value : int or float

the magnitude of the dimension

unit : DimensionUnit

the unit this dimension is expressed in. Default: `PT`.

grow (value)

Grow this dimension (in-place)

The `value` is interpreted as a magnitude expressed in the same unit as this dimension.

Parameters

value : int or float

the amount to add to the magnitude of this dimension

Returns

`Dimension` – this (grewed) dimension itself

```
rinoh.dimension.PT = DimensionUnit(1.0, 'pt')
```

PostScript points

```
rinoh.dimension.PICA = DimensionUnit(12.0, 'pc')
```

computer pica

```
rinoh.dimension.INCH = DimensionUnit(72.0, 'in')
```

imperial/US inch

```
rinoh.dimension.MM = DimensionUnit(2.8346456692913384, 'mm')
```

millimeter

```
rinoh.dimension.CM = DimensionUnit(28.346456692913385, 'cm')
```

centimeter

```
rinoh.dimension.PERCENT = FractionUnit(100, '%')
```

fraction of 100

```
rinoh.dimension.QUARTERS = FractionUnit(4, '/4')
```

fraction of 4

5.4 Document (`rinoh.document`)

```
class rinoh.document.DocumentTree ( flowables, options=None, style=None, source=None )
```

Holds the document's contents as a tree of flowables

Parameters

flowables : list[Flowable]

the list of top-level flowables

options : Reader

frontend-specific options

```
class rinoh.document.Document ( document_tree, stylesheet, language, strings=None, backend=None )
```

Renders a document tree to pages

Parameters

document_tree : DocumentTree

a tree of the document's contents

stylesheet : StyleSheet
 style sheet used to style document elements

language : Language
 the language to use for standard strings

strings : Strings
 overrides localized strings provided by *language*

backend=None
 the backend used for rendering the document

render (filename_root=None, file=None)
 Render the document repeatedly until the output no longer changes due to cross-references that need some iterations to converge.

5.4.1 Pages

class rinoh.document.Page (document_part, number, paper, orientation='portrait', display_sideways=None)

A single page in a document.

A Page is a Container, so other containers can be added as children.

Parameters

document_part : DocumentPart
 the document part this page is part of

number : int
 the 1-based index of this page in the document part

paper : Paper
 determines the dimensions of this page

orientation : PageOrientation
 the orientation of this page

display_sideways : Sideways
 display the page rotated

property page
 Returns the page itself.

render ()
 Render the contents of this container to its canvas.
 Note that the rendered contents need to be `place()`d on the parent container's canvas before they become visible.

place ()
 Place this container's canvas onto the parent container's canvas.

class rinoh.document.PageOrientation
 Accepts: portrait, landscape

class rinoh.document.PageType
 Accepts: left, right, any

class rinoh.document.PageNumberFormat
 How (or if) page numbers are displayed
 Accepts: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman, continue

5.5 Drawing Primitives (`rinoh.draw`)

class `rinoh.draw.Stroke` (*width, color*)

The display properties of a line

Parameters

width : `Dimension`

the width of the line

color : `Color`

the color of the line

class `rinoh.draw.Line` (*start, end, style=None, parent=None*)

Draws a line

Parameters

start : `2-tuple`

coordinates for the start point of the line

end : `2-tuple`

coordinates for the end point of the line

style_class

alias of `LineStyle`

class `rinoh.draw.Shape` (*style=None, parent=None*)

Base class for closed shapes

style_class

alias of `ShapeStyle`

class `rinoh.draw.Polygon` (*points, style=None, parent=None*)

class `rinoh.draw.Rectangle` (*bottom_left, width, height, style=None, parent=None*)

5.6 Flowable (`rinoh.flowable`)

class `rinoh.flowable.Flowable` (*align=None, width=None, id=None, style=None, parent=None, source=None*)

A document element that can be “flowed” into a container on the page.

A flowable can adapt to the width of the container, or it can horizontally align itself in the container.

Parameters

align : `HorizontalAlignment`

horizontal alignment of the flowable

width : `FlowableWidth` or `DimensionBase`

the width of the flowable.

class `rinoh.flowable.FlowableState` (*flowable, _initial=True*)

Stores a flowable’s rendering state, which can be copied.

This enables saving the rendering state at certain points in the rendering process, so rendering can later be resumed at those points, if needed.

5.6.1 No-Output Flowables

These flowables do not directly place anything on the page. All except `DummyFlowable` do have side-effects however. Some of these side-effects affect the rendering of the document in an indirect way.

class `rinoh.flowable.DummyFlowable` (*id=None, parent=None*)

A flowable that does not directly place anything on the page.

Subclasses can produce side-effects to affect the output in another way.

class `rinoh.flowable.AnchorFlowable` (*id=None, parent=None*)

A dummy flowable that registers a destination anchor.

Places a destination for the flowable's ID at the current cursor position.

class `rinoh.flowable.SetMetadataFlowable` (*parent=None, **metadata*)

A dummy flowable that stores metadata in the document.

The metadata is passed as keyword arguments. It will be available to other flowables during the rendering stage.

class `rinoh.flowable.WarnFlowable` (*message, parent=None*)

A dummy flowable that emits a warning during the rendering stage.

Parameters

message : `str`

the warning message to emit

class `rinoh.flowable.PageBreak` (*page_break='any'*)

5.6.2 Labeled Flowables

class `rinoh.flowable.LabeledFlowable` (*label, flowable, id=None, style=None, parent=None*)

A flowable with a label.

The flowable and the label are rendered side-by-side. If the label exceeds the *label_max_width* style attribute value, the flowable is rendered below the label.

Parameters

label : `Flowable`

the label for the flowable

flowable : `Flowable`

the flowable to label

style_class

alias of `LabeledFlowableStyle`

prepare (*flowable_target*)

Determine number labels and register references with the document

render (*container, last_descender, state, label_column_width=None, space_below=0, **kwargs*)

Renders the flowable's content to *container*, with the flowable's top edge lining up with the container's cursor. *descender* is the descender height of the preceding line or *None*.

class `rinoh.flowable.LabeledFlowableState` (*flowable, content_flowable_state, _initial=True*)

5.6.3 Grouping Flowables

```
class rinoh.flowable.GroupedFlowables ( align=None, width=None, id=None, style=None, parent=None, source=None )
```

Groups a list of flowables and renders them one below the other.

Makes sure that a flowable for which *keep_with_next* is enabled is not separated from the flowable that follows it.

Subclasses should implement `flowables()`.

```
style_class
```

alias of `GroupedFlowablesStyle`

```
flowables ( container )
```

Generator yielding the `Flowables` to group

```
render ( container, descender, state, first_line_only=False, **kwargs )
```

Renders the flowable's content to *container*, with the flowable's top edge lining up with the container's cursor. *descender* is the descender height of the preceding line or *None*.

```
class rinoh.flowable.GroupedFlowablesState ( groupedflowables, flowables, first_flowable_state=None, _initial=True, _index=0 )
```

```
class rinoh.flowable.StaticGroupedFlowables ( flowables, align=None, width=None, id=None, style=None, parent=None, source=None )
```

Groups a static list of flowables.

Parameters

```
flowables : iterable[Flowable]
```

the flowables to group

```
flowables ( container )
```

Generator yielding the `Flowables` to group

```
build_document ( flowable_target )
```

Set document metadata and populate front and back matter

```
prepare ( flowable_target )
```

Determine number labels and register references with the document

```
class rinoh.flowable.GroupedLabeledFlowables ( align=None, width=None, id=None, style=None, parent=None, source=None )
```

Groups a list of labeled flowables, lining them up.

```
render ( container, descender, state, **kwargs )
```

Renders the flowable's content to *container*, with the flowable's top edge lining up with the container's cursor. *descender* is the descender height of the preceding line or *None*.

5.6.4 Floating Flowables

```
class rinoh.flowable.Float ( align=None, width=None, id=None, style=None, parent=None, source=None )
```

A flowable that can optionally be placed elsewhere on the page.

If this flowable's *float* style attribute is set to `True`, it is not flowed in line with the surrounding flowables, but it is instead flowed into another container pointed to by the former's `Container.float_space` attribute.

This is typically used to place figures and tables at the top or bottom of a page, instead of in between paragraphs.

style_class

alias of `FloatStyle`

flow (*container*, *last_descender*, *state=None*, ***kwargs*)

Flow this flowable into *container* and return the vertical space consumed.

The flowable's contents are preceded by a vertical space with a height as specified in its style's *space_above* attribute. Similarly, the flowed content is followed by a vertical space with a height given by the *space_below* style attribute.

5.6.5 Styling Properties

class `rinoh.flowable.HorizontalAlignment`

Controls horizontal placement

Accepts: `left`, `right`, `center`

class `rinoh.flowable.FlowableWidth`

Controls the width of a flowable

Accepts: `auto`, `fill` or a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

5.7 Fonts and Typefaces (`rinoh.font`)

Classes for fonts and typefaces.

class `rinoh.font.Font` (*filename*, *weight*, *slant*, *width*)

A collection of glyphs in a particular style

This is a base class for classes that parse different font formats. See `rinoh.font.type1` and `rinoh.font.opentype`.

Parameters

filename : `str`

filename of the font file to load

weight : `FontWeight`

weight of the font

slant : `FontSlant`

slant of the font

width : `FontWidth`

width of the font

encoding

If no encoding is set for the `Font`, glyphs are addressed by glyph ID (and thus support more than 256 glyphs).

get_glyph_metrics (*char*, *variant*)

Return the glyph metrics for a particular character

If the glyph of requested font variant is not present in the font, the *normal* variant is returned instead. If that is not present either, an exception is raised.

Parameters

char : `str` of length 1

the character for which to find the glyph

variant : FontVariant
the variant of the glyph to return

Returns

GlyphMetrics – the requested glyph metrics

Raises

MissingGlyphException – when the requested glyph is not present in the font

get_ligature (*glyph, successor_glyph*)

Return the ligature to replace the given glyphs

If no ligature is defined in the font for the given glyphs, return *None*.

Parameters

glyph : GlyphMetrics
the first of the glyphs to combine

successor_glyph : GlyphMetrics
the second of the glyphs to combine

Returns

GlyphMetrics or *None* – the ligature to replace the given glyphs

get_kerning (*a, b*)

Look up the kerning for two glyphs

Parameters

a : GlyphMetrics
the first of the glyphs

b : GlyphMetrics
the second of the glyphs

Returns

float – the kerning value in font units

class *rinoh.font.Typeface* (*name, *fonts*)

A set of fonts that share common design features

The fonts collected in a typeface differ in weight, width and/or slant.

Parameters

***fonts : Font**
the fonts that make up this typeface

fonts ()

Generator yielding all fonts of this typeface

Yields

Font – the next font in this typeface

get_font (*weight=400, slant='upright', width=5*)

Return the font matching or closest to the given style

If a font with the given weight, slant and width is available, return it. Otherwise, return the font that is closest in style.

Parameters

weight : FontWeight
weight of the font

slant : FontSlant
slant of the font
width : FontWidth
width of the font

Returns

Font – the requested font

class rinoh.font.style.**FontWeight**

Accepts: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

class rinoh.font.style.**FontSlant**

Accepts: upright, oblique, italic

class rinoh.font.style.**FontWidth**

Accepts: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

class rinoh.font.style.**FontVariant**

Accepts: normal, small capital, oldstyle figures

class rinoh.font.style.**TextPosition**

Accepts: normal, superscript, subscript

5.8 Images and Figures (**rinoh.image**)

class rinoh.image.**Image** (*filename_or_file*, *scale=1.0*, *width=None*, *height=None*, *dpi=None*, *rotate=0*, *limit_width=<rinoh.dimension.Fraction object>*, *align=None*, *id=None*, *style=None*, *parent=None*, *source=None*)

class rinoh.image.**InlineImage** (*filename_or_file*, *scale=1.0*, *width=None*, *height=None*, *dpi=None*, *rotate=0*, *baseline=None*, *id=None*, *style=None*, *parent=None*, *source=None*)

arguments

alias of InlineImageArgs

class rinoh.image.**BackgroundImage** (*filename_or_file*, *scale=1.0*, *width=None*, *height=None*, *dpi=None*, *rotate=0*, *limit_width=<rinoh.dimension.Fraction object>*, *align=None*, *id=None*, *style=None*, *parent=None*, *source=None*)

Image to place in the background of a page

Takes the same arguments as Image.

arguments

alias of ImageArgs

class rinoh.image.**ImageArgs** (*base=None*, ***attributes*)

limit_width

Limit the image width when none of *scale*, *width* and *height* are given and the image would be wider than the container

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 100%

align

How to align the image within the page

Accepts `HorizontalAlignment`: left, right, center

Default: left

file_or_filename

Path to the image file (inherited from `ImageArgsBase`)

Accepts `ImagePath`: path to an image file enclosed in quotes

Default: none

scale

Scaling factor for the image (inherited from `ImageArgsBase`)

Accepts `Scale`: fit, fill or a float larger than 0

Default: fit

width

The width to scale the image to (inherited from `ImageArgsBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: none

height

The height to scale the image to (inherited from `ImageArgsBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: none

dpi

Overrides the DPI value set in the image (inherited from `ImageArgsBase`)

Accepts `Integer`: a natural number (positive integer)

Default: (no value)

rotate

Angle in degrees to rotate the image (inherited from `ImageArgsBase`)

Accepts `Integer`: a natural number (positive integer)

Default: (no value)

class `rinoh.image.Scale`

Scaling factor for images

Can be a numerical value where a value of 1 keeps the image's original size or one of values.

Accepts: fit, fill or a float larger than 0

class `rinoh.image.Caption` (*content*, *custom_label=None*, *align=None*, *width=None*, *id=None*, *style=None*, *parent=None*, *source=None*)

style_class

alias of `CaptionStyle`

class `rinoh.image.Figure` (*flowables*, *align=None*, *width=None*, *id=None*, *style=None*, *parent=None*, *source=None*)

style_class

alias of `FigureStyle`

```

class rinoh.image.ListOfFiguresSection
    list_class
        alias of ListOfFigures

class rinoh.image.ListOfFigures ( local=False, id=None, style=None, parent=None )

```

5.9 Index (rinoh.index)

```

class rinoh.index.IndexSection ( title=None, flowables=None, style=None )

class rinoh.index.Index ( id=None, style=None, parent=None )
    style_class
        alias of IndexStyle

    flowables ( container )
        Generator yielding the Flowables to group

class rinoh.index.IndexLabel ( content, custom_label=None, align=None, width=None,
id=None, style=None, parent=None, source=None )

class rinoh.index.IndexTerm ( *levels )

class rinoh.index.InlineIndexTarget ( index_terms, *args, **kwargs )
    to_string ( flowable_target )
        Return the text content of this styled text.

class rinoh.index.IndexTarget ( index_terms, parent=None )
    flow ( container, last_descender, state=None, **kwargs )
        Flow this flowable into container and return the vertical space consumed.
        The flowable's contents are preceded by a vertical space with a height as specified in its
        style's space_above attribute. Similarly, the flowed content is followed by a vertical space
        with a height given by the space_below style attribute.

```

5.10 Language (rinoh.language)

```

class rinoh.language.Language ( code, name )
    Collects localized strings for a particular language

    Parameters
        code : str
            short code identifying the language
        name : str
            native name of the language

    languages
        Dictionary mapping codes to Languages

```

The following languages are supported:

```

rinoh.language.CS = Language('cs', 'Česky')
    Localized strings for Česky

```

- SectionTitles
- Contents
 - Obsah
- List_of_figures
 - Seznam obrázků
- List_of_tables
 - Seznam tabulek
- Chapter
 - Kapitola
- Index
 - Rejstřík
- AdmonitionTitles
- Attention
 - Pozor!
- Caution
 - Pozor!
- Danger
 - !NEBEZPEČÍ!
- Error
 - Chyba
- Hint
 - Poznámka
- Important
 - Důležité
- Note
 - Poznámka
- Tip Tip
- Warning
 - Varování
- Seealso
 - Viz také

```
rinoh.language.EN = Language('en', 'English')
Localized strings for English
SectionTitles
Contents
  Table of Contents
List_of_figures
  List of Figures
List_of_tables
  List of Tables
```

- Chapter
 - Chapter
- Index
 - Index
- AdmonitionTitles
- Attention
 - Attention!
- Caution
 - Caution!
- Danger
 - !DANGER!
- Error
 - Error
- Hint
 - Hint
- Important
 - Important
- Note
 - Note
- Tip Tip
- Warning
 - Warning
- Seealso
 - See also

```
rinoh.language.FR = Language('fr', 'Français')
```

- Localized strings for Français

- SectionTitles

- Contents

- Table des Matières

- List_of_figures

- Liste des Figures

- List_of_tables

- Liste des Tableaux

- Chapter

- Chapitre

- Index

- Index

- AdmonitionTitles

- Attention

- Attention!

Caution
 Prudence!
 Danger
 !DANGER!
 Error
 Erreur
 Hint
 Conseil
 Important
 Important
 Note
 Note
 Tip Astuce
 Warning
 Avertissement
 Seealso
 Voir aussi

```
rinoh.language.IT = Language('it', 'Italiano')
```

Localized strings for Italiano

SectionTitles

Contents

Contenuti

List_of_figures

Elenco delle Figure

List_of_tables

Elenco delle Tabelle

Chapter

Capitolo

Index

Indice

AdmonitionTitles

Attention

Attenzione!

Caution

Prudenza!

Danger

!PERICOLO!

Error

Errore

Hint

Consiglio

Important

Importante

Note

Nota

Tip Suggestimento

Warning

Avvertimento

Seealso

Vedi anche

```
rinoh.language.NL = Language('nl', 'Nederlands')
```

Localized strings for Nederlands

SectionTitles

Contents

Inhoudsopgave

List_of_figures

Lijst van Figuren

List_of_tables

Lijst van Tabellen

Chapter

Hoofdstuk

Index

Index

AdmonitionTitles

Attention

Opgelet!

Caution

Pas op!

Danger

!GEVAAR!

Error

Fout

Hint

Hint

Important

Belangrijk

Note

Noot

Tip Tip

Warning

Waarschuwing

Seealso

Zie ook

```
rinoh.language.PL = Language('pl', 'Polski')
```

Localized strings for Polski

SectionTitles

Contents

Spis Treści

List_of_figures

Spis Ilustracji

List_of_tables

Spis Tabel

Chapter

Rozdział

Index

Skorowidz

AdmonitionTitles

Attention

Uwaga!

Caution

Ostrożnie!

Danger

!NIEBEZPIECZEŃSTWO!

Error

Błąd

Hint

Wskazówka

Important

Ważne

Note

Notatka

Tip Porada

Warning

Ostrzeżenie

Seealso

Zobacz również

5.11 Number (rinoh.number)

```
class rinoh.number.NumberFormat
```

How (or if) numbers are displayed

Instead of a numbering format, it's possible to supply a custom label (`StyledText`) to

show instead of the number.

Accepts: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

class rinoh.number.**Label** (*custom_label=None*)

Mixin class that formats a label

Parameters

custom_label : **StyledText**

a frontend can supply a custom label to use instead of an automatically determined label (typically a number)

class rinoh.number.**LabelStyle** (*base=None, **attributes*)

Style class for Label

label_prefix

Text to prepend to the label

Accepts **StyledText**: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label

Accepts **StyledText**: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified

Accepts **Bool**: true or false

Default: false

hide

Suppress rendering this element (inherited from **Style**)

Accepts **Bool**: true or false

Default: false

class rinoh.number.**NumberStyle** (*base=None, **attributes*)

Style class for Number

number_format

How numbers are formatted

Accepts **NumberFormat**: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

label_prefix

Text to prepend to the label (inherited from **LabelStyle**)

Accepts **StyledText**: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from **LabelStyle**)

Accepts **StyledText**: a list of styled text strings, separated by spaces. A styled text

string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)
Accepts `Bool`: true or false
Default: false

hide

Suppress rendering this element (inherited from `Style`)
Accepts `Bool`: true or false
Default: false

`rinoh.number.format_number (number, format)`
Format *number* according the given *format* (`NumberFormat`)

5.12 Paper sizes (`rinoh.paper`)

The `Paper` class and a number of predefined paper formats.

class `rinoh.paper.Paper (name, width, height)`

Defines a paper size.

Parameters

name : str

the name of this paper type

width : Dimension

the (portrait) width of this paper type

height : Dimension

the (portrait) height of this paper type

`rinoh.paper.A0 = Paper('A0', width=841*MM, height=1189*MM)`

`rinoh.paper.A1 = Paper('A1', width=594*MM, height=841*MM)`

`rinoh.paper.A2 = Paper('A2', width=420*MM, height=594*MM)`

`rinoh.paper.A3 = Paper('A3', width=297*MM, height=420*MM)`

`rinoh.paper.A4 = Paper('A4', width=210*MM, height=297*MM)`

`rinoh.paper.A5 = Paper('A5', width=148*MM, height=210*MM)`

`rinoh.paper.A6 = Paper('A6', width=105*MM, height=148*MM)`

`rinoh.paper.A7 = Paper('A7', width=74*MM, height=105*MM)`

`rinoh.paper.A8 = Paper('A8', width=52*MM, height=74*MM)`

`rinoh.paper.A9 = Paper('A9', width=37*MM, height=52*MM)`

`rinoh.paper.A10 = Paper('A10', width=26*MM, height=37*MM)`

`rinoh.paper.LETTER = Paper('letter', width=8.5*INCH, height=11*INCH)`

`rinoh.paper.LEGAL = Paper('legal', width=8.5*INCH, height=14*INCH)`

```

rinoh.paper.JUNIOR_LEGAL = Paper('junior legal', width=8*INCH,
height=5*INCH)

rinoh.paper.LEDGER = Paper('ledger', width=17*INCH, height=11*INCH)

rinoh.paper.TABLOID = Paper('tabloid', width=11*INCH, height=17*INCH)

```

5.13 Paragraph (**rinoh.paragraph**)

```

class rinoh.paragraph.ParagraphBase ( custom_label=None, align=None, width=None,
id=None, style=None, parent=None, source=None )

```

Base class for paragraphs

A paragraph holds styled text and other line elements to be flowed into a container.

style_class

alias of ParagraphStyle

prepare (*flowable_target*)

Determine number labels and register references with the document

render (*container, descender, state, space_below=0, first_line_only=False*)

Typeset the paragraph

The paragraph is typeset in the given container starting below the current cursor position of the container. When the end of the container is reached, the rendering state is preserved to continue setting the rest of the paragraph when this method is called with a new container.

Parameters

container : Container

the container to render to

descender : float or None

descender height of the preceding line

state : ParagraphState

the state where rendering will continue

first_line_only : bool

typeset only the first line

```

class rinoh.paragraph.Paragraph ( content, custom_label=None, align=None, width=None,
id=None, style=None, parent=None, source=None )

```

```

class rinoh.paragraph.ParagraphState ( paragraph, language, span_index=0,
group_index=None, nested_flowable_state=None, _first_word=None, _initial=True )

```

5.13.1 Styled Text (**rinoh.text**)

```

class rinoh.text.StyledText ( id=None, style=None, parent=None, source=None )

```

Base class for text that has a TextStyle associated with it.

to_string (*flowable_target*)

Return the text content of this styled text.

is_script (*container*)

Returns *True* if this styled text is super/subscript.

script_level (*container*)
Nesting level of super/subscript.

height (*container*)
Font size after super/subscript size adjustment.

y_offset (*container*)
Vertical baseline offset (up is positive).

property items
The list of items in this StyledText.

style_class
alias of `TextStyle`

class `rinoh.text.SingleStyledText` (*text*, *style=None*, *parent=None*, *source=None*)
Text with a single style applied

class `rinoh.text.MixedStyledText` (*text_or_items*, *id=None*, *style=None*, *parent=None*, *source=None*)

Concatenation of styled text

Parameters

text_or_items : **str**, **StyledText** or iterable of these
mixed styled text

style=None
see `Styled`

parent=None
see `DocumentElement`

prepare (*flowable_target*)
Determine number labels and register references with the document

append (*item*)
Append *item* (`StyledText` or `str`) to the end of this mixed-styled text.
The parent of *item* is set to this mixed-styled text.

property items
The list of items in this StyledText.

copy (*parent=None*)
Return a shallow copy of the list.

class `rinoh.text.Locale`
Selects a language

class `rinoh.text.NoBreakAfter` (*iterable=()*, */*)
List of words after which no line break will be allowed

5.13.2 Inline Elements (`rinoh.inline`)

class `rinoh.inline.InlineFlowable` (*baseline=None*, *id=None*, *style=None*, *parent=None*, *source=None*)

style_class
alias of `InlineFlowableStyle`

5.13.3 Styling Properties

class `rinoh.paragraph.TextAlign`
Text justification
Accepts: left, right, center, justify

Line Spacing

class `rinoh.paragraph.LineSpacing`
Base class for line spacing types
Line spacing is defined as the distance between the baselines of two consecutive lines of text in a paragraph.

advance (*line, last_descender, container*)
Return the distance between the descender of the previous line and the baseline of the current line.

class `rinoh.paragraph.DefaultSpacing`
The default line spacing as specified by the font.

advance (*line, last_descender, container*)
Return the distance between the descender of the previous line and the baseline of the current line.

class `rinoh.paragraph.ProportionalSpacing` (*factor*)
Line spacing proportional to the line height

Parameters

factor : float
amount by which the line height is multiplied to obtain the line spacing

advance (*line, last_descender, container*)
Return the distance between the descender of the previous line and the baseline of the current line.

class `rinoh.paragraph.FixedSpacing` (*pitch, minimum=ProportionalSpacing(1.0)*)

Fixed line spacing, with optional minimum spacing

Parameters

pitch : Dimension
the distance between the baseline of two consecutive lines of text

minimum : LineSpacing
the minimum line spacing to prevents lines with large fonts (or inline elements) from overlapping; set to `None` if no minimum is required, set to `None`

advance (*line, last_descender, container*)
Return the distance between the descender of the previous line and the baseline of the current line.

class `rinoh.paragraph.Leading` (*leading*)
Line spacing determined by the space in between two lines

Parameters

leading : Dimension
the space between the bottom of a line and the top of the next line of text

advance (*line*, *last_descender*, *container*)

Return the distance between the descender of the previous line and the baseline of the current line.

The following standard line spacings have been predefined:

`rinoh.paragraph.DEFAULT = DefaultSpacing()`

The default line spacing as specified by the font.

`rinoh.paragraph.STANDARD = ProportionalSpacing(1.2)`

Line spacing of 1.2 times the line height.

`rinoh.paragraph.SINGLE = ProportionalSpacing(1.0)`

Line spacing equal to the line height (no leading).

`rinoh.paragraph.DOUBLE = ProportionalSpacing(2.0)`

Line spacing of double the line height.

Tabulation

class `rinoh.paragraph.TabAlign`

Alignment of text with respect to a tab stop

Accepts: left, right, center

class `rinoh.paragraph.TabStop` (*position*, *align*= 'left', *fill*=None)

Horizontal position for aligning text of successive lines

Parameters

position

tab stop position

align : `TabAlign`

the alignment of text with respect to the tab stop position

fill : `str`

string pattern to fill the empty tab space with

get_position (*line_width*)

Return the absolute position of this tab stop.

class `rinoh.paragraph.TabStopList` (*iterable*=(), /)

List of tab stop positions (with alignment and fill string)

5.13.4 Rendering Internals

class `rinoh.paragraph.Glyph` (*metrics*, *width*, *char*)

class `rinoh.paragraph.GlyphsSpan` (*span*, *chars_to_glyphs*, *glyphs*=[])

5.13.5 Miscellaneous Internals

class `rinoh.paragraph.HyphenatorStore`

5.14 Cross-References and Fields (`rinoh.reference`)

```
class rinoh.reference.Reference ( target_id, *args, **kwargs )

class rinoh.reference.ReferenceField ( type=None, custom_title=None, style=None,
parent=None, source=None )

class rinoh.reference.ReferenceText ( id=None, style=None, parent=None, source=None
)

class rinoh.reference.ReferenceType
    Accepts: reference, number, title, page, custom

class rinoh.reference.ReferencingParagraph ( target_id_or_flowable, id=None,
style=None, parent=None )

    style_class
        alias of ReferencingParagraphStyle

    target_style ( document )
        Filter selection on the style attribute of the target flowable

    target_has_class ( document )
        Filter selection on a class of the target flowable

    target_has_classes ( document )
        Filter selection on a set of classes of the target flowable

    target_is_of_type ( document )
        Filter selection on the type of the target flowable

class rinoh.reference.Note ( flowable, id=None, style=None, parent=None )

    style_class
        alias of NoteStyle

    flow ( container, last_descender, state=None, footnote=False, **kwargs )
        Flow this flowable into container and return the vertical space consumed.
        The flowable's contents are preceded by a vertical space with a height as specified in its
        style's space_above attribute. Similarly, the flowed content is followed by a vertical space
        with a height given by the space_below style attribute.

class rinoh.reference.NoteMarkerBase ( custom_label=None, **kwargs )

    style_class
        alias of NoteMarkerStyle

    prepare ( flowable_target )
        Determine number labels and register references with the document

class rinoh.reference.NoteMarkerByID ( target_id, *args, **kwargs )

class rinoh.reference.NoteMarkerWithNote ( referenceable, type='number', **kwargs )

    prepare ( flowable_target )
        Determine number labels and register references with the document
```



```
class rinoh.reference.Field ( type, id=None, style=None, parent=None, source=None )
```

5.15 Structure (rinoh.structure)

5.15.1 Sections

```
class rinoh.structure.Section ( flowables, align=None, width=None, id=None, style=None,  
parent=None, source=None )
```

A subdivision of a document

A section usually has a heading associated with it, which is optionally numbered.

```
class rinoh.structure.Heading ( content, custom_label=None, align=None, width=None,  
id=None, style=None, parent=None, source=None )
```

The title for a section

Parameters

title : **StyledText**
this heading's text

style_class
alias of `HeadingStyle`

prepare (*container*)
Determine number labels and register references with the document

flow (*container*, *last_descender*, *state=None*, ***kwargs*)
Flow this flowable into *container* and return the vertical space consumed.
The flowable's contents are preceded by a vertical space with a height as specified in its style's *space_above* attribute. Similarly, the flowed content is followed by a vertical space with a height given by the *space_below* style attribute.

```
class rinoh.structure.SectionTitles ( **strings )
```

Collection of localized titles for common sections

contents
Title for the table of contents section
Type
`String`

list_of_figures
Title for the list of figures section
Type
`String`

list_of_tables
Title for the list of tables section
Type
`String`

chapter
Label for top-level sections

Type
String

index
Title for the index section

Type
String

5.15.2 Lists

```
class rinoh.structure.List ( list_items, start_index=1, id=None, style=None, parent=None )

    style_class
        alias of ListStyle

class rinoh.structure.DefinitionList ( flowables, align=None, width=None, id=None,
style=None, parent=None, source=None )
```

5.15.3 Table of Contents

```
class rinoh.structure.TableOfContentsSection

class rinoh.structure.TableOfContents ( local=False, id=None, style=None,
parent=None )

    style_class
        alias of TableOfContentsStyle

    flowables ( container )
        Generator yielding the Flowables to group

class rinoh.structure.TableOfContentsEntry ( flowable, id=None, style=None,
parent=None )

    style_class
        alias of TableOfContentsEntryStyle
```

5.15.4 Admonitions

```
class rinoh.structure.Admonition ( flowables, title=None, type=None, id=None,
style=None, parent=None )

    style_class
        alias of AdmonitionStyle

    flowables ( container )
        Generator yielding the Flowables to group

class rinoh.structure.AdmonitionTitles ( **strings )
    Collection of localized titles for common admonitions

    attention
        Title for attention admonitions
```

```

    Type
        String

caution
    Title for caution admonitions
    Type
        String

danger
    Title for danger admonitions
    Type
        String

error
    Title for error admonitions
    Type
        String

hint
    Title for hint admonitions
    Type
        String

important
    Title for important admonitions
    Type
        String

note
    Title for note admonitions
    Type
        String

tip
    Title for tip admonitions
    Type
        String

warning
    Title for warning admonitions
    Type
        String

seealso
    Title for see-also admonitions
    Type
        String

```

5.15.5 Horizontal Rule

class `rinoh.structure.HorizontalRule` (*align=None, width=None, id=None, style=None, parent=None, source=None*)

style_class

alias of `HorizontalRuleStyle`

render (*container, descender, state, **kwargs*)

Renders the flowable's content to *container*, with the flowable's top edge lining up with the container's cursor. *descender* is the descender height of the preceding line or *None*.

5.16 Strings (`rinoh.strings`)

class `rinoh.strings.String` (*description*)

Descriptor used to describe a configurable string

Parameters

description : str

a short description for this string

class `rinoh.strings.StringCollection` (***strings*)

A collection of related configurable strings

Subclasses

- `AdmonitionTitles`
- `SectionTitles`
- `UserStrings`

class `rinoh.strings.UserStrings` (***strings*)

Collection of user-specified strings

Unlike other string collections, these are not limited to a predefined set.

Attributes:

class `rinoh.strings.Strings` (**string_collections*)

Stores several `StringCollections`

class `rinoh.strings.StringField` (*strings_class, key, style=None, parent=None, source=None*)

Styled text that will be substituted with a configured string

The displayed string is either the localized string as determined by the language set for the document or the user-supplied string passed to the `TemplateConfiguration`.

5.17 Style (`rinoh.style`)

class `rinoh.style.Styled` (*id=None, style=None, parent=None, source=None*)

A document element who's style can be configured.

Parameters

style : str, Style

the style to associate with this element. If *style* is a string, the corresponding style is lookup up in the document's style sheet by means of selectors.

style_class

The `Style` subclass that corresponds to this `Styled` subclass.

configuration_class = `None`

property has_id

Filter selection on an ID of this `Styled`

property has_class

Filter selection on a class of this `Styled`

property has_classes

Filter selection on a set of classes of this `Styled`

class `rinoh.style.Style (base=None, **attributes)`

Dictionary storing style attributes.

The style attributes associated with this `Style` are specified as class attributes of type `Attribute`.

Style attributes can also be accessed as object attributes.

hide

Suppress rendering this element

Accepts Bool: `true` or `false`

Default: `false`

5.17.1 Style Sheet

class `rinoh.style.StyleSheet (name, matcher=None, base=None, source=None, description=None, pygments_style=None, **user_options)`

Dictionary storing a collection of related styles by name.

Styles stored in a `StyleSheet` can refer to their base style by name.

Parameters

name : str

a label for this style sheet

matcher : StyledMatcher

the matcher providing the selectors the styles contained in this style sheet map to.
If no matcher is given and *base* is specified, the *base*'s matcher is used. If *base* is not set, the default matcher is used.

base : StyleSheet or str

the style sheet to extend

description : str

a short string describing this style sheet

pygments_style : str

the Pygments style to use for styling code blocks

get_selector (name)

Find a selector mapped to a style in this or a base style sheet.

Parameters

name : str

a style name

Returns

`Selector` – the selector mapped to the style *name*

Raises

KeyError – if the style *name* was not found in this or a base style sheet

class `rinoh.style.StyleSheetFile` (*filename*, *base=None*, *source=None*, ***kwargs*)

Loads styles defined in a *.rts* file (INI format).

Parameters

filename : `str`

the path to the style sheet file

`StyleSheetFile` takes the same optional arguments as `StyleSheet`. These can also be specified in the [STYLESHEET] section of the style sheet file. If an argument is specified in both places, the one passed as an argument overrides the one specified in the style sheet file.

class `rinoh.style.StyledMatcher` (*mapping_or_iterable=None*, ***kwargs*)

Dictionary mapping labels to selectors.

This matcher can be initialized in the same way as a `dict` by passing a mapping, an iterable and/or keyword arguments.

update (***F* [, *E*]) → `None`. Update *D* from dict/iterable *E* and *F*.

If *E* is present and has a `.keys()` method, then does: for *k* in *E*: *D*[*k*] = *E*[*k*] If *E* is present and lacks a `.keys()` method, then does: for *k*, *v* in *E*: *D*[*k*] = *v* In either case, this is followed by: for *k* in *F*: *D*[*k*] = *F*[*k*]

5.18 Tables (`rinoh.table`)

class `rinoh.table.Table` (*body*, *head=None*, *align=None*, *width=None*, *column_widths=None*, *id=None*, *style=None*, *parent=None*)

style_class

alias of `TableStyle`

prepare (*flowable_target*)

Determine number labels and register references with the document

render (*container*, *last_descender*, *state*, *space_below=0*, ***kwargs*)

Renders the flowable's content to *container*, with the flowable's top edge lining up with the container's cursor. *descender* is the descender height of the preceding line or `None`.

class `rinoh.table.TableWithCaption` (*flowables*, *align=None*, *width=None*, *id=None*, *style=None*, *parent=None*, *source=None*)

style_class

alias of `TableWithCaptionStyle`

class `rinoh.table.TableSection` (*rows*, *style=None*, *parent=None*)

prepare (*flowable_target*)

Determine number labels and register references with the document

class `rinoh.table.TableHead` (*rows*, *style=None*, *parent=None*)

class `rinoh.table.TableBody` (*rows*, *style=None*, *parent=None*)

```

class rinoh.table.TableRow ( cells, style=None, parent=None )
    prepare ( flowable_target )
        Determine number labels and register references with the document

    get_rowspanned_columns ( )
        Return a dictionary mapping column indices to the number of columns spanned.

class rinoh.table.TableCell ( flowables, rowspan=1, colspan=1, id=None, style=None,
parent=None )
    style_class
        alias of TableCellStyle

class rinoh.table.TableCellBorder ( rendered_cell, cell_height, position, style=None )
    style_class
        alias of TableCellBorderStyle

class rinoh.table.TableCellBackground ( bottom_left, width, height, style=None,
parent=None )
    style_class
        alias of TableCellBackgroundStyle

class rinoh.table.VerticalAlign
    Accepts: top, middle, bottom

class rinoh.table.ListOfTables ( local=False, id=None, style=None, parent=None )

class rinoh.table.ListOfTablesSection
    list_class
        alias of ListOfTables

```

5.19 Templates (rinoh.template)

5.19.1 Documents

Document templates are created by subclassing `DocumentTemplate`, just like the Chapter 4 shipped with rinohtype.

```

class rinoh.template.DocumentTemplate ( document_tree, configuration=None,
backend=None )
    Template for documents

    Parameters
        document_tree : DocumentTree
            a tree of the document's contents
        configuration : TemplateConfiguration
            configuration for this template
        backend=None
            the backend used for rendering the document

    language
        The main language of the document

```

Accepts `Language`: the code of one of the supported languages
Default: `EN` (English)

strings

Strings to override standard element names

Accepts `Strings`: `strings` need to be entered in INI sections named after the `StringCollection` subclasses

Default: `none`

stylesheet

The stylesheet to use for styling document elements

Accepts `StyleSheet`: the name of an Section 3.1 or the filename of a stylesheet file (with the `.rts` extension)

Default: `sphinx` (= `rinoh.stylesheets.sphinx`)

parts

The parts making up this document

Accepts `PartsList`: a space-separated list of document part template names

Default: (empty list)

Configuration

alias of `DocumentTemplateConfiguration`

ConfigurationFile

alias of `DocumentTemplateConfigurationFile`

Document templates can be customized by setting values for the configuration attributes defined in a `DocumentTemplate` subclass in a `TemplateConfiguration`. An template configuration can be passed as *configuration* on template instantiation. However, it is better to make use of the `document` method, however.

```
class rinoh.template.TemplateConfiguration ( name, base=None, source=None,  
template=None, description=None, **options )
```

Stores a configuration for a `DocumentTemplate`

Parameters

name : **str**

a label for this template configuration

base : **TemplateConfiguration**

the template configuration to extend

template : **DocumentTemplateMeta** or **str**

the document template to configure

description : **str**

a short string describing this style sheet

****options**

configuration values for the configuration attributes defined by the document template

template = `None`

The `DocumentTemplate` subclass to configure

document (*document_tree*, *backend=None*)

Create a `DocumentTemplate` object based on the given document tree and this template configuration

Parameters

document_tree : DocumentTree

tree of the document's contents

backend=None

the backend to use when rendering the document

class rinoh.template.**PartsList** (**parts*)

Stores the names of the document part templates making up a document

Parameters

***parts : list[str]**

the names of the document parts

5.19.2 Document Parts

class rinoh.template.**DocumentPart** (*template, document, flowables, last_number_format*)

Part of a document.

Parameters

template : DocumentPartTemplate

the template that determines the contents and style of this document part

document : Document

the document this part belongs to

flowables : list[Flowable]

the flowables to render in this document part

configuration_class

alias of DocumentPartTemplate

add_page (*page*)

Append *page* (Page) to this DocumentPart.

new_page (*page_number, chain, new_chapter, sideways=False*)

Called by render() with the Chain's that need more :class:`Container`s. This method should create a new :class:`Page` which contains a container associated with *chain*.

The document part templates which are listed by name in DocumentTemplate.parts are looked up as attributes of the DocumentTemplate subclass. They are instances of DocumentPartTemplate subclasses:

class rinoh.template.**DocumentPartTemplate** (*base=None, **attributes*)

A template that produces a document part

The document part is created given a set of flowables, and page templates. The latter are looked up in the TemplateConfiguration where this part template was.

page_number_prefix

Text to place in front of the page number.

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

page_number_format

The format for page numbers in this document part.

Accepts PageNumberFormat: none, number, symbol, lowercase character,

uppercase character, lowercase roman, uppercase roman, continue
Default: number

end_at_page

The type of page to end this document part on
Accepts PageType: left, right, any
Default: any

drop_if_empty

Exclude this part from the document if it is empty (no flowables)
Accepts Bool: true or false
Default: true

The following document part templates are used in the standard document templates:

class rinoh.template.**TitlePartTemplate** (*base=None, **attributes*)

The title page of a document.

drop_if_empty

Exclude this part from the document if it is empty (no flowables) (inherited from DocumentPartTemplate)
Accepts Bool: true or false
Default: false (overrides DocumentPartTemplate default)

page_number_prefix

Text to place in front of the page number. (inherited from DocumentPartTemplate)
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

page_number_format

The format for page numbers in this document part. (inherited from DocumentPartTemplate)
Accepts PageNumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman, continue
Default: number

end_at_page

The type of page to end this document part on (inherited from DocumentPartTemplate)
Accepts PageType: left, right, any
Default: any

class rinoh.template.**ContentsPartTemplate** (*base=None, **attributes*)

The body of a document.

Renders all of the content present in the DocumentTree passed to the DocumentTemplate.

page_number_prefix

Text to place in front of the page number. (inherited from DocumentPartTemplate)
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

page_number_format

The format for page numbers in this document part. (inherited from

DocumentPartTemplate)

Accepts PageNumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman, continue

Default: number

end_at_page

The type of page to end this document part on (inherited from DocumentPartTemplate)

Accepts PageType: left, right, any

Default: any

drop_if_empty

Exclude this part from the document if it is empty (no flowables) (inherited from DocumentPartTemplate)

Accepts Bool: true or false

Default: true

class rinoh.template.FixedDocumentPartTemplate (base=None, **attributes)

A document part template that renders a fixed list of flowables

flowables

The list of flowables to include in this document part

Accepts FlowablesList: Python source code that represents a list of Flowables

Default: []

page_number_prefix

Text to place in front of the page number. (inherited from DocumentPartTemplate)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

page_number_format

The format for page numbers in this document part. (inherited from DocumentPartTemplate)

Accepts PageNumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman, continue

Default: number

end_at_page

The type of page to end this document part on (inherited from DocumentPartTemplate)

Accepts PageType: left, right, any

Default: any

drop_if_empty

Exclude this part from the document if it is empty (no flowables) (inherited from DocumentPartTemplate)

Accepts Bool: true or false

Default: true

5.19.3 Page Templates

The document templates make use of page templates:

```
class rinoh.template.BodyPageTemplateBase ( base=None, **attributes )
```

header_footer_distance
 Distance of the header and footer to the content area
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 14pt

columns
 The number of columns for the body text
Accepts Integer: a natural number (positive integer)
Default: 1

column_spacing
 The spacing between columns
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 1cm

header_text
 The text to place in the page header
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: '{SECTION_NUMBER(1)}' ' ' ' '{SECTION_TITLE(1)}'

footer_text
 The text to place in the page footer
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: '\t' '{PAGE_NUMBER}' ' ' / ' '{NUMBER_OF_PAGES}'

page_size
 The format of the pages in the document (inherited from PageTemplateBase)
Accepts Paper: the name of a Section 5.12 or <width> * <height> where width and height are Dimensions
Default: A4

page_orientation
 The orientation of pages in the document (inherited from PageTemplateBase)
Accepts PageOrientation: portrait, landscape
Default: portrait

left_margin
 The margin size on the left of the page (inherited from PageTemplateBase)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 3cm

right_margin
 The margin size on the right of the page (inherited from PageTemplateBase)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 3cm

top_margin
 The margin size at the top of the page (inherited from PageTemplateBase)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 3cm

bottom_margin

The margin size at the bottom of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

background

An image to place in the background of the page (inherited from `PageTemplateBase`)

Accepts `BackgroundImage`: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (`<keyword>=<value>`) that determine how the image is displayed

Default: none

after_break_background

An image to place in the background after a page break (inherited from `PageTemplateBase`)

Accepts `BackgroundImage`: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (`<keyword>=<value>`) that determine how the image is displayed

Default: none

sideways

Rotate sideways pages to the left or right (inherited from `PageTemplateBase`)

Accepts `Sideways`: left, right

Default: right

```
class rinoh.template.BodyPageTemplate ( base=None, **attributes )
```

chapter_header_text

The text to place in the header on a page that starts a new chapter

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

chapter_footer_text

The text to place in the footer on a page that starts a new chapter

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

chapter_title_flowables

Generator that yields the flowables to represent the chapter title

Accepts `FlowablesList`: Python source code that represents a list of `Flowables`

Default: none

chapter_title_height

The height of the container holding the chapter title

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 150pt

header_footer_distance

Distance of the header and footer to the content area (inherited from `BodyPageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 14pt

columns

The number of columns for the body text (inherited from `BodyPageTemplateBase`)

Accepts `Integer`: a natural number (positive integer)

Default: 1

column_spacing

The spacing between columns (inherited from `BodyPageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 1cm

header_text

The text to place in the page header (inherited from `BodyPageTemplateBase`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '{SECTION_NUMBER(1)}' ' ' '{SECTION_TITLE(1)}'

footer_text

The text to place in the page footer (inherited from `BodyPageTemplateBase`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '\t' '{PAGE_NUMBER}' '/' '{NUMBER_OF_PAGES}'

page_size

The format of the pages in the document (inherited from `PageTemplateBase`)

Accepts `Paper`: the name of a Section 5.12 or <width> * <height> where width and height are `Dimensions`

Default: A4

page_orientation

The orientation of pages in the document (inherited from `PageTemplateBase`)

Accepts `PageOrientation`: portrait, landscape

Default: portrait

left_margin

The margin size on the left of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

right_margin

The margin size on the right of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

top_margin

The margin size at the top of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

bottom_margin

The margin size at the bottom of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

background

An image to place in the background of the page (inherited from `PageTemplateBase`)

Accepts `BackgroundImage`: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (`<keyword>=<value>`) that determine how the image is displayed

Default: none

after_break_background

An image to place in the background after a page break (inherited from `PageTemplateBase`)

Accepts `BackgroundImage`: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (`<keyword>=<value>`) that determine how the image is displayed

Default: none

sideways

Rotate sideways pages to the left or right (inherited from `PageTemplateBase`)

Accepts `Sideways`: left, right

Default: right

```
class rinoh.template.TitlePageTemplate ( base=None, **attributes )
```

extra

Extra text to include on the title page below the title

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

page_size

The format of the pages in the document (inherited from `PageTemplateBase`)

Accepts `Paper`: the name of a Section 5.12 or `<width> * <height>` where width and height are `Dimensions`

Default: A4

page_orientation

The orientation of pages in the document (inherited from `PageTemplateBase`)

Accepts `PageOrientation`: portrait, landscape

Default: portrait

left_margin

The margin size on the left of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

right_margin

The margin size on the right of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

top_margin

The margin size at the top of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

bottom_margin

The margin size at the bottom of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

background

An image to place in the background of the page (inherited from `PageTemplateBase`)

Accepts `BackgroundImage`: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (`<keyword>=<value>`) that determine how the image is displayed

Default: none

after_break_background

An image to place in the background after a page break (inherited from `PageTemplateBase`)

Accepts `BackgroundImage`: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (`<keyword>=<value>`) that determine how the image is displayed

Default: none

sideways

Rotate sideways pages to the left or right (inherited from `PageTemplateBase`)

Accepts `Sideways`: left, right

Default: right

The base class for these collects the common options:

```
class rinoh.template.PageTemplateBase ( base=None, **attributes )
```

page_size

The format of the pages in the document

Accepts `Paper`: the name of a Section 5.12 or `<width> * <height>` where width and height are `Dimensions`

Default: A4

page_orientation

The orientation of pages in the document

Accepts `PageOrientation`: portrait, landscape

Default: portrait

left_margin

The margin size on the left of the page

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

right_margin

The margin size on the right of the page

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

top_margin

The margin size at the top of the page

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

bottom_margin

The margin size at the bottom of the page

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

background

An image to place in the background of the page

Accepts `BackgroundImage`: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

after_break_background

An image to place in the background after a page break

Accepts `BackgroundImage`: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

sideways

Rotate sideways pages to the left or right

Accepts `Sideways`: left, right

Default: right

Python Module Index

r

rhino

- rhino.attribute, 97
- rhino.color, 98
- rhino.dimension, 98
- rhino.document, 99
- rhino.draw, 101
- rhino.flowable, 101
- rhino.font, 104
- rhino.font.style, 106
- rhino.image, 106
- rhino.index, 108
- rhino.inline, 117
- rhino.language, 108
- rhino.number, 113
- rhino.paper, 115
- rhino.paragraph, 116
- rhino.reference, 120
- rhino.strings, 124
- rhino.structure, 121
- rhino.style, 124
- rhino.stylesheets, 11
- rhino.table, 126
- rhino.template, 127
- rhino.templates.article, 91
- rhino.templates.book, 92
- rhino.text, 116

Index

Symbols

- docs
 - rinoh command line option, 6
- format
 - rinoh command line option, 5
- help
 - rinoh command line option, 5
- install-resources
 - rinoh command line option, 5
- list-fonts
 - rinoh command line option, 6
- list-formats
 - rinoh command line option, 6
- list-options
 - rinoh command line option, 6
- list-stylesheets
 - rinoh command line option, 5
- list-templates
 - rinoh command line option, 5
- option
 - rinoh command line option, 5
- output
 - rinoh command line option, 5
- paper
 - rinoh command line option, 5
- stylesheet
 - rinoh command line option, 5
- template
 - rinoh command line option, 5
- version
 - rinoh command line option, 6
- versions
 - rinoh command line option, 6
- f
 - rinoh command line option, 5
- h
 - rinoh command line option, 5
- i
 - rinoh command line option, 5
- O
 - rinoh command line option, 5
- o

- rinoh command line option, 5
- P
 - rinoh command line option, 5
- s
 - rinoh command line option, 5
- t
 - rinoh command line option, 5

A

- A0 (in module rinoh.paper), 115
- A1 (in module rinoh.paper), 115
- A10 (in module rinoh.paper), 115
- A2 (in module rinoh.paper), 115
- A3 (in module rinoh.paper), 115
- A4 (in module rinoh.paper), 115
- A5 (in module rinoh.paper), 115
- A6 (in module rinoh.paper), 115
- A7 (in module rinoh.paper), 115
- A8 (in module rinoh.paper), 115
- A9 (in module rinoh.paper), 115
- abstract_location (rinoh.templates.article.Article attribute), 91
- AbstractLocation (class in rinoh.templates.article), 92
- AcceptNoneAttributeType (class in rinoh.attribute), 97
- add_page() (rinoh.template.DocumentPart method), 129
- Admonition (class in rinoh.structure), 122
- AdmonitionStyle (class in rinoh.structure), 79
- AdmonitionTitles (class in rinoh.structure), 122
- advance() (rinoh.paragraph.DefaultSpacing method), 118
- advance() (rinoh.paragraph.FixedSpacing method), 118
- advance() (rinoh.paragraph.Leading method), 119
- advance() (rinoh.paragraph.LineSpacing method), 118
- advance() (rinoh.paragraph.ProportionalSpacing method), 118
- after (rinoh.image.CaptionStyle attribute), 32
- after (rinoh.inline.InlineFlowableStyle attribute), 46
- after (rinoh.paragraph.ParagraphStyle attribute), 41
- after (rinoh.reference.NoteMarkerStyle attribute), 53
- after (rinoh.reference.ReferencingParagraphStyle attribute), 51
- after (rinoh.structure.HeadingStyle attribute), 60
- after (rinoh.structure.ListItemLabelStyle attribute), 68
- after (rinoh.structure.TableOfContentsEntryStyle attribute), 79
- after (rinoh.structure.TableOfContentsStyle attribute), 74
- after (rinoh.text.TextStyle attribute), 43
- after_break_background (rinoh.template.BodyPageTemplate attribute), 135
- after_break_background (rinoh.template.BodyPageTemplateBase attribute), 133
- after_break_background (rinoh.template.PageTemplateBase attribute), 137
- after_break_background (rinoh.template.TitlePageTemplate attribute), 136
- align (rinoh.image.ImageArgs attribute), 107
- align_baselines (rinoh.flowable.LabeledFlowableStyle attribute), 20
- AnchorFlowable (class in rinoh.flowable), 102
- append() (rinoh.text.MixedStyledText method), 117
- arguments (rinoh.image.BackgroundImage attribute), 106
- arguments (rinoh.image.InlineImage attribute), 106
- Article (class in rinoh.templates.article), 91
- attention (rinoh.structure.AdmonitionTitles attribute), 122
- Attribute (class in rinoh.attribute), 97
- AttributesDictionary (class in rinoh.attribute), 97

B

`back_matter` (rinoh.templates.book.Book attribute), 94
`back_matter_left_page` (rinoh.templates.book.Book attribute), 96
`back_matter_page` (rinoh.templates.book.Book attribute), 95
`back_matter_right_page` (rinoh.templates.book.Book attribute), 96
`background` (rinoh.template.BodyPageTemplate attribute), 135
`background` (rinoh.template.BodyPageTemplateBase attribute), 133
`background` (rinoh.template.PageTemplateBase attribute), 137
`background` (rinoh.template.TitlePageTemplate attribute), 136
`background_color` (rinoh.flowable.FloatStyle attribute), 27
`background_color` (rinoh.flowable.FlowableStyle attribute), 20
`background_color` (rinoh.flowable.GroupedFlowablesStyle attribute), 25
`background_color` (rinoh.flowable.LabeledFlowableStyle attribute), 22
`background_color` (rinoh.image.CaptionStyle attribute), 30
`background_color` (rinoh.image.FigureStyle attribute), 34
`background_color` (rinoh.index.IndexStyle attribute), 36
`background_color` (rinoh.inline.InlineFlowableStyle attribute), 45
`background_color` (rinoh.paragraph.ParagraphStyle attribute), 39
`background_color` (rinoh.reference.ReferencingParagraphStyle attribute), 48
`background_color` (rinoh.structure.AdmonitionStyle attribute), 81
`background_color` (rinoh.structure.HeadingStyle attribute), 58
`background_color` (rinoh.structure.HorizontalRuleStyle attribute), 83
`background_color` (rinoh.structure.ListItemLabelStyle attribute), 66
`background_color` (rinoh.structure.ListStyle attribute), 63
`background_color` (rinoh.structure.SectionStyle attribute), 55
`background_color` (rinoh.structure.TableOfContentsEntryStyle attribute), 76
`background_color` (rinoh.structure.TableOfContentsStyle attribute), 71
`background_color` (rinoh.table.TableCellStyle attribute), 88
`background_color` (rinoh.table.TableStyle attribute), 85
`BackgroundImage` (class in rinoh.image), 106
`baseline` (rinoh.inline.InlineFlowableStyle attribute), 43
`before` (rinoh.image.CaptionStyle attribute), 32
`before` (rinoh.inline.InlineFlowableStyle attribute), 45
`before` (rinoh.paragraph.ParagraphStyle attribute), 41
`before` (rinoh.reference.NoteMarkerStyle attribute), 53
`before` (rinoh.reference.ReferencingParagraphStyle attribute), 50
`before` (rinoh.structure.HeadingStyle attribute), 60
`before` (rinoh.structure.ListItemLabelStyle attribute), 68
`before` (rinoh.structure.TableOfContentsEntryStyle attribute), 78
`before` (rinoh.structure.TableOfContentsStyle attribute), 74
`before` (rinoh.text.TextStyle attribute), 43
`BodyPageTemplate` (class in rinoh.template), 133
`BodyPageTemplateBase` (class in rinoh.template), 132
`Book` (class in rinoh.templates.book), 92
`Bool` (class in rinoh.attribute), 97
`border` (rinoh.flowable.FloatStyle attribute), 26
`border` (rinoh.flowable.FlowableStyle attribute), 19
`border` (rinoh.flowable.GroupedFlowablesStyle attribute), 24
`border` (rinoh.flowable.LabeledFlowableStyle attribute), 22
`border` (rinoh.image.CaptionStyle attribute), 29
`border` (rinoh.image.FigureStyle attribute), 33
`border` (rinoh.index.IndexStyle attribute), 36
`border` (rinoh.inline.InlineFlowableStyle attribute), 45
`border` (rinoh.paragraph.ParagraphStyle attribute), 39
`border` (rinoh.reference.ReferencingParagraphStyle attribute), 48
`border` (rinoh.structure.AdmonitionStyle attribute), 80
`border` (rinoh.structure.HeadingStyle attribute), 58

border (rinoh.structure.HorizontalRuleStyle attribute), 82
border (rinoh.structure.ListItemLabelStyle attribute), 66
border (rinoh.structure.ListStyle attribute), 62
border (rinoh.structure.SectionStyle attribute), 55
border (rinoh.structure.TableOfContentsEntryStyle attribute), 76
border (rinoh.structure.TableOfContentsStyle attribute), 70
border (rinoh.table.TableCellStyle attribute), 87
border (rinoh.table.TableStyle attribute), 85
border_bottom (rinoh.flowable.FloatStyle attribute), 27
border_bottom (rinoh.flowable.FlowableStyle attribute), 20
border_bottom (rinoh.flowable.GroupedFlowablesStyle attribute), 24
border_bottom (rinoh.flowable.LabeledFlowableStyle attribute), 22
border_bottom (rinoh.image.CaptionStyle attribute), 29
border_bottom (rinoh.image.FigureStyle attribute), 34
border_bottom (rinoh.index.IndexStyle attribute), 36
border_bottom (rinoh.inline.InlineFlowableStyle attribute), 45
border_bottom (rinoh.paragraph.ParagraphStyle attribute), 39
border_bottom (rinoh.reference.ReferencingParagraphStyle attribute), 48
border_bottom (rinoh.structure.AdmonitionStyle attribute), 81
border_bottom (rinoh.structure.HeadingStyle attribute), 58
border_bottom (rinoh.structure.HorizontalRuleStyle attribute), 83
border_bottom (rinoh.structure.ListItemLabelStyle attribute), 66
border_bottom (rinoh.structure.ListStyle attribute), 63
border_bottom (rinoh.structure.SectionStyle attribute), 55
border_bottom (rinoh.structure.TableOfContentsEntryStyle attribute), 76
border_bottom (rinoh.structure.TableOfContentsStyle attribute), 71
border_bottom (rinoh.table.TableCellStyle attribute), 88
border_bottom (rinoh.table.TableStyle attribute), 85
border_left (rinoh.flowable.FloatStyle attribute), 26
border_left (rinoh.flowable.FlowableStyle attribute), 19
border_left (rinoh.flowable.GroupedFlowablesStyle attribute), 24
border_left (rinoh.flowable.LabeledFlowableStyle attribute), 22
border_left (rinoh.image.CaptionStyle attribute), 29
border_left (rinoh.image.FigureStyle attribute), 33
border_left (rinoh.index.IndexStyle attribute), 36
border_left (rinoh.inline.InlineFlowableStyle attribute), 45
border_left (rinoh.paragraph.ParagraphStyle attribute), 39
border_left (rinoh.reference.ReferencingParagraphStyle attribute), 48
border_left (rinoh.structure.AdmonitionStyle attribute), 80
border_left (rinoh.structure.HeadingStyle attribute), 58
border_left (rinoh.structure.HorizontalRuleStyle attribute), 82
border_left (rinoh.structure.ListItemLabelStyle attribute), 66
border_left (rinoh.structure.ListStyle attribute), 62
border_left (rinoh.structure.SectionStyle attribute), 55
border_left (rinoh.structure.TableOfContentsEntryStyle attribute), 76
border_left (rinoh.structure.TableOfContentsStyle attribute), 70
border_left (rinoh.table.TableCellStyle attribute), 87
border_left (rinoh.table.TableStyle attribute), 85
border_right (rinoh.flowable.FloatStyle attribute), 26
border_right (rinoh.flowable.FlowableStyle attribute), 19
border_right (rinoh.flowable.GroupedFlowablesStyle attribute), 24
border_right (rinoh.flowable.LabeledFlowableStyle attribute), 22
border_right (rinoh.image.CaptionStyle attribute), 29
border_right (rinoh.image.FigureStyle attribute), 33
border_right (rinoh.index.IndexStyle attribute), 36
border_right (rinoh.inline.InlineFlowableStyle attribute), 45
border_right (rinoh.paragraph.ParagraphStyle attribute), 39
border_right (rinoh.reference.ReferencingParagraphStyle attribute), 48

- `border_right` (rinoh.structure.AdmonitionStyle attribute), 81
- `border_right` (rinoh.structure.HeadingStyle attribute), 58
- `border_right` (rinoh.structure.HorizontalRuleStyle attribute), 83
- `border_right` (rinoh.structure.ListItemLabelStyle attribute), 66
- `border_right` (rinoh.structure.ListStyle attribute), 63
- `border_right` (rinoh.structure.SectionStyle attribute), 55
- `border_right` (rinoh.structure.TableOfContentsEntryStyle attribute), 76
- `border_right` (rinoh.structure.TableOfContentsStyle attribute), 70
- `border_right` (rinoh.table.TableCellStyle attribute), 87
- `border_right` (rinoh.table.TableStyle attribute), 85
- `border_top` (rinoh.flowable.FloatStyle attribute), 27
- `border_top` (rinoh.flowable.FlowableStyle attribute), 20
- `border_top` (rinoh.flowable.GroupedFlowablesStyle attribute), 24
- `border_top` (rinoh.flowable.LabeledFlowableStyle attribute), 22
- `border_top` (rinoh.image.CaptionStyle attribute), 29
- `border_top` (rinoh.image.FigureStyle attribute), 33
- `border_top` (rinoh.index.IndexStyle attribute), 36
- `border_top` (rinoh.inline.InlineFlowableStyle attribute), 45
- `border_top` (rinoh.paragraph.ParagraphStyle attribute), 39
- `border_top` (rinoh.reference.ReferencingParagraphStyle attribute), 48
- `border_top` (rinoh.structure.AdmonitionStyle attribute), 81
- `border_top` (rinoh.structure.HeadingStyle attribute), 58
- `border_top` (rinoh.structure.HorizontalRuleStyle attribute), 83
- `border_top` (rinoh.structure.ListItemLabelStyle attribute), 66
- `border_top` (rinoh.structure.ListStyle attribute), 63
- `border_top` (rinoh.structure.SectionStyle attribute), 55
- `border_top` (rinoh.structure.TableOfContentsEntryStyle attribute), 76
- `border_top` (rinoh.structure.TableOfContentsStyle attribute), 70
- `border_top` (rinoh.table.TableCellStyle attribute), 88
- `border_top` (rinoh.table.TableStyle attribute), 85
- `bottom_margin` (rinoh.template.BodyPageTemplate attribute), 134
- `bottom_margin` (rinoh.template.BodyPageTemplateBase attribute), 133
- `bottom_margin` (rinoh.template.PageTemplateBase attribute), 137
- `bottom_margin` (rinoh.template.TitlePageTemplate attribute), 136
- `build_document()` (rinoh.flowable.StaticGroupedFlowables method), 103
- `bullet` (rinoh.structure.ListStyle attribute), 61

C

- `Caption` (class in rinoh.image), 107
- `CaptionStyle` (class in rinoh.image), 27
- `caution` (rinoh.structure.AdmonitionTitles attribute), 123
- `chapter` (rinoh.structure.SectionTitles attribute), 121
- `chapter_footer_text` (rinoh.template.BodyPageTemplate attribute), 133
- `chapter_header_text` (rinoh.template.BodyPageTemplate attribute), 133
- `chapter_title_flowables` (rinoh.template.BodyPageTemplate attribute), 133
- `chapter_title_height` (rinoh.template.BodyPageTemplate attribute), 133
- CM (in module rinoh.dimension), 99
- `Color` (class in rinoh.color), 98
- `column_spacing` (rinoh.template.BodyPageTemplate attribute), 134
- `column_spacing` (rinoh.template.BodyPageTemplateBase attribute), 132
- `column_widths` (rinoh.table.TableStyle attribute), 83
- `columns` (rinoh.template.BodyPageTemplate attribute), 134
- `columns` (rinoh.template.BodyPageTemplateBase attribute), 132
- `Configuration` (rinoh.template.DocumentTemplate attribute), 128
- `Configuration` (rinoh.templates.article.Article attribute), 92
- `Configuration` (rinoh.templates.book.Book attribute), 96
- `configuration_class` (rinoh.style.Styled attribute), 125

configuration_class (rinoh.template.DocumentPart attribute), 129
 ConfigurationFile (rinoh.template.DocumentTemplate attribute), 128
 ConfigurationFile (rinoh.templates.article.Article attribute), 92
 ConfigurationFile (rinoh.templates.book.Book attribute), 96
 contents (rinoh.structure.SectionTitles attribute), 121
 contents (rinoh.templates.article.Article attribute), 92
 contents (rinoh.templates.book.Book attribute), 93
 contents_left_page (rinoh.templates.book.Book attribute), 95
 contents_page (rinoh.templates.article.Article attribute), 92
 contents_page (rinoh.templates.book.Book attribute), 95
 contents_right_page (rinoh.templates.book.Book attribute), 95
 ContentsPartTemplate (class in rinoh.template), 130
 copy() (rinoh.text.MixedStyledText method), 117
 cover (rinoh.templates.book.Book attribute), 93
 cover_page (rinoh.templates.book.Book attribute), 94
 CS (in module rinoh.language), 108
 custom_label (rinoh.image.CaptionStyle attribute), 30
 custom_label (rinoh.number.LabelStyle attribute), 114
 custom_label (rinoh.number.NumberStyle attribute), 115
 custom_label (rinoh.paragraph.ParagraphStyle attribute), 40
 custom_label (rinoh.reference.NoteMarkerStyle attribute), 53
 custom_label (rinoh.reference.ReferencingParagraphStyle attribute), 49
 custom_label (rinoh.structure.HeadingStyle attribute), 59
 custom_label (rinoh.structure.ListItemLabelStyle attribute), 67
 custom_label (rinoh.structure.ListStyle attribute), 64
 custom_label (rinoh.structure.TableOfContentsEntryStyle attribute), 77
 custom_label (rinoh.structure.TableOfContentsStyle attribute), 72

D

danger (rinoh.structure.AdmonitionTitles attribute), 123
 DEFAULT (in module rinoh.paragraph), 119
 DefaultSpacing (class in rinoh.paragraph), 118
 DefinitionList (class in rinoh.structure), 122
 depth (rinoh.structure.TableOfContentsStyle attribute), 69
 Dimension (class in rinoh.dimension), 98
 doc_format() (rinoh.color.Color class method), 98
 Document (class in rinoh.document), 99
 document() (rinoh.template.TemplateConfiguration method), 128
 DocumentPart (class in rinoh.template), 129
 DocumentPartTemplate (class in rinoh.template), 129
 DocumentTemplate (class in rinoh.template), 127
 DocumentTree (class in rinoh.document), 99
 DOUBLE (in module rinoh.paragraph), 119
 dpi (rinoh.image.ImageArgs attribute), 107
 drop_if_empty (rinoh.template.ContentsPartTemplate attribute), 131
 drop_if_empty (rinoh.template.DocumentPartTemplate attribute), 130
 drop_if_empty (rinoh.template.FixedDocumentPartTemplate attribute), 131
 drop_if_empty (rinoh.template.TitlePartTemplate attribute), 130
 DummyFlowable (class in rinoh.flowable), 102

E

EN (in module rinoh.language), 109
 encoding (rinoh.font.Font attribute), 104
 end_at_page (rinoh.template.ContentsPartTemplate attribute), 131
 end_at_page (rinoh.template.DocumentPartTemplate attribute), 130
 end_at_page (rinoh.template.FixedDocumentPartTemplate attribute), 131
 end_at_page (rinoh.template.TitlePartTemplate attribute), 130

error (rinoh.structure.AdmonitionTitles attribute), 123
extra (rinoh.template.TitlePageTemplate attribute), 135

F

Field (class in rinoh.reference), 121
Figure (class in rinoh.image), 107
FigureStyle (class in rinoh.image), 32
file_or_filename (rinoh.image.ImageArgs attribute), 107
fill_color (rinoh.draw.ShapeStyle attribute), 18
fill_color (rinoh.table.TableCellBackgroundStyle attribute), 88
find_source() (rinoh.attribute.RuleSet method), 97
FixedDocumentPartTemplate (class in rinoh.template), 131
FixedSpacing (class in rinoh.paragraph), 118
Float (class in rinoh.flowable), 103
float (rinoh.flowable.FloatStyle attribute), 25
float (rinoh.image.FigureStyle attribute), 32
FloatStyle (class in rinoh.flowable), 25
flow() (rinoh.flowable.Float method), 104
flow() (rinoh.index.IndexTarget method), 108
flow() (rinoh.reference.Note method), 120
flow() (rinoh.structure.Heading method), 121
Flowable (class in rinoh.flowable), 101
flowable_spacing (rinoh.flowable.GroupedFlowablesStyle attribute), 23
flowable_spacing (rinoh.image.FigureStyle attribute), 34
flowable_spacing (rinoh.index.IndexStyle attribute), 35
flowable_spacing (rinoh.structure.AdmonitionStyle attribute), 79
flowable_spacing (rinoh.structure.ListStyle attribute), 61
flowable_spacing (rinoh.structure.SectionStyle attribute), 54
flowable_spacing (rinoh.structure.TableOfContentsStyle attribute), 69
flowable_spacing (rinoh.table.TableCellStyle attribute), 86
flowables (rinoh.template.FixedDocumentPartTemplate attribute), 131
flowables() (rinoh.flowable.GroupedFlowables method), 103
flowables() (rinoh.flowable.StaticGroupedFlowables method), 103
flowables() (rinoh.index.Index method), 108
flowables() (rinoh.structure.Admonition method), 122
flowables() (rinoh.structure.TableOfContents method), 122
FlowableState (class in rinoh.flowable), 101
FlowableStyle (class in rinoh.flowable), 18
FlowableWidth (class in rinoh.flowable), 104
Font (class in rinoh.font), 104
font_color (rinoh.image.CaptionStyle attribute), 31
font_color (rinoh.paragraph.ParagraphStyle attribute), 40
font_color (rinoh.reference.NoteMarkerStyle attribute), 52
font_color (rinoh.reference.ReferencingParagraphStyle attribute), 50
font_color (rinoh.structure.HeadingStyle attribute), 59
font_color (rinoh.structure.ListItemLabelStyle attribute), 67
font_color (rinoh.structure.TableOfContentsEntryStyle attribute), 78
font_color (rinoh.structure.TableOfContentsStyle attribute), 73
font_color (rinoh.text.TextStyle attribute), 42
font_size (rinoh.image.CaptionStyle attribute), 31
font_size (rinoh.paragraph.ParagraphStyle attribute), 40
font_size (rinoh.reference.NoteMarkerStyle attribute), 52
font_size (rinoh.reference.ReferencingParagraphStyle attribute), 49
font_size (rinoh.structure.HeadingStyle attribute), 59
font_size (rinoh.structure.ListItemLabelStyle attribute), 67
font_size (rinoh.structure.TableOfContentsEntryStyle attribute), 77
font_size (rinoh.structure.TableOfContentsStyle attribute), 73

font_size (rinoh.text.TextStyle attribute), 42
 font_slant (rinoh.image.CaptionStyle attribute), 30
 font_slant (rinoh.paragraph.ParagraphStyle attribute), 40
 font_slant (rinoh.reference.NoteMarkerStyle attribute), 51
 font_slant (rinoh.reference.ReferencingParagraphStyle attribute), 49
 font_slant (rinoh.structure.HeadingStyle attribute), 59
 font_slant (rinoh.structure.ListItemLabelStyle attribute), 67
 font_slant (rinoh.structure.TableOfContentsEntryStyle attribute), 77
 font_slant (rinoh.structure.TableOfContentsStyle attribute), 72
 font_slant (rinoh.text.TextStyle attribute), 42
 font_variant (rinoh.image.CaptionStyle attribute), 31
 font_variant (rinoh.paragraph.ParagraphStyle attribute), 41
 font_variant (rinoh.reference.NoteMarkerStyle attribute), 52
 font_variant (rinoh.reference.ReferencingParagraphStyle attribute), 50
 font_variant (rinoh.structure.HeadingStyle attribute), 60
 font_variant (rinoh.structure.ListItemLabelStyle attribute), 67
 font_variant (rinoh.structure.TableOfContentsEntryStyle attribute), 78
 font_variant (rinoh.structure.TableOfContentsStyle attribute), 73
 font_variant (rinoh.text.TextStyle attribute), 42
 font_weight (rinoh.image.CaptionStyle attribute), 30
 font_weight (rinoh.paragraph.ParagraphStyle attribute), 40
 font_weight (rinoh.reference.NoteMarkerStyle attribute), 51
 font_weight (rinoh.reference.ReferencingParagraphStyle attribute), 49
 font_weight (rinoh.structure.HeadingStyle attribute), 59
 font_weight (rinoh.structure.ListItemLabelStyle attribute), 67
 font_weight (rinoh.structure.TableOfContentsEntryStyle attribute), 77
 font_weight (rinoh.structure.TableOfContentsStyle attribute), 72
 font_weight (rinoh.text.TextStyle attribute), 42
 font_width (rinoh.image.CaptionStyle attribute), 30
 font_width (rinoh.paragraph.ParagraphStyle attribute), 40
 font_width (rinoh.reference.NoteMarkerStyle attribute), 51
 font_width (rinoh.reference.ReferencingParagraphStyle attribute), 49
 font_width (rinoh.structure.HeadingStyle attribute), 59
 font_width (rinoh.structure.ListItemLabelStyle attribute), 67
 font_width (rinoh.structure.TableOfContentsEntryStyle attribute), 77
 font_width (rinoh.structure.TableOfContentsStyle attribute), 72
 font_width (rinoh.text.TextStyle attribute), 42
 fonts() (rinoh.font.Typeface method), 105
 FontSlant (class in rinoh.font.style), 106
 FontVariant (class in rinoh.font.style), 106
 FontWeight (class in rinoh.font.style), 106
 FontWidth (class in rinoh.font.style), 106
 footer_text (rinoh.template.BodyPageTemplate attribute), 134
 footer_text (rinoh.template.BodyPageTemplateBase attribute), 132
 format_number() (in module rinoh.number), 115
 FR (in module rinoh.language), 110
 front_matter (rinoh.templates.book.Book attribute), 93
 front_matter_left_page (rinoh.templates.book.Book attribute), 95
 front_matter_page (rinoh.templates.book.Book attribute), 94
 front_matter_right_page (rinoh.templates.book.Book attribute), 94

G

get_font() (rinoh.font.Typeface method), 105
 get_glyph_metrics() (rinoh.font.Font method), 104
 get_kerning() (rinoh.font.Font method), 105
 get_ligature() (rinoh.font.Font method), 105
 get_position() (rinoh.paragraph.TabStop method), 119

- get_rowspanned_columns() (rinoh.table.TableRow method), 127
- get_selector() (rinoh.style.StyleSheet method), 125
- Glyph (class in rinoh.paragraph), 119
- GlyphsSpan (class in rinoh.paragraph), 119
- Gray (class in rinoh.color), 98
- GroupedFlowables (class in rinoh.flowable), 103
- GroupedFlowablesState (class in rinoh.flowable), 103
- GroupedFlowablesStyle (class in rinoh.flowable), 23
- GroupedLabeledFlowables (class in rinoh.flowable), 103
- grow() (rinoh.dimension.Dimension method), 99

H

- has_class (rinoh.style.Styled property), 125
- has_classes (rinoh.style.Styled property), 125
- has_id (rinoh.style.Styled property), 125
- header_footer_distance (rinoh.template.BodyPageTemplate attribute), 133
- header_footer_distance (rinoh.template.BodyPageTemplateBase attribute), 132
- header_text (rinoh.template.BodyPageTemplate attribute), 134
- header_text (rinoh.template.BodyPageTemplateBase attribute), 132
- Heading (class in rinoh.structure), 121
- HeadingStyle (class in rinoh.structure), 56
- height (rinoh.image.ImageArgs attribute), 107
- height() (rinoh.text.StyledText method), 117
- HexColor (class in rinoh.color), 98
- hide (rinoh.draw.LineStyle attribute), 18
- hide (rinoh.draw.ShapeStyle attribute), 18
- hide (rinoh.flowable.FloatStyle attribute), 27
- hide (rinoh.flowable.FlowableStyle attribute), 20
- hide (rinoh.flowable.GroupedFlowablesStyle attribute), 25
- hide (rinoh.flowable.LabeledFlowableStyle attribute), 22
- hide (rinoh.image.CaptionStyle attribute), 32
- hide (rinoh.image.FigureStyle attribute), 34
- hide (rinoh.index.IndexStyle attribute), 37
- hide (rinoh.inline.InlineFlowableStyle attribute), 45
- hide (rinoh.number.LabelStyle attribute), 114
- hide (rinoh.number.NumberStyle attribute), 115
- hide (rinoh.paragraph.ParagraphStyle attribute), 39
- hide (rinoh.reference.NoteMarkerStyle attribute), 53
- hide (rinoh.reference.ReferencingParagraphStyle attribute), 51
- hide (rinoh.structure.AdmonitionStyle attribute), 81
- hide (rinoh.structure.HeadingStyle attribute), 61
- hide (rinoh.structure.HorizontalRuleStyle attribute), 83
- hide (rinoh.structure.ListItemLabelStyle attribute), 68
- hide (rinoh.structure.ListStyle attribute), 63
- hide (rinoh.structure.SectionStyle attribute), 56
- hide (rinoh.structure.TableOfContentsEntryStyle attribute), 79
- hide (rinoh.structure.TableOfContentsStyle attribute), 71
- hide (rinoh.style.Style attribute), 125
- hide (rinoh.table.TableCellBackgroundStyle attribute), 89
- hide (rinoh.table.TableCellBorderStyle attribute), 88
- hide (rinoh.table.TableCellStyle attribute), 88
- hide (rinoh.table.TableStyle attribute), 86
- hide (rinoh.text.TextStyle attribute), 43
- hint (rinoh.structure.AdmonitionTitles attribute), 123
- horizontal_align (rinoh.flowable.FloatStyle attribute), 25
- horizontal_align (rinoh.flowable.FlowableStyle attribute), 18
- horizontal_align (rinoh.flowable.GroupedFlowablesStyle attribute), 23

horizontal_align (rinoh.flowable.LabeledFlowableStyle attribute), 21
 horizontal_align (rinoh.image.CaptionStyle attribute), 28
 horizontal_align (rinoh.image.FigureStyle attribute), 32
 horizontal_align (rinoh.index.IndexStyle attribute), 35
 horizontal_align (rinoh.inline.InlineFlowableStyle attribute), 44
 horizontal_align (rinoh.paragraph.ParagraphStyle attribute), 38
 horizontal_align (rinoh.reference.ReferencingParagraphStyle attribute), 47
 horizontal_align (rinoh.structure.AdmonitionStyle attribute), 79
 horizontal_align (rinoh.structure.HeadingStyle attribute), 57
 horizontal_align (rinoh.structure.HorizontalRuleStyle attribute), 81
 horizontal_align (rinoh.structure.ListItemLabelStyle attribute), 65
 horizontal_align (rinoh.structure.ListStyle attribute), 61
 horizontal_align (rinoh.structure.SectionStyle attribute), 54
 horizontal_align (rinoh.structure.TableOfContentsEntryStyle attribute), 75
 horizontal_align (rinoh.structure.TableOfContentsStyle attribute), 69
 horizontal_align (rinoh.table.TableCellStyle attribute), 86
 horizontal_align (rinoh.table.TableStyle attribute), 84
 HorizontalAlignment (class in rinoh.flowable), 104
 HorizontalRule (class in rinoh.structure), 124
 HorizontalRuleStyle (class in rinoh.structure), 81
 hyphen_chars (rinoh.image.CaptionStyle attribute), 31
 hyphen_chars (rinoh.paragraph.ParagraphStyle attribute), 41
 hyphen_chars (rinoh.reference.NoteMarkerStyle attribute), 52
 hyphen_chars (rinoh.reference.ReferencingParagraphStyle attribute), 50
 hyphen_chars (rinoh.structure.HeadingStyle attribute), 60
 hyphen_chars (rinoh.structure.ListItemLabelStyle attribute), 68
 hyphen_chars (rinoh.structure.TableOfContentsEntryStyle attribute), 78
 hyphen_chars (rinoh.structure.TableOfContentsStyle attribute), 73
 hyphen_chars (rinoh.text.TextStyle attribute), 43
 hyphen_lang (rinoh.image.CaptionStyle attribute), 31
 hyphen_lang (rinoh.paragraph.ParagraphStyle attribute), 41
 hyphen_lang (rinoh.reference.NoteMarkerStyle attribute), 52
 hyphen_lang (rinoh.reference.ReferencingParagraphStyle attribute), 50
 hyphen_lang (rinoh.structure.HeadingStyle attribute), 60
 hyphen_lang (rinoh.structure.ListItemLabelStyle attribute), 68
 hyphen_lang (rinoh.structure.TableOfContentsEntryStyle attribute), 78
 hyphen_lang (rinoh.structure.TableOfContentsStyle attribute), 73
 hyphen_lang (rinoh.text.TextStyle attribute), 43
 hyphenate (rinoh.image.CaptionStyle attribute), 31
 hyphenate (rinoh.paragraph.ParagraphStyle attribute), 41
 hyphenate (rinoh.reference.NoteMarkerStyle attribute), 52
 hyphenate (rinoh.reference.ReferencingParagraphStyle attribute), 50
 hyphenate (rinoh.structure.HeadingStyle attribute), 60
 hyphenate (rinoh.structure.ListItemLabelStyle attribute), 68
 hyphenate (rinoh.structure.TableOfContentsEntryStyle attribute), 78
 hyphenate (rinoh.structure.TableOfContentsStyle attribute), 73
 hyphenate (rinoh.text.TextStyle attribute), 43
 HyphenatorStore (class in rinoh.paragraph), 119

I

Image (class in rinoh.image), 106
 ImageArgs (class in rinoh.image), 106
 important (rinoh.structure.AdmonitionTitles attribute), 123
 INCH (in module rinoh.dimension), 99
 indent_first (rinoh.image.CaptionStyle attribute), 27
 indent_first (rinoh.paragraph.ParagraphStyle attribute), 37
 indent_first (rinoh.reference.ReferencingParagraphStyle attribute), 46

- indent_first (rinoh.structure.HeadingStyle attribute), 56
- indent_first (rinoh.structure.ListItemLabelStyle attribute), 64
- indent_first (rinoh.structure.TableOfContentsEntryStyle attribute), 74
- indent_first (rinoh.structure.TableOfContentsStyle attribute), 71
- Index (class in rinoh.index), 108
- index (rinoh.structure.SectionTitles attribute), 122
- IndexLabel (class in rinoh.index), 108
- IndexSection (class in rinoh.index), 108
- IndexStyle (class in rinoh.index), 34
- IndexTarget (class in rinoh.index), 108
- IndexTerm (class in rinoh.index), 108
- initials (rinoh.index.IndexStyle attribute), 34
- inline_title (rinoh.structure.AdmonitionStyle attribute), 79
- InlineFlowable (class in rinoh.inline), 117
- InlineFlowableStyle (class in rinoh.inline), 43
- InlineImage (class in rinoh.image), 106
- InlineIndexTarget (class in rinoh.index), 108
- input
 - rinoh command line option, 5
- Integer (class in rinoh.attribute), 97
- is_script() (rinoh.text.StyledText method), 116
- IT (in module rinoh.language), 111
- items (rinoh.text.MixedStyledText property), 117
- items (rinoh.text.StyledText property), 117

J

- JUNIOR_LEGAL (in module rinoh.paper), 116

K

- keep_with_next (rinoh.flowable.FloatStyle attribute), 26
- keep_with_next (rinoh.flowable.FlowableStyle attribute), 19
- keep_with_next (rinoh.flowable.GroupedFlowablesStyle attribute), 24
- keep_with_next (rinoh.flowable.LabeledFlowableStyle attribute), 22
- keep_with_next (rinoh.image.CaptionStyle attribute), 29
- keep_with_next (rinoh.image.FigureStyle attribute), 33
- keep_with_next (rinoh.index.IndexStyle attribute), 36
- keep_with_next (rinoh.inline.InlineFlowableStyle attribute), 45
- keep_with_next (rinoh.paragraph.ParagraphStyle attribute), 39
- keep_with_next (rinoh.reference.ReferencingParagraphStyle attribute), 48
- keep_with_next (rinoh.structure.AdmonitionStyle attribute), 80
- keep_with_next (rinoh.structure.HeadingStyle attribute), 56
- keep_with_next (rinoh.structure.HorizontalRuleStyle attribute), 82
- keep_with_next (rinoh.structure.ListItemLabelStyle attribute), 66
- keep_with_next (rinoh.structure.ListStyle attribute), 62
- keep_with_next (rinoh.structure.SectionStyle attribute), 55
- keep_with_next (rinoh.structure.TableOfContentsEntryStyle attribute), 76
- keep_with_next (rinoh.structure.TableOfContentsStyle attribute), 70
- keep_with_next (rinoh.table.TableCellStyle attribute), 87
- keep_with_next (rinoh.table.TableStyle attribute), 85
- kerning (rinoh.image.CaptionStyle attribute), 31
- kerning (rinoh.paragraph.ParagraphStyle attribute), 41
- kerning (rinoh.reference.NoteMarkerStyle attribute), 52
- kerning (rinoh.reference.ReferencingParagraphStyle attribute), 50
- kerning (rinoh.structure.HeadingStyle attribute), 60
- kerning (rinoh.structure.ListItemLabelStyle attribute), 68
- kerning (rinoh.structure.TableOfContentsEntryStyle attribute), 78
- kerning (rinoh.structure.TableOfContentsStyle attribute), 73

Kerning (rinoh.text.TextStyle attribute), 42

L

Label (class in rinoh.number), 114
label_max_width (rinoh.flowable.LabeledFlowableStyle attribute), 20
label_min_width (rinoh.flowable.LabeledFlowableStyle attribute), 20
label_prefix (rinoh.image.CaptionStyle attribute), 30
label_prefix (rinoh.number.LabelStyle attribute), 114
label_prefix (rinoh.number.NumberStyle attribute), 114
label_prefix (rinoh.paragraph.ParagraphStyle attribute), 40
label_prefix (rinoh.reference.NoteMarkerStyle attribute), 53
label_prefix (rinoh.reference.ReferencingParagraphStyle attribute), 49
label_prefix (rinoh.structure.HeadingStyle attribute), 59
label_prefix (rinoh.structure.ListItemLabelStyle attribute), 66
label_prefix (rinoh.structure.ListStyle attribute), 63
label_prefix (rinoh.structure.TableOfContentsEntryStyle attribute), 77
label_prefix (rinoh.structure.TableOfContentsStyle attribute), 72
label_spacing (rinoh.flowable.LabeledFlowableStyle attribute), 20
label_suffix (rinoh.image.CaptionStyle attribute), 30
label_suffix (rinoh.number.LabelStyle attribute), 114
label_suffix (rinoh.number.NumberStyle attribute), 114
label_suffix (rinoh.paragraph.ParagraphStyle attribute), 40
label_suffix (rinoh.reference.NoteMarkerStyle attribute), 53
label_suffix (rinoh.reference.ReferencingParagraphStyle attribute), 49
label_suffix (rinoh.structure.HeadingStyle attribute), 59
label_suffix (rinoh.structure.ListItemLabelStyle attribute), 67
label_suffix (rinoh.structure.ListStyle attribute), 63
label_suffix (rinoh.structure.TableOfContentsEntryStyle attribute), 77
label_suffix (rinoh.structure.TableOfContentsStyle attribute), 72
LabeledFlowable (class in rinoh.flowable), 102
LabeledFlowableState (class in rinoh.flowable), 102
LabeledFlowableStyle (class in rinoh.flowable), 20
LabelStyle (class in rinoh.number), 114
Language (class in rinoh.language), 108
language (rinoh.template.DocumentTemplate attribute), 127
language (rinoh.templates.article.Article attribute), 91
language (rinoh.templates.book.Book attribute), 93
languages (rinoh.language.Language attribute), 108
Leading (class in rinoh.paragraph), 118
LEDGER (in module rinoh.paper), 116
left_margin (rinoh.template.BodyPageTemplate attribute), 134
left_margin (rinoh.template.BodyPageTemplateBase attribute), 132
left_margin (rinoh.template.PageTemplateBase attribute), 136
left_margin (rinoh.template.TitlePageTemplate attribute), 135
LEGAL (in module rinoh.paper), 115
LETTER (in module rinoh.paper), 115
ligatures (rinoh.image.CaptionStyle attribute), 31
ligatures (rinoh.paragraph.ParagraphStyle attribute), 41
ligatures (rinoh.reference.NoteMarkerStyle attribute), 52
ligatures (rinoh.reference.ReferencingParagraphStyle attribute), 50
ligatures (rinoh.structure.HeadingStyle attribute), 60
ligatures (rinoh.structure.ListItemLabelStyle attribute), 68
ligatures (rinoh.structure.TableOfContentsEntryStyle attribute), 78
ligatures (rinoh.structure.TableOfContentsStyle attribute), 73
ligatures (rinoh.text.TextStyle attribute), 43
limit_width (rinoh.image.ImageArgs attribute), 106
Line (class in rinoh.draw), 101

line_spacing (rinoh.image.CaptionStyle attribute), 28
 line_spacing (rinoh.paragraph.ParagraphStyle attribute), 37
 line_spacing (rinoh.reference.ReferencingParagraphStyle attribute), 46
 line_spacing (rinoh.structure.HeadingStyle attribute), 56
 line_spacing (rinoh.structure.ListItemLabelStyle attribute), 64
 line_spacing (rinoh.structure.TableOfContentsEntryStyle attribute), 74
 line_spacing (rinoh.structure.TableOfContentsStyle attribute), 71
 LineSpacing (class in rinoh.paragraph), 118
 LineStyle (class in rinoh.draw), 17
 link (rinoh.reference.NoteMarkerStyle attribute), 51
 List (class in rinoh.structure), 122
 list_class (rinoh.image.ListOfFiguresSection attribute), 108
 list_class (rinoh.table.ListOfTablesSection attribute), 127
 list_of_figures (rinoh.structure.SectionTitles attribute), 121
 list_of_tables (rinoh.structure.SectionTitles attribute), 121
 ListItemLabelStyle (class in rinoh.structure), 64
 ListOfFigures (class in rinoh.image), 108
 ListOfFiguresSection (class in rinoh.image), 108
 ListOfTables (class in rinoh.table), 127
 ListOfTablesSection (class in rinoh.table), 127
 ListStyle (class in rinoh.structure), 61
 Locale (class in rinoh.text), 117
 location (rinoh.attribute.RuleSetFile property), 97

M

margin_left (rinoh.flowable.FloatStyle attribute), 25
 margin_left (rinoh.flowable.FlowableStyle attribute), 19
 margin_left (rinoh.flowable.GroupedFlowablesStyle attribute), 23
 margin_left (rinoh.flowable.LabeledFlowableStyle attribute), 21
 margin_left (rinoh.image.CaptionStyle attribute), 28
 margin_left (rinoh.image.FigureStyle attribute), 32
 margin_left (rinoh.index.IndexStyle attribute), 35
 margin_left (rinoh.inline.InlineFlowableStyle attribute), 44
 margin_left (rinoh.paragraph.ParagraphStyle attribute), 38
 margin_left (rinoh.reference.ReferencingParagraphStyle attribute), 47
 margin_left (rinoh.structure.AdmonitionStyle attribute), 80
 margin_left (rinoh.structure.HeadingStyle attribute), 57
 margin_left (rinoh.structure.HorizontalRuleStyle attribute), 82
 margin_left (rinoh.structure.ListItemLabelStyle attribute), 65
 margin_left (rinoh.structure.ListStyle attribute), 62
 margin_left (rinoh.structure.SectionStyle attribute), 54
 margin_left (rinoh.structure.TableOfContentsEntryStyle attribute), 75
 margin_left (rinoh.structure.TableOfContentsStyle attribute), 69
 margin_left (rinoh.table.TableCellStyle attribute), 87
 margin_left (rinoh.table.TableStyle attribute), 84
 margin_right (rinoh.flowable.FloatStyle attribute), 26
 margin_right (rinoh.flowable.FlowableStyle attribute), 19
 margin_right (rinoh.flowable.GroupedFlowablesStyle attribute), 23
 margin_right (rinoh.flowable.LabeledFlowableStyle attribute), 21
 margin_right (rinoh.image.CaptionStyle attribute), 28
 margin_right (rinoh.image.FigureStyle attribute), 33
 margin_right (rinoh.index.IndexStyle attribute), 35
 margin_right (rinoh.inline.InlineFlowableStyle attribute), 44
 margin_right (rinoh.paragraph.ParagraphStyle attribute), 38
 margin_right (rinoh.reference.ReferencingParagraphStyle attribute), 47
 margin_right (rinoh.structure.AdmonitionStyle attribute), 80
 margin_right (rinoh.structure.HeadingStyle attribute), 57

- margin_right (rinoh.structure.HorizontalRuleStyle attribute), 82
- margin_right (rinoh.structure.ListItemLabelStyle attribute), 65
- margin_right (rinoh.structure.ListStyle attribute), 62
- margin_right (rinoh.structure.SectionStyle attribute), 54
- margin_right (rinoh.structure.TableOfContentsEntryStyle attribute), 75
- margin_right (rinoh.structure.TableOfContentsStyle attribute), 70
- margin_right (rinoh.table.TableCellStyle attribute), 87
- margin_right (rinoh.table.TableStyle attribute), 84
- matcher (in module rinoh.stylesheets), 11
- MixedStyledText (class in rinoh.text), 117
- MM (in module rinoh.dimension), 99
- module
 - rinoh.attribute, 97
 - rinoh.color, 98
 - rinoh.dimension, 98
 - rinoh.document, 99
 - rinoh.draw, 101
 - rinoh.flowable, 101
 - rinoh.font, 104
 - rinoh.font.style, 106
 - rinoh.image, 106
 - rinoh.index, 108
 - rinoh.inline, 117
 - rinoh.language, 108
 - rinoh.number, 113
 - rinoh.paper, 115
 - rinoh.paragraph, 116
 - rinoh.reference, 120
 - rinoh.strings, 124
 - rinoh.structure, 121
 - rinoh.style, 124
 - rinoh.stylesheets, 11
 - rinoh.table, 126
 - rinoh.template, 127
 - rinoh.templates.article, 91
 - rinoh.templates.book, 92
 - rinoh.text, 116

N

- new_page() (rinoh.template.DocumentPart method), 129
- NL (in module rinoh.language), 112
- no_break_after (rinoh.image.CaptionStyle attribute), 31
- no_break_after (rinoh.paragraph.ParagraphStyle attribute), 41
- no_break_after (rinoh.reference.NoteMarkerStyle attribute), 52
- no_break_after (rinoh.reference.ReferencingParagraphStyle attribute), 50
- no_break_after (rinoh.structure.HeadingStyle attribute), 60
- no_break_after (rinoh.structure.ListItemLabelStyle attribute), 68
- no_break_after (rinoh.structure.TableOfContentsEntryStyle attribute), 78
- no_break_after (rinoh.structure.TableOfContentsStyle attribute), 73
- no_break_after (rinoh.text.TextStyle attribute), 43
- NoBreakAfter (class in rinoh.text), 117
- Note (class in rinoh.reference), 120
- note (rinoh.structure.AdmonitionTitles attribute), 123
- NoteMarkerBase (class in rinoh.reference), 120
- NoteMarkerByID (class in rinoh.reference), 120
- NoteMarkerStyle (class in rinoh.reference), 51
- NoteMarkerWithNote (class in rinoh.reference), 120

- number_format (rinoh.image.CaptionStyle attribute), 27
- number_format (rinoh.number.NumberStyle attribute), 114
- number_format (rinoh.paragraph.ParagraphStyle attribute), 37
- number_format (rinoh.reference.NoteMarkerStyle attribute), 53
- number_format (rinoh.reference.ReferencingParagraphStyle attribute), 47
- number_format (rinoh.structure.HeadingStyle attribute), 57
- number_format (rinoh.structure.ListItemLabelStyle attribute), 64
- number_format (rinoh.structure.ListStyle attribute), 63
- number_format (rinoh.structure.TableOfContentsEntryStyle attribute), 75
- number_format (rinoh.structure.TableOfContentsStyle attribute), 71
- number_separator (rinoh.image.CaptionStyle attribute), 28
- number_separator (rinoh.paragraph.ParagraphStyle attribute), 38
- number_separator (rinoh.reference.ReferencingParagraphStyle attribute), 47
- number_separator (rinoh.structure.HeadingStyle attribute), 57
- number_separator (rinoh.structure.ListItemLabelStyle attribute), 64
- number_separator (rinoh.structure.TableOfContentsEntryStyle attribute), 75
- number_separator (rinoh.structure.TableOfContentsStyle attribute), 72
- NumberFormat (class in rinoh.number), 113
- numbering_level (rinoh.image.CaptionStyle attribute), 27
- numbering_level (rinoh.paragraph.ParagraphStyle attribute), 38
- numbering_level (rinoh.reference.ReferencingParagraphStyle attribute), 47
- numbering_level (rinoh.structure.HeadingStyle attribute), 56
- numbering_level (rinoh.structure.ListItemLabelStyle attribute), 65
- numbering_level (rinoh.structure.TableOfContentsEntryStyle attribute), 75
- numbering_level (rinoh.structure.TableOfContentsStyle attribute), 72
- NumberStyle (class in rinoh.number), 114

O

- OptionSet (class in rinoh.attribute), 97
- ordered (rinoh.structure.ListStyle attribute), 61
- OverrideDefault (class in rinoh.attribute), 97

P

- padding (rinoh.flowable.FloatStyle attribute), 26
- padding (rinoh.flowable.FlowableStyle attribute), 19
- padding (rinoh.flowable.GroupedFlowablesStyle attribute), 24
- padding (rinoh.flowable.LabeledFlowableStyle attribute), 21
- padding (rinoh.image.CaptionStyle attribute), 29
- padding (rinoh.image.FigureStyle attribute), 33
- padding (rinoh.index.IndexStyle attribute), 35
- padding (rinoh.inline.InlineFlowableStyle attribute), 44
- padding (rinoh.paragraph.ParagraphStyle attribute), 38
- padding (rinoh.reference.ReferencingParagraphStyle attribute), 47
- padding (rinoh.structure.AdmonitionStyle attribute), 80
- padding (rinoh.structure.HeadingStyle attribute), 57
- padding (rinoh.structure.HorizontalRuleStyle attribute), 82
- padding (rinoh.structure.ListItemLabelStyle attribute), 65
- padding (rinoh.structure.ListStyle attribute), 62
- padding (rinoh.structure.SectionStyle attribute), 54
- padding (rinoh.structure.TableOfContentsEntryStyle attribute), 75
- padding (rinoh.structure.TableOfContentsStyle attribute), 70
- padding (rinoh.table.TableCellStyle attribute), 87
- padding (rinoh.table.TableStyle attribute), 84
- padding_bottom (rinoh.flowable.FloatStyle attribute), 26
- padding_bottom (rinoh.flowable.FlowableStyle attribute), 19
- padding_bottom (rinoh.flowable.GroupedFlowablesStyle attribute), 24
- padding_bottom (rinoh.flowable.LabeledFlowableStyle attribute), 22

padding_bottom (rinoh.image.CaptionStyle attribute), 29
padding_bottom (rinoh.image.FigureStyle attribute), 33
padding_bottom (rinoh.index.IndexStyle attribute), 36
padding_bottom (rinoh.inline.InlineFlowableStyle attribute), 44
padding_bottom (rinoh.paragraph.ParagraphStyle attribute), 39
padding_bottom (rinoh.reference.ReferencingParagraphStyle attribute), 48
padding_bottom (rinoh.structure.AdmonitionStyle attribute), 80
padding_bottom (rinoh.structure.HeadingStyle attribute), 58
padding_bottom (rinoh.structure.HorizontalRuleStyle attribute), 82
padding_bottom (rinoh.structure.ListItemLabelStyle attribute), 65
padding_bottom (rinoh.structure.ListStyle attribute), 62
padding_bottom (rinoh.structure.SectionStyle attribute), 55
padding_bottom (rinoh.structure.TableOfContentsEntryStyle attribute), 76
padding_bottom (rinoh.structure.TableOfContentsStyle attribute), 70
padding_bottom (rinoh.table.TableCellStyle attribute), 87
padding_bottom (rinoh.table.TableStyle attribute), 85
padding_left (rinoh.flowable.FloatStyle attribute), 26
padding_left (rinoh.flowable.FlowableStyle attribute), 19
padding_left (rinoh.flowable.GroupedFlowablesStyle attribute), 24
padding_left (rinoh.flowable.LabeledFlowableStyle attribute), 21
padding_left (rinoh.image.CaptionStyle attribute), 29
padding_left (rinoh.image.FigureStyle attribute), 33
padding_left (rinoh.index.IndexStyle attribute), 35
padding_left (rinoh.inline.InlineFlowableStyle attribute), 44
padding_left (rinoh.paragraph.ParagraphStyle attribute), 38
padding_left (rinoh.reference.ReferencingParagraphStyle attribute), 47
padding_left (rinoh.structure.AdmonitionStyle attribute), 80
padding_left (rinoh.structure.HeadingStyle attribute), 57
padding_left (rinoh.structure.HorizontalRuleStyle attribute), 82
padding_left (rinoh.structure.ListItemLabelStyle attribute), 65
padding_left (rinoh.structure.ListStyle attribute), 62
padding_left (rinoh.structure.SectionStyle attribute), 54
padding_left (rinoh.structure.TableOfContentsEntryStyle attribute), 75
padding_left (rinoh.structure.TableOfContentsStyle attribute), 70
padding_left (rinoh.table.TableCellStyle attribute), 87
padding_left (rinoh.table.TableStyle attribute), 84
padding_right (rinoh.flowable.FloatStyle attribute), 26
padding_right (rinoh.flowable.FlowableStyle attribute), 19
padding_right (rinoh.flowable.GroupedFlowablesStyle attribute), 24
padding_right (rinoh.flowable.LabeledFlowableStyle attribute), 21
padding_right (rinoh.image.CaptionStyle attribute), 29
padding_right (rinoh.image.FigureStyle attribute), 33
padding_right (rinoh.index.IndexStyle attribute), 36
padding_right (rinoh.inline.InlineFlowableStyle attribute), 44
padding_right (rinoh.paragraph.ParagraphStyle attribute), 38
padding_right (rinoh.reference.ReferencingParagraphStyle attribute), 48
padding_right (rinoh.structure.AdmonitionStyle attribute), 80
padding_right (rinoh.structure.HeadingStyle attribute), 58
padding_right (rinoh.structure.HorizontalRuleStyle attribute), 82
padding_right (rinoh.structure.ListItemLabelStyle attribute), 65
padding_right (rinoh.structure.ListStyle attribute), 62
padding_right (rinoh.structure.SectionStyle attribute), 55
padding_right (rinoh.structure.TableOfContentsEntryStyle attribute), 76
padding_right (rinoh.structure.TableOfContentsStyle attribute), 70
padding_right (rinoh.table.TableCellStyle attribute), 87
padding_right (rinoh.table.TableStyle attribute), 84
padding_top (rinoh.flowable.FloatStyle attribute), 26
padding_top (rinoh.flowable.FlowableStyle attribute), 19

padding_top (rinoh.flowable.GroupedFlowablesStyle attribute), 24

padding_top (rinoh.flowable.LabeledFlowableStyle attribute), 21

padding_top (rinoh.image.CaptionStyle attribute), 29

padding_top (rinoh.image.FigureStyle attribute), 33

padding_top (rinoh.index.IndexStyle attribute), 36

padding_top (rinoh.inline.InlineFlowableStyle attribute), 44

padding_top (rinoh.paragraph.ParagraphStyle attribute), 38

padding_top (rinoh.reference.ReferencingParagraphStyle attribute), 48

padding_top (rinoh.structure.AdmonitionStyle attribute), 80

padding_top (rinoh.structure.HeadingStyle attribute), 58

padding_top (rinoh.structure.HorizontalRuleStyle attribute), 82

padding_top (rinoh.structure.ListItemLabelStyle attribute), 65

padding_top (rinoh.structure.ListStyle attribute), 62

padding_top (rinoh.structure.SectionStyle attribute), 55

padding_top (rinoh.structure.TableOfContentsEntryStyle attribute), 76

padding_top (rinoh.structure.TableOfContentsStyle attribute), 70

padding_top (rinoh.table.TableCellStyle attribute), 87

padding_top (rinoh.table.TableStyle attribute), 85

Page (class in rinoh.document), 100

page (rinoh.document.Page property), 100

page (rinoh.templates.article.Article attribute), 92

page (rinoh.templates.book.Book attribute), 94

page_break (rinoh.flowable.FloatStyle attribute), 27

page_break (rinoh.flowable.FlowableStyle attribute), 20

page_break (rinoh.flowable.GroupedFlowablesStyle attribute), 25

page_break (rinoh.flowable.LabeledFlowableStyle attribute), 22

page_break (rinoh.image.CaptionStyle attribute), 30

page_break (rinoh.image.FigureStyle attribute), 34

page_break (rinoh.index.IndexStyle attribute), 37

page_break (rinoh.inline.InlineFlowableStyle attribute), 45

page_break (rinoh.paragraph.ParagraphStyle attribute), 39

page_break (rinoh.reference.ReferencingParagraphStyle attribute), 49

page_break (rinoh.structure.AdmonitionStyle attribute), 81

page_break (rinoh.structure.HeadingStyle attribute), 58

page_break (rinoh.structure.HorizontalRuleStyle attribute), 83

page_break (rinoh.structure.ListItemLabelStyle attribute), 66

page_break (rinoh.structure.ListStyle attribute), 63

page_break (rinoh.structure.SectionStyle attribute), 56

page_break (rinoh.structure.TableOfContentsEntryStyle attribute), 77

page_break (rinoh.structure.TableOfContentsStyle attribute), 71

page_break (rinoh.table.TableCellStyle attribute), 88

page_break (rinoh.table.TableStyle attribute), 85

page_number_format (rinoh.template.ContentsPartTemplate attribute), 130

page_number_format (rinoh.template.DocumentPartTemplate attribute), 129

page_number_format (rinoh.template.FixedDocumentPartTemplate attribute), 131

page_number_format (rinoh.template.TitlePartTemplate attribute), 130

page_number_prefix (rinoh.template.ContentsPartTemplate attribute), 130

page_number_prefix (rinoh.template.DocumentPartTemplate attribute), 129

page_number_prefix (rinoh.template.FixedDocumentPartTemplate attribute), 131

page_number_prefix (rinoh.template.TitlePartTemplate attribute), 130

page_orientation (rinoh.template.BodyPageTemplate attribute), 134

page_orientation (rinoh.template.BodyPageTemplateBase attribute), 132

page_orientation (rinoh.template.PageTemplateBase attribute), 136

page_orientation (rinoh.template.TitlePageTemplate attribute), 135

page_size (rinoh.template.BodyPageTemplate attribute), 134

page_size (rinoh.template.BodyPageTemplateBase attribute), 132

page_size (rinoh.template.PageTemplateBase attribute), 136

page_size (rinoh.template.TitlePageTemplate attribute), 135

PageBreak (class in rinoh.flowable), 102
 PageNumberFormat (class in rinoh.document), 100
 PageOrientation (class in rinoh.document), 100
 PageTemplateBase (class in rinoh.template), 136
 PageType (class in rinoh.document), 100
 Paper (class in rinoh.paper), 115
 Paragraph (class in rinoh.paragraph), 116
 ParagraphBase (class in rinoh.paragraph), 116
 ParagraphState (class in rinoh.paragraph), 116
 ParagraphStyle (class in rinoh.paragraph), 37
 parse_string() (rinoh.color.Color class method), 98
 ParseError, 97
 parts (rinoh.template.DocumentTemplate attribute), 128
 parts (rinoh.templates.article.Article attribute), 91
 parts (rinoh.templates.book.Book attribute), 92
 PartsList (class in rinoh.template), 129
 PERCENT (in module rinoh.dimension), 99
 PICA (in module rinoh.dimension), 99
 PL (in module rinoh.language), 113
 place() (rinoh.document.Page method), 100
 Polygon (class in rinoh.draw), 101
 position (rinoh.image.CaptionStyle attribute), 31
 position (rinoh.paragraph.ParagraphStyle attribute), 41
 position (rinoh.reference.NoteMarkerStyle attribute), 52
 position (rinoh.reference.ReferencingParagraphStyle attribute), 50
 position (rinoh.structure.HeadingStyle attribute), 60
 position (rinoh.structure.ListItemLabelStyle attribute), 67
 position (rinoh.structure.TableOfContentsEntryStyle attribute), 78
 position (rinoh.structure.TableOfContentsStyle attribute), 73
 position (rinoh.text.TextStyle attribute), 42
 prepare() (rinoh.flowable.LabeledFlowable method), 102
 prepare() (rinoh.flowable.StaticGroupedFlowables method), 103
 prepare() (rinoh.paragraph.ParagraphBase method), 116
 prepare() (rinoh.reference.NoteMarkerBase method), 120
 prepare() (rinoh.reference.NoteMarkerWithNote method), 120
 prepare() (rinoh.structure.Heading method), 121
 prepare() (rinoh.table.Table method), 126
 prepare() (rinoh.table.TableRow method), 127
 prepare() (rinoh.table.TableSection method), 126
 prepare() (rinoh.text.MixedStyledText method), 117
 ProportionalSpacing (class in rinoh.paragraph), 118
 PT (in module rinoh.dimension), 99

Q

QUARTERS (in module rinoh.dimension), 99
 quiet (rinoh.reference.NoteMarkerStyle attribute), 51

R

Rectangle (class in rinoh.draw), 101
 Reference (class in rinoh.reference), 120
 ReferenceField (class in rinoh.reference), 120
 ReferenceText (class in rinoh.reference), 120
 ReferenceType (class in rinoh.reference), 120
 ReferencingParagraph (class in rinoh.reference), 120
 ReferencingParagraphStyle (class in rinoh.reference), 46
 render() (rinoh.document.Document method), 100
 render() (rinoh.document.Page method), 100

- render() (rinoh.flowable.GroupedFlowables method), 103
- render() (rinoh.flowable.GroupedLabeledFlowables method), 103
- render() (rinoh.flowable.LabeledFlowable method), 102
- render() (rinoh.paragraph.ParagraphBase method), 116
- render() (rinoh.structure.HorizontalRule method), 124
- render() (rinoh.table.Table method), 126
- repeat_head (rinoh.table.TableStyle attribute), 84
- rgba (rinoh.color.Color property), 98
- right_margin (rinoh.template.BodyPageTemplate attribute), 134
- right_margin (rinoh.template.BodyPageTemplateBase attribute), 132
- right_margin (rinoh.template.PageTemplateBase attribute), 136
- right_margin (rinoh.template.TitlePageTemplate attribute), 135
- rinoh command line option
 - docs, 6
 - format, 5
 - help, 5
 - install-resources, 5
 - list-fonts, 6
 - list-formats, 6
 - list-options, 6
 - list-stylesheets, 5
 - list-templates, 5
 - option, 5
 - output, 5
 - paper, 5
 - stylesheet, 5
 - template, 5
 - version, 6
 - versions, 6
 - f, 5
 - h, 5
 - i, 5
 - O, 5
 - o, 5
 - p, 5
 - s, 5
 - t, 5
 - input, 5
- rinoh.attribute
 - module, 97
- rinoh.color
 - module, 98
- rinoh.dimension
 - module, 98
- rinoh.document
 - module, 99
- rinoh.draw
 - module, 101
- rinoh.flowable
 - module, 101
- rinoh.font
 - module, 104
- rinoh.font.style
 - module, 106
- rinoh.image
 - module, 106
- rinoh.index
 - module, 108

- rinoh.inline
 - module, 117
- rinoh.language
 - module, 108
- rinoh.number
 - module, 113
- rinoh.paper
 - module, 115
- rinoh.paragraph
 - module, 116
- rinoh.reference
 - module, 120
- rinoh.strings
 - module, 124
- rinoh.structure
 - module, 121
- rinoh.style
 - module, 124
- rinoh.stylesheets
 - module, 11
- rinoh.table
 - module, 126
- rinoh.template
 - module, 127
- rinoh.templates.article
 - module, 91
- rinoh.templates.book
 - module, 92
- rinoh.text
 - module, 116
- rinoh_documents
 - Sphinx builder configuration value, 7
- rinoh_domain_indices
 - Sphinx builder configuration value, 9
- rinoh_logo
 - Sphinx builder configuration value, 9
- rinoh_metadata
 - Sphinx builder configuration value, 9
- rinoh_paper_size
 - Sphinx builder configuration value, 8
- rinoh_stylesheet
 - Sphinx builder configuration value, 8
- rinoh_targets
 - Sphinx builder configuration value, 8
- rinoh_template
 - Sphinx builder configuration value, 8
- root (rinoh.attribute.RuleSetFile property), 97
- rotate (rinoh.image.ImageArgs attribute), 107
- RuleSet (class in rinoh.attribute), 97
- RuleSetFile (class in rinoh.attribute), 97

S

- same_page (rinoh.flowable.GroupedFlowablesStyle attribute), 23
- same_page (rinoh.image.FigureStyle attribute), 34
- same_page (rinoh.index.IndexStyle attribute), 35
- same_page (rinoh.structure.AdmonitionStyle attribute), 79
- same_page (rinoh.structure.ListStyle attribute), 61

same_page (rinoh.structure.SectionStyle attribute), 54
 same_page (rinoh.structure.TableOfContentsStyle attribute), 69
 same_page (rinoh.table.TableCellStyle attribute), 86
 Scale (class in rinoh.image), 107
 scale (rinoh.image.ImageArgs attribute), 107
 script_level() (rinoh.text.StyledText method), 117
 Section (class in rinoh.structure), 121
 SectionStyle (class in rinoh.structure), 53
 SectionTitles (class in rinoh.structure), 121
 seealso (rinoh.structure.AdmonitionTitles attribute), 123
 SetMetadataFlowable (class in rinoh.flowable), 102
 Shape (class in rinoh.draw), 101
 ShapeStyle (class in rinoh.draw), 18
 show_in_toc (rinoh.structure.SectionStyle attribute), 53
 sideways (rinoh.template.BodyPageTemplate attribute), 135
 sideways (rinoh.template.BodyPageTemplateBase attribute), 133
 sideways (rinoh.template.PageTemplateBase attribute), 137
 sideways (rinoh.template.TitlePageTemplate attribute), 136
 SINGLE (in module rinoh.paragraph), 119
 SingleStyledText (class in rinoh.text), 117
 space_above (rinoh.flowable.FloatStyle attribute), 25
 space_above (rinoh.flowable.FlowableStyle attribute), 18
 space_above (rinoh.flowable.GroupedFlowablesStyle attribute), 23
 space_above (rinoh.flowable.LabeledFlowableStyle attribute), 21
 space_above (rinoh.image.CaptionStyle attribute), 28
 space_above (rinoh.image.FigureStyle attribute), 32
 space_above (rinoh.index.IndexStyle attribute), 35
 space_above (rinoh.inline.InlineFlowableStyle attribute), 44
 space_above (rinoh.paragraph.ParagraphStyle attribute), 38
 space_above (rinoh.reference.ReferencingParagraphStyle attribute), 47
 space_above (rinoh.structure.AdmonitionStyle attribute), 79
 space_above (rinoh.structure.HeadingStyle attribute), 57
 space_above (rinoh.structure.HorizontalRuleStyle attribute), 81
 space_above (rinoh.structure.ListItemLabelStyle attribute), 65
 space_above (rinoh.structure.ListStyle attribute), 61
 space_above (rinoh.structure.SectionStyle attribute), 54
 space_above (rinoh.structure.TableOfContentsEntryStyle attribute), 75
 space_above (rinoh.structure.TableOfContentsStyle attribute), 69
 space_above (rinoh.table.TableCellStyle attribute), 86
 space_above (rinoh.table.TableStyle attribute), 84
 space_below (rinoh.flowable.FloatStyle attribute), 25
 space_below (rinoh.flowable.FlowableStyle attribute), 18
 space_below (rinoh.flowable.GroupedFlowablesStyle attribute), 23
 space_below (rinoh.flowable.LabeledFlowableStyle attribute), 21
 space_below (rinoh.image.CaptionStyle attribute), 28
 space_below (rinoh.image.FigureStyle attribute), 32
 space_below (rinoh.index.IndexStyle attribute), 35
 space_below (rinoh.inline.InlineFlowableStyle attribute), 44
 space_below (rinoh.paragraph.ParagraphStyle attribute), 38
 space_below (rinoh.reference.ReferencingParagraphStyle attribute), 47
 space_below (rinoh.structure.AdmonitionStyle attribute), 80
 space_below (rinoh.structure.HeadingStyle attribute), 57
 space_below (rinoh.structure.HorizontalRuleStyle attribute), 82
 space_below (rinoh.structure.ListItemLabelStyle attribute), 65
 space_below (rinoh.structure.ListStyle attribute), 62
 space_below (rinoh.structure.SectionStyle attribute), 54
 space_below (rinoh.structure.TableOfContentsEntryStyle attribute), 75
 space_below (rinoh.structure.TableOfContentsStyle attribute), 69

- space_below (rinoh.table.TableCellStyle attribute), 86
- space_below (rinoh.table.TableStyle attribute), 84
- sphinx (in module rinoh.stylesheets), 11
- Sphinx builder configuration value
 - rinoh_documents, 7
 - rinoh_domain_indices, 9
 - rinoh_logo, 9
 - rinoh_metadata, 9
 - rinoh_paper_size, 8
 - rinoh_stylesheet, 8
 - rinoh_targets, 8
 - rinoh_template, 8
- sphinx_article (in module rinoh.stylesheets), 11
- sphinx_base14 (in module rinoh.stylesheets), 11
- split_minimum_rows (rinoh.table.TableStyle attribute), 84
- STANDARD (in module rinoh.paragraph), 119
- StaticGroupedFlowables (class in rinoh.flowable), 103
- String (class in rinoh.strings), 124
- StringCollection (class in rinoh.strings), 124
- StringField (class in rinoh.strings), 124
- Strings (class in rinoh.strings), 124
- strings (rinoh.template.DocumentTemplate attribute), 128
- strings (rinoh.templates.article.Article attribute), 91
- strings (rinoh.templates.book.Book attribute), 93
- Stroke (class in rinoh.draw), 101
- stroke (rinoh.draw.LineStyle attribute), 17
- stroke (rinoh.draw.ShapeStyle attribute), 18
- stroke (rinoh.structure.HorizontalRuleStyle attribute), 83
- stroke (rinoh.table.TableCellBackgroundStyle attribute), 89
- stroke (rinoh.table.TableCellBorderStyle attribute), 88
- Style (class in rinoh.style), 125
- style_class (rinoh.draw.Line attribute), 101
- style_class (rinoh.draw.Shape attribute), 101
- style_class (rinoh.flowable.Float attribute), 104
- style_class (rinoh.flowable.GroupedFlowables attribute), 103
- style_class (rinoh.flowable.LabeledFlowable attribute), 102
- style_class (rinoh.image.Caption attribute), 107
- style_class (rinoh.image.Figure attribute), 107
- style_class (rinoh.index.Index attribute), 108
- style_class (rinoh.inline.InlineFlowable attribute), 117
- style_class (rinoh.paragraph.ParagraphBase attribute), 116
- style_class (rinoh.reference.Note attribute), 120
- style_class (rinoh.reference.NoteMarkerBase attribute), 120
- style_class (rinoh.reference.ReferencingParagraph attribute), 120
- style_class (rinoh.structure.Admonition attribute), 122
- style_class (rinoh.structure.Heading attribute), 121
- style_class (rinoh.structure.HorizontalRule attribute), 124
- style_class (rinoh.structure.List attribute), 122
- style_class (rinoh.structure.TableOfContents attribute), 122
- style_class (rinoh.structure.TableOfContentsEntry attribute), 122
- style_class (rinoh.style.Styled attribute), 125
- style_class (rinoh.table.Table attribute), 126
- style_class (rinoh.table.TableCell attribute), 127
- style_class (rinoh.table.TableCellBackground attribute), 127
- style_class (rinoh.table.TableCellBorder attribute), 127
- style_class (rinoh.table.TableWithCaption attribute), 126
- style_class (rinoh.text.StyledText attribute), 117
- Styled (class in rinoh.style), 124

- StyledMatcher (class in rinoh.style), 126
- StyledText (class in rinoh.text), 116
- StyleSheet (class in rinoh.style), 125
- stylesheet (rinoh.template.DocumentTemplate attribute), 128
- stylesheet (rinoh.templates.article.Article attribute), 91
- stylesheet (rinoh.templates.book.Book attribute), 92
- StyleSheetFile (class in rinoh.style), 126

T

- tab_stops (rinoh.image.CaptionStyle attribute), 28
- tab_stops (rinoh.paragraph.ParagraphStyle attribute), 37
- tab_stops (rinoh.reference.ReferencingParagraphStyle attribute), 46
- tab_stops (rinoh.structure.HeadingStyle attribute), 56
- tab_stops (rinoh.structure.ListItemLabelStyle attribute), 64
- tab_stops (rinoh.structure.TableOfContentsEntryStyle attribute), 74
- tab_stops (rinoh.structure.TableOfContentsStyle attribute), 71
- TabAlign (class in rinoh.paragraph), 119
- Table (class in rinoh.table), 126
- TableBody (class in rinoh.table), 126
- TableCell (class in rinoh.table), 127
- TableCellBackground (class in rinoh.table), 127
- TableCellBackgroundStyle (class in rinoh.table), 88
- TableCellBorder (class in rinoh.table), 127
- TableCellBorderStyle (class in rinoh.table), 88
- TableCellStyle (class in rinoh.table), 86
- TableHead (class in rinoh.table), 126
- TableOfContents (class in rinoh.structure), 122
- TableOfContentsEntry (class in rinoh.structure), 122
- TableOfContentsEntryStyle (class in rinoh.structure), 74
- TableOfContentsSection (class in rinoh.structure), 122
- TableOfContentsStyle (class in rinoh.structure), 69
- TableRow (class in rinoh.table), 127
- TableSection (class in rinoh.table), 126
- TableStyle (class in rinoh.table), 83
- TableWithCaption (class in rinoh.table), 126
- TABLOID (in module rinoh.paper), 116
- TabStop (class in rinoh.paragraph), 119
- TabStopList (class in rinoh.paragraph), 119
- target_has_class() (rinoh.reference.ReferencingParagraph method), 120
- target_has_classes() (rinoh.reference.ReferencingParagraph method), 120
- target_is_of_type() (rinoh.reference.ReferencingParagraph method), 120
- target_style() (rinoh.reference.ReferencingParagraph method), 120
- template (rinoh.template.TemplateConfiguration attribute), 128
- TemplateConfiguration (class in rinoh.template), 128
- text (rinoh.reference.ReferencingParagraphStyle attribute), 46
- text (rinoh.structure.TableOfContentsEntryStyle attribute), 74
- text_align (rinoh.image.CaptionStyle attribute), 28
- text_align (rinoh.paragraph.ParagraphStyle attribute), 37
- text_align (rinoh.reference.ReferencingParagraphStyle attribute), 46
- text_align (rinoh.structure.HeadingStyle attribute), 56
- text_align (rinoh.structure.ListItemLabelStyle attribute), 64
- text_align (rinoh.structure.TableOfContentsEntryStyle attribute), 74
- text_align (rinoh.structure.TableOfContentsStyle attribute), 71
- TextAlign (class in rinoh.paragraph), 118
- TextPosition (class in rinoh.font.style), 106
- TextStyle (class in rinoh.text), 42
- tip (rinoh.structure.AdmonitionTitles attribute), 123

- title (rinoh.flowable.GroupedFlowablesStyle attribute), 23
- title (rinoh.image.FigureStyle attribute), 34
- title (rinoh.index.IndexStyle attribute), 35
- title (rinoh.structure.AdmonitionStyle attribute), 79
- title (rinoh.structure.ListStyle attribute), 61
- title (rinoh.structure.SectionStyle attribute), 54
- title (rinoh.structure.TableOfContentsStyle attribute), 69
- title (rinoh.table.TableCellStyle attribute), 86
- title (rinoh.templates.book.Book attribute), 93
- title_page (rinoh.templates.book.Book attribute), 94
- TitlePageTemplate (class in rinoh.template), 135
- TitlePartTemplate (class in rinoh.template), 130
- to_string() (rinoh.index.InlineIndexTarget method), 108
- to_string() (rinoh.text.StyledText method), 116
- top_margin (rinoh.template.BodyPageTemplate attribute), 134
- top_margin (rinoh.template.BodyPageTemplateBase attribute), 132
- top_margin (rinoh.template.PageTemplateBase attribute), 136
- top_margin (rinoh.template.TitlePageTemplate attribute), 135
- type (rinoh.reference.NoteMarkerStyle attribute), 51
- Typeface (class in rinoh.font), 105
- typeface (rinoh.image.CaptionStyle attribute), 30
- typeface (rinoh.paragraph.ParagraphStyle attribute), 40
- typeface (rinoh.reference.NoteMarkerStyle attribute), 51
- typeface (rinoh.reference.ReferencingParagraphStyle attribute), 49
- typeface (rinoh.structure.HeadingStyle attribute), 59
- typeface (rinoh.structure.ListItemLabelStyle attribute), 67
- typeface (rinoh.structure.TableOfContentsEntryStyle attribute), 77
- typeface (rinoh.structure.TableOfContentsStyle attribute), 72
- typeface (rinoh.text.TextStyle attribute), 42

U

- update() (rinoh.style.StyledMatcher method), 126
- UserStrings (class in rinoh.strings), 124

V

- vertical_align (rinoh.table.TableCellStyle attribute), 86
- VerticalAlign (class in rinoh.table), 127

W

- WarnFlowable (class in rinoh.flowable), 102
- warning (rinoh.structure.AdmonitionTitles attribute), 123
- width (rinoh.flowable.FloatStyle attribute), 25
- width (rinoh.flowable.FlowableStyle attribute), 18
- width (rinoh.flowable.GroupedFlowablesStyle attribute), 23
- width (rinoh.flowable.LabeledFlowableStyle attribute), 21
- width (rinoh.image.CaptionStyle attribute), 27
- width (rinoh.image.FigureStyle attribute), 32
- width (rinoh.image.ImageArgs attribute), 107
- width (rinoh.index.IndexStyle attribute), 35
- width (rinoh.inline.InlineFlowableStyle attribute), 44
- width (rinoh.paragraph.ParagraphStyle attribute), 37
- width (rinoh.reference.ReferencingParagraphStyle attribute), 46
- width (rinoh.structure.AdmonitionStyle attribute), 79
- width (rinoh.structure.HeadingStyle attribute), 56
- width (rinoh.structure.HorizontalRuleStyle attribute), 81
- width (rinoh.structure.ListItemLabelStyle attribute), 64
- width (rinoh.structure.ListStyle attribute), 61

width (rinoh.structure.SectionStyle attribute), 54
width (rinoh.structure.TableOfContentsEntryStyle attribute), 74
width (rinoh.structure.TableOfContentsStyle attribute), 69
width (rinoh.table.TableCellStyle attribute), 86
width (rinoh.table.TableStyle attribute), 84
wrap_label (rinoh.flowable.LabeledFlowableStyle attribute), 21

Y

y_offset() (rinoh.text.StyledText method), 117