

# <u>Jawahar Education Societys Annasaheb Chudaman Patil College of Engineering, Kharghar</u> Navi Mumbai

**Experiment No: 06** 

•Aim: To implement a Simple Neural Network using backpropagation.

### • Theory:


### What is Backpropagation?

Backpropagation is the essence of neural network training. It is the method of fine-tuning the weights of a neural network based on the error rate obtained in the previous epoch (i.e., iteration). Proper tuning of the weights allows you to reduce error rates and make the model reliable by increasing its generalization.

## **How Backpropagation Algorithm Works**

The Back propagation algorithm in neural network computes the gradient of the loss function for a single weight by the chain rule. It efficiently computes one layer at a time, unlike a native direct computation. It computes the gradient, but it does not define how the gradient is used. It generalizes the computation in the delta rule.

Consider the following Back propagation neural network example diagram to understand:



- 1. Inputs X, arrive through the preconnected path
- 2. Input is modeled using real weights W. The weights are usually randomly selected.
- 3. Calculate the output for every neuron from the input layer, to the hidden layers, to the output layer.
- 4. Calculate the error in the outputs

ErrorB= Actual Output – Desired Output

5. Travel back from the output layer to the hidden layer to adjust the weights such that the error is decreased.



# <u>Jawahar Education Societys Annasaheb Chudaman Patil College of Engineering, Kharghar</u> Navi Mumbai

## **Types of Backpropagation Networks**

Two Types of Backpropagation Networks are:

- Static Back-propagation
- Recurrent Backpropagation

### **Static back-propagation:**

It is one kind of backpropagation network which produces a mapping of a static input for static output. It is useful to solve static classification issues like optical character recognition.

### **Recurrent Backpropagation:**

Recurrent Back propagation in data mining is fed forward until a fixed value is achieved. After that, the error is computed and propagated backward.

The main difference between both of these methods is: that the mapping is rapid in static back-propagation while it is non static in recurrent backpropagation

## **Best practice Backpropagation**

Backpropagation in neural network can be explained with the help of "Shoe Lace" analogy

#### Too little tension =

Not enough constraining and very loose

#### Too much tension =

- Too much constraint (overtraining)
- Taking too much time (relatively slow process)
- Higher likelihood of breaking

### Pulling one lace more than other =

Discomfort (bias)

## **Disadvantages of using Backpropagation**

- The actual performance of backpropagation on a specific problem is dependent on the input data.
- Back propagation algorithm in data mining can be quite sensitive to noisy data
- You need to use the matrix-based approach for backpropagation instead of mini-batch.



## <u>Jawahar Education Societys Annasaheb Chudaman Patil College of Engineering, Kharghar</u> Navi Mumbai

## To implement a Simple Neural Network using backpropagation:

```
Jupyter Simple Neural Network Last Checkpoint: 09/20/2023 (autosaved)
                                                                                                                                                         Logout
      Edit View Insert Cell Kernel Widgets Help
                                                                                                                             Not Trusted
                                                                                                                                            Python 3 (ipykernel) O
P → Run ■ C >> Code
                                                                v
     In [25]: # Import Libraries
               import numpy as np
               import pandas as pd
               from sklearn.datasets import load_iris
               from sklearn.model_selection import train_test_split
               {\color{red}\mathsf{import}}\ {\color{blue}\mathsf{matplotlib.pyplot}}\ {\color{blue}\mathsf{as}}\ {\color{blue}\mathsf{plt}}
     In [26]: # Load dataset
               data = load_iris()
               # Get features and target
               X=data.data
               y=data.target
     In [27]: # Get dummy variable
y = pd.get_dummies(y).values
               y[:3]
     Out[27]: array([[1, 0, 0],
                       [1, 0, 0]
                       [1, 0, 0]], dtype=uint8)
               Split train and test set
```

```
In [28]: #Split data into train and test data
         X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=20, random_state=4)
         Initialize Hyperparameters and Weights
In [29]: # Initialize variables
         learning_rate = 0.1
         iterations = 5000
         N = y_train.size
          # number of input features
         input_size = 4
          # number of hidden Layers neurons
         hidden_size = 2
          # number of neurons at the output layer
          output_size = 3
         results = pd.DataFrame(columns=["mse", "accuracy"])
In [30]: # Initialize weights
         np.random.seed(10)
         # initializing weight for the hidden layer
W1 = np.random.normal(scale=0.5, size=(input_size, hidden_size))
          # initializing weight for the output layer
         W2 = np.random.normal(scale=0.5, size=(hidden_size , output_size))
```

```
In [31]: def sigmoid(x):
    return 1 / (1 + np.exp(-x))

def mean_squared_error(y_pred, y_true):
    return ((y_pred - y_true)**2).sum() / (2*y_pred.size)

def accuracy(y_pred, y_true):
    acc = y_pred.argmax(axis=1) == y_true.argmax(axis=1)
    return acc.mean()
```

MLBT PRIYUSH B KHOBRAGADE -52



# <u>Jawahar Education Societys Annasaheb Chudaman Patil College of Engineering, Kharghar</u> <u>Navi Mumbai</u>

```
Backpropagation Neural Network

In [33]:

for itr in range(iterations):

# feedforward propagation
# on hidden layer
Z1 = np.dot(X_train, W1)
A1 = sigmoid(Z1)


# on output layer
Z2 = np.dot(A1, W2)
A2 = sigmoid(Z2)


# Calculating error
mse = mean_squared_error(A2, y_train)
acc = accuracy(A2, y_train)
results-results.append({"mse":mse, "accuracy":acc},ignore_index=True )

# backpropagation
E1 = A2 - y_train
dW1 = E1 * A2 * (1 - A2)

E2 = np.dot(dW1, W2.T)
dW2 = E2 * A1 * (1 - A1)

# weight updates
W2_update = np.dot(X_train.T, dW2) / N
W1_update = np.dot(X_train.T, dW2) / N
W2 = W2 - learning_rate * W2_update
W1 = W1 - learning_rate * W1_update
```





MLBT PRIYUSH B KHOBRAGADE -52



# <u>Jawahar Education Societys Annasaheb Chudaman Patil College of Engineering, Kharghar</u> <u>Navi Mumbai</u>

```
In [37]: # feedforward
Z1 = np.dot(X_test, W1)
A1 = sigmoid(Z1)

Z2 = np.dot(A1, W2)
A2 = sigmoid(Z2)

acc = accuracy(A2, y_test)
print("Accuracy: {}".format(acc))

Accuracy: 0.8
In []:
```

## • Conclusion:

Implementing a simple neural network using backpropagation is a foundational step in the world of machine learning and artificial intelligence. It provides a solid understanding of how neural networks learn from data and how to train them to perform various tasks, from image classification to natural language processing and beyond. Further exploration and practice with more complex neural network architectures and real-world datasets will deepen your expertise in this exciting field.

MLBT PRIYUSH B KHOBRAGADE -52