

This specification covers the technical requirement of graphic films to be used. Graphic Films are being used for branding on dry, smooth, prepared surfaces

Premium Print Film - Cast Film (Technical Requirement)

Characteristic	Description
Vinyl	High quality opaque self-adhesive Cast vinyl manufactured for indoor and outdoor applications.
Color	Opaque White with excellent hiding power.
Thickness of Vinyl	Without adhesive: 2 mils (0.05 mm) With adhesive: 3 – 4 mils (0.08 – 0.10 mm)
Type of Adhesive	Pressure-activated (slide, tack, snap up, reposition) with air release channels. Includes Comply™ Adhesive for fast, easy bubble-free installations. Pressure-activated adhesive for easy sliding, tacking, snap up and repositioning.
Adhesive Color	Grey Pigmented Adhesive for Opaque White Film.
Liner	Polyethylene Coated Lay flat.
Tensile strength (min)	5 pounds/inch at 73°F (0.9 kg/cm at 23°C)
Adhesion Typical (24 hours post application)	Fruehauf pre-painted panels 3-5 pounds/inch (0.54-0.89 kg/cm)
Surface Burning Characteristics	Film must be classified as Class I or (A) rating when tested for ASTM E84 Standard. i.e. it is the most fire-resistant category that NFPA recognizes as necessary for interior wall and ceiling finish materials.
RoHS Compliance	The Vinyl should be RoHS Compliant
EU Reach Compliance	The product should not contain any SVHC >0.1% by weight according to Article 59.

Premium Over-laminate Film - Cast Film (Technical Requirement)

Characteristic	Description
Over-lamination / Graphic Protection Film	Highly conformable, high quality self-adhesive cast vinyl manufactured for indoor and outdoor applications.
Thickness of Vinyl	2 mils (0.05 mm)
Liner	Kraft Paper Liner
Chemical Resistance of Overlamine	Resists fuel vapors, mild acids, mild alkalis, and salts. Excellent resistance to water (this does not include immersion)
Protective Overlamine for Graphics protection	Entire graphic construction must be protected using Luster / Matt finished over-lamine with high-performance cast vinyl, not more than 2mil thickness.
Surface Burning Characteristics	Film must be classified as Class I or (A) rating when tested for ASTM E84 Standard. i.e. it is the most fire-resistant category that NFPA recognizes as necessary for interior wall and ceiling finish materials.

Wide Format Printing Specification (Technical Requirement)

Printing Platform	Latex Wide Format Digital Printing with Media OEM Co-Branded Inks / UV Wide Format Digital Printing with Media OEM Co-Branded Inks Only (i.e. Inks either Manufactured by Media OEM or Inks Certified by Media OEM with clear Label indication on Ink cartridges supplied globally) for Indoor and Outdoor application.
Ink Specification	Printing on face material must be done with Latex Wide Format Digital Printer with GREENGUARD / GREENGUARD GOLD Certified Inks or UV Wide Format Digital Printer with GREENGUARD / GREENGUARD GOLD Certified Inks only. Ink Layer should not peel, crack from base substrate used in the intended print application. Inks must be designed for outdoor application with excellent print durability. Print Substrate can be printed with minimum 600 dpi resolution with 10 Pass printing mode for excellent quality printing. Ink configuration should be 6 color printing process - Cyan, Magenta, Yellow, Black, Light Cyan, Light Magenta Inks to maintain excellent print quality and color production consistency.

Edge Sealer	The color of the edge sealer should be clear liquid Edge sealer should be an Acrylic/Vinyl solution in xylene Should have a Minimum viscosity of 300 Centipoise The sealer should resist mild acids, mild alkalis, and salts and should have excellent water resistance. Application temperature of the sealer should be between 50°F to 100°F (10°C to 38°C) Service temperature range of product in use
-------------	---

	-60°F to +150°F (-51°C to + 65°C).
--	------------------------------------

Note:

1. Graphic application to be done by Endorsed / Certified Application team and must be certified by Original manufacturer of Media. The Vendor should have a minimum of 2 Certified applicators and 2 trained applicators certified by the Original Manufacturers (OEM) of films. Applicator must be thoroughly trained and have thorough knowledge on execution process of graphic film application.
2. The Vendor must be authorized Converter of Media Original Manufacturers (OEM) for the specified applications done in India.
3. All the Graphic components (films, inks, over-laminate) used in the manufacturing of the graphic should be manufactured or co-branded with the film manufacturer. This is to ensure that Finished Graphic Warranty is applicable on all components used in manufacture of a graphic.
4. The Original Manufacturers (OEM) of films must have a QC team and a laboratory set-up within India to check and assure quality and resolve complaints.
5. The warranties must be issued in electronic form through an automated portal/system of issuing warranty by the film manufacturer. All the terms and conditions of the warranty should be clearly published on the manufacturer's website and available publicly.
6. Branding shall be treated as completed only if duly certified by OEM Finished Graphic Warranty Certificate is offered to OKI.
7. The surface preparation and the application should be done using manufacturers recommended procedures and the warranty should be provided by manufacturer directly.
8. Edges of graphics to be protected with Edge Sealer - the color of the edge sealer must be clear liquid. Edge sealer should be an Acrylic/Vinyl solution in xylene. Should have a Minimum viscosity of 300 centipoise. The sealer should resist mild acids, mild alkalis and salts. Must possess excellent water resistance.