

**CS 341 Automata Theory**  
**Geoffrey Parker - grp352**  
**Homework 10**  
**Due: Tuesday, March 27**

This assignment reviews Chapter 13 and covers Chapter 14 and Sections 17.1 - 17.3.

- 1) For each of the following languages  $L$ , state whether  $L$  is regular, context-free but not regular, or not context-free and prove your answer.

a)  $\{w : w = uu^R \text{ or } w = ua^n : n = |u|, u \in \{a, b\}^*\}$ .

*Answer.* Context-free but not regular. □

*Proof.* This language is generated by this context-free grammar so it must be context-free:

$$\begin{aligned} S &\rightarrow A \mid B \\ A &\rightarrow aAa \mid bAa \mid \epsilon \\ B &\rightarrow aBa \mid bBb \mid \epsilon \end{aligned}$$

This language  $L$  is not regular. Let  $w = b^k a^k$  for some integer  $k \geq 1$ . Then  $y$  must be  $b^p$  for some integer  $p$  such that  $1 \leq p \leq n$ . Pumping out  $y$  generates a new string  $w' = b^{k-p} a^k$  which is not in the language. Therefore by the pumping theorem this language is not regular. □

b)  $\{a^n b^{2n} c^m\} \cap \{a^n b^m c^{2m}\}$ .

*Answer.* Not context-free. This language is equivalent to  $L = \{a^n b^{2n} c^{4n}\}$ . □

*Proof.* Let  $w = a^k b^{2k} c^{4k}$ . Let region 1 be the  $a$ 's, region 2 be the  $b$ 's and region 3 be the  $c$ 's. In any case where  $vxy$  crosses a region boundary, pumping in will result in a new string with out of order  $a$ 's  $b$ 's or  $c$ 's, and thus not in the language. If  $vxy$  is contained solely within a region, pumping out will disrupt the cardinality requirement, thus also generating a string not in the language. Therefore by the pumping theorem for context-free languages this language is not context-free. □

c)  $L^*$ , where  $L = \{0^i 1^i 0^i : i \geq 0\}$ .

*Answer.* □

*Proof.* □

d)  $\neg L_0$ , where  $L_0 = \{ww : w \in \{a, b\}^*\}$ .

*Answer.* □

*Proof.* □

e)  $\{x \in \{a, b\}^* : |x| \text{ is even and the first half of } x \text{ has one more } a \text{ than does the second half}\}$ .

*Answer.* □

*Proof.* □

- 2) Give a decision procedure to answer the following question: given a context-free grammar  $G$ , does  $G$  generate any even length strings?

*Solution.*

□

- 3) Construct a standard, one-tape Turing machine  $M$  to decide the language  $L = \{x*y = z : x, y, z \in 1^+ \text{ and, when } x, y, \text{ and } z \text{ are viewed as unary numbers, } xy = z\}$ . For example, the string  $1111*11 = 11111111 \in L$ . Describe  $M$  in the macro language described in Section 17.1.5.

*Solution.*

□

- 4) Construct a standard 1-tape Turing machine  $M$  to compute the function  $sub_3$ , which is defined as follows:

$$sub_3(n) = \begin{cases} n - 3 & \text{if } n > 2 \\ 0 & \text{if } n \leq 2. \end{cases}$$

Specifically, compute  $sub_3$  of a natural number represented in binary. For example, on input 10111,  $M$  should output 10100. On input 11101,  $M$  should output 11010. (Hint: you may want to define a subroutine.)

*Solution.*

□