

Level Up OOP
Week 3: Momentum Builds
C# Vocabulary and Concepts
Ch. 4 - 6

[**T**] 1. Array (p.27)
[**P**] 2. dot operator (p.28)
[**OO**] 3. Methods (p.28)
[**Z**] 4. Properties (p.28)
[**V**] 5. Arguments (p.29)
[**K**] 6. Copy() (p.29)
[**LL**] 7. Length (p.29)
[**H**] 8. IndexOf() (p.30)
[**M**] 9. Sort() (p.30)
[**O**] 10. Concatenate (p.31)

[**BB**] 11. Substring() (p.32)
[**U**] 12. Equals() (p.33)
[**SS**] 13. Split() (p.33)
[**KK**] 14. Add() (p.35)
[**J**] 15. Count (p.36)
[**E**] 16. Insert() (p.36)
[**II**] 17. Remove() (p.36)
[**S**] 18. RemoveAt() (p.36)
[**R**] 19. Clear() (p.37)
[**CC**] 20. Contains() (p.37)

[**Q**] 21. reference type (p.37)
[**PP**] 22. value type (p.37)
[**RR**] 23. Write() (p.39)
[**GG**] 24. Console (p.40)
[**C**] 25. Placeholders (p.42)
[**EE**] 26. format specifier (p.43)
[**MM**] 27. Backslash (p.45)
[**AA**] 28. Newline (p.46)
[**JJ**] 29. Tab (p.45)
[**N**] 30. ReadLine() (p.46)

[**W**] 31. Convert (p.47)
[**X**] 32..ToInt32() (p.47)
[**A**] 33. ToDecimal() (p.48)
[**UU**] 34. ToDouble() (p.48)
[**B**] 35. ToSingle() (p.48)
[**I**] 36. Comparison (p.51)
[**Y**] 37. condition statement (p.51)
[**TT**] 38. control flow statement (p.51)
[**FF**] 39. logical operators (p.52)
[**HH**] 40. Break (p.57)

[**G**] 41. Default (p.57)
[**NN**] 42. jump statement (p.57)
[**QQ**] 43. Continue (p.65)
[**DD**] 44. Try-catch-finally (p.66)
[**L**] 45. Exception (p.68)
[**D**] 46. FormatException (p.69)
[**F**] 47. IndexOutOfRangeException (p.69)

- A. Used to convert to a decimal
- B. Converts the value of the specified Decimal to the equivalent single-precision floating-point number
- C. Curly braces that indicate where values are to be passed in to and concatenate with strings
- D. A class that handles the specific error that occurs when the format of an argument is invalid
- E. Method to add members at a specific position of a list
- F. A class that handles the specific error that occurs when you try to access an element of an array with an index that is outside its bounds
- G. An optional statement that is executed if no other case in a switch statement applies
- H. Method to determine if a certain value exists in an array
- I. `==`; to compare whether two variables are the same
- J. Property to find out the number of elements in a list
- K. Method that allows you to copy the contents of one array into another array, starting from the first element
- L. A class that handles general errors
- M. Method used to sort array
- N. Used to accept input from users; reads a line of characters
- O. To join two strings
- P. An operator used when we want to access a property or method of a class
- Q. A data type that stores a reference to the data
- R. Method to remove all items in a list
- S. Method to remove a member at a specific location
- T. A collection of data that are normally related to each other
- U. Method to compare if two strings are identical
- V. Data passed into a method
- W. Used to convert data from one data type to another
- X. Used to a 32-bit signed integer
- Y. A statement that evaluates to true or false
- Z. Represents a class's data
- AA. `\n`; Used to add a newline to text in code
- BB. Method used to extract a string from a longer string
- CC. Method to check if a list contains a certain member
- DD. Controls how the program proceeds when an error occurs
- EE. Used to specify the format of numeric data in placeholders
- FF. Useful to combine multiple condition statements

- GG. Class that represents the standard input, output, and error streams for console applications
- HH. A jump statement that instructs the compiler to exit the current block
- II. Method to remove members from a list
- JJ. `\t`; Used to add a tab to text in code
- KK. Method to add members to a list
- LL. Property of an array; tells the number of items the array has
- MM. `\`; Used to escape characters that otherwise have a different meaning
- NN. A statement that instructs the compiler to jump to another line in the program
- OO. Represent a class's behavior
- PP. A data type that stores its own data
- QQ. A jump statement that instructs the compiler to skip the rest of the loop thereafter
- RR. Method to display messages to users
- SS. Method to split a string into substrings based on an array of user-defined separators
- TT. A statement that determines whether or not other statements will be evaluated
- UU. Converts the value of the specified Decimal to the equivalent double-precision floating-point number