

Practical 1

Aim: Introduction to OS and shell.

1. Access the command Line
2. Manage files and directories from command line
3. Create, edit and and view text files

Commands for reference:

Directory: mkdir, rmdir, cd, pwd, ls, mv

Editor: vi, gedit

File Handling/Text: cp, mv, rm, sort, cat, file, less, more, cmp, diff, comm, head, tail, cut, grep, touch, tr, uniq

Self-Study:

User Access: login, logout, passwd, exit


Information: man, who, date, cal, tty, calendar, time, bc, who, whoami, which, hostname, history, wc, finger, uname

Help: man, help

Terminal: echo, clear

Exercise - 0

Enter these commands at the UNIX prompt, and try to interpret the output.

Que.	1. Passwd
Command	1.passwd
Output	

Que.	2. Date 3. Hostname 4. Arch 5. uname -a
Command	2. date

	3. hostname 4. arch 5. uname -a
Output	<pre>buntu@ubuntu:~\$ date Thu Jul 11 14:39:43 IST 2024 buntu@ubuntu:~\$ hostname buntu buntu@ubuntu:~\$ arch x86_64 buntu@ubuntu:~\$ uname -a Linux ubuntu 6.8.0-31-generic #31-Ubuntu SMP PREEMPT_DYNAMIC Sat Apr 20 00:40:06 UTC 2024 x86_64 x86_64 x86_64 GNU/Linux</pre>

Que.	6. whoami 7. who 8. id 9. echo \$SHELL 10. echo {con,pre} {sent,fer} {s,ed}
Command	6. whoami 7. who 8. id 9. echo \$SHELL 10. echo {con,pre} {sent,fer} {s,ed}
Output	<pre>ubuntu@ubuntu:~\$ whoami ubuntu ubuntu@ubuntu:~\$ who ubuntu seat0 2024-06-27 15:41 (login screen) ubuntu :0 2024-06-27 15:41 (:0) ubuntu@ubuntu:~\$ id uid=1000(ubuntu) gid=1000(ubuntu) groups=1000(ubuntu),4(adm),24(cdrom),27(sudo), 30(dip),46(plugdev),100(users),114(lpadmin),124(sambashare) ubuntu@ubuntu:~\$ echo \$SHELL /bin/bash ubuntu@ubuntu:~\$ echo {con,pre}{sent,fer}{s,ed} consents consented confers conferred presents presented prefers preferred</pre>

Que.	11. man ls 12. man who
Command	11. man ls 12. man who

Output

```
LS(1)                                User Commands                                LS(1)

NAME
    ls - list directory contents

SYNOPSIS
    ls [OPTION]... [FILE]...

DESCRIPTION
    List information about the FILES (the current directory by default).
    Sort entries alphabetically if none of -cftuvSUX nor --sort is specified.

    Mandatory arguments to long options are mandatory for short options too.

    -a, --all
        do not ignore entries starting with .

    -A, --almost-all
        do not list implied . and ..

    --author
Manual page ls(1) line 1 (press h for help or q to quit)
```

```
WHO(1)                                User Commands                                WHO(1)

NAME
    who - show who is logged on

SYNOPSIS
    who [OPTION]... [ FILE | ARG1 ARG2 ]

DESCRIPTION
    Print information about users who are currently logged in.

    -a, --all
        same as -b -d --login -p -r -t -T -u

    -b, --boot
        time of last system boot

    -d, --dead
        print dead processes

    -H, --heading
        print line of column headings
Manual page who(1) line 1 (press h for help or q to quit)
```

Que.	13. who can tell me why I got divorced 14. clear
Command	13. who can tell me why I got divorced 14. clear
Output	<pre>ubuntu@ubuntu:~\$ who can tell me why i got divorced who: extra operand 'me' Try 'who --help' for more information.</pre>

Que.	15. cal 2000
Command	15. sudo apt install ncal

	cal 2000
Output	<pre> ubuntu@ubuntu:~\$ cal 2000 2000 January February March Su Mo Tu We Th Fr Sa Su Mo Tu We Th Fr Sa Su Mo Tu We Th Fr Sa 1 1 2 3 4 5 1 2 3 4 2 3 4 5 6 7 8 6 7 8 9 10 11 12 5 6 7 8 9 10 11 9 10 11 12 13 14 15 13 14 15 16 17 18 19 12 13 14 15 16 17 18 16 17 18 19 20 21 22 20 21 22 23 24 25 26 19 20 21 22 23 24 25 23 24 25 26 27 28 29 27 28 29 26 27 28 29 30 31 30 31 April May June Su Mo Tu We Th Fr Sa Su Mo Tu We Th Fr Sa Su Mo Tu We Th Fr Sa 1 1 2 3 4 5 6 1 2 3 2 3 4 5 6 7 8 7 8 9 10 11 12 13 4 5 6 7 8 9 10 9 10 11 12 13 14 15 14 15 16 17 18 19 20 11 12 13 14 15 16 17 16 17 18 19 20 21 22 21 22 23 24 25 26 27 18 19 20 21 22 23 24 23 24 25 26 27 28 29 28 29 30 31 25 26 27 28 29 30 30 July August September Su Mo Tu We Th Fr Sa Su Mo Tu We Th Fr Sa Su Mo Tu We Th Fr Sa 1 1 2 3 4 5 1 2 2 3 4 5 6 7 8 6 7 8 9 10 11 12 3 4 5 6 7 8 9 9 10 11 12 13 14 15 13 14 15 16 17 18 19 10 11 12 13 14 15 16 16 17 18 19 20 21 22 20 21 22 23 24 25 26 17 18 19 20 21 22 23 23 24 25 26 27 28 29 27 28 29 30 31 24 25 26 27 28 29 30 30 31 October November December Su Mo Tu We Th Fr Sa Su Mo Tu We Th Fr Sa Su Mo Tu We Th Fr Sa 1 2 3 4 5 6 7 1 2 3 4 1 2 8 9 10 11 12 13 14 5 6 7 8 9 10 11 3 4 5 6 7 8 9 15 16 17 18 19 20 21 12 13 14 15 16 17 18 10 11 12 13 14 15 16 22 23 24 25 26 27 28 19 20 21 22 23 24 25 17 18 19 20 21 22 23 29 30 31 26 27 28 29 30 24 25 26 27 28 29 30 31 </pre>


Que.	16. cal 9 1752 17. bc -l 18. echo 5+4 bc -l
Command	16. cal 9 1752 17. bc -l 18. echo 5+4 bc -l
Output	<pre> ubuntu@ubuntu:~\$ cal 9 1752 September 1752 Su Mo Tu We Th Fr Sa 1 2 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 ubuntu@ubuntu:~\$ bc -l bc 1.07.1 Copyright 1991-1994, 1997, 1998, 2000, 2004, 2006, 2008, 2012-2017 Free Software Foundation, Inc. This is free software with ABSOLUTELY NO WARRANTY. For details type `warranty'. ubuntu@ubuntu:~\$ echo 5+4 bc -l 9 </pre>

Que.	19. yes please 20. time sleep 5
Command	19. yes please 20. time sleep 5
Output	<pre> please please please please please please please please pleas^C ubuntu@ubuntu:~\$ time sleep 5 real 0m6.649s user 0m0.008s sys 0m0.008s </pre>

Que.	21. history
Command	21. history
Output	<pre> ubuntu@ubuntu:~\$ history 1 date 2 cd 3 date 4 passwd 5 date 6 hostname 7 arch 8 uname -a 9 whoami 10 who 11 id 12 echo \$SHELL 13 echo {con,pre}{sent,fer}{s,ed} 14 man ls 15 man who 16 who can tell me why i got divorced 17 cal 2000 18 cal 2024 19 cal 9 1752 20 bc -l 21 bc -l 22 echo 5+4 bc -l 23 yes please </pre>

Exercise-1

Try the following command sequence.

Que.	1. Display username of current user. 2. Display current working directory. 3. Make a sub directory named CE in a directory named CSPIT. 4. Create an empty file “ce1.txt” from command prompt.
Command	1. whoami 2. pwd 3. mkdir -p CSPIT/CE 4. touch CSPIT/CE/ce1.txt
Output	 <pre>ubuntu@ubuntu:~\$ whoami ubuntu ubuntu@ubuntu:~\$ pwd /home/ubuntu ubuntu@ubuntu:~\$ mkdir -p CSPIT/CE ubuntu@ubuntu:~\$ touch CSPIT/CE/ce1.txt ubuntu@ubuntu:~\$</pre>

Que.	5. Add the content from command prompt in “ce1.txt”. 6. Display the content of “ce1.txt” file. 7. Change working directory to CE. 8. Make 5 empty files named file1.txt to file5.txt in same directory. 9. List all the files in the directory CE. 10. Add the Name, ID no, and address with pin code to “file1.txt”. 11. Copy contents of file1.txt to file2.txt. 12. Rename file3.txt to “f3.txt”. 13. Display the number of lines, number of words, number of characters of “file1.txt”.
Command	5. echo -e “Probin” 6. cat file1.txt 7. cd CSPIT/CE 8. touch file{1..5}.txt 9. ls 10. echo -e “Name: Probin \nID: 22DCE006\nAddress: Changa”>file1.txt 11. cp file1.txt file2.txt

	12. mv file3.txt f3.txt 13. wc file1.txt
Output	<pre> ubuntu@ubuntu:~\$ cd CSPIT/CE ubuntu@ubuntu:~/CSPIT/CE\$ touch file{1..5}.txt ubuntu@ubuntu:~/CSPIT/CE\$ ls ce1.txt file1.txt file2.txt file3.txt file4.txt file5.txt ubuntu@ubuntu:~/CSPIT/CE\$ echo -e"Name:Probin\nID:22DCE006\nAddress:Changa">file1.txt ubuntu@ubuntu:~/CSPIT/CE\$ cp file1.txt file2.txt ubuntu@ubuntu:~/CSPIT/CE\$ mv file3.txt f3.txt ubuntu@ubuntu:~/CSPIT/CE\$ wc file1.txt 1 1 43 file1.txt </pre>

Que.	14. Compare the files “file1.txt” to “file2.txt” 15. Update the content of “file2.txt”. Add your skill to existing file. 16. Compare the files “file1.txt” to “file2.txt” 17. Report what is common in the above given files.
Command	14. diff file1.txt file2.txt 15. echo “Skills : JAVA” >> file2.txt 16. diff file1.txt file2.txt 17. comm -12 <(sort file1.txt) <(sort file2.txt)
Output	<pre> ubuntu@ubuntu:~/CSPIT/CE\$ diff file1.txt file2.txt ubuntu@ubuntu:~/CSPIT/CE\$ echo "Skills:JAVA">>file2.txt ubuntu@ubuntu:~/CSPIT/CE\$ diff file1.txt file2.txt 1a2 > Skills:JAVA ubuntu@ubuntu:~/CSPIT/CE\$ comm -12<(sort file1.txt)<(sort file2.txt) comm: syntax error near unexpected token `newline' comm: syntax error ubuntu@ubuntu:~/CSPIT/CE\$ comm -12<(sort file1.txt)<(sort file2.txt) comm: invalid option -- '/' Try 'comm --help' for more information. ubuntu@ubuntu:~/CSPIT/CE\$ comm -12<(sort file1.txt)<(sort file2.txt) comm: invalid option -- '/' Try 'comm --help' for more information. ubuntu@ubuntu:~/CSPIT/CE\$ comm -12<(sort file1.txt) <(sort file2.txt) comm: invalid option -- '/' Try 'comm --help' for more information. ubuntu@ubuntu:~/CSPIT/CE\$ comm -12 <(sort file1.txt) <(sort file2.txt) -eName:Probin\nID:22DCE006\nAddress:Changa ubuntu@ubuntu:~/CSPIT/CE\$ </pre>

Que.	18. Add the content in “file4.txt” as given: India United States of America
-------------	---

	United Kingdom Australia
Command	18. cat > file4.txt India United States of America United Kingdom Australia
Output	<pre>ubuntu@ubuntu:~/CSPIT/CE\$ echo -e "India\nUnited States of America\nUnited Kingdom\nAustralia">file4.txt ubuntu@ubuntu:~/CSPIT/CE\$ cat CSPIT/CE/file4.txt cat: CSPIT/CE/file4.txt: No such file or directory ubuntu@ubuntu:~/CSPIT/CE\$ cat file4.txt India United States of America United Kingdom Australia ubuntu@ubuntu:~/CSPIT/CE\$</pre>

Que.	19. Add the content in “file5.txt” as given: India Canada United Kingdom Australia Germany 20. Find the difference between “file4.txt” and “file5.txt”. How to make these files identical?
Command	19. cat > file5.txt India Canada United Kingdom Australia Germany 20. diff file4.txt file5.txt

Output

```
ubuntu@ubuntu:~/CSPIT/CE$ echo -e"India
> Canada
> United Kingdom
> Australia
> Germany">file5.txt
ubuntu@ubuntu:~/CSPIT/CE$ cat file5.txt
-eIndia
Canada
United Kingdom
Germany
ubuntu@ubuntu:~/CSPIT/CE$ diff file4.txt file5.txt
1,2c1,2
< India
< United States of America
---
> -eIndia
> Canada
4a5
> Germany
ubuntu@ubuntu:~/CSPIT/CE$
```

Que.

21. Create “file6.txt” by adding ten name of students.
22. Create “file7.txt” by adding ten name of students.(few names should be common to “file6.txt”)

Command

21. echo -e “david raj prem josh raju shyam juhi hetvi aayush john
”>file6.txt
cat file6.txt
22.echo -e “raj prem josh raju shyam ranjesh ranjan diya deepika
”>file7.txt
cat file7.txt

Output	<pre> > Germany ubuntu@ubuntu:~/CSPIT/CE\$ echo -e"david raj prem josh raju shyam juhi hetv ohn">file6.txt ubuntu@ubuntu:~/CSPIT/CE\$ cat file6.txt Terminal raj prem josh raju shyam juhi hetvi aayush john ubuntu@ubuntu:~/CSPIT/CE\$ echo -e"david raj prem josh raju shyam juhi kara alu">file6.txt ubuntu@ubuntu:~/CSPIT/CE\$ cat file6.txt -edavid raj prem josh raju shyam juhi karan nityam lalu ubuntu@ubuntu:~/CSPIT/CE\$ cat file6.txt -edavid raj prem josh raju shyam juhi rohan ram shyam ubuntu@ubuntu:~/CSPIT/CE\$ echo -e"david raj prem josh raju shyam rajesh ra deepkia">file7.txt ubuntu@ubuntu:~/CSPIT/CE\$ cat file7.txt -edavid raj prem josh raju shyam rajesh ranjan diya deepkia ubuntu@ubuntu:~/CSPIT/CE\$ </pre>
---------------	---

Que.	<p>23. Sort the content of “file6.txt” and “file7.txt”</p> <p>24. Find the common and unique content in “file6.txt” and “file7.txt”</p> <p>25. Merge the content of above two files in “file8.txt”</p> <p>26. Remove the duplicate names from “file8.txt”</p>
Command	<p>23. sort file6.txt -o file6.txt sort file7.txt -o file7.txt</p> <p>24. comm -12 file6.txt file7.txt comm -23 file6.txt file7.txt comm -13 file6.txt file7.txt</p> <p>25. cat file6.txt file7.txt > file8.txt</p> <p>26. sort -u file8.txt -o file8.txt cat file8.txt</p>
Output	<pre> ubuntu@ubuntu:~/CSPIT/CE\$ ubuntu@ubuntu:~/CSPIT/CE\$ sort file6.txt -o file6.txt ubuntu@ubuntu:~/CSPIT/CE\$ sort file7.txt -o file7.txt ubuntu@ubuntu:~/CSPIT/CE\$ comm -12 file6.txt file7.txt ubuntu@ubuntu:~/CSPIT/CE\$ comm -23 file6.txt file7.txt -edavid raj prem josh raju shyam juhi rohan ram shyam ubuntu@ubuntu:~/CSPIT/CE\$ comm -13 file6.txt file7.txt -edavid raj prem josh raju shyam rajesh ranjan diya deepkia ubuntu@ubuntu:~/CSPIT/CE\$ cat file6.txt file7.txt>file8.txt ubuntu@ubuntu:~/CSPIT/CE\$ sort -u file8.txt -o file8.txt ubuntu@ubuntu:~/CSPIT/CE\$ cat file8.txt -edavid raj prem josh raju shyam juhi rohan ram shyam -edavid raj prem josh raju shyam rajesh ranjan diya deepkia </pre>

Que.	<p>27. Translate the content of “file1.txt”:</p> <p>a. Lower case to upper case</p>
-------------	---

	b. Remove digits from file
Command	27. a. tr '[:lower:]' '[:upper:]' < file1.txt > file1_no_digits.txt b. tr -d '[:digit:]' < file1.txt > file1_no_digits.txt cat file1_no_digits.txt
Output	<pre>ubuntu@ubuntu:~/CSPIT/CE\$ ubuntu@ubuntu:~/CSPIT/CE\$ tr '[:lower:]' '[:upper:]' <file1.txt>file1_no_digits.txt ubuntu@ubuntu:~/CSPIT/CE\$ cat file1.txt -eName:Probin\nID:22DCE006\nAddress:Changa ubuntu@ubuntu:~/CSPIT/CE\$ tr -d '[:digit:]' <file1.txt>file1_no_digits.txt ubuntu@ubuntu:~/CSPIT/CE\$ cat file1_no_digits.txt -eName:Probin\nID:DCE\nAddress:Changa ubuntu@ubuntu:~/CSPIT/CE\$</pre>

Que.	28. Apply head and tail command to see the content of “file8.txt” with different arguments.
Command	28. head -n 5 file8.txt tail -n 5 file8.txt
Output	<pre>ubuntu@ubuntu:~/CSPIT/CE\$ head -n 5 file8.txt -edavid raj prem josh raju ubuntu@ubuntu:~/CSPIT/CE\$ tail -n 5 file8.txt shyam rajesh ranjan diya deepkia ubuntu@ubuntu:~/CSPIT/CE\$</pre>

Que.	29. Differentiate between less and more command and check why less is faster than more command. 30. Create a file “file9.txt” having content: Linux is great os. Linux is open source. Linux is free os. You can learn operating system with linux. Unix or linux which one you choose. liNux is easy to learn. Linux is a multiuser os. Learn linux. Linux is a powerful. 31. Find the lines which contains “linux”.
Command	29. less file8.txt more file8.txt 30. cat > file9.txt Linux is great os. Linux is open source. Linux is free os.

	<p>You can learn operating system with linux.</p> <p>Unix or linux which one you choose.</p> <p>liNux is easy to learn. Linux is a multiuser os. Learn linux. Linux is a powerful.</p> <p>31. grep -i 'linux' file9.txt</p>
Output	<pre> ubuntu@ubuntu:~/CSPIT/CE\$ cat file9.txt Linux is great os.Linux is open source. Linux is free os. You can learn operating system with linux. Unix or linux which one you choose. liNux is easy to learn.Linux is multiuser os.Learn linux.Linux is a ubuntu@ubuntu:~/CSPIT/CE\$ grep -i "linux" file9.txt Linux is great os.Linux is open source. Linux is free os. You can learn operating system with linux. Unix or linux which one you choose. liNux is easy to learn.Linux is multiuser os.Learn linux.Linux is a ubuntu@ubuntu:~/CSPIT/CE\$ </pre>

Que.	<p>32. Count the number of lines that matches the “linux”</p> <p>33. Show the line number of file with the line matched</p> <p>34. Find the lines which start with “linux”</p> <p>38. Check the file type of lab manual and other files created.</p> <p>39. Apply history command and redirect your output to “ID No_date.txt”</p>
Command	<p>32. grep -i 'linux' file9.txt wc -l</p> <p>33. grep -in 'linux' file9.txt</p> <p>34. grep -i '^linux' file9.txt</p> <p>38. file file9.txt</p> <p>File view</p> <p>39. history > 22DCE006_\$(date +%Y%m%d).txt</p>
Output	<pre> ubuntu@ubuntu:~/CSPIT/CE\$ grep -i "linux" file9.txt wc -l 4 ubuntu@ubuntu:~/CSPIT/CE\$ grep -in "linux" file9.txt 1:Linux is great os. Linux is open source. Linux is free os. 2:You can learn operating system with linux. 3:Unix or Linux which you choose. 4:liNux is easy to learn. Linux is a multiuser os. Learn linux. Linux is a powerful. ubuntu@ubuntu:~/CSPIT/CE\$ grep -i "^linux" file9.txt Linux is great os. Linux is open source. Linux is free os. liNux is easy to learn. Linux is a multiuser os. Learn linux. Linux is a powerful. </pre>

Que.	<p>35. Find the lines which ends with “os”.</p> <p>36. Display the file name that contains “linux”.</p>
Command	<p>35. grep -i 'os\$' file9.txt</p> <p>36. grep -il 'linux' file9.txt</p>

Output	<pre> ubuntu@ubuntu:~/CSPIT/CE\$ ubuntu@ubuntu:~/CSPIT/CE\$ grep -i "os\$" file9.txt ubuntu@ubuntu:~/CSPIT/CE\$ grep -il "linux" file9.txt file9.txt ubuntu@ubuntu:~/CSPIT/CE\$ </pre>
---------------	--

Que.	37. Download lab manual from department course website.
Command	37. wget <URL>
Output	<pre> ubuntu@ubuntu:~\$ wget https://drive.google.com/file/d/14ru3X0tNv_dhyWQjeB5061p02wFESKP6/view --2024-07-11 09:23:58-- https://drive.google.com/file/d/14ru3X0tNv_dhyWQjeB5061p02wFESKP6/view Resolving drive.google.com (drive.google.com)... 142.250.183.78, 2404:6800:4009:814::200e Connecting to drive.google.com (drive.google.com) 142.250.183.78 :443... connect ed. HTTP request sent, awaiting response... 200 OK Length: unspecified [text/html] Saving to: 'view' view [<=>] 90.59K 315KB/s in 0.3s 2024-07-11 09:24:00 (315 KB/s) - 'view' saved [92764] </pre>

Exercise - 1.1 (Advanced)

Try the following command sequence.

Que.	<ol style="list-style-type: none">1. Change back into your home directory.2. Make subdirectories called work and play3. Delete the subdirectory called work.4. Copy the file /etc/passwd into your home directory.5. Move it into the subdirectory play6. What is the difference between listing the contents of directory play with <code>ls -l</code> and <code>ls -L</code>?7. Create a file called hello.txt that contains the words "hello world". Can you use <code>"cp "</code> using "terminal" as the source file to achieve the same effect?
Command	<ol style="list-style-type: none">1. <code>cd ~</code>2. <code>mkdir work play</code>3. <code>rmdir work</code>4. <code>cp /etc/passwd ~</code>5. <code>mv ~/passwd ~/play/</code>6. <code>ls -l</code> (Lists files with detailed information including permissions, number of links, owner, group, size, and timestamp.) <code>Ls -L</code> {follows symbolic links (shows the file or directory the link points to)}7. <code>cat > hello.txt</code> Hello world or <code>echo "hello world" cp /dev/stdin hello.txt</code>

Output

```
ubuntu@ubuntu:~/CSPIT/CE$ cd ~
ubuntu@ubuntu:~$ mkdir work play
ubuntu@ubuntu:~$ rmdir work
ubuntu@ubuntu:~$ cp /etc/passwd ~
ubuntu@ubuntu:~$ mv ~/passwd ~/play/
ubuntu@ubuntu:~$ ls -l
total 0
drwxrwxr-x 3 ubuntu ubuntu 60 Jul 7 04:16 CSPIT
drwxr-xr-x 2 ubuntu ubuntu 60 Jul 7 03:39 Desktop
drwxr-xr-x 2 ubuntu ubuntu 40 Jul 7 03:40 Documents
drwxr-xr-x 2 ubuntu ubuntu 40 Jul 7 03:40 Downloads
drwxr-xr-x 2 ubuntu ubuntu 40 Jul 7 03:40 Music
drwxr-xr-x 2 ubuntu ubuntu 40 Jul 7 03:40 Pictures
drwxr-xr-x 2 ubuntu ubuntu 40 Jul 7 03:40 Public
drwxr-xr-x 2 ubuntu ubuntu 40 Jul 7 03:40 Templates
drwxr-xr-x 2 ubuntu ubuntu 40 Jul 7 03:40 Videos
drwxrwxr-x 2 ubuntu ubuntu 60 Jul 7 10:37 play
drwx----- 6 ubuntu ubuntu 120 Jul 7 06:09 snap
ubuntu@ubuntu:~$ ls -L
CSPIT  Documents  Music      Public     Videos  snap
Desktop Downloads  Pictures   Templates  play
ubuntu@ubuntu:~$ cat > hello.txt
hello world
```

Que.

8. Copy hello.txt to terminal. What happens?
9. Imagine you were working on a system and someone accidentally deleted the ls command (/bin/ls). How could you get a list of the files in the current directory? Try it. (Do not delete ls command, copy it to some other location from bin)
10. How would you create and then delete a file called "\$SHELL"? Try it.
11. How would you create and then delete a file that begins with the symbol #? Try it
12. How would you create and then delete a file that begins with the symbol -? Try it.

Command

8. cp hello.txt terminal (As terminal named file is not present, therefore file with name 'terminal' gets created and content of file hello.txt copied to it.)
9. echo *
10. touch '\$SHELL'
rm '\$SHELL'
11. touch '#new_file'
rm '#new_file'
12. touch - '-file'
rm - '-file'

Output

```
ubuntu@ubuntu:~$ cp hello.txt terminal
ubuntu@ubuntu:~$ echo *
CSPIT Desktop Documents Downloads Music Pictures Public Templates Videos hello.txt p
lay snap terminal
ubuntu@ubuntu:~$ touch '$SHELL'
ubuntu@ubuntu:~$ rm '$SHELL'
ubuntu@ubuntu:~$ touch '#new_file'
ubuntu@ubuntu:~$ rm '#new_file'
ubuntu@ubuntu:~$ touch -- '-file'
ubuntu@ubuntu:~$ rm -- '-file'
```