

3-8 附：配置 Keepalived - 备

配置 Keepalived - 备

1. 通过命令 vim keepalived.conf 打开配置文件

```
global_defs {
    router_id keep_172
}

vrrp_instance VI_1 {
    # 备用机设置为BACKUP
    state BACKUP
    interface ens33
    virtual_router_id 51
    # 权重低于MASTER
    priority 80
    advert_int 2
    authentication {
        auth_type PASS
        auth_pass 1111
    }
    virtual_ipaddress {
        # 注意：主备两台的vip都是一样的，绑定到同一个vip
        192.168.1.161
    }
}
```

2. 启动 Keepalived

```
# 启动keepalived
systemctl start keepalived
# 停止keepalived
systemctl stop keepalived
# 重启keepalived
systemctl restart keepalived
```

3. 查看进程

```
ps -ef|grep keepalived
```

```
[root@nginx sbin]# ps -ef|grep keepalived
root      20175      1    0 17:33 ?          00:00:00 ./keepalived
root      20176    20175    0 17:33 ?          00:00:00 ./keepalived
root      20196    7817    0 17:34 pts/0    00:00:00 grep --color=auto keepa
```

检测到您还没有关注慕课网服务号，无法接收课程更新通知。请扫描二维码即可绑定



下一节

3-8 附：配置 Keepalived - 备

播放下一节

重新观看