

Week3_Part2

September 13, 2019

1 GWU STAT 4197/6197

1.0.1 Week 3 SAS Code Examples (Part 2): Transforming Data

- Creating New Variable by Using
 - Assignment Statements
 - SELECT/WHEN/OTHERWISE Statements
 - IFC/IFN/WHICHC/WHICHN Functions
 - Case Expression in PROC SQL
 - SUM and RETAIN Statements

1.0.2 Creating a New Variable by Recoding Distinct Values

```
In [4]: data work.demographics;
        set sashelp.demographics;
        length region_name$ 22.;
        if region = 'AFR' then region_name = 'Africa';
        else if region = 'AMR' then region_name = 'Americas';
        else if region = 'EUR' then region_name = 'Europe';
        else if region = 'EMR' then region_name = 'Eastern Mediterranean';
        else if region = 'SEAR' then region_name = 'South-East Asia';
        else if region = 'WPR' then region_name = 'Western Pacific';
        run;

        proc freq data=work.demographics;
            tables region_name;
        run;
```

Out[4]: <IPython.core.display.HTML object>

```
In [ ]: ### Creating
```

```
In [20]: options nocenter nodate nonumber;
         data Heart;
         length AgeAtDeath_group $25;
         set sashelp.heart;

         /*Character-type categorical variables using an assignment statement;
```

IF-THEN/Else Statements are used to conditionally assign values to variables./*

```
if 36<=AgeAtDeath<=49 then AgeAtDeath_group='36-49 Years';
else if 50<=AgeAtDeath<=64 then AgeAtDeath_group= '50-64 Years';
else if 65<=AgeAtDeath<=79 then AgeAtDeath_group= '65-79 Years';
else if 80<=AgeAtDeath<=94 then AgeAtDeath_group= '80-94 Years';
else AgeAtDeath_group= ' ';

title "Age at Death Grouping Created with an Assignment Statement";
title2 '(IF-THEN/ELSE-IF-THEN in DATA Step)';

proc freq data=Heart;
  table AgeAtDeath_group;
run;
```

Out[20]: <IPython.core.display.HTML object>

1.0.3 Creating Character-Type Categorical Variables by Using a PUT Function in the Assignment Statement

```
In [23]: proc format ;
         value agefmt low-49 = '36-49 Years'
              50-64 = '50-64 Years'
              65-79 = '65-79 Years'
              80-94 = '80-94 Years' ;

         data Heart;
         length AgeAtDeath_group $25;
         set sashelp.heart;
         *Character-type categorical variables using a PUT function;
         if ageatdeath ne . then ageatdeath_group=put(ageatdeath, agefmt.);

         title 'Age at Death Grouping Created with an Assignment Statement';
         title2 'and the PUT Function in DATA Step';
         proc freq data=Heart;
         table ageatdeath_group ;
run;
title;
```

Out[23]: <IPython.core.display.HTML object>

```
In [26]: data Heart;
         length AgeAtDeath_group AgeAtDeath_group_x $25;
         set sashelp.heart;
         if 36<=ageatdeath <=49 then
             DO;
                 AgeAtDeath_group = '36-49 Years';
                 AgeAtDeath_group_x= 'Adults';
             END;
         else if 50<=ageatdeath<=64 then
```

```

DO;
  AgeAtDeath_group = '50-64 Years';
  AgeAtDeath_group_x = 'Middle-Aged Adults';
END;

else if ageatdeath>=65 then
DO;
  AgeAtDeath_group = '65+ Years';
  AgeAtDeath_group_x = 'Older Adults';
END;

title 'Listing of Multiple Variables Created with DO Group';
title;
proc freq data=Heart;
  tables AgeAtDeath_group AgeAtDeath_group_x;
run;

```

Out[26]: <IPython.core.display.HTML object>

1.0.4 The IFC Function

- uses the IF-THEN/ELSE logic
- can be used to create a new Variable with this function that normally uses three arguments
 - 1st argument - a logical expression () – a condition (true/false) to be evaluated
 - 2nd argument - character value returned when true
 - 3rd argument – character value to returned when false ##### The IFN Function

It is the same as the IFC function except that the IFN function returns the numeric value. For a logical expression with a missing value as in the following example, you can have a 4th argument for SAS to return the value in the 4th argument.

```

In [1]: proc format;
  value agefmt
    . = 'Unknown'
    1 = '36-64 Years'
    0 = '65+ Years';
data IFC1_IFN1;
  length agedth_group_IFC1 $10;
  set sashelp.heart;
  agedth_group_IFC1 = IFC(36<=ageatdeath<=64, '36-64 Years', '65+ Years');
  agedth_LE64_IFN1 = IFN(36<=ageatdeath<=64, 1, 0);
  agedth_LE64_IFN1_formatted = put(agedth_LE64_IFN1, agefmt.);
  title1 'Ex12_IFC_IFN_Function.sas';
proc freq;
  tables agedth_group_IFC1 agedth_LE64_IFN1 agedth_LE64_IFN1_formatted;
run;
title;

```

SAS Connection established. Subprocess id is 740

Out[1]: <IPython.core.display.HTML object>

```
In [29]: *Ex13_IFN_Fourth_Argument.sas;
DATA Work.Ifnc_Func;
INPUT property_value;
property_tax = ifn(property_value GE 150000,
                  property_value*.02,
                  property_value*.015, .);
format property_value property_tax dollar8.;
datalines;
150000
.
250000
100000
;
title1 'Ex13_IFN_Fourth_Argument.sas';
proc print data=Work.Ifnc_Func;
run;
title1;
```

Out[29]: <IPython.core.display.HTML object>

1.0.5 WHICHC/WHICHN Functions

These two functions are used to search through a list of arguments and return the index of the first one that matches a given reference value.

```
In [11]: options nonotes nocenter nodate nonumber nosource;
ods html close;
DATA _NULL_;
x = whichc("ECON", "STAT", "MATH", "ECON");
y = whichn(8,7, 8,9);
put x= y=;
run;
```

Out[11]: <IPython.core.display.HTML object>

```
In [30]: *Ex14_in_whichn_whichc.sas;
* Adapted from Joe Matise's code (SAS-L) - 5/16/2016;
data have1;
set sashelp.class (obs=3);
Age_13_dummy = whichn(13,age);
Gender_male_dummy= whichc('M',sex);
run;
title1 'Ex14_in_whichn_whichc.sas';
proc print data=have1 noobs; run;
title1;
```

Out[30]: <IPython.core.display.HTML object>

Ex20_SELECT_WHEN.sas

[See example code on SELECT WHEN here](#)

1.0.6 Using WHEN Statements in a SELECT Group

- Evaluating the when-expression When a select-expression Is Included
- Evaluating the when-expression When a select-expression Is Not Included
- Evaluating the when-expression When a statement-list Is Not Included Comparisons

1.0.7 Examples

- Example 1: SELECT with a select-expression
- Example 2: SELECT without a select-expression
- Example 3: SELECT without an IF Expression

```
In [40]: *Ex21_create_variable_in_SQL.sas (Part 1);
options nocenter nodate nonumber;
title1 'Ex21_create_variable_in_SQL.sas (Part 1)';
PROC SQL;
SELECT
  CASE
    WHEN weight <100 THEN '<100 lbs'
    WHEN weight GE 100 AND weight LT 120 THEN '100-<120 lbs'
    WHEN weight GE 120 AND weight LE 150 THEN '120-150 lbs'
    ELSE '120-150 lbs'
  END AS Weight_Cat label= 'Weight Category',
  count(*) as freq_count
FROM sashelp.class
group by Weight_Cat
order by freq_count desc;
quit;
```

Out[40]: <IPython.core.display.HTML object>

1.0.8 The SUM Statement:

- (by default), creates the sum or accumulator variable that is automatically set to 0 before the first observation is read. The variable's value is retained from one iteration to the next, as if it had appeared in a RETAIN statement. The sum statement is equivalent to using the SUM function and the RETAIN statement.
- has an expression that is evaluated and the results are added to the accumulator variable.
- automatically retains the variable across iterations of the DATA step
- ignores the missing values

```
In [41]: *Ex22_Retain_Sum_Statement.sas (Part 1);
DATA temp ;
  INPUT month sales @@;
```

```

        Total_sales+sales;
FORMAT Sales Total_sales dollar8.;
DATALINES;
    1 4000 2 5000 3 . 4 5500 5 5000
;
title1 'Ex22_Retain_Sum_Statement.sas (Part 1)';
title2 'SUM Statement';
PROC PRINT noobs; run;

```

Out[41]: <IPython.core.display.HTML object>

1.0.9 The SUM Statement Coupled with the RETAIN Statement

- To reset the sum variable to a value other than zero, you need to include the accumulator variable in a RETAIN statement with an initial value.

```

In [2]: *Ex22_Retain_Sum_Statement.sas (Part 3);
options nocenter nodate nonumber;
DATA temp;
    RETAIN Total_sales 1000;
    INPUT month sales @@;
    Total_sales+sales;
    FORMAT Sales Total_sales dollar8.;
    DATALINES;
    1 4000 2 5000 3 . 4 5500 5 5000
;
title 'Ex22_Retain_Sum_Statement.sas (Part 3)';
title2 'RETAIN and SUM Statements';
PROC PRINT noobs;
    var month sales Total_sales;
RUN;
title;

```

Out[2]: <IPython.core.display.HTML object>

1.0.10 The RETAIN Statement (as an Alternative to the SUM Statement)

- returns the value of the variable in the PDV across iterations of the DATA step
- initializes the retained variable to missing or a specified value before the first iteration of the DATA step
- is a compile-time statement

The RETAIN statement has no effect on variables that are read with SET, MERGE, or UPDATE statements. Variables read from SAS data sets are retained automatically.

```

In [42]: *Ex22_Retain_Sum_Statement.sas (Part 2);
DATA temp1 ;
    RETAIN Total_sales 0;
    FORMAT Sales Total_sales dollar8.;

```

```

INPUT month sales @@;
Total_sales= sum(Total_sales, sales);
DATALINES;
1 4000 2 5000 3 . 4 5500 5 5000
;
title1 'Ex22_Retain_Sum_Statement.sas (Part 2)';
title2 'RETAIN Statement';
PROC PRINT data=temp1;
VAR month sales Total_sales;
run;

```

Out[42]: <IPython.core.display.HTML object>

1.0.11 The SUM Statement in DATA Step with BY-Group Processing

The SASHELP.CARS has 428 rows categorized into 38 makes. How to count the number of cars for each of these 38 makes?

Code Explanation (Programming for SAS Viya)

- The PROC SORT step and the DATA step with BY-Group Processing calculates the number of cars by MAKE.
- The data set must first be sorted to take advantage of the DATA step with By-Group processing.
- The program uses FIRST. processing to set the first observation of COUNT to 0 at the beginning of the each MAKE.
- The program uses LAST. processing to write the last observation of the MAKE that contains the final accumulated COUNT for each MAKE.

```

In [1]: *Ex22_Retain_Sum_Statement.sas (Part 4);
proc sort data = sashelp.cars out=cars; by make; run;
data cars_x;
set cars;
count + 1;
by make;
if first.make then count = 1;
if last.make;
run;
title 'Ex22_Retain_Sum_Statement.sas (Part 4)';
title2 'SUM Statement';
proc print data=cars_x;
var make count;
sum count;
run;
title;

```

SAS Connection established. Subprocess id is 5100