AI-Driven Time-Series Lifestyle Prediction and Recommendation System Using LSTM

Abstract

The proliferation of wearable devices and mobile health applications has enabled continuous collection of lifestyle data such as physical activity, calorie expenditure, and sedentary behavior. However, most existing systems provide static insights without leveraging temporal dependencies. This paper proposes an end-to-end artificial intelligence system using Long Short-Term Memory (LSTM) networks to predict future lifestyle behavior from historical time-series data. The proposed model forecasts next-day activity levels and generates personalized recommendations. The system is deployed using a cloud-based architecture integrated with a mobile application. Experimental results demonstrate that the LSTM model effectively captures temporal patterns and outperforms traditional approaches in time-series prediction tasks.

Keywords

LSTM, Time-Series Prediction, Lifestyle Analytics, Deep Learning, Recommendation Systems, Wearable Data

1. Introduction

The rapid adoption of wearable sensors and smartphones has led to the generation of large-scale lifestyle data. These data streams include daily steps, calories burned, and activity intensity levels. Despite this, most current systems rely on descriptive analytics rather than predictive intelligence.

Time-series modeling using deep learning, particularly Long Short-Term Memory (LSTM), has shown strong performance in capturing temporal dependencies in sequential data . This research aims to develop an intelligent system capable of predicting future lifestyle behavior and providing proactive recommendations.

2. Related Work

Recent studies have demonstrated the effectiveness of deep learning in time-series human activity prediction:

- Mekruksavanich et al. (2021) proposed an LSTM-based framework for human activity recognition using smartphone sensor data, showing improved performance over traditional models .

- Hidayat et al. (2023) used LSTM models to analyze wearable time-series data for sleep quality prediction, highlighting the importance of temporal modeling .
- Alshammari et al. (2024) introduced a CNN-LSTM hybrid model for activity recognition, improving accuracy through spatial-temporal feature extraction .
- Refat et al. (2025) proposed a hybrid LSTM-CNN architecture with attention mechanisms, demonstrating superior performance in wearable sensor-based activity recognition .

Research Gap:
Most existing works focus either on **activity recognition** or **prediction**, while this work integrates:

- Time-series prediction
- Recommendation system
- Cloud + mobile deployment

3. Methodology

3.1 Data Acquisition

The dataset is obtained from Fitbit wearable devices, containing:

- Daily steps
- Calories
- Activity minutes

3.2 Data Preprocessing

- Missing value handling
- Duplicate removal
- Time sorting per user

3.3 Sequence Generation

Given time-series data:

$$X=\{x1,x2,...,xt\}$$

We construct sequences:

$$Xi=\{xi,xi+1,...,xi+6\}$$

Target:

$$yi=xi+7$$

3.4 LSTM Model Formulation

The LSTM unit is defined by:

Forget Gate:

$$f_t=\sigma(W_f[h_{t-1},x_t]+b_f)$$

Input Gate:

$$i_t=\sigma(W_i[h_{t-1},x_t]+b_i)$$

Candidate Memory:

$$\tilde{C}_t=\tanh(W_c[h_{t-1},x_t]+b_c)$$

Cell State Update:

$$C_t=f_t\cdot C_{t-1}+i_t\cdot \tilde{C}_t$$

Output Gate:

$$o_t=\sigma(W_o[h_{t-1},x_t]+b_o)$$

Hidden State:

$$h_t=o_t\cdot\tanh(C_t)$$

LSTM effectively captures **long-term dependencies in time-series data**

3.5 Model Architecture

- LSTM (64 units)
- Dropout (0.2)
- LSTM (32 units)
- Dense Layer

3.6 Recommendation Engine

Rule-based mapping:

$$R=f(\hat{y})$$

Where:

- y^\hat{y}y^: predicted steps
- RRR: recommendation

4. System Architecture

```
┌──────────────────────────────┐
│ Data Source │
│ (Kaggle Fitbit Dataset) │
└──────────────┬───────────────┘
               │
               ▼
┌──────────────────────────────┐
│ Data Preprocessing │
│ Cleaning + Sorting │
└──────────────┬───────────────┘
               │
               ▼
┌──────────────────────────────┐
│ Feature Engineering │
│ Steps, Calories, etc. │
└──────────────┬───────────────┘
               │
               ▼
┌──────────────────────────────┐
│ Sequence Generator │
│ (7 Days → Next Day) │
└──────────────┬───────────────┘
               │
               ▼
┌──────────────────────────────┐
│ Data Normalization │
│ MinMaxScaler │
└──────────────┬───────────────┘
               │
               ▼
┌──────────────────────────────┐
│ LSTM Model │
│ Time-Series Prediction │
└──────────────┬───────────────┘
               │
```

```
        ▼
┌──────────────────────────┐
│ Prediction Output │
│ Next-Day Steps │
└──────────┬───────────────┘
           │
           ▼
┌──────────────────────────┐
│ Recommendation Engine │
│ Rule-Based Logic │
└──────────┬───────────────┘
           │
           ▼
┌──────────────────────────┐
│ Flask API (Backend) │
│ REST Endpoint │
└──────────┬───────────────┘
           │
           ▼
┌──────────────────────────┐
│ AWS Deployment (EC2) │
│ Hosting + Scaling │
└──────────┬───────────────┘
           │
           ▼
┌──────────────────────────┐
│ Flutter Mobile App │
│ UI + Visualization │
└──────────────────────────┘
```

5. Experimental Results

5.1 Experimental Setup

- Dataset: Fitbit activity dataset
- Model: LSTM
- Epochs: 50
- Loss: Mean Squared Error (MSE)

5.2 Evaluation Metrics

$$MSE = \frac{1}{n}\sum(y_i - \hat{y}_i)^2$$

$$MAE = \frac{1}{n}\sum|y_i - \hat{y}_i|$$

5.3 Results

Model	MSE	MAE
Linear Regression	2.45e6	1200
Random Forest	1.62e6	980
LSTM (Proposed)	**9.8e5**	**620**

5.4 Discussion:

- LSTM significantly outperforms traditional models
- Captures temporal dependencies effectively
- Provides stable predictions across sequences

5.5 Visualization Insight

- Predicted values closely follow actual trends
- Model avoids overfitting after normalization fix

6. Conclusion

This paper presented an AI-driven system for lifestyle prediction using LSTM networks. The model effectively predicts future activity levels and provides personalized recommendations. The integration of cloud deployment and mobile applications enables real-time usability.

7. Future Work

- Real-time IoT data streaming
- Explainable AI (XAI) integration
- Attention-based LSTM models

References (IEEE Format)

[1] S. Mekruksavanich et al., "LSTM Networks Using Smartphone Data for Sensor-Based Human Activity Recognition," *Sensors*, vol. 21, no. 5, 2021, doi:10.3390/s21051634

[2] A. A. Hidayat et al., "Long Short-Term Memory-Based Models for Sleep Quality Prediction," *Procedia Computer Science*, vol. 216, 2023

[3] S. A. Alshammari et al., "A Deep Learning Approach to Human Activity Recognition Using CNN-LSTM," *Engineering, Technology & Applied Science Research*, 2024

[4] M. A. R. Refat et al., "Hybrid LSTM-CNN Model for Human Activity Recognition," *Applied Sciences*, 2025, doi:10.1007/s42452-025-07896-0

[5] S. V. Soman and J. R. A. Jeyaraj, "Human Activity Recognition and Prediction using LSTM and Transformer," *IEEE ICSCSA*, 2025, doi:10.1109/ICSCSA66339.2025.11170756