Component

권기웅

1. 기본 Component

1.1 Text

1.1.1 기본

notice.js

```
import React from 'react';
import {Text} from 'react-native';

const Notice = () => {
  return (
    <>
      <Text style={{fontSize: 40}}>
        공지 : 강의실에서 야동 좀 그만 보는 방향으로 추진할 궁리를 해보시길
        바랍니다.
      </Text>
    </>
  );
};

export default Notice;
```

App.js

```
import React from 'react';
import {View} from 'react-native';
import Notice from './notice';

const App = () => {
  return (
    <View style={{flex: 1}}>
      <Notice />
    </View>
  );
};

export default App;
```

1.1.2 numberOfLines

notice.js

```
import React from 'react';
import {Text} from 'react-native';

const Notice = () => {
  return (
    <>
      <Text style={{fontSize: 40}} numberOfLines={2}>
        공지 : 강의실에서 야동 좀 그만 보는 방향으로 추진할 궁리를 해보시길
        바랍니다.
      </Text>
    </>
  );
};

export default Notice;
```

1.1.3 마트료시카

notice.js

```
import React from 'react';
import {Text} from 'react-native';

const Notice = () => {
  return (
    <>
      <Text style={{fontSize: 40}} numberOfLines={2}>
        공지 : 강의실에서{' '}
        <Text style={{fontSize: 50, color: 'red', fontWeight: '900'}}>
          야동
        </Text>{' '}
        좀 그만 보는 방향으로 추진할 궁리를 해보시길 바랍니다.
      </Text>
    </>
  );
};

export default Notice;
```

1.2 Image

1.2.1 Image

파일 넣고



jjh.js

```
import React from 'react';
import {Image} from 'react-native';

const JJH = () => {
  return (
    <>
      <Image
        style={{width: 100, height: 200}}
        source={require('./img/jjh.png')}
      />
      <Image
        style={{width: 100, height: 200}}
        resizeMode={'contain'}
        source={require('./img/jjh.png')}
      />
      <Image
        style={{width: 100, height: 'auto', aspectRatio: 3 / 1}}
        source={require('./img/jjh.png')}
      />
    </>
  );
};

export default JJH;
```

App.js

```
import React from 'react';
import {View} from 'react-native';
import JJH from './jjh';
import Notice from './notice';

const App = () => {
  return (
    <View style={{flex: 1}}>
      <Notice />
      <JJH />
    </View>
  );
};

export default App;
```

1.2.2 ImageBackground

App.js

```
import React from 'react';
import {ImageBackground, View} from 'react-native';
import JJH from './jjh';
import Notice from './notice';

const App = () => {
  return (
    <View style={{flex: 1}}>
      <ImageBackground style={{flex: 1}} source={require('./img/bg.jpg')}>
        <Notice />
        <JJH />
      </ImageBackground>
    </View>
  );
};

export default App;
```

1.2.3 웹 이미지

jjh.js

```
import React from 'react';
import {Image} from 'react-native';

const JJH = () => {
  return (
    <>
      <Image
        style={{width: 100, height: 200}}
        resizeMode={'contain'}
        source={require('./img/jjh.png')}
      />

      <Image
        style={{width: '100%', height: 200}}
        resizeMode={'contain'}
        source={{
          uri: 'https://w.namu.la/s/ffbd747fba46fbef2fd4bd
        }}
      />

    </>
  );
};

export default JJH;
```

1.3 TextInput

1.3.1 속성들

jjh.js

```
import React from 'react';
import {Image, TextInput} from 'react-native';

const JJH = () => {
  return (
    <>
      <TextInput placeholder="사이즈" keyboardType="number-pad" />

      <Image
        style={{width: 100, height: 100}}
        resizeMode={'contain'}
        source={require('./img/jjh.png')}
      />
    </>
  );
};

export default JJH;
```

1.3.2 이벤트

jjh.js

```
import React, {useState} from 'react';
import {Alert, Image, TextInput} from 'react-native';

const JJH = () => {
  const [size, setSize] = useState(100);

  return (
    <>
      <TextInput
        placeholder="사이즈"
        keyboardType="number-pad"
        onChangeText={t => {
          setSize(t === '' ? 100 : parseInt(t));
        }}
        onEndEditing={() => {
          Alert.alert('ㅠ', '웃');
        }}
      />

      <Image
        style={{width: size, height: size}}
        resizeMode={'contain'}
        source={require('./img/jjh.png')}
      />
    </>
  );
};

export default JJH;
```

2. User Interface

2.1 Button

notice.js

```
import React, {useState} from 'react';
import {Button, Text} from 'react-native';

const Notice = () => {
  const [nol, setNol] = useState(1);

  return (
    <>
      <Button
        title="펼치기"
        color={'green'}
        onPress={() => {
          nol === 1 ? setNol(0) : setNol(1);
        }}
      />

      <Text style={{fontSize: 40}} numberOfLines={nol}>
        공지 : 강의실에서{' '}
        <Text style={{fontSize: 50, color: 'red', fontWeight: '900'}}>
          야동
        </Text>{' '}
        좀 그만 보는 방향으로 추진할 궁리를 해보시길 바랍니다.
      </Text>
    </>
  );
};

export default Notice;
```

2.2 Switch

jjh.js

```
import React, {useState} from 'react';
import {Alert, Image, Switch, TextInput} from 'react-native';

const JJH = () => {
  const [size, setSize] = useState(200);
  const [img, setImg] = useState(true);

  return (
    <>
      <TextInput
        placeholder="사이즈"…
        }}
      />

      <Image
        style={{width: size, height: size}}
        resizeMode={'contain'}
        source={
          img === true ? require('./img/jjh.png') : require('./img/back6.jpg')
        }
      />

      <Switch
        value={img}
        style={{width: size, height: size / 2}}
        thumbColor="#004D40"
        trackColor={{false: '#E0F2F1', true: '#80CBC4'}}
        onValueChange={v => {
          setImg(v);
        }}
      />
    </>
  );
};

export default JJH;
```

3. List View

3.1 FlatList

students.js

```
import React from 'react';
import {FlatList, Text} from 'react-native';

const Students = () => {
  let students = [];
  for (let index = 0; index < 18; index++) {
    students = students.concat({no: index, name: '이상한 학생 ' + index});
  }

  return (
    <>
      <FlatList
        data={students}
        renderItem={({item}) => (
          <Text
            style={{
              backgroundColor: '#ECEFF1',
              height: 50,
              padding: 5,
              margin: 5,
            }}>
            {item.name}
          </Text>
        )}
        keyExtractor={(item, index) => index}
      />
    </>
  );
};

export default Students;
```

App.js

```
import React from 'react';
import {ImageBackground, View} from 'react-native';
import JJH from './jjh';
import Notice from './notice';
import Students from './students';

const App = () => {
  return (
    <View style={{flex: 1}}>
      <ImageBackground style={{flex: 1}} source={require('./img/bg.jpg')}>
        <Notice />
        <JJH />
        <Students />
      </ImageBackground>
    </View>
  );
};

export default App;
```

3.2 SectionList

students.js

```
import React from 'react';
import {SectionList, Text} from 'react-native';

const Students = () => {
  let students = [];
  students = students.concat({
    type: '반장',
    data: [{no: 0, name: '제일 이상함'}],
  });
  let t = [];
  for (let index = 1; index < 18; index++) {
    t = t.concat({no: index, name: '이상한 학생 ' + index});
  }
  students = students.concat({type: '학생', data: t});

  return (
    <>
      <SectionList
        sections={students}
        renderSectionHeader={({section: {type}}) => (
          <Text style={{fontSize: 20}}>{type}</Text>
        )}
        renderItem={({item}) => (
          <Text
            style={{
              backgroundColor: '#ECEFF1',      height: 50,
              padding: 5,                      margin: 5,
            }}>
            {item.name}
          </Text>
        )}
        keyExtractor={item => item.no}
      />
    </>
  );
};

export default Students;
```

4. 기타

4.1 ActivityIndicator

etc.js

```
import React from 'react';
import {ActivityIndicator} from 'react-native';

const Etc = () => {
  return (
    <>
      <ActivityIndicator />
      <ActivityIndicator size={'large'} />
      <ActivityIndicator size={'large'} color={'#F9A825'} />
    </>
  );
};

export default Etc;
```

App.js

```
import React from 'react';
import {View} from 'react-native';
import Etc from './etc';

const App = () => {
  return (
    <View style={{flex: 1}}>
      <Etc />
    </View>
  );
};

export default App;
```

4.2 Alert

etc.js

```
import React, {useState} from 'react';
import {ActivityIndicator, Alert, Button} from 'react-native';

const Etc = () => {
  const [go, setGo] = useState(true);

  const two = () => {
    Alert.alert('2', '개짜리', [
      {text: '멈춰', onPress: () => { setGo(false); },},
      {text: '돌려', onPress: () => { setGo(true); },},
    ]);
  };

  const three = () => {
    Alert.alert('3', '개짜리', [
      {text: 'ㅋ'},
      {text: '멈춰', onPress: () => { setGo(false); },},
      {text: '돌려', onPress: () => { setGo(true);  },},
    ]);
  };

  return (
    <>
      <Button title="2개짜리" onPress={two} />
      <Button title="3개짜리" onPress={three} />
      <ActivityIndicator animating={go} />
      <ActivityIndicator size={'large'} animating={go} />
      <ActivityIndicator size={'large'} color={'#F9A825'} animating={go} />
    </>
  );
};

export default Etc;
```

4.3 Dimensions

4.3.1 Dimensions

etc.js

```
import React, {useState} from 'react';
import {ActivityIndicator, Alert, Button, Dimensions, Text} from 'react-native';

const Etc = () => {
  const [go, setGo] = useState(true);
  const two = () => {…
  };
  const three = () => {…
  };

  return (
    <>
      <Button title="2개짜리" onPress={two} />
      <Button title="3개짜리" onPress={three} />
      <ActivityIndicator animating={go} />
      <ActivityIndicator size={'large'} animating={go} />
      <ActivityIndicator size={'large'} color={'#F9A825'} animating={go} />
      <Text>{JSON.stringify(Dimensions.get('window'))}</Text>
      <Text>{JSON.stringify(Dimensions.get('screen'))}</Text>
    </>
  );
};

export default Etc;
```

4.3.2 useWindowDimensions Hook

etc.js

```
import React, {useState} from 'react';
import {
  ActivityIndicator,
  Alert,
  Button,
  Dimensions,
  Text,
  useWindowDimensions,
} from 'react-native';

const Etc = () => {
  const [go, setGo] = useState(true);
  const two = () => {…
  };
  const three = () => {…
  };

  const {height, width} = useWindowDimensions();

  return (
    <>
      <Button title="2개짜리" onPress={two} />
      <Button title="3개짜리" onPress={three} />
      <ActivityIndicator animating={go} />
      <ActivityIndicator size={'large'} animating={go} />
      <ActivityIndicator size={'large'} color={'#F9A825'} animating={go} />
      <Text>{JSON.stringify(Dimensions.get('window'))}</Text>
      <Text>{JSON.stringify(Dimensions.get('screen'))}</Text>
      <Text>{width}</Text>
      <Text>{height}</Text>
    </>
  );
};

export default Etc;
```

4.4 KeyboardAvoidingView

4.4.1 KeyboardAvoidingView

App.js

```
import React from 'react';
import {KeyboardAvoidingView, TextInput, View} from 'react-native';
import Etc from './etc';

const App = () => {
  return (
    <KeyboardAvoidingView behavior={'height'} style={{flex: 1}}>
      <View style={{flex: 1, justifyContent: 'space-around'}}>
        <Etc />
        <TextInput
          style={{borderStyle: 'solid', borderColor: 'red', borderWidth: 3}}
        />
      </View>
    </KeyboardAvoidingView>
  );
};

export default App;
```

4.4.2 키보드 빼기

App.js

```
import React from 'react';
import {
  Keyboard,
  KeyboardAvoidingView,
  TextInput,
  TouchableWithoutFeedback,
  View,
} from 'react-native';
import Etc from './etc';

const App = () => {
  return (
    <KeyboardAvoidingView behavior={'height'} style={{flex: 1}}>
      <TouchableWithoutFeedback onPress={Keyboard.dismiss}>
        <View style={{flex: 1, justifyContent: 'space-around'}}>
          <Etc />
          <TextInput
            style={{borderStyle: 'solid', borderColor: 'red', borderWidth: 3}}
          />
        </View>
      </TouchableWithoutFeedback>
    </KeyboardAvoidingView>
  );
};

export default App;
```

4.5 Modal

App.js

```
import React, {useState} from 'react';
import {Button, Image, Modal, View} from 'react-native';

const App = () => {
  const [v, setV] = useState(false);
  return (
    <View style={{flex: 1}}>
      <Modal visible={v} transparent={true} animationType={'slide'}>
        <View style={{flex: 1, justifyContent: 'center', alignItems: 'center', backgroundColor: '#37474F99'}}>
          <Image
            style={{width: 200, height: 'auto', aspectRatio: 9 / 16, margin: 10}}
            source={require('./img/gansik.jpg')}
          />
          <Button
            title="도망가기"
            onPress={() => {
              setV(false);
            }}
          />
        </View>
      </Modal>

      <Button
        title="간식 훔치기"
        onPress={() => {
          setV(true);
        }}
      />
    </View>
  );
};

export default App;
```

4.6 ScrollView

4.6.1 ScrollView

App.js

```
import React, {useEffect, useState} from 'react';
import {ScrollView, Text, View} from 'react-native';

const App = () => {
  const [v, setV] = useState([]);

  const re = () => {
    let ar = [];
    for (let index = 0; index < 50; index++) {
      ar = ar.concat(
        <Text key={index} style={{fontSize: 50}}>
          {Math.round(Math.random() * 100)}
        </Text>,
      );
    }
    setV(ar);
  };

  useEffect(() => {
    re();
  }, []);

  return (
    <View style={{flex: 1}}>
      <ScrollView>{v}</ScrollView>
    </View>
  );
};

export default App;
```

4.6.2 RefreshControl

App.js

```
import React, {useEffect, useState} from 'react';
import {RefreshControl, ScrollView, Text, View} from 'react-native';

const App = () => {
  const [v, setV] = useState([]);
  const [f5, setF5] = useState(false);

  const re = () => {…
  };

  useEffect(() => {…
  }, []);

  const doRC = () => {
    setF5(true);
    re();
    setTimeout(() => {
      setF5(false);
    }, 1000);
  };

  return (
    <View style={{flex: 1}}>
      <ScrollView
        refreshControl={<RefreshControl refreshing={f5} onRefresh={doRC} />}>
        {v}
      </ScrollView>
    </View>
  );
};

export default App;
```

4.7 StatusBar

4.7.1 StatusBar

App.js

```
import React, {useState} from 'react';
import {Button, StatusBar, View} from 'react-native';

const App = () => {
  const styles = ['default', 'light-content', 'dark-content'];
  const [bs, setBs] = useState(0);
  const [h, setH] = useState(false);

  return (
    <View style={{flex: 1}}>
      <StatusBar barStyle={styles[bs]} hidden={h} />
      <Button
        title="넣고빼기"
        onPress={() => {
          setH(!h);
        }}
      />
      <Button
        title="디자인바꾸기"
        onPress={() => {
          bs === 2 ? setBs(0) : setBs(bs + 1);
        }}
      />
    </View>
  );
};

export default App;
```

4.7.2 Android 만

App.js

```
import React, {useState} from 'react';
import {Button, StatusBar, Text, View} from 'react-native';

const App = () => {
  const styles = ['default', 'light-content', 'dark-content'];
  const [bs, setBs] = useState(0);
  const [h, setH] = useState(false);

  return (
    <View style={{flex: 1}}>
      <StatusBar
        barStyle={styles[bs]}
        hidden={h}
        backgroundColor="#43A047AA"
        translucent={true}
      />
      <Text>ㅋㅋㅋ
```