애니메이션

권기웅

1. 기본

1.1 Animated.timing(...)

first.js

```
import React, {useEffect, useRef} from 'react';
import {Animated, Easing} from 'react-native';

const First = () => {
  const anim = useRef(new Animated.Value(0)).current;

  useEffect(() => {
    Animated.timing(anim, {
      toValue: 1,
      duration: 5000,
      useNativeDriver: true,
      easing: Easing.linear,
    }).start();
  }, []);

  return (
    <>
      <Animated.Text style={{fontSize: 50, opacity: anim}}>
        고려
      </Animated.Text>
    </>
  );
};

export default First;
```

App.js

```
import React from 'react';
import {View} from 'react-native';
import First from './first';

const App = () => {
  return (
    <View style={{flex: 1, justifyContent: 'center', alignItems: 'center'}}>
      <First />
    </View>
  );
};

export default App;
```

2. 보간

2.1 Animated.spring(...)

second.js

```
import React, {useRef, useState} from 'react';
import {Animated, TouchableWithoutFeedback} from 'react-native';

const Second = () => {
  const anim = useRef(new Animated.Value(0)).current;
  const [zero, setZero] = useState(1);

  const showAnim = () => {
    Animated.spring(anim, {
      toValue: zero, speed: 0.3, bounciness: 15, useNativeDriver: true,
    }).start();
    setZero(zero === 0 ? 1 : 0);
  };

  return (
    <>
      <TouchableWithoutFeedback onPress={showAnim}>
        <Animated.Image
          style={{
            width: '30%', height: 'auto', aspectRatio: 9 / 16,
            transform: [
              {
                rotateZ: anim.interpolate({
                  inputRange: [0, 1],
                  outputRange: ['0deg', '360deg'],
                }),
              },
            ],
          }}
          source={require('./img/holo.jpg')}
        />
      </TouchableWithoutFeedback>
    </>
  );
};

export default Second;
```

App.js

```
import React from 'react';
import {View} from 'react-native';
import First from './first';
import Second from './second';

const App = () => {
  return (
    <View style={{flex: 1, justifyContent: 'center', alignItems: 'center'}}>
      <Second/>
      <First />
    </View>
  );
};

export default App;
```

3. 연속

3.1 Animated.sequence(...)

third.js

```
import React, {useRef, useState} from 'react';
import {Animated, TouchableWithoutFeedback} from 'react-native';

const Third = () => {
  const anim = useRef(new Animated.Value(0)).current;
  const anim2 = useRef(new Animated.Value(0.5)).current;
  const [zero, setZero] = useState(1);

  const showAnim = () => {
    Animated.sequence([
      Animated.spring(anim, {toValue: zero, speed: 0.3, bounciness: 15, useNativeDriver: true}),
      Animated.spring(anim2, {toValue: zero === 0 ? 0.5 : 1, speed: 0.3, bounciness: 20, useNativeDriver: true}),
    ]).start();
    setZero(zero === 0 ? 1 : 0);
  };

  return (
    <>
      <TouchableWithoutFeedback onPress={showAnim}>
        <Animated.Image
          style={{
            width: '40%', height: 'auto', aspectRatio: 9 / 16, margin:20,
            transform: [
              {
                rotateZ: anim.interpolate({
                  inputRange: [0, 1], outputRange: ['0deg', '360deg'],
                }),
              },
              {scale: anim2},
            ],
          }}
          source={require('./img/holo2.jpg')}
        />
      </TouchableWithoutFeedback>
    </>
  );
};

export default Third;
```

App.js

```
import React from 'react';
import {View} from 'react-native';
import First from './first';
import Second from './second';
import Third from './third';

const App = () => {
  return (
    <View style={{flex: 1, justifyContent: 'center', alignItems: 'center'}}>
      <Third />
      <Second />
      <First />
    </View>
  );
};

export default App;
```

4. 끝나고

4.1 끝나고

third.js

```
import React, {useRef, useState} from 'react';
import {Animated, Text, TouchableWithoutFeedback} from 'react-native';

const Third = () => {
  const anim = useRef(new Animated.Value(0)).current;
  const anim2 = useRef(new Animated.Value(0.5)).current;
  const [zero, setZero] = useState(1);
  const [cmt, setCmt] = useState('질문 하나만 해도 되나요');
  const showAnim = () => {
    Animated.sequence([
      Animated.spring(anim, {toValue: zero, speed: 0.3, bounciness: 15, useNativeDriver: true}),
      Animated.spring(anim2, {toValue: zero === 0 ? 0.5 : 1, speed: 0.3, bounciness: 20, useNativeDriver: true}),
    ]).start(() => { setCmt(zero === 0 ? '질문 하나만 해도 되나요' : '어? 됐다')});
    setZero(zero === 0 ? 1 : 0);
  };

  return (
    <>
      <TouchableWithoutFeedback onPress={showAnim}>…
      </TouchableWithoutFeedback>
      <Text style={{fontSize: 30, margin:20}}>{cmt}</Text>
    </>
  );
};

export default Third;
```