```
Assignment 4
Juan Silva
ECE 309
Feb. 21, 2018
```

Problem Set 7


Problem Set 7-1:

Generate a plot for the decaying exponential: $s(t) = \sin(4\pi t) \exp(-t)$, for t values from 0 to 1 sec.

```
t = 0:0.001:1;
s = sin(4*pi*t) .* exp(-t);

plot(t,s), xlabel('t'),ylabel('s(t)')
grid, title('Exponential Decay')
```


Results



Problem Set 7-2:

Plot $y(t) = t^3$ and $z(t) = t^(1/3)$, for $0 \le t \le 2$, on a single graph. Make the plot for z a dashed line, and the plot for y a solid line.

```
t = 0:0.001:2;
y = t.^3;
z = t.^(1/3);
plot(t,y,t,z,'--')
xlabel('t'), ylabel('f(t)');
grid, title('Mathematical Functions');
legend('y(t)', 'z(t)')
```




Problem Set 7-3:

Plot $s(t) = e^{(t/2)}$, and $w(t) = \sin(2pt)$, for $0 \le t \le p$, one underneath the other on a single page. Use circles for the data points for s, with no line connecting the points. Use triangles for the data points for w, with a solid line connecting the points.

s(t)

```
t = linspace(0, pi, 100);
s = exp(t/2);
w = sin(2*pi*t);
subplot(2,1,1), plot(t,s,'o')
grid, title('s(t)');
subplot(2,1,2), plot(t,w,'-^')
grid, title('w(t)'); figure
```


Results



Problem Set 7-4:

```
Recall that the x and y coordinates for a point on a circle of radius r, at
angle q, are:
               x = r \cos(q), y = r \sin(q). To plot a circle of radius 5:
% a. Create a vector containing 100 q-values, linearly spaced
% between 0 and 2pi.
v = linspace(0, 2*pi, 100);
% b. Create a vector of corresponding x values (one for each value of q)
% and another vector of corresponding y values (one for each value of q),
% assuming that the radius of the circle is 5.
x = 5 * cos(v);
y = 5 * sin(v);
% d. Generate a plot of (x, y) values. After your plot command, insert the
% command: axis('equal') to make the scaling on the x and y axes
identical (to avoid distortion of the circle).
plot(x, y)
title('Circle with Radius 5')
axis('equal')
figure
```


Results



Problem Set 7-5:

Plot the function y = 10x, for x values ranging from 0 to 4, using a linear scale on the x-axis and a log scale on the y-axis.


```
x = linspace(0,4,100);
y = 10.^x;
semilogy(x,y), grid
title('Function y(x)')
```



Problem Set 7-6:

Generate a vector x containing 20 points, logarithmically spaced, between 1 and 10,000. Plot y = ln(x), using a log scale on both the x and y axes.


Results



Problem Set 7-7:

```
% 7a. For integer values of n ranging from 0 to 8, plot the discrete data set:  
% x[n] = ln(n)  
n = [0:8];  
x = log(n);  
stem(n,x)
```

```
% 7b. Generate another plot for the data given in 7a, with the data circles filled in.
m = [0:8];
y = log(m);
stem(m,'ro', 'filled')
```



Problem Set 7-8:

Recall that the RC filter has transfer function: $H(f) = (1 + 2*pi*f*R*C)^-1$. For frequencies ranging from f = -200 KHz to 200 KHz, with R = 10 K Ω and C = 1 μF , plot the magnitude and phase angle for the transfer function, on one plot, with the left vertical axis showing |H(f)|, and the right vertical axis showing the phase angle, in radians.

```
% Program Name: graphs.m
% Author: Juan Silva Last Modified: Feb. 20, 2018
% Description: This program will graph the transfer function using plotyy in
order to graph two separate plots into one graph.
clear, clc, close all
format short, format compact
% *** Define variables ***
R = 10e3;
             %kΩ
C = 1e-6;
              %µF
% *** Start Code ***
f = linspace(-200e3, 200e3, 200);
h = (1 + j*2*pi*f*R*C).^{-1};
                                     %Produce magnitude
magH = abs(h);
                                     %Produce angle in radians
angH = angle(h);
% Magnitude is left side
plotyy(f,magH,f,angH)
grid
title('RC Filter - Transfer Function');
legend('Magnitude', 'Angle (in radians)')
xlabel('Frequency (in Hz)')
```

