

CIS507: Design & Analysis of Algorithms  
*Homework 1 (with answers), Spring 2014*

**Student Name:** - - - - -

**Student ID:** - - - - -

**Q1.** Give asymptotic upper bounds for  $T(n)$  for each of the following recurrences (use the  $O$ -notation). Assume that  $T(n)$  is a non-negative constant for  $n$  sufficiently large (in terms of  $\alpha$ ). Make your bounds as tight as possible, and justify your answers.

1. **(1 point)**  $T(n) = n^{1-\alpha} \cdot T(n^\alpha) + \Theta(n)$ , for a constant  $\alpha \in (0, 1)$ .
2. **(1 points)**  $T(n) = T(n-1) + T(\alpha \cdot n) + 1$ , for a constant  $\alpha \in (0, 1)$ .

**ANSWER:**

Write your answer here ...

**Q2. (2 points)** Consider the following problem called MAXCUT: given an undirected graph  $G = (V, E)$  with non-negative edge weights  $w_e$  for  $e \in E$ , find a partition  $(S, V \setminus S)$  of the vertices that maximizes the total weight of the edges crossing the cut, that is,  $\sum_{e \in \delta(S)} w_e$ , where  $\delta(S)$  is the set of edges that have one end-point in  $S$  and another in  $V \setminus S$ .

Consider the following randomized algorithm: Select a subset  $S$  by picking each vertex in  $V$  independently with probability  $\frac{1}{2}$ . Show that the expected weight of the edges in the cut  $(S, V \setminus S)$  is a factor of  $\frac{1}{2}$  of the total weight, that is:

$$\mathbb{E} \left[ \sum_{e \in \delta(S)} w_e \right] = \frac{1}{2} \sum_{e \in E} w_e$$

(Hint: use an indicator random variable for each edge.)

**Q3.** Suppose that we would like to analyze the change in price for a given stock. We observe the different prices over a period of  $n$  days. Let  $A[i]$  be the observed price in day  $i$ . We would like to compute:

- (I) the smallest absolute price difference:  $\min_{1 \leq i, j \leq n, i \neq j} |A[i] - A[j]|$ ;

- (II) the largest absolute price difference:  $\max_{1 \leq i, j \leq n} |A[i] - A[j]|$ ;
  - (III) the average absolute price difference:  $\frac{1}{n(n-1)} \sum_{1 \leq i, j \leq n} |A[i] - A[j]|$ ;
  - (IV) the median absolute price difference:  $\text{median}(\{|A[i] - A[j]| : 1 \leq i, j \leq n\})$ .
- (i) **(1 point)** give an  $O(n^2)$  deterministic algorithm for computing (I), (II), (III) and (IV);
  - (ii) **(1 point)** give an  $O(n \log n)$  deterministic algorithm for computing (I);
  - (iii) **(1 point)** give an  $O(n)$  deterministic algorithm for computing (II);
  - (iv) **(1 point)** give an  $O(n \log n)$  deterministic algorithm for computing (III);
  - (v) **(1 point)** give a randomized algorithm with  $O(n^2)$  expected running time for computing (IV).

Implement the four algorithms in (ii), (iii), (iv) and (v). For testing purposes, your program should accept as an input a file "test.in", containing  $n$ , followed by the set of  $n$  numbers (1 per line). It should output the four values described in (I), (II), (III), and (IV).

**Q4. (4 points)** Implement a *perfect* hash table, where keys are decimal numbers, each having at most 10 digits. For both hash levels, use the class of universal hash functions of the dot-product form: if the hash table size is a prime  $m$ , pick a random sequence  $\mathbf{a} := \langle a_0, a_1, \dots, a_9 \rangle$ , where each  $a_i \in \{0, 1, \dots, m-1\}$ ; given a key  $k$ , decompose it into a sequence of decimal digits  $\mathbf{k} := \langle k_0, k_1, \dots, k_9 \rangle$ , then use hash functions of the form  $h_{\mathbf{a}}(k) = (\sum_{r=0}^9 a_r k_r) \bmod m$ . Your table should have no collisions, and uses at most  $8n$  table entries, in total. (*Hint*: use the fact that for any positive integer  $n$ , there is at least one prime between  $n$  and  $2n$ .)

For testing purposes, your program should accept as an input a file "test.in" containing the number of keys  $n$ , followed by the set of keys to be hashed (1 per line). It should output in another file "test.out", the following lines: the first line (call it line 0) contains the values chosen for the first-level hash function in the following order (separated by spaces):  $m, a_0, a_1, \dots, a_r$ ; then for  $i = 1, \dots, m$ , the  $i$ th line contains the values corresponding to the second level-hash function chosen at the  $i$ th row in the first level table (again in the order  $m(i), a_0(i), a_1(i), \dots, a_r(i)$ ; output "0 0" if that row is empty). Following this, the file should contain triples (one per line):  $(k, h(k), h_i(k))$ , where  $k$  is the key,  $i = h(k)$  is the index in the first-level hash table,  $h_i(k)$  is the index in the second level hash table.