

CIS507: Design & Analysis of Algorithms
Homework 1 (with answers), Spring 2014

March 5th, 2014

Student Name: Yanan Xiao

Student ID: 131102019

Q1. Give asymptotic upper bounds for $T(n)$ for each of the following recurrences (use the O -notation). Assume that $T(n)$ is a non-negative constant for n sufficiently large (in terms of α). Make your bounds as tight as possible, and justify your answers.

1. **(1 point)** $T(n) = n^{1-\alpha} \cdot T(n^\alpha) + \Theta(n)$, for a constant $\alpha \in (0, 1)$.
2. **(1 points)** $T(n) = T(n-1) + T(\alpha \cdot n) + 1$, for a constant $\alpha \in (0, 1)$.

ANSWER:

1.

$$T(n) = n^{1-\alpha} \cdot T(n^\alpha) + \Theta(n) \Leftrightarrow \frac{T(n)}{n} = \frac{T(n^\alpha)}{n^\alpha} + \Theta(1)$$

Let

$$\frac{T(n)}{n} = P(n) \Rightarrow \frac{T(n)}{n} = \frac{T(n^\alpha)}{n^\alpha} + \Theta(1) \Leftrightarrow P(n) = P(n^\alpha) + \Theta(1)$$

Let

$$n = 2^m \Leftrightarrow m = \log n \Rightarrow S(2^m) = S(2^{\alpha m}) + \Theta(1)$$

Let

$$Q(m) = P(2^m) \Rightarrow Q(m) = Q(\alpha m) + \Theta(1)$$

By Master Theorem, we can get

$$m^{\log_b a} = m^{\log_{\frac{1}{\alpha}} 1} = m^0 = 1 \Rightarrow Q(m) = \Theta(\log m) \Rightarrow P(n) = \Theta(\log \log n)$$

But

$$T(n) = nP(n) \Rightarrow T(n) = \Theta(n \log \log n) = O(n \log \log n)$$

2. From the question description we can see that $T(n)$ is sufficiently large in terms of α .

To be specific, let's assume $\alpha = 0.5$, then we can rewrite the recurrence equation as $T(n) = T(n-1) + T(0.5n) + 1$. By using tree induction it is not hard to guess $T(n) = O(n \log n)$. The proof is as follows.

Q2. (2 points) Consider the following problem called MAXCUT: given an undirected graph $G = (V, E)$ with non-negative edge weights w_e for $e \in E$, find a partition $(S, V \setminus S)$ of the vertices that maximizes the total weight of the edges crossing the cut, that is, $\sum_{e \in \delta(S)} w_e$, where $\delta(S)$ is the set of edges that have one end-point in S and another in $V \setminus S$.

Consider the following randomized algorithm: Select a subset S by picking each vertex in V independently with probability $\frac{1}{2}$. Show that the expected weight of the edges in the cut $(S, V \setminus S)$ is a factor of $\frac{1}{2}$ of the total weight, that is:

$$\mathbb{E} \left[\sum_{e \in \delta(S)} w_e \right] = \frac{1}{2} \sum_{e \in E} w_e$$

(Hint: use an indicator random variable for each edge.)

ANSWER: Let's define an indicator random variable P_e where

$$P_e = \begin{cases} 1 & \text{the edge crosses the cut} \\ 0 & \text{the edge does not cross the cut} \end{cases} \quad (1)$$

Since each vertex is picked up independently with a 0.5 probability, therefore the probability for a vertex's both ends are in the same set is 0.5. Thus we have $\mathbb{E}P_e = 0.5$.

$$\sum_{e \in \delta(S)} w_e = \sum_{e \in E} w_e P_e$$

Q3. Suppose that we would like to analyze the change in price for a given stock. We observe the different prices over a period of n days. Let $A[i]$ be the observed price in day i . We would like to compute:

- (I) the smallest absolute price difference: $\min_{1 \leq i, j \leq n, i \neq j} |A[i] - A[j]|$;
 - (II) the largest absolute price difference: $\max_{1 \leq i, j \leq n} |A[i] - A[j]|$;
 - (III) the average absolute price difference: $\frac{1}{n(n-1)} \sum_{1 \leq i, j \leq n} |A[i] - A[j]|$;
 - (IV) the median absolute price difference: $\text{median}(\{|A[i] - A[j]| : 1 \leq i, j \leq n\})$.
- (i) **(1 point)** give an $O(n^2)$ deterministic algorithm for computing (I), (II), (III) and (IV);
 - (ii) **(1 point)** give an $O(n \log n)$ deterministic algorithm for computing (I);

- (iii) **(1 point)** give an $O(n)$ deterministic algorithm for computing (II);
- (iv) **(1 point)** give an $O(n \log n)$ deterministic algorithm for computing (III);
- (v) **(1 point)** give a randomized algorithm with $O(n^2)$ expected running time for computing (IV).

Implement the four algorithms in (ii), (iii), (iv) and (v). For testing purposes, your program should accept as an input a file "test.in", containing n , followed by the set of n numbers (1 per line). It should output the four values described in (I), (II), (III), and (IV).

Q4. (4 points) Implement a *perfect* hash table, where keys are decimal numbers, each having at most 10 digits. For both hash levels, use the class of universal hash functions of the dot-product form: if the hash table size is a prime m , pick a random sequence $\mathbf{a} := \langle a_0, a_1, \dots, a_9 \rangle$, where each $a_i \in \{0, 1, \dots, m-1\}$; given a key k , decompose it into a sequence of decimal digits $\mathbf{k} := \langle k_0, k_1, \dots, k_9 \rangle$, then use hash functions of the form $h_{\mathbf{a}}(k) = (\sum_{r=0}^9 a_r k_r) \bmod m$. Your table should have no collisions, and uses at most $8n$ table entries, in total. (*Hint:* use the fact that for any positive integer n , there is at least one prime between n and $2n$.)

For testing purposes, your program should accept as an input a file "test.in" containing the number of keys n , followed by the set of keys to be hashed (1 per line). It should output in another file "test.out", the following lines: the first line (call it line 0) contains the values chosen for the first-level hash function in the following order (separated by spaces): m, a_0, a_1, \dots, a_r ; then for $i = 1, \dots, m$, the i th line contains the values corresponding to the second level-hash function chosen at the i th row in the first level table (again in the order $m(i), a_0(i), a_1(i), \dots, a_r(i)$; output "0 0" if that row is empty). Following this, the file should contain triples (one per line): $(k, h(k), h_i(k))$, where k is the key, $i = h(k)$ is the index in the first-level hash table, $h_i(k)$ is the index in the second level hash table.