

How to Change the World with Donald Knuth

Abraham Xiao

Masdar Institute of Science and Technology

Information Security Project Presentation

- 1 Discrete Logarithm
- 2 ElGamal Cryptosystem
- 3 Attack Techniques
- 4 Appendices

Discrete Logarithm in a Nutshell

The security of many cryptographic techniques depends on the intractability of discrete logarithm problem.

A partial list of these include:

- DiffieHellman key agreement and its derivatives.
- ElGamal encryption.
- ElGamal signature scheme and its variants.

General setting for algorithms in this section are:

- A (multiplicatively written) finite cyclic group G
- n is the order of group G
- α is a generator of group G ¹

¹For more math background, refer to [Ros12].

Relevant Definitions

Cyclic group and its generator.

Definition

A group is *cyclic* if there is an element $\alpha \in G$ such that for each $b \in G$ there is an integer i with $b = \alpha^i$. Such an element α is called a generator of G .

Discrete logarithm.

Definition

Let G be a finite cyclic group of order n . Let α be a generator of G , and let $\beta \in G$. The *discrete logarithm of β to the base α* , denoted $\log_{\alpha} \beta$, is the unique integer x , $0 \leq x \leq n - 1$, such that $\beta = \alpha^x$ [MVO96].

A Discrete Logarithm Example

Example

Let $p = 97$. Then \mathbb{Z}_{97}^* is a cyclic group of order $n = 96$. A generator of \mathbb{Z}_{97}^* is $\alpha = 5$. Since $5^{32} \equiv 35 \pmod{97}$, $\log_5 35 = 32$ in \mathbb{Z}_{97}^* .

The DiffieHellman Problem

The DiffieHellman problem is closely related to the well-studied discrete logarithm problem.

Definition

The *DiffieHellman problem* is the following: given a prime p , a generator α of \mathbb{Z}_p^* , and elements $\alpha^a \bmod p$ and $\alpha^b \bmod p$, find $\alpha^{ab} \bmod p$.

Wait! Could we just possibly do

$$\alpha^a \times \alpha^b \rightarrow \alpha^{ab} \quad (1)$$

Well, life is not as easy as it looks like. . .

$$\alpha^a \times \alpha^b = \alpha^{a+b} \quad (2)$$

Links between Discrete Logarithm and DiffieHellman Problem

Suppose that the discrete logarithm problem in \mathbb{Z}_p^* could be efficiently solved². Then given α , p , $\alpha^a \bmod p$ and $\alpha^b \bmod p$, one could first find a from α , p and $\alpha^a \bmod p$ by what?!

Solving a discrete logarithm problem, and then compute $(\alpha^b)^a = \alpha^{ab} \bmod p$.

²In math, the assumption is as important as, if not more important than induction in many situations.

ElGamal public-key encryption

The ElGamal public-key encryption scheme can be viewed as Diffie–Hellman key agreement³ in key transfer mode. Its security is **based on** the intractability of the discrete logarithm problem (Section 1) and the DiffieHellman problem (Section 2).

³Yet another fancy nickname for key exchange

Ensure: A public key and its corresponding private key is created for every entity.

Steps to generate key pairs are described as follows:

- 1 Generate a prime p that is large enough and cannot be predicted, i.e. it should be generated randomly. Find a generator α of the multiplicative group \mathbb{Z}_p^* of integers modulo p .
- 2 Randomly select an integer a satisfying $1 \leq a \leq p - 2$. Then calculate $\alpha^a \bmod p$.
- 3 The public key is returned as (p, α, α^a) ; The private key is returned as a .

Figure : Algorithm Key generation for ElGamal public-key encryption

Ensure: B uses A 's public key to encrypt a message m . Then A uses decrypts using his private key.

① *Encryption.* The steps for B to take are as follows:

- ① Require or obtain A 's authentic public key (p, α, α^a) .
- ② Express the plaintext message as an integer in the scale $0, 1, \dots, p-1$.
- ③ Randomly select an integer k satisfying $1 \leq k \leq p-2$.
- ④ Calculate $\gamma = \alpha^k \bmod p$ and $\delta = m \cdot (\alpha^a)^k \bmod p$.
- ⑤ Transmit the ciphertext $c = (\gamma, \delta)$ to A .

② *Decryption.* The decrypt steps for A are described as follows:

- ① Calculate $\gamma^{p-1-a} \bmod p$ using A 's private key. (note: due to the characteristic of modulus, $\gamma^{p-1-a} = \gamma^{-a} = \alpha^{-ak}$).
- ② Calculate plaintext m by evaluating $(\gamma^{-a} \cdot \delta \bmod p)$.

Figure : **Algorithm** ElGamal public-key encryption [Elg85]

ElGamal Encryption with artificially small parameters

Key generation. Entity A selects the prime $p = 2357$ and a generator $\alpha = 2$ of \mathbb{Z}_{2357}^* . A chooses the private key $a = 1751$ and computes

$$\alpha^a \bmod p = 2^{1751} \bmod 2357 = 1185 \quad (3)$$

A 's public key is $(p = 2357, \alpha = 2, \alpha^a = 1185)$.

Encryption. To encrypt a message $m = 2035$, B selects a random integer $k = 1520$ and computes

$$\gamma = 2^{1520} \bmod 2537 = 1430 \quad (4)$$

and

$$\delta = 2035 \cdot 1185^{1520} \bmod 2357 = 697 \quad (5)$$

ElGamal Encryption cont.

B sends $\gamma = 1430$ and $\delta = 697$ to A.

Decryption. To decrypt, A computes

$$\gamma^{p-1-a} = 1430^{605} \mod 2357 = 872 \quad (6)$$

and recovers m by computing

$$m = 872 \cdot 697 \mod 2357 = 2305 \quad (7)$$

A clear **disadvantage** of ElGamal encryption is that there is a *message expansion* by a factor of 2. That is, the ciphertext is **twice** as long as the corresponding plaintext.

$$m = 2035 \Rightarrow (\gamma = 1430, \delta = 697) \quad (8)$$

Exhaustive Search

The most obvious algorithm for discrete logarithm problem is to successively compute $\alpha^0, \alpha^1, \alpha^2, \dots$ until β is obtained.

This method takes $O(n)$ multiplications, where n is the order of α , and is therefore inefficient if n is large (i.e. in cases of cryptographic interest).




Say we use 1024 bits, then the number should be maximum 2^{1024} as large.

2^{64}	=	18,446,744,073,709,551,616	2^{80}	=	1,208,925,819,614,629,174,706,176
2^{65}	=	36,893,488,147,419,103,232	2^{81}	=	2,417,851,639,229,258,349,412,352
2^{66}	=	73,786,976,294,838,206,464	2^{82}	=	4,835,703,278,458,516,698,824,704
2^{67}	=	147,573,952,589,676,412,928	2^{83}	=	9,671,406,556,917,033,397,649,408
2^{68}	=	295,147,905,179,352,825,856	2^{84}	=	19,342,813,113,834,066,795,298,816
2^{69}	=	590,295,810,358,705,651,712	2^{85}	=	38,685,626,227,668,133,590,597,632
2^{70}	=	1,180,591,620,717,411,303,424	2^{86}	=	77,371,252,455,336,267,181,195,264
2^{71}	=	2,361,183,241,434,822,606,848	2^{87}	=	154,742,504,910,672,534,362,390,528
2^{72}	=	4,722,366,482,869,645,213,696	2^{88}	=	309,485,009,821,345,068,724,781,056
2^{73}	=	9,444,732,965,739,290,427,392	2^{89}	=	618,970,019,642,690,137,449,562,112
2^{74}	=	18,889,465,931,478,580,854,784	2^{90}	=	1,237,940,039,285,380,274,899,124,224
2^{75}	=	37,778,931,862,957,161,709,568	2^{91}	=	2,475,880,078,570,760,549,798,248,448
2^{76}	=	75,557,863,725,914,323,419,136	2^{92}	=	4,951,760,157,141,521,099,596,496,896
2^{77}	=	151,115,727,451,828,646,838,272	2^{93}	=	9,903,520,314,283,042,199,192,993,792
2^{78}	=	302,231,454,903,657,293,676,544	2^{94}	=	19,807,040,628,566,084,398,385,987,584
2^{79}	=	604,462,909,807,314,587,353,088	2^{95}	=	39,614,081,257,132,168,796,771,975,168

Figure : Power of Two

Index Calculus

References I

-  T. Elgamal, *A public key cryptosystem and a signature scheme based on discrete logarithms*, Information Theory, IEEE Transactions on **31** (1985), no. 4, 469–472.
-  Alfred J. Menezes, Scott A. Vanstone, and Paul C. Van Oorschot, *Handbook of applied cryptography*, 1st ed., CRC Press, Inc., Boca Raton, FL, USA, 1996.
-  Kenneth H. Rosen, *Discrete mathematics and its applications*, 7th ed., McGraw-Hill Higher Education, 2012.