
Reader

Convert a URL to LLM-friendly input, by simply adding `r.jina.ai` in front.

API	Demo	Pricing

Reader API

Convert a URL to LLM-friendly input,
by simply adding `r.jina.ai` in front.



Add API Key for Higher Rate Limit

Enter your Jina API key to access a higher rate limit. For latest rate limit information, please refer to the table below.

LEARN MORE

GET RESPONSE

Browser Engine (Quality/Speed)

Choose the browser engine for fetching the webpage content. This affects the quality, speed, completeness, accessibility of the content.

Default

LEARN

API key

••••••••••••••••••••...

Available tokens

10,000,000

This is your unique key. Store it securely!

Jina VLM: Small Multilingual Vision Language Model

A 2.4B parameter vision-language model that achieves state-of-the-art multilingual visual question answering among open 2B-scale VLMs.

-

ReaderLM v2: Small Language Model for


HTML to Markdown and JSON

ReaderLM-v2 is a 1.5B parameter language model specialized in HTML-to-Markdown conversion and HTML-to-JSON extraction. It supports documents up to 512K tokens across 29 languages and offers 20% higher accuracy compared to its predecessor.

-


What is Reader?

Feeding web information into LLMs is an important step of grounding, yet it can be challenging. The simplest method is to scrape the webpage and feed the raw HTML. However, scraping can be complex and often blocked, and raw HTML is cluttered with extraneous elements like markups and scripts. The Reader API addresses these issues by extracting the core content from a URL and converting it into clean, LLM-friendly text, ensuring high-quality input for your agent and RAG systems.



Reader for web search and SERP

Reader can be used as SERP API. It allows you to feed your LLM with the content behind the search results engine page. Simply prepend `https://s.jina.ai/?q=` to your query, and Reader will search the web and return the top five results with their URLs and contents, each in clean, LLM-friendly text. This way, you can always keep your LLM up-to-date, improve its factuality, and reduce hallucinations.




Reader also reads images!

Images on the webpage are automatically captioned using a vision language model in the reader and formatted as image alt tags in the output. This gives your downstream LLM just enough hints to incorporate those images into its reasoning and summarizing processes. This means you can ask questions about the images, select specific ones, or even forward their URLs to a more powerful VLM for deeper analysis!

Reader also reads PDFs!

Yes, Reader natively supports PDF reading. It's compatible with most PDFs, including those with many images, and it's lightning fast! Combined with an LLM, you can easily build a ChatPDF or document analysis AI in no time.



The best part? It's free!

Reader API is available for free and offers flexible rate limit and pricing. Built on a scalable infrastructure, it offers high accessibility, concurrency, and reliability. We strive to be your preferred grounding solution for your LLMs.

Rate Limit

Rate limits are tracked in three ways: **RPM** (requests per minute), and **TPM** (tokens per minute). Limits are enforced

per IP/API key and will be triggered when either the RPM or TPM threshold is reached first. When you provide an API key in the request header, we track rate limits by key rather than IP address.

Search

Columns

	Product	API Endpoint
	Reader API	https://r.jina.a
	Reader API	https://s.jina.a
	Embedding API	https://api.jina
	Reranker API	https://api.jina
	Classifier API	https://api.jina
	Classifier API (Few-shot)	https://api.jina
	Classifier API (Zero-shot)	https://api.jina

	Segmenter API	`https://api.jin`
	DeepSearch	`https://deepsea`

Don't panic! Every new API key contains ten millions free tokens!

GET YOUR API KEY	$ CHECK THE PRICE TABLE

API Pricing

API pricing is based on the token usage. One API key gives you access to all search foundation products.



With Jina Search Foundation API

The easiest way to access all of our products. Top-up tokens as you go.





This is your unique key. Store it securely!



Have a different API key to top up? Paste above and click 'Save'.



Top up this API key with more tokens

Depending on your location, you may be charged in USD, EUR, or other currencies. Taxes may apply.

Toy Experiment	Prototype Development	Production Deployment
10 Millio	1 Billio	11 Billion
Tokens valid for:	Tokens valid for:	Tokens valid for:
Non-commercial use (CC-BY-NC).	Standard key Basic key management Technical support	Premium key with much higher rate limits Advanced key management Premium customer support in 24 hours One-hour integration consultation
Free Enjoy your new API key with free tokens, no cr card required.	**$50** 0.050 / 1M tokens	**$500** 0.045 / 1M tokens

Understand the rate limit

Rate limits are the maximum number of requests that can be made to an API within a minute per IP address/API key (RPM). Find out more about the rate limits for each product and tier below.

Auto top-up on low token balance

Recommended for uninterrupted service in production. When you...

ⓘ We introduced a new pricing model on May 6th, 2025. If you enabled auto-recharge before...


Top up when
< 1M Tokens

FAQ

- What are the costs associated with using the Reader API?
- How does the Reader API function?
- Is the Reader API open source?
- What is the typical latency for the Reader API?
- Why should I use the Reader API instead of scraping the page myself?
- Does the Reader API support multiple languages?
- What should I do if a website blocks the Reader API?
- Can the Reader API extract content from PDF files?

- Can the Reader API process media content from web pages?
- Is it possible to use the Reader API on local HTML files?
- Does Reader API cache the content?
- Can I use the Reader API to access content behind a login?
- Can I use the Reader API to access PDF on arXiv?
- How does image caption work in Reader?
- What is the scalability of the Reader? Can I use it in production?
- What is the rate limit of the Reader API?
- What is Reader-LM? How can I use it?
- How do I extract structured data from webpages?
- Does Reader actively bypass website anti-bot protection?
- Will upgrading from a free to a paid API key give me access to more websites?

How to get my API key?



What's the rate limit?

Rate Limit

Rate limits are tracked in three ways: **RPM** (requests per minute), and **TPM** (tokens per minute). Limits are enforced per IP/API key and will be

triggered when either the RPM or TPM threshold is reached first. When you provide an API key in the request header, we track rate limits by key rather than IP address.

Search Columns

	Product	API Endpoint
	Reader API	`https://r.jina.ai`
	Reader API	`https://s.jina.ai`
	Embedding API	`https://api.jina.`
	Reranker API	`https://api.jina.`
	Classifier API	`https://api.jina.`
	Classifier API (Few-shot)	`https://api.jina.`
	Classifier API (Zero-shot)	`https://api.jina.`
	Segmenter API	`https://api.jina.`

DeepSearch https://deepsearc

API-related common questions

- Can I use the same API key for reader, embedding, reranking, classifying and fine-tuning APIs?
- Can I monitor the token usage of my API key?
- What should I do if I forget my API key?
- Do API keys expire?
- Can I transfer tokens between API keys?
- Can I revoke my API key?
- Why is the first request for some models slow?
- Is my API data used to train your models?
- What are the rate limits for Jina APIs?
- Are there batch size limits for the APIs?

Billing-related common questions

- Is billing based on the number of sentences or requests?
- Is there a free trial available for new users?
- Are tokens charged for failed requests?

$ What payment methods are accepted?

$ Is invoicing available for token purchases?