

Printable Quiz

1. C1: Basic if

What happens here if amount = -10?

```
if (amount > 0) { balance = balance + amount; }
```

- (A) balance increases by -10
- (B) Nothing happens
- (C) Compilation error
- (D) balance decreases by 10

2. C2: If-else form

Complete behaviour of this code for positive vs non-positive values?

```
if (amount > 0) { balance = balance + amount; } else { System.out.printf("Use a positive amount: %d%n", amount); }
```

- (A) Positive adds to balance; otherwise prints a message
- (B) Always adds to balance
- (C) Always prints the message
- (D) Throws an exception for negative values

3. C3: Else-if chain

What prints for age = 15?

```
if (age
```

- (A) Child
- (B) Teenager
- (C) Adult
- (D) Nothing

4. C4: First true branch wins

How many branches execute in an if/else-if/else chain?

- (A) All branches that are true
- (B) Exactly one branch
- (C) Zero or two branches
- (D) All branches always

5. C5: Braces optionality

Which two snippets are equivalent?

// A if (price

- (A) A and B are equivalent when the block has one statement
- (B) A and B are never equivalent
- (C) B is invalid Java
- (D) A executes twice

6. C6: Stray semicolon

What is wrong with the following?

if (price)

- (A) The semicolon ends the if; block always runs
- (B) Missing braces
- (C) Needs else
- (D) Correct as-is

7. C7: Ticket machine (simple)

What purpose does the condition serve?

```
public void insertMoney(int amount) {  
    if (amount > 0) {  
        balance = balance + amount;  
    }  
}
```

- (A) Avoids adding non-positive amounts
- (B) Forces balance to 0 for negatives
- (C) Always adds amount
- (D) Throws exception for negatives

8. C8: Ticket machine (tiers)

What is the outcome for amount = 60?

```
public void specialOffer(int amount) { if (amount > 100) { balance = balance + 50; } else if  
(amount > 50) { balance = balance + 25; } else { amount = amount + 5; } }
```

- (A) Adds 50 to balance
- (B) Adds 25 to balance
- (C) Adds 5 to amount

- (D) Does nothing

9. C9: Condition definition

Which best defines a boolean condition used by an if statement?

- (A) An expression that evaluates to true or false
- (B) A statement that prints output
- (C) A block of multiple statements
- (D) A method that returns an int

10. C10: Relational operator reminder

Which statement is correct about = vs ==?

- (A) = assigns; == tests equality for primitives
- (B) = tests equality; == assigns
- (C) Both test equality
- (D) Java uses === for equality

11. Q1: If statement—basic behaviour

In Java, what happens with the statements inside the braces of an if statement?

```
if (condition) { // statements }
```

- (A) They execute only if the boolean condition evaluates to
- (B) They always execute once, regardless of the condition.
- (C) They execute repeatedly until the condition becomes false.
- (D) They execute only after the

12. Q7: Relational operators list

Which list contains only Java relational operators?

- (A)
- (B)
- (C)
- (D)

13. Q8: Else-if syntax

Which is the correct syntax for an else if clause in Java?

- (A)
- (B)
- (C)

- (D)

14. Q10: After-the-if code

Given:

`// do some work if (flag) { process(); } // more work here` What can you say about the “more work here” section?

- (A) It will execute whether
 - (B) It executes only when
 - (C) It executes only when
 - (D) It never executes because
-

Answer Key

1. B
2. A
3. B
4. B
5. A
6. A
7. A
8. B
9. A
10. A
11. A
12. A
13. A
14. A