

Printable Quiz

1. Q1. Why arrays

Why are arrays used in programming?

- (A) To store a single value of any type
- (B) To store many values of the same type efficiently
- (C) To store only numbers in sequential order
- (D) To replace all loops in code

2. Q2. Reusing n in loop

What happens when you read a number into the same variable n repeatedly in a loop?

- (A) Each number is stored permanently
- (B) The previous number is overwritten
- (C) The numbers are all added automatically
- (D) A syntax error occurs

3. Q3. Declare int[10]

In Java, how do you declare an array of 10 integers?

- (A) `int numbers = new int(10);`
- (B) `int numbers[] = new int[10];`
- (C) `numbers = new int[10];`
- (D) `int numbers = [10];`

4. Q4. Default int value

What is the default value for elements in a new int array?

- (A) 1
- (B) null
- (C) 0
- (D) undefined

5. Q5. Access elements

How are array elements accessed in Java?

- (A) Using the `get()` method
- (B) By index starting at 0
- (C) By key names

- (D) Randomly

6. Q6. Print numbers[2]

What will `System.out.println(numbers[2])` print if `numbers[2]` has been set to 18?

- (A) 0
- (B) 2
- (C) 18
- (D) null

7. Q7. length meaning

What does `numbers.length` return?

- (A) The last index used
- (B) The total capacity of the array
- (C) The number of elements currently populated
- (D) The sum of all elements

8. Q8. Rule for input data

What is the main rule when dealing with input data, as described in the slides?

- (A) Never store input data
- (B) Always lose old input
- (C) Never lose input data
- (D) Avoid loops with input

9. Q9. String[] declaration

Which of the following is a valid declaration for an array of String objects?

- (A) `String words = new String(4);`
- (B) `String[] words = new String[4];`
- (C) `String words[] = {"Dog", "Cat"};`
- (D) Both B and C

10. Q10. Out-of-range access

What happens if an array index outside its range is accessed?

- (A) Java assigns a default value
- (B) Java ignores the statement
- (C) Java throws an `ArrayIndexOutOfBoundsException`
- (D) The program exits successfully

11. Q11. Print all elements

How do you print all elements of an array named words?

- (A) `System.out.println(words);`
- (B) `for (int i = 0; i < words.length; i++) { System.out.println(words[i]); }`
- (C) `System.out.println(words[i]);`
- (D) `print(words.all());`

12. Q12. Types storable

What kind of data can arrays in Java store?

- (A) Only primitive data types
- (B) Only objects
- (C) Both primitive types and objects
- (D) Only Strings

13. Q13. Default in Person[]

In an array `Person[] friends = new Person[4]`, what does each element initially contain?

- (A) A new Person object
- (B) A random value
- (C) null
- (D) Empty

14. Q14. Average on partial array

If an array results has 15 elements but only 12 are used, how should you calculate the average?

- (A) Divide by 15
- (B) Divide by 12
- (C) Divide by `results.length()`
- (D) Java automatically adjusts

15. Q15. Method call on element

In a Person array, what does `friends[i].printFirstName()` do?

- (A) Creates a new Person
- (B) Calls a method on the Person object stored at index i
- (C) Accesses an element without printing anything
- (D) Causes a compile error

Answer Key

1. B
2. B
3. B
4. C
5. B
6. C
7. B
8. C
9. D
10. C
11. B
12. C
13. C
14. B
15. B