

Test name: Test Bank as of Oct 2018

Question 1 of 200

Theory - Terminology

What is **cout**? If more than one applies select all that apply.

- ☐ A) command
- ☐ B) Keyword
- ☐ C) stream
- ☐ D) object
- ☐ E) class
- ☐ F) function name
- ☐ G) string
- ☐ H) statement
- ☐ I) operator

Question 2 of 200

Theory - Terminology

What is **<<** ?

- ☐ A) punctuation mark
- ☐ B) command
- ☐ C) operator
- ☐ D) directive
- ☐ E) keyword
- ☐ F) has no meaning in C++
- ☐ G) object
- ☐ H) string
- ☐ I) statement

Question 3 of 200

Theory - Terminology

What is **=>** ?

- ☐ A) directive
- ☐ B) punctuation mark

- ☐ C) command
- ☐ D) statement
- ☐ E) symbol
- ☐ F) object
- ☐ G) has no meaning in C++
- ☐ H) stream
- ☐ I) string
- ☐ J) operator

Question 4 of 200

Theory - Terminology

Match the word/symbol with the definition.

1. [] <<	A. stream insertion operator
2. [] >>	B. stream extraction object
	C. stream command
	D. stream insertion object
	E. stream object
	F. stream extraction operator

Question 5 of 200

write code

Give the **escape sequence** that goes moves the cursor to the **beginning** of the **next line**. Write **ONLY** the escape sequence.

Question 6 of 200

write code

Give the **escape sequence** that makes the computer **beep**. Write **ONLY** the escape sequence.

Question 7 of 200

write code

Give the **stream manipulator** that moves the cursor to the **next line**.

Question 8 of 200

Theory - Terminology

What is the **full and proper name** of
cout

Must give ALL terms and in correct order. Be careful with the spelling.

Question 9 of 200

Theory - Terminology

Give the full and proper name of
cin

Must give ALL terms and in correct order. Be careful with the spelling.

Question 10 of 200

Theory - Terminology

Give the full and proper name of
<<

Must give ALL terms and in correct order. Be very careful with the spelling.

Question 11 of 200

Theory - Terminology

What is **include**? Select **ALL** that apply.

- ☐ **A)** command
- ☐ **B)** a library name
- ☐ **C)** variable
- ☐ **D)** stream

☐☐ **E)** object☐ **F)** keyword☐ **G)** string☐ **H)** has no meaning in C++☐ **I)** pre-processor directive☐ **J)** reserved word**Question 12 of 200**

Theory - Terminology

What does the **A** in **ASCII** stand for?

Question 13 of 200

Theory - Terminology

What does the **FIRST I** in **ASCII** stand for? Be careful with the spelling!

Question 14 of 200

Theory - Terminology

What does the **SECOND I** in **ASCII** stand for? Be careful with the spelling!

Question 15 of 200

Theory - Terminology

What does the **C** in **ASCII** stand for? Be careful with the spelling!

Question 16 of 200

Theory - Terminology

What does the **S** in **ASCII** stand for? Be careful with the spelling!

Question 17 of 200

Theory - Terminology

What does the **I** in **IDE** stand for? Be careful with the spelling!

Question 18 of 200

Theory - Terminology

What does the **D** in **IDE** stand for? Be careful with the spelling!

Question 19 of 200

Theory - Terminology

What does the **E** in **IDE** stand for? Be careful with the spelling!

Question 20 of 200

Theory - Terminology

What does the **C** in **CPU** stand for? Be careful with the spelling.

Question 21 of 200

Theory - Terminology

What does the **P** in **CPU** stand for? Be careful with the spelling.

Question 22 of 200

Theory - Terminology

What does the **U** in **CPU** stand for? Be careful with the spelling.

Question 23 of 200

Theory - Terminology

What does the **A** in **ALU** stand for? Be careful with the spelling.

Question 24 of 200

Theory - Terminology

What does the **L** in **ALU** stand for? Be careful with the spelling.

Question 25 of 200

Theory - Terminology

Parts of the **CPU** are the **ALU** and the _____ ?
Write the **WORDS not** just the acronym.

Question 26 of 200

Theory - Terminology

What does the **A** in **RAM** stand for? Be careful with the spelling.

Question 27 of 200

Theory - Terminology

What does the **R** in **RAM** stand for? Be careful with the spelling.

Question 28 of 200

Theory - Terminology

What does the **M** in **RAM** stand for? Be careful with the spelling.

Question 29 of 200

Theory - Terminology

How many **bits** is a **byte**? Type an number and only the number.

Question 30 of 200

Theory - Terminology

What does the **U** in **USB** stand for? Be careful with the spelling.

Question 31 of 200

Theory - Terminology

What does the **S** in **USB** stand for? Be careful with the spelling.

Question 32 of 200

Theory - Terminology

What does the **B** in **USB** stand for? Be careful with the spelling.

Question 33 of 200

Theory - Terminology

In what software category do **utility programs** belong to?

Question 34 of 200

Theory - Terminology

In Visual Studio what is the **file name extension** of the file in which **you type your code**?
Write the extension **ONLY**.

Question 35 of 200

Theory - Terminology

What is the **file name extension** of the program that you **sell to your customers**?
Write the extension **ONLY**.

Question 36 of 200

Theory - Terminology

What is the **file name extension** of the file you need to open in order to **open the whole Visual Studio IDE**?
Write the file extension **ONLY**.

Question 37 of 200

Theory - Terminology

An other term for **keywords** is _____ words. (note that **only one word is missing**). Be careful with the spelling.

Question 38 of 200

Theory - Terminology

In C++ you can have a **keyword** that contains capital letters.

- ☐ A) True
- ☐ B) False

Question 39 of 200

Theory - Terminology

What makes a C++ statement?

Question 40 of 200

Theory - Terminology

What are the **three primary activities of a program**? Write them in order with just a space between them (no , or and). Be careful with the spelling.

Question 41 of 200

Theory - Terminology

A variable must be _____ before it is used in a program.

Question 42 of 200

Theory - Terminology

A(n) _____ is a diagram that graphically illustrate the structure of a program.

Question 43 of 200

Theory - Terminology

Name the **first** stage of the **CPU's** cycle.

Question 44 of 200

Theory - Terminology

Name the **second** stage of the **CPU's** cycle.

Question 45 of 200

Theory - Terminology

Name the **third stage** of the **CPU's** cycle.

Question 46 of 200

Theory - Terminology

What indicates the **beginning** of a **comment line** in C++?

Question 47 of 200

Theory - Terminology

In C++ **main** is a _____. (note that **only one word is missing**). Be careful with the spelling.

Question 48 of 200

Theory - Terminology

In C++ **return** is a _____. (note that **only one word is missing**). **Be careful with the spelling.**

Question 49 of 200

Theory - Terminology

In C++ **endl** is a _____ . (note that **you need to write two words**). Be careful with the spelling.

Question 50 of 200

Theory - Terminology

\n is a _____. (note that **you need to write two words**). Be careful with the spelling. Have one space only between the words and nothing else.

Question 51 of 200

write a statement

Write the C++ **statement** that assigns the character **backslash** to an already declared character variable named **myChar**. Be careful with the formatting.

Question 52 of 200

Theory - Terminology

= is the _____ operator. Be careful with the spelling.

Question 53 of 200

Theory - Terminology

In the statement
cout << "Delta";
"Delta" is _____. Select **ALL** that apply.

- ☐ A) string
- ☐ B) an object
- ☐ C) literal
- ☐ D) an identifier
- ☐ E) stream
- ☐ F) reserved word
- ☐ G) comment
- ☐ H) keyword
- ☐ I) the name of a constant
- ☐ J) the name of a variable

Question 54 of 200

Theory - Terminology

In the statement

```
cout << "a";
```

the "a" is ...

Select **ALL** that apply.

- ☐ A) an identifier
- ☐ B) keyword
- ☐ C) comment
- ☐ D) reserved word
- ☐ E) object
- ☐ F) literal
- ☐ G) string
- ☐ H) the name of a variable
- ☐ I) character
- ☐ J) the name of a constant

Question 55 of 200

result of code

The statement

```
char letterA = "C";
```

will result in

Select **ALL** that apply.

- ☐ A) syntax error
- ☐ B) run time error
- ☐ C) storing the character C in the memory location letterA
- ☐ D) logical error
- ☐ E) storing the ASCII value of C represented in binary in the memory location letterA

Question 56 of 200

Theory - Terminology

What is the **ASCII value** of capital A? Write a number.

Question 57 of 200

Theory - Terminology

What is the **ASCII value** of '0' (the character zero)? Write a **number**.

Question 58 of 200

Theory - Terminology

What is the ASCII value of **lower case a**? Write a number.

Question 59 of 200

Theory - Terminology

How many **bytes** are needed to store **the string "A"** ? Write a **number**.

Question 60 of 200

Theory - Terminology

How many **bits** are needed to store **the string "A"**? Write a number.

Question 61 of 200

result of code

What will be the result of the following code

```
int x = 3.6;
```

if typed in a complete C++ program.

-
- ☐ A) syntax error
- ☐ B) 3.6 will be stored in the memory location x
- ☐ C) the result will depend on the compiler you are using
- ☐ D) 4 will be stored in the memory location x
- ☐ E) 3 will be stored in the memory location x
- ☐ F) run time error

Question 62 of 200

Theory - Terminology

What **category** does the = operator belong to when the classification is done **by the number of operands**?

Question 63 of 200

Theory - Terminology

What is the name of the % operator?

Question 64 of 200

write code

How do you indicate the **BEGINNING** of multi-line comments in C++?

Question 65 of 200

write code

How do you indicate the **END** of multi-line comments in C++?

Question 66 of 200

Theory - Terminology

How do you call operators that **take 3 operands**? Give the name of the category.

Question 67 of 200

Theory - Terminology

How do you call operators that take **1 operand**? Give the category name.

Question 68 of 200

Theory - Terminology

How do you call operators that take **2 operands**? Give the category name.

Question 69 of 200

Theory - Terminology

'\n' is Select **ALL** that apply. Note the quotes!

- ☐ A) escape sequence
- ☐ B) character
- ☐ C) literal
- ☐ D) variable
- ☐ E) object
- ☐ F) stream
- ☐ G) keyword
- ☐ H) reserved word
- ☐ I) string
- ☐ J) stream manipulator

Question 70 of 200

write code

Write the function call that calculates n^k (k is the exponent).
You need to write the function call **ONLY** and **NOT** the statement.
You need to write the **complete call**, **not** just the name of the function! Be careful with the formatting.

Question 71 of 200

result of code

What is the result of this statement:
cout << 5%3;
Assume it is part of a complete C++ program.

- ☐ A) run time error
- ☐ B) 2
- ☐ C) depends on the compiler
- ☐ D) none of the given answers
- ☐ E) 1

- ☐
- ☐ F) syntax error
- ☐ G) 3
- ☐ H) 5

Question 72 of 200

result of code

What is the result of the following code:

```
cout << 7.0 % 5;
```

Assume it is part of a complete C++ program.

-
- ☐ A) 7
 - ☐ B) depends on the compiler
 - ☐ C) run time error
 - ☐ D) 5
 - ☐ E) 2
 - ☐ F) 1
 - ☐ G) syntax error
 - ☐ H) none of the given answers

Question 73 of 200

result of code

What is the result of the following code:

```
cout << 3 % 9;
```

Assume it is part of a complete C++ program.

-
- ☐ A) 3
 - ☐ B) 9
 - ☐ C) none of the given answers
 - ☐ D) 6
 - ☐ E) syntax error
 - ☐ F) 0
 - ☐ G) run time error
 - ☐ H) depends on the compiler

Question 74 of 200

result of code

What is the result of the following statement:

```
cout << 0 % 11;
```

Assume it is part of a complete C++ program.

- ☐ A) depends on the compiler
- ☐ B) none of the given answers
- ☐ C) 11
- ☐ D) 1
- ☐ E) run time error
- ☐ F) 0
- ☐ G) syntax error

Question 75 of 200

result of code

What is the result of the following statement:

```
cout << 13 % 0;
```

Assume it is part of a complete C++ program.

- ☐ A) 1
- ☐ B) run time error
- ☐ C) depends on the compiler
- ☐ D) 13
- ☐ E) none of the given answers
- ☐ F) syntax error
- ☐ G) 0

Question 76 of 200

result of code

What is the result of the following statements:

```
char ch = 65;
```

```
cout << ch + 1;
```

Assume it is part of a complete C++ program.

- ☐ A) 66
- ☐ B) syntax error
- ☐ C) the character A
- ☐ D) ch1
- ☐ E) depends on the compiler
- ☐ F) none of the given answers
- ☐ G) ch 1
- ☐ H) the character B
- ☐ I) run time error
- ☐ J) ch

Question 77 of 200

result of code

What is the result of the following statements:

```
char c = 65;
```

```
cout << c;
```

Assume it is part of a complete C++ program.

- ☐ A) the character c
- ☐ B) the character A
- ☐ C) none of the given answers
- ☐ D) the character a
- ☐ E) syntax error
- ☐ F) 65
- ☐ G) run time error
- ☐ H) depends on the compiler

Question 78 of 200

result of code

What is the result of the following statements:

```
int x = 8;
```

```
if ( (x > 88) && (x = 3) )
```

```
    cout << x;
```

```
cout << "x = " << x;
```

Assume it is part of a complete C++ program.

- ☐ A) run time error
- ☐ B) x = 3
- ☐ C) depends on the compiler
- ☐ D) 3x = 3
- ☐ E) 8x = 3
- ☐ F) xx = x
- ☐ G) 8x = x
- ☐ H) 8x = 8
- ☐ I) x = 8
- ☐ J) syntax error

Question 79 of 200

result of code

What is the result of the following statements:

```
int x = 180;
```

```
if ( (x > 88) && (x = 3) )
```

```
    cout << x;
```

```
cout << "x = " << x;
```

Assume it is part of a complete C++ program.

- ☐ A) syntax error
- ☐ B) $xx = x$
- ☐ C) $x = 8$
- ☐ D) $180x = 180$
- ☐ E) $88 = 8$
- ☐ F) $3x = 3$
- ☐ G) $8x = 8$
- ☐ H) depends on the compiler
- ☐ I) $180x = 3$
- ☐ J) run time error

Question 80 of 200

result of code

What is the result of the following statements:

```
int x = 8;  
if ((x = 3) && (x > 88))  
cout << x;  
cout << "x = " << x;
```

Assume it is part of a complete C++ program.

- ☐ A) none of the given answers
- ☐ B) run time error
- ☐ C) syntax error
- ☐ D) nothing will print on the monitor
- ☐ E) $x = 3$
- ☐ F) $x = 8$
- ☐ G) $8x = 8$
- ☐ H) depends on the compiler
- ☐ I) $8x = 3$
- ☐ J) $3x = 3$

Question 81 of 200

result of code

What is the result of the following statements:

```
int x = 1;  
if ((x = 3) && (x > 2))  
cout << x;  
cout << "x = " << x;
```

Assume it is part of a complete C++ program.

- ☐ A) run time error
- ☐ B) $x = 1$
- ☐ C) $3x = 1$
- ☐ D) syntax error
- ☐ E) $3x = 3$
- ☐ F) depends on the compiler
- ☐ G) $x = 3$
- ☐ H) $1x = 1$
- ☐ I) none of the given answers

Question 82 of 200

result of code

What is the result of the following statements:

```
int x = 1;  
if ((x = 3) && (x > 2))  
    cout << x;  
cout << "x = " << x;
```

Assume it is part of a complete C++ program.

-
- ☐ A) $x = 3$
 - ☐ B) depends on the compiler
 - ☐ C) syntax error
 - ☐ D) $1x = 3$
 - ☐ E) run time error
 - ☐ F) none of the given answers
 - ☐ G) $1x = 1$
 - ☐ H) $3x = 3$

Question 83 of 200

result of code

What is the result of the following statements:

```
int x = 1;  
if ((x > 2) && (x = 3))  
    cout << x;  
cout << "x = " << x;
```

Assume it is part of a complete C++ program.

-
- ☐ A) $1x = 1$
 - ☐ B) $x = 1$
 - ☐ C) $1x = 3$
 - ☐ D) run time error

- ☐ E) $3x = 3$
- ☐ F) depends on the compiler
- ☐ G) $3x = 1$
- ☐ H) syntax error
- ☐ I) none of the given answers

Question 84 of 200

result of code

What is the result of the following statements:

```
char c = 'B';  
bool t = (c > 'a' ? true : false);  
if(t) cout << c;  
else cout << c + 2;
```

Assume it is part of a complete C++ program.

- ☐ A) 'e'
- ☐ B) 'B'
- ☐ C) 'd'
- ☐ D) syntax error
- ☐ E) 68
- ☐ F) 'D'
- ☐ G) 67
- ☐ H) run time error
- ☐ I) 66
- ☐ J) depends on the compiler

Question 85 of 200

result of code

What will happen if you have the following condition in an if statement in C++:

-5 < x <= -1

- ☐ A) true if x is in the (-5, -1] range - beginning of range is **EX**clusive end is **IN**clusive
- ☐ B) true if x is in the [-5, -1] range - both ends of the range are **IN**clusive
- ☐ C) run time error
- ☐ D) none of the given answers
- ☐ E) syntax error
- ☐ F) true if x is in the (-5, -1) range - both ends of the range are **EX**clusive
- ☐ G) The condition will be always false
- ☐ H) The condition will be always true
- ☐ I) depends on the compiler

- ☐ J) true if x is in the [-5, -1) range - beginning of range is **IN**clusive end is **EX**clusive

Question 86 of 200

result of code

What will happen if you have the following condition in an if statement in C++:
x > 20 && x <= 10

- ☐ A) true if x is in the (-5, -1] range - beginning of range is **EX**clusive end is **IN**clusive
- ☐ B) depends on the compiler
- ☐ C) true if x is in the (10, 20) range - both ends of the range are **EX**clusive
- ☐ D) none of the given answers
- ☐ E) The condition will be always true
- ☐ F) syntax error
- ☐ G) run time error
- ☐ H) The condition will be always false
- ☐ I) true if x is in the [10, 20) range - beginning of range is **IN**clusive end is **EX**clusive
- ☐ J) true if x is in the [10, 20] range - both ends of the range are **IN**clusive

Question 87 of 200

result of code

What is the result of this code:
int x = 3;
cout << (x > 3 ? '\t' : "false");
Assume it is part of a complete C++ program.

- ☐ A) 1 will be printed on the monitor
- ☐ B) run time error
- ☐ C) t will be printed on the monitor
- ☐ D) the cursor will be move forward 8 spaces
- ☐ E) 0 will be printed on the monitor
- ☐ F) depends on the compiler
- ☐ G) none of the given answers
- ☐ H) false will be printed on the monitor
- ☐ I) the cursor will moved to the next tab stop
- ☐ J) syntax error

Question 88 of 200

result of code

What is the result of the following statements:
int x = 54.99;
cout << (x > 54 ? x+2 : x);
Assume they are part of a complete C++ program.

- ☐ A) run time error
- ☐ B) 56.99 will print on the monitor
- ☐ C) none of the provided answers
- ☐ D) 56 will print on the monitor
- ☐ E) syntax error
- ☐ F) 54 will print on the monitor
- ☐ G) 54.99 will print on the monitor
- ☐ H) depends on the compiler

Question 89 of 200

Theory - Terminology

How many ternary operators are there. Write a number.

Question 90 of 200

Theory - Terminology

What type of operator is `<=`. Select ALL that apply.

- ☐ A) combination
- ☐ B) arithmetic
- ☐ C) This operator does not exist in C++
- ☐ D) relational
- ☐ E) shortcut
- ☐ F) ternary
- ☐ G) binary
- ☐ H) logical
- ☐ I) unary

Question 91 of 200

Theory - Terminology

What type of operator is `&&`? Select ALL that apply.

- ☐ A) relational
- ☐ B) unary
- ☐ C) binary
- ☐ D) This operator does not exist in C++

- ☐ E) logical
- ☐ F) ternary
- ☐ G) comparison

Question 92 of 200

Theory - Terminology

Which library do you need to include if you want to use **formatting stream manipulators**?
Give **ONLY** the library name.

Question 93 of 200

result of code

What is the result of the following code:
double grade = 100;
switch (grade) {
case 100: case 99: cout << "Good Job!";
default: cout << "You could have done better."
}
Assume it is part of a complete C++ program.

- ☐ A) run time error
- ☐ B) "Good Job!" will print on the monitor.
- ☐ C) depends on the compiler
- ☐ D) "Good Job! You could have done better." will print on the monitor in two lines.
- ☐ E) Nothing will print on the monitor.
- ☐ F) "You could have done better." will print on the monitor.
- ☐ G) syntax error
- ☐ H) "Good Job!You could have done better." will print on the monitor in one line.

Question 94 of 200

result of code

What is the result of the following statements:

```
int main () {  
    int i = 3.5, y = 0.5;  
  
    cout << i/y;  
    system("pause");  
    return 0;  
}
```

Assume it is part of a complete C++ program.

- ☐ A) syntax error
- ☐ B) 0
- ☐ C) 6
- ☐ D) run time error
- ☐ E) 7
- ☐ F) 3
- ☐ G) 1
- ☐ H) none of the provided answers
- ☐ I) depends on the compiler

Question 95 of 200

result of code

What is the result of the following statements:

```
int main() {  
    int x, y, c;  
    char ch;  
  
    cin >> x;  
    c = cin.get();  
    cin >> y;  
    cout << y;  
    system("pause");  
    return 0;  
}
```

Assume it is part of a complete C++ program and **IF** it runs the user will enter 36.25.

- ☐ A) run time error
- ☐ B) the ASCII value of '2'
- ☐ C) 25
- ☐ D) 36
- ☐ E) The ASCII value of '.'
- ☐ F) syntax error
- ☐ G) 2
- ☐ H) depends on the compiler

Question 96 of 200

result of code

What is the result of the following statements:

```
for ( int x = 1 ; x < 10; x++)  
    cout << x;
```

```
cout << "x = " << x;
```

Assume it is part of a complete C++ program.

- A) run time error**

- ☐
- ☐ B) x = 10
- ☐ C) syntax error
- ☐ D) 123459789
- ☐ E) infinite loop printing 1 for ever
- ☐ F) 12345978910x=10
- ☐ G) nothing, just a blank screen
- ☐ H) 123459789x=10
- ☐ I) x = 9
- ☐ J) x = 1

Question 97 of 200

result of code

What is the result of the following statements:

```
int x;  
for ( x = 1 ; x < 10; x+2)  
    cout << x;  
cout << "x = " << x;
```

Assume it is part of a complete C++ program.

- ☐ A) depends on the compiler
- ☐ B) 1357911x=11
- ☐ C) 13579x=11
- ☐ D) x=11
- ☐ E) prints 1 for ever
- ☐ F) prints 9 for ever
- ☐ G) syntax error
- ☐ H) run time error
- ☐ I) prints 10 for ever
- ☐ J) 13579x=9

Question 98 of 200

result of code

What is the result of the following statements:

```
int x = 10;  
while ( 1 > x > 20 )  
    cout << x++;  
cout << "x = " << x;
```

Assume it is part of a complete C++ program.

- ☐ A) run time error

- ☐ B) infinite loop
- ☐ C) 1011121314151617181920x = 21
- ☐ D) x = 10
- ☐ E) depends on the compiler
- ☐ F) 10111213141516171819x = 20
- ☐ G) syntax error
- ☐ H) 11121314151617181920x = 20
- ☐ I) 111213141516171819x = 20
- ☐ J) 1011121314151617181920x = 20

Question 99 of 200

result of code

What is the result of the following statements:

```
char ch = 65;
while ( ch = 'A' )
    cout << ch++;
cout << "ch = " << ch;
Assume it is part of a complete C++ program.
```

- ☐ A) ch = 65
- ☐ B) Ach=B
- ☐ C) infinite loop. Prints BBBBBBBB... for ever
- ☐ D) syntax error
- ☐ E) depends on the compiler
- ☐ F) ch = A
- ☐ G) 66 ch = A
- ☐ H) infinite loop. Prints AAAAAA... for ever
- ☐ I) 65ch = A
- ☐ J) Bch= B

Question 100 of 200

result of code

What is the result of the following statements:

```
int x = 0;
while (x++ < 10) {
    cout << ++x;
}
cout << "x = " << x;
Assume it is part of a complete C++ program.
```

- ☐ A) syntax error
- ☐ B) 02468x = 10

- ☐ C) 13579x = 11
- ☐ D) 13579x = 10
- ☐ E) 0246810x = 11
- ☐ F) 0246810x = 10
- ☐ G) 0246810x = 12
- ☐ H) depends on the compiler
- ☐ I) 246810x = 11
- ☐ J) 246810x = 12

Question 101 of 200

result of code

What is the result of the following statements:

```
int x = 0;
while (++x != 10) {
    cout << x++;
}
```

```
cout << "x = " << x;
```

Assume it is part of a complete C++ program.

- ☐ A) run time error
- ☐ B) 0123456789x= 10
- ☐ C) 123456789x= 10
- ☐ D) 12345678910x= 10
- ☐ E) syntax error
- ☐ F) 135791113151719.... infinite loop
- ☐ G) 123456789x= 9
- ☐ H) 012345678910x= 10
- ☐ I) 0123456789x= 9
- ☐ J) depends on the compiler

Question 102 of 200

result of code

What is the result of the following statements:

```
int x = 10;
while (x > 10)
    cout << x;
    x++;
```

```
cout << "x = " << x;
```

Assume it is part of a complete C++ program.

- ☐ A) 10x= 11
- ☐ B) x = 10
- ☐ C) 10

- ☐ D) syntax error
- ☐ E) x = 11
- ☐ F) run time error
- ☐ G) 10x = 10
- ☐ H) infinite loop prints 101010101010 for ever
- ☐ I) depends on the compiler
- ☐ J) none of the provided answers

Question 103 of 200

result of code

What is the result of the following statements:

```
int x = 100;  
while (x > 10) ;  
    cout << (x +=10);  
cout << "x = " << x;
```

Assume it is part of a complete C++ program.

Notice the ';' after the condition of the while!

- ☐ A) 100x = 100
- ☐ B) none of the provided answers
- ☐ C) 100x= 110
- ☐ D) infinite loop printing nothing
- ☐ E) syntax error
- ☐ F) run time error
- ☐ G) 110x = 110
- ☐ H) x = 100
- ☐ I) depends on the compiler
- ☐ J) x = 110

Question 104 of 200

result of code

What is the result of the following statements:

```
void f2( int &w) {  
    for (int k = 1; k < 10; k++)  
        cout << w++;  
}
```

```
int main() {  
    f2(19);  
    return 0;  
}
```

Assume it is part of a complete C++ program.

- ☐ A) none of the provided answers

- ☐ B) run time error
- ☐ C) will print 20 and the function will return
- ☐ D) syntax error
- ☐ E) will print 11 and the function will return
- ☐ F) depends on the compiler
- ☐ G) will print 10 and the function will return
- ☐ H) will print 19 and the function will return
- ☐ I) infinite loop

Question 105 of 200

result of code

What is the result of the following statements:

```
void f1(double &x) {  
    x++;  
}
```

```
int main() {  
    int k = 9;  
    f1(k);  
    cout << k;  
    return 0;  
}
```

Assume it is part of a complete C++ program.

-
- ☐ A) 9
 - ☐ B) will print logical garbage
 - ☐ C) depends on the compiler
 - ☐ D) syntax error
 - ☐ E) will print nothing
 - ☐ F) 10
 - ☐ G) run time error
 - ☐ H) none of the provided answers

Question 106 of 200

result of code

What is the result of the following statements:

```
// Function definition  
int f(double x) {  
    if (x = 25) return x/2.0;  
    return x+2;  
}
```

```
int main() {  
    cout << f (9);  
    return 0;  
}
```

```
}
```

Assume it is part of a complete C++ program.

- ☐ A) syntax error
- ☐ B) 12
- ☐ C) 4
- ☐ D) run time error
- ☐ E) 11
- ☐ F) logical garbage
- ☐ G) 12.5
- ☐ H) depends on the compiler
- ☐ I) 5
- ☐ J) 4.5

Question 107 of 200

result of code

```
string myName = "Delta";  
cout << myName[1];
```

- ☐ A) Delta
- ☐ B) noting
- ☐ C) e
- ☐ D) syntax error
- ☐ E) none of the provided answers
- ☐ F) depends on the compiler
- ☐ G) \0
- ☐ H) run time error
- ☐ I) D

Question 108 of 200

result of code

What is the result of the following statements:

```
string myString = "Really long name";  
myString[4] = myString[5] = '\0';  
cout << myString << endl;
```


Assume it is part of a complete C++ program.

- ☐ A) run time error
- ☐ B) nothing
- ☐ C) real
- ☐ D) syntax error

- ☐ E) none of the provided answers
- ☐ F) long string
- ☐ G) depends on the compiler
- ☐ H) real long name
- ☐ I) really long name

Question 109 of 200

result of code

What is the result of the following statements:

```
char myString[] = "Really long name";
```

```
myString[4] = myString[5] = '\0';
```

```
cout << myString << endl;
```

Assume it is part of a complete C++ program.

- ☐ A) really long name
- ☐ B) noting
- ☐ C) none of the provided answers
- ☐ D) real
- ☐ E) run time error
- ☐ F) real long name
- ☐ G) logical garbage
- ☐ H) depends on the compiler
- ☐ I) syntax error

Question 110 of 200

result of code

What is the result of the following statements:

```
char myNameCh[] = "Delta";
```

```
char yourNameCh[] = "Bob";
```

```
yourNameCh[0] = myNameCh;
```

```
myNameCh = "Professor";
```

```
cout << yourName;
```

Assume it is part of a complete C++ program.

- ☐ A) run time error
- ☐ B) depends on the compiler
- ☐ C) syntax error
- ☐ D) Professor
- ☐ E) logical garbage
- ☐ F) Delta
- ☐ G) none of the provided answers

☐ H) Bob

Question 111 of 200

result of code

What is the result of the following statements:

```
void setArray(int a[], int size) {  
    a[1] = 5;  
}
```

```
int main() {  
    double a[9];  
    setArray(a, 9);  
    cout << a[1] << endl;  
    system("pause");  
    return 0;  
}
```

Assume it is part of a complete C++ program.

- ☐ A) 9
- ☐ B) syntax error
- ☐ C) run time error
- ☐ D) depends on the compiler
- ☐ E) 1
- ☐ F) 5
- ☐ G) none of the provided answers

Question 112 of 200

result of code

What will be the result of the following code

```
int x = 9 / 0;
```

if typed in a complete C++ program.

- ☐ A) none of the provided answers
- ☐ B) the value in variable x will remain unchanged
- ☐ C) 0 will be stored in variable x
- ☐ D) the value in variable x will have "logical garbage" - random 0s and 1s
- ☐ E) logical error
- ☐ F) depends on the compiler
- ☐ G) run time error
- ☐ H) syntax error
- ☐ I) 9 will be stored in variable x

Question 113 of 200

result of code

What will be the result of the following code

```
int x = 17 / 2.0;
```

if typed in a complete C++ program.

- ☐ A) 0 will be stored in variable x
- ☐ B) 8.5 will be stored in variable x
- ☐ C) depends on the compiler
- ☐ D) logical error
- ☐ E) 1 will be stored in variable x
- ☐ F) 8 will be stored in variable x
- ☐ G) syntax error
- ☐ H) none of the above
- ☐ I) variable x will have logical garbage - random 0s and 1s
- ☐ J) run time error

Question 114 of 200

result of code

What will be the result of the following code

```
int x = 0.9;
```

```
cout << 99 / x;
```

if typed in a complete C++ program.

- ☐ A) run time error
- ☐ B) logical error
- ☐ C) syntax error
- ☐ D) logical garbage will print on the monitor
- ☐ E) 10 will print on the monitor
- ☐ F) depends on the compiler
- ☐ G) 9 will print on the monitor
- ☐ H) 11 will print on the monitor
- ☐ I) none of the above
- ☐ J) 0 will print on the monitor

Question 115 of 200

write code

Write an expression (**NOT** a statement) that **finds** the ASCII value of a character ch.

Assume that ch is already declared and assigned a value. You are **NOT** allowed to use any arithmetic operators or use any other variables. You need to write **ONLY** the expression the **finds** the ASCII value. You should **NOT** print it anywhere or store it anywhere!

Question 116 of 200

Theory - Terminology

In C++ it is legal to have **TWO** statements in the same line.

- ☐ A) True
- ☐ B) False

Question 117 of 200

Theory - Terminology

In the following statement

system("pause");
system is ____ . Select ALL that apply.

- ☐ A) object
- ☐ B) keyword
- ☐ C) argument
- ☐ D) function
- ☐ E) reserved word
- ☐ F) variable
- ☐ G) pre-processor directive
- ☐ H) library
- ☐ I) command
- ☐ J) class name

Question 118 of 200

Theory - Terminology

In C++ if you see an identifier named **STATE_TAX**, according to the style rules you can assume that this variable is ____ . Select **ALL** that apply.

- ☐ A) integer
- ☐ B) function name
- ☐ C) keyword
- ☐ D) method name
- ☐ E) number literal
- ☐ F) constant
- ☐ G) double
- ☐ H) object name
- ☐ I) class name
- ☐ J) reserved word

**Question 119 of 200**

Theory - Terminology

In the C++ statement
using namespace std;
std is _____. Select **ALL** that apply.

- ☐ A) method name
- ☐ B) none of the listed options
- ☐ C) library name
- ☐ D) an argument
- ☐ E) function name
- ☐ F) variable name
- ☐ G) object name
- ☐ H) keyword
- ☐ I) reserved word
- ☐ J) constant name

Question 120 of 200

result of code

What is the result of the following statement:
cout << "13 % 1";
Assume it is part of a complete C++ program.

- ☐ A) 13 will print on the monitor
- ☐ B) none of the provided answers
- ☐ C) 1 will print on the monitor
- ☐ D) 0 will print on the monitor
- ☐ E) run time error
- ☐ F) logical error
- ☐ G) depends on the compiler
- ☐ H) logical garbage will print on the monitor
- ☐ I) syntax error

Question 121 of 200

Theory - Terminology

What is **>=** in C++?

- ☐ A) operator
- ☐ B) symbol

- ☐ C) punctuation mark
- ☐ D) has no meaning in C++
- ☐ E) none of the provided answers
- ☐ F) depends on the compiler

Question 122 of 200

Theory - Terminology

Give the **escape sequence** that moves the cursor to the **beginning of the current line**.

Question 123 of 200

Theory - Terminology

Give the **escape sequence** for the **null character**.

Question 124 of 200

Theory - Terminology

When you have more than one **assignment operator** in the same expression, which one evaluated **first**? Ex. $x = y = z = k$. Note there are no parenthesis or other operators.

- ☐ A) the last one
- ☐ B) depends on the compiler - there is no standard order
- ☐ C) The first one

Question 125 of 200

result of code

What will happen if you have the following condition in an if statement in C++?
 $12 < x < 6$

- ☐ A) The condition will always be true
- ☐ B) the condition will always be false - there is no number that is both bigger and 12 and smaller than 6
- ☐ C) syntax error
- ☐ D) run time error
- ☐ E) depends on the compiler - there is no standard
- ☐ F) the condition will be true if x is in the range (6, 12) - both ends **EX**clusive

- ☐ **G)** the condition will be true if x is in the range [6, 12] - both ends **IN**clusive
- ☐ **H)** none of the provided answers

Question 126 of 200

result of code

What will happen if you have the following condition in an if statement in C++?
 $65 < x < 70$

- ☐ **A)** The condition will always be false
- ☐ **B)** the condition will always be true
- ☐ **C)** syntax error
- ☐ **D)** run time error
- ☐ **E)** true if x is in the [65, 70] - both ends of the range are **IN**clusive
- ☐ **F)** true if x is in the (65, 70) range - both ends of the range are **EX**clusive
- ☐ **G)** true if x is in the [65, 70) range - beginning of range is **IN**clusive end is **EX**clusive
- ☐ **H)** true if x is in the (65, 70] range - beginning of range is **EX**clusive end is **IN**clusive

Question 127 of 200

result of code

What is the result of the following statements:

```
char ch = 'K';  
if ( ch = 65+3)  
    cout << 'T';  
else  
    cout << "F";  
cout << ch;
```

Assume it is part of a complete C++ program.

- ☐ **A)** FM
- ☐ **B)** FD
- ☐ **C)** run time error
- ☐ **D)** TD
- ☐ **E)** FK
- ☐ **F)** FN
- ☐ **G)** depends on the compiler
- ☐ **H)** TC
- ☐ **I)** syntax error
- ☐ **J)** TK

Question 128 of 200

result of code

What is the result of the following statements:

```
char ch = 'K';  
if ( ch == 65+3)  
    cout << 'T';  
else  
    cout << "F";  
cout << ch;
```

Assume it is part of a complete C++ program.

- ☐ A) TK
- ☐ B) run time error
- ☐ C) FD
- ☐ D) TC
- ☐ E) FN
- ☐ F) TD
- ☐ G) FK
- ☐ H) FM
- ☐ I) depends on the compiler
- ☐ J) syntax error

Question 129 of 200

result of code

What is the result of the following statements:

```
int x = 27.7;  
if ( x = 13.7)  
    cout << 6.41;  
else  
    cout << 23.77;  
cout << x;
```

Assume it is part of a complete C++ program.

- ☐ A) 6.4113
- ☐ B) 6.4123.77x
- ☐ C) run time error
- ☐ D) depends on the compiler
- ☐ E) syntax error
- ☐ F) 23.77x
- ☐ G) none of the listed options
- ☐ H) 23.7727.7
- ☐ I) 6.41x
- ☐ J) 6.4127.7

Question 130 of 200

result of code

What is the result of the following statements:

```
int x = 27.7;
```

```
if ( 27.7 = x)
```

```
    cout << 6.41;
```

```
else
```

```
    cout << 23.77;
```

```
cout << x;
```

Assume it is part of a complete C++ program.

- ☐ A) 13.723.77
- ☐ B) 23.77x
- ☐ C) depends on the compiler
- ☐ D) syntax error
- ☐ E) 6.4123.77x
- ☐ F) 6.4113
- ☐ G) 6.4123.77
- ☐ H) run time error
- ☐ I) 23.7727.7
- ☐ J) none of the listed options

Question 131 of 200

result of code

What is the result of the following statements:

```
int x = 27.7;
```

```
if ( x = 27.7)
```

```
    cout << 6.41;
```

```
else
```

```
    cout << 23.77;
```

```
cout << x;
```

Assume it is part of a complete C++ program.

- ☐ A) syntax error
- ☐ B) none of the listed options
- ☐ C) 6.4113
- ☐ D) run time error
- ☐ E) 6.41x
- ☐ F) 13.723.77
- ☐ G) 23.7727.7
- ☐ H) 6.4127.7
- ☐ I) 23.77x
- ☐ J) 6.4123.77x

Question 132 of 200

result of code

What is the result of the following statements:

```
int x = 0.7;  
if ( x = 0.7)  
    cout << 6.41;  
else  
    cout << 23.77;  
cout << x;
```

Assume it is part of a complete C++ program.

- ☐ A) 6.41x
- ☐ B) none of the listed options
- ☐ C) 23.770
- ☐ D) 23.770.7
- ☐ E) 6.410.7
- ☐ F) syntax error
- ☐ G) run time error
- ☐ H) 23.77
- ☐ I) 23.77x
- ☐ J) depends on the compiler

Question 133 of 200

result of code

What is the result of the following statements:

```
int x = 44.7;  
if ( x = 44.7)  
    cout << 6.41;  
else  
    cout << 23.77;  
cout << x;
```

Assume it is part of a complete C++ program.

- ☐ A) syntax error
- ☐ B) 23.7744.7
- ☐ C) 6.4123.7744.7
- ☐ D) run time error
- ☐ E) none of the listed options
- ☐ F) 6.41x
- ☐ G) depends on the compiler
- ☐ H) 6.4144
- ☐ I) 6.4144.7
- ☐ J) 23.7744

Question 134 of 200

result of code

What is the result of the following statements:

```
char ch = A;
```

```
if ( ch == 65)
```

```
    cout << 6.41;
```

```
else
```

```
    cout << 23.77;
```

```
cout << ch;
```

Assume it is part of a complete C++ program.

- ☐ A) 6.4165
- ☐ B) 6.41A
- ☐ C) syntax error
- ☐ D) none of the listed options
- ☐ E) 23.7765
- ☐ F) depends on the compiler
- ☐ G) run time error
- ☐ H) 6.4123.77A
- ☐ I) 23.77A
- ☐ J) 6.41ch

Question 135 of 200

result of code

What is the result of the following statements:

```
char ch = "A";
```

```
if ( ch == 65)
```

```
    cout << 6.41;
```

```
else
```

```
    cout << 23.77;
```

```
cout << ch;
```

Assume it is part of a complete C++ program.

- ☐ A) none of the listed options
- ☐ B) 23.7765
- ☐ C) 6.4165
- ☐ D) run time error
- ☐ E) 6.41A
- ☐ F) 23.77A
- ☐ G) syntax error
- ☐ H) 6.4123.77A
- ☐ I) 6.41ch
- ☐ J) depends on the compiler

Question 136 of 200

result of code

What is the result of the following statements:

```
char ch = 'A';
```

```
if ( ch == 65)
```

```
    cout << 6.41;
```

```
else
```

```
    cout << 23.77;
```

```
cout << ch;
```

Assume it is part of a complete C++ program.

- ☐ A) 23.77A
- ☐ B) none of the listed options
- ☐ C) 6.4165
- ☐ D) depends on the compiler
- ☐ E) 6.4123.77A
- ☐ F) 6.41A
- ☐ G) syntax error
- ☐ H) 23.7765
- ☐ I) 6.41ch
- ☐ J) run time error

Question 137 of 200

result of code

What is the result of the following statements:

```
int x = 44.7;
```

```
if ( x == 44.7)
```

```
    cout << 6.41;
```

```
else
```

```
    cout << 23.77;
```

```
cout << x;
```

Assume it is part of a complete C++ program.

- ☐ A) 6.4123.7744.7
- ☐ B) run time error
- ☐ C) none of the listed options
- ☐ D) 23.7744
- ☐ E) depends on the compiler
- ☐ F) 23.7744.7
- ☐ G) syntax error
- ☐ H) 6.4144.7
- ☐ I) 6.4144
- ☐ J) 6.41x

Question 138 of 200

write code

Fill in the missing code:

```
double x;  
cout << "Please give the number and I will find its absolute value: ";  
cin >> x;  
cout << ( _____ ) << " is the absolute value of " << x << endl;
```

You are **NOT** allowed to use the abs function.

Note that this is a fill in the blank question. You are **not** allowed to make any changes to the existing code. Type **ONLY** the missing part so the code will do what it promises **without any logical, syntax or run time errors**. Be careful with the formatting!

Question 139 of 200

write code

Fill in the missing code:

```
int x;  
cout << "Please give me a number and I will tell you if it is even or odd: ";  
cin >> x;  
cout << x << " is " << ( _____ ) << endl;
```

Note that this is a fill in the blank question. You are **not** allowed to make any changes to the existing code. Type **ONLY** the missing part so the code will do what it promises **without any logical, syntax or run time errors**. Be careful with the formatting!

Question 140 of 200

result of code

What is the result of the following statements:

```
double x = 44.7;  
if ( x = 44.7 )  
    cout << 6.41;  
else  
    cout << 23.77;  
cout << x;
```

Assume it is part of a complete C++ program.

- ☐ A) 6.4144
- ☐ B) run time error
- ☐ C) depends on the compiler
- ☐ D) none of the listed options
- ☐ E) syntax error

- ☐ F) 6.4144.7
- ☐ G) 6.41x
- ☐ H) 6.4123.7744.7
- ☐ I) 23.7744.7
- ☐ J) 23.7744

Question 141 of 200

result of code

In the following code is the condition true or false?

```
double x = 0.7;  
if ( x = 0.75)  
    cout << 6.41;  
else  
    cout << 23.77;  
cout << x;  
Assume it is part of a complete C++ program.
```

- ☐ A) NA because it is a syntax error doubles and bools are not compatible types
- ☐ B) FALSE
- ☐ C) none of the provided answers
- ☐ D) TRUE

Question 142 of 200

Theory - Terminology

In C++ you can have **two** statements in the same line.

- ☐ A) True
- ☐ B) False

Question 143 of 200

Theory - Terminology

In C++ you can have one statement in **TWO** lines.

- ☐ A) True
- ☐ B) False

Question 144 of 200

result of code

What is the result of the following statements:

```
int x = 27;  
cout << (x % 2 ? 'e' : "o");
```

Assume it is part of a complete C++ program.

- ☐ A) logical error it will print e but 27 is odd
- ☐ B) run time error
- ☐ C) syntax error
- ☐ D) it will print nothing because there is no comparison operator
- ☐ E) depends on the compiler
- ☐ F) oe
- ☐ G) none of the above provided answers
- ☐ H) eo
- ☐ I) it will print o because x is odd

Question 145 of 200

result of code

What is the result of the following statements:
int x = 27;
cout << (x % 2 == 0 ? "even" : "odd");
Assume it is part of a complete C++ program.

- ☐ A) syntax error
- ☐ B) prints odd
- ☐ C) none of the provided answers
- ☐ D) run time error
- ☐ E) logical error - prints even but x is odd
- ☐ F) prints evenodd
- ☐ G) depends on the compiler

Question 146 of 200

result of code

What is the result of the following statements:
int x = 27;
cout << (x % 2 == 1 ? "even" : "odd");
Assume it is part of a complete C++ program.

- ☐ A) logical error - prints even but 27 is odd
- ☐ B) syntax error
- ☐ C) none of the provided answers
- ☐ D) prints even
- ☐ E) even
- ☐ F) odd
- ☐ G) evenodd
- ☐ H) depends on the compiler
- ☐ I) run time error

**Question 147 of 200**

result of code

What is the result of the following statements:

```
int x = 27;
```

```
cout << (x % 2 == 1 ? "even" : "odd");
```

Assume it is part of a complete C++ program.

- ☐ A) logical error - prints even but 27 is odd
- ☐ B) prints odd
- ☐ C) depends on the compiler
- ☐ D) evenodd
- ☐ E) syntax error
- ☐ F) none of the provided answers
- ☐ G) run time error

Question 148 of 200

result of code

What is the result of the following statements:

```
int x = 27.9;
```

```
cout << (x % 2 == 1 ? "even" : "odd");
```

Assume it is part of a complete C++ program.

- ☐ A) syntax error - you can't have % of 27.9
- ☐ B) none of the provided answers
- ☐ C) depends on the compiler
- ☐ D) syntax error - you can not take the modulo of a double
- ☐ E) evenodd
- ☐ F) syntax error - a double can not be assigned to an integer
- ☐ G) odd
- ☐ H) logical error - prints even but 27 is odd
- ☐ I) run time error - you can't have % of 27.9

Question 149 of 200

result of code

What is the result of the following statements:

```
int x = 27;
```

```
cout << (x % 2 ? "even" : "odd");
```

Assume it is part of a complete C++ program.

- ☐ A) evenodd

- ☐ B) logical error - prints even but 27 is odd
- ☐ C) syntax error
- ☐ D) prints nothing
- ☐ E) depends on the compiler
- ☐ F) none of the provided answers
- ☐ G) prints odd
- ☐ H) run time error

Question 150 of 200

result of code

What is the result of the following statements:

```
int x = 28;  
cout << (x % 2 ? "even" : "odd");  
Assume it is part of a complete C++ program.
```

- ☐ A) logical error - prints odd but 28 is even
- ☐ B) run time error
- ☐ C) none of the provided answers
- ☐ D) prints even
- ☐ E) evenodd
- ☐ F) prints nothing
- ☐ G) depends on the compiler
- ☐ H) syntax error

Question 151 of 200

result of code

What is the result of the following statements:

```
int x = 28;  
cout << (x % 2 ? "odd" : "even");  
Assume it is part of a complete C++ program.
```

- ☐ A) logical error - prints odd but 28 is even
- ☐ B) depends on the compiler
- ☐ C) oddeven
- ☐ D) nothing
- ☐ E) syntax error
- ☐ F) run time error
- ☐ G) even

Question 152 of 200

result of code

What is the result of the following statements:

```
double x = 28;
```

```
cout << (x % 2 ? "odd" : "even");
```

Assume it is part of a complete C++ program.

- ☐ A) prints nothing
- ☐ B) syntax error
- ☐ C) depends on the compiler
- ☐ D) oddeven
- ☐ E) even
- ☐ F) run time error
- ☐ G) logical error - prints odd but 28 is even

Question 153 of 200

result of code

What is the result of the following statements:

```
int x = 58;
```

```
cout << ((x = x % 2) ? 3 : 4);
```

Assume it is part of a complete C++ program.

- ☐ A) syntax error
- ☐ B) nothing
- ☐ C) 3
- ☐ D) 4
- ☐ E) 34
- ☐ F) depends on the compiler
- ☐ G) run time error

Question 154 of 200

result of code

What is the result of the following statements:

```
int x = 58
```

```
cout << ((x = x % 2) ? x+5 : x+6);
```

Assume it is part of a complete C++ program.

- ☐ A) none of the provided answers
- ☐ B) run time error
- ☐ C) 6
- ☐ D) depends on the compiler
- ☐ E) 5
- ☐ F) 63

- ☐ G) 56
- ☐ H) 64
- ☐ I) nothing
- ☐ J) syntax error

Question 155 of 200

result of code

What is the result of the following statements:

```
int x = 59;
```

```
cout << ( (x += x % 2) ? x+10 : x+20);
```

Assume it is part of a complete C++ program.

- ☐ A) syntax error
- ☐ B) 10
- ☐ C) 70
- ☐ D) 80
- ☐ E) run time error
- ☐ F) 20
- ☐ G) depends on the compiler
- ☐ H) non of the provided answers
- ☐ I) 79
- ☐ J) 69

Question 156 of 200

Theory - Terminology

A(n) _____ is a diagram that graphically illustrate the "logic" and the order code is to be executed in a program.

Question 157 of 200

Theory - Terminology

A(n) _____ is a diagram that graphically illustrate the break down of tasks and sub-tasks (top down design) in a program.

Question 158 of 200

Theory - Terminology

If a function has 6 mandatory arguments and 4 optional arguments, how many signatures are created?

- ☐ A) can not be calculated with the information provided
- ☐ B) Depends on the compiler
- ☐ C) 5
- ☐ D) 10
- ☐ E) 6
- ☐ F) 4
- ☐ G) The magic 8 ball will tell you

Question 159 of 200

result of code

What is the result of the following statements:

```
int SIZE = 3;
```

```
char a[SIZE];
```

Assume it is part of a complete C++ program.

- ☐ A) syntax error
- ☐ B) an array of 4 elements will be declared, each one an integer
- ☐ C) none of the provided answers
- ☐ D) an array of 4 elements will be declared, each one a character
- ☐ E) depends on the compiler
- ☐ F) can not tell with the information provided
- ☐ G) an array of 3 elements will be declared, each one an integer
- ☐ H) an array of 3 elements will be declared, each one a character

Question 160 of 200

Theory - Terminology

How many bytes are allocated in the following statement?

```
char a[9];
```

- ☐ A) zero because that is a syntax error
- ☐ B) 9
- ☐ C) 7
- ☐ D) can't tell with the information provided
- ☐ E) 8

Question 161 of 200

result of code

What is the result of the following statements:

```
void fun1(const int a[], int size, double val) {  
    for (int i = 0; i < size; i++)  
        a[i] = val;  
}  
  
int main(){  
    int a[20];  
    fun1(a, 15, 6.9);  
    return 0;  
}
```

- ☐ A) depends on the compiler
- ☐ B) creates an array for 20 elements and initializes all of them to 6
- ☐ C) creates an array for 20 elements and initializes the first 15 of them to 6.9
- ☐ D) creates an array for 15 elements and initializes all of them to 6.9
- ☐ E) none of the provided answers
- ☐ F) syntax error
- ☐ G) creates an array for 20 elements and initializes the first 15 of them to 6
- ☐ H) run time error
- ☐ I) creates an array for 15 elements and initializes all of them to 6
- ☐ J) creates an array for 20 elements and initializes all of them to 6.9

Question 162 of 200

result of code

What is the result of the following statements:

```
void fun1(int b[], int s, double val) {  
    for (int i = 0; i < size; i++)  
        a[i] = val;  
}  
  
int main(){  
    int a[15];  
    fun1(a, 10, 12.8);  
    return 0;  
}
```

If part of a complete C++ program.

- ☐ A) run time error
- ☐ B) creates an array for 10 elements and initializes all of them to 12.8
- ☐ C) creates an array for 15 elements and initializes the first 10 of them to 12
- ☐ D) creates an array for 15 elements and initializes all of them to 12.8
- ☐ E) depends on the compiler
- ☐ F) creates an array for 15 elements and initializes all of them to 12
- ☐ G) creates an array for 15 elements and initializes the first 10 of them to 12.8

- ☐ H) none of the provided answers
- ☐ I) syntax error
- ☐ J) creates an array for 10 elements and initializes all of them to 12

Question 163 of 200

result of code

What is the result of the following statements:

```
void f2( int &w) {  
    for (int k = 1; k < w; k++)  
        cout << "Boo";  
}
```

```
int main() {  
    const int VAL = 7;  
    f2(VAL);  
    return 0;  
}
```

Assume it is part of a complete C++ program.

- ☐ A) compiles but it prints nothing
- ☐ B) prints "Boo" 7 times
- ☐ C) syntax error
- ☐ D) prints "Boo" 6 times
- ☐ E) run time error
- ☐ F) prints "Boo" once
- ☐ G) depends on the compiler
- ☐ H) none of the provided answers

Question 164 of 200

result of code

What is the result of the following statements:

```
void f2( int &w) {  
    for (int w = 1; w < 4; w++)  
        cout << w+3;  
}
```

```
int main() {  
    int val = 13;  
    f2(val);  
    return 0;  
}
```

Assume it is part of a complete C++ program.

- ☐ A) run time error
- ☐ B) syntax error

- ☐ C) prints 13 three times
- ☐ D) prints 13 four times
- ☐ E) prints 16 four times
- ☐ F) prints 13 thirteen times
- ☐ G) none of the provided answers
- ☐ H) depends on the compiler
- ☐ I) prints 16 three times
- ☐ J) prints 16 thirteen times

Question 165 of 200

result of code

What is the result of the following statements

```
void fun1(int a[], int s, double val) {  
    for (int i = 0; i < size; i++)  
        a[i] = val;  
}
```

```
int main(){  
    int a[15];  
    fun1(a, 10, 12.8);  
    return 0;  
}
```

If part of a complete C++ program.

- ☐ A) creates an array for 10 elements and initializes all of them to 12.8
- ☐ B) creates an array for 10 elements and initializes all of them to 12
- ☐ C) depends on the compiler
- ☐ D) run time error
- ☐ E) none of the provided answers
- ☐ F) creates an array for 15 elements and initializes the first 10 of them to 12.8
- ☐ G) creates an array for 15 elements and initializes the first 10 of them to 12
- ☐ H) creates an array for 15 elements and initializes all of them to 12.8
- ☐ I) creates an array for 15 elements and initializes all of them to 12
- ☐ J) syntax error

Question 166 of 200

result of code

What is the result of the following statements

```
void fun1(int a[], int s, double val) {  
    for (int i = 0; i < s; i++)  
        a[i] = val;  
}
```

```
int main(){  
    int a[15];
```

```
    fun1(a, 10, 12.8);  
    return 0;  
}
```

If part of a complete C++ program.

- ☐ A) run time error
- ☐ B) creates an array for 15 elements and initializes the first 10 of them to 12
- ☐ C) creates an array for 15 elements and initializes the first 10 of them to 12.8
- ☐ D) creates an array for 15 elements and initializes all of them to 12
- ☐ E) creates an array for 15 elements and initializes all of them to 12.8
- ☐ F) none of the provided answers
- ☐ G) syntax error
- ☐ H) creates an array for 10 elements and initializes all of them to 12.8
- ☐ I) creates an array for 10 elements and initializes all of them to 12.8
- ☐ J) creates an array for 10 elements and initializes all of them to 12

Question 167 of 200

write code

Fill in the blank so the code below will work correctly:

```
cout << "The 5th root of " << x << " is: " << _____ ;
```

You may assume that x is declared and initialized.

Write **ONLY** the missing code. Try to pay attention to the spacing.

Question 168 of 200

Generic

What is the result of the following code if it is embedded in a complete C++ program?

```
double x = 4;  
cout << pow(x, 1/2);
```

- ☐ A) 16
- ☐ B) run time error
- ☐ C) 4
- ☐ D) 1
- ☐ E) depends on the compiler
- ☐ F) syntax error
- ☐ G) 2

Question 169 of 200

result of code

What will be the result of the following code if it part of a complete C++ program?

```
const int TAX_RATE = 0.06;  
double price = 100;  
cout << TAX_RATE*price;
```

Question 170 of 200

result of code

What will be the result of the following condition?

$a > b > c$

Assume it is part of a complete program and variables a, b and c are already declared and initialized.

- ☐ A) The condition will **ALWAYS** be **true** if a, b and c are in **ascending** order
- ☐ B) The condition will **ALWAYS** be **true** if c is **less** than 1 no matter what a and b are
- ☐ C) There is no way the condition will be **true** if $a \leq b$
- ☐ D) The condition will **ALWAYS** be **false** no matter what the values of a, b and c are
- ☐ E) The condition will be **true** if c is **less or equal** to 0 no matter what a and b are
- ☐ F) The condition will **ALWAYS** be **true** if c is **less** than 0 no matter what a and b are
- ☐ G) The condition will **ALWAYS** be **true** if a, b and c are in **descending** order
- ☐ H) The condition will **ALWAYS** be **true** if c is **less or equal** to 1 no matter what a and b are
- ☐ I) The condition will **ALWAYS** be **true** if c is **more** than 1
- ☐ J) The condition will always **ALWAYS** be **true** no matter what the values of a, b and c are

Question 171 of 200

result of code

What is the result of the following code if it is part of a complete C++ program?

```
int n = 2, t = '2';  
if ( t == n) n = 5;  
else n == 9;  
cout << t << n;
```

- ☐ A) 25
- ☐ B) 550
- ☐ C) 505
- ☐ D) syntax error
- ☐ E) none of the provided answers

- ☐ F) run time error
- ☐ G) 502
- ☐ H) 22
- ☐ I) 250

Question 172 of 200

write code

Fill in the blank so the code below will work correctly:

```
cout << "The 7th root of " << x << " is: " << _____ ;
```

You may assume that x is declared and initialized.

Write **ONLY** the missing code. Try to pay attention to the spacing.

Question 173 of 200

Theory - Terminology

Which method you need to call **connect** a file stream to a file?

Question 174 of 200

Theory - Terminology

Which method you need to call to **terminate the connection** of a file stream?

Question 175 of 200

Theory - Terminology

How many arguments do you need to pass to the `.close()` method? Write a **NUMBER**.

Question 176 of 200

Theory - Terminology

What is the type of the **argument** the `.open()` method takes?

Question 177 of 200

Theory - Terminology

Which method do you need to call to see if a stream was correctly connected to a file?

Question 178 of 200

Theory - Terminology

What is the **return type** of the fail() method?

Question 179 of 200

Theory - Terminology

Can a stream point to **TWO** different files **at the same time**?

- ☐ A) True
- ☐ B) False

Question 180 of 200

Theory - Terminology

Can you reuse a stream object by connecting it to a different file?

- ☐ A) True
- ☐ B) False

Question 181 of 200

Theory - Terminology

Can you open **the same file** for input **and** output in the same program?

- ☐ A) True
- ☐ B) False

Question 182 of 200

Theory - Terminology

What library do you need to include if you want to use file streams?

Question 183 of 200

Theory - Terminology

You can use the `setw()` stream manipulator with an **output FILE stream**.

- ☐ A) True
- ☐ B) False

Question 184 of 200

Theory - Terminology

Which operator can you use with **INPUT file streams**?

- ☐ A) `>>`
- ☐ B) `<<`
- ☐ C) both `>>` and `<<`
- ☐ D) none of the provided answers

Question 185 of 200

Theory - Terminology

What do you need to have as the **RIGHT (second)** operand on the stream **EXTRACTION** operator? Select ALL that apply.

- ☐ A) an output stream object
- ☐ B) any expression
- ☐ C) a literal
- ☐ D) an input stream object
- ☐ E) Any modifiable memory location
- ☐ F) a function call
- ☐ G) a condition

Question 186 of 200

Theory - Terminology

What qualifies to be the **LEFT** operand of the **stream insertion** operator? Select ALL that apply.

- ☐ A) a string

- ☐ B) a variable
- ☐ C) a literal
- ☐ D) an arithmetic expression
- ☐ E) a function call
- ☐ F) any output stream object

Question 187 of 200

Theory - Terminology

Which library do you need to include to use the **fixed** stream manipulator?

Question 188 of 200

Theory - Terminology

Is there a **center** stream manipulator?

- ☐ A) True
- ☐ B) False

Question 189 of 200

Theory - Terminology

What qualifies to be the **LEFT** operand of the **assignment** operator? Select ALL that apply.

- ☐ A) a function call
- ☐ B) an output stream
- ☐ C) an arithmetic expression
- ☐ D) a string
- ☐ E) a keyword
- ☐ F) a regular variable
- ☐ G) a literal
- ☐ H) anything you want
- ☐ I) a constant variable
- ☐ J) an input stream

Question 190 of 200

Theory - Terminology

What are the two types of type casting according to the "direction"?

Question 191 of 200

Theory - Terminology

What are the two types of type casting according to who "initiates" it?

Question 192 of 200

Theory - Terminology

What type of type casting happens in this code segment?

```
int x = 3.6;
```

- ☐ A) manual demotion
- ☐ B) automatic demotion
- ☐ C) no typecasting - the operation is illegal in C++
- ☐ D) manual promotion
- ☐ E) automatic promotion

Question 193 of 200

Theory - Terminology

What kind of type casting happens in the following code segment?

```
char ch = "A";
```

- ☐ A) automatic demotion
- ☐ B) manual promotion
- ☐ C) no type casting - the operation is illegal in C++
- ☐ D) manual demotion
- ☐ E) automatic promotion

Question 194 of 200

Theory - Terminology

What kind of type casting happens in the following code?

```
if (x%2) cout << "Boo";
```

- ☐ A) automatic promotion
- ☐ B) manual promotion
- ☐ C) automatic demotion
- ☐ D) manual demotion

- ☐ E) no typecasting - the operation is illegal in C++

Question 195 of 200

Theory - Terminology

Which **category of operators** has priority (higher precedence) in C++, **relational** or **logical**?

- ☐ A) none - you can not have them together in the same expression
- ☐ B) logical
- ☐ C) relational
- ☐ D) none, they evaluate right to left
- ☐ E) none - you have to put parenthesis so they can work together in the same expression
- ☐ F) none, they evaluate left to right

Question 196 of 200

Theory - Terminology

Which **category of operators** has priority (higher precedence) in C++, **relational** or **arithmetic**?

- ☐ A) none - you have to put parenthesis so they can work together in the same expression
- ☐ B) none, they evaluate right to left
- ☐ C) none, they evaluate left to right
- ☐ D) arithmetic
- ☐ E) relational
- ☐ F) none - you can not have them together in the same expression

Question 197 of 200

Theory - Terminology

How many relational operators are there? **Write a number.**

Question 198 of 200

Theory - Terminology

In a flowchart what symbol (shape) represents **decisions** (conditions)?

Question 199 of 200

result of code

What is the result of the following statements:

```
int x = 7.7;  
if ( x > 7)  
    cout << "Big";  
cout << "Number";  
else  
    cout << "Small";  
cout << "Potato";
```

Assume it is part of a complete C++ program.

- ☐ A) run time error
- ☐ B) Big
Number
Potato
- ☐ C) Depends on the compiler
- ☐ D) BigNumber
- ☐ E) BigNumberPotato
- ☐ F) Nothing will print because the code will not compile - Syntax error
- ☐ G) BigPotato
- ☐ H) SmallPotato
- ☐ I) Small
Potato
- ☐ J) Logical error

Question 200 of 200

Theory - Terminology

Can you have two main functions in the same Visual Studio project?

- ☐ A) True
- ☐ B) False

www.classmarker.com