Презентация лабораторной работы №6

Бакулин Никита 1032201747

Цель работы

• Настроить статическую маршрутизацию VLAN в сети.


Задачи

- Добавить в локальную сеть маршрутизатор, провести его первоначальную настройку.
- Настроить статическую маршрутизацию VLAN.

Результаты выполнения

• Добавили в локальную сеть маршрутизатор, провести его первоначальную настройку.

Router>enable



```
Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router (config) #hostname msk-donskaya-nabakulin-gw-1
msk-donskaya-nabakulin-gw-1(config)#line vty 0 4
msk-donskaya-nabakulin-gw-1 (config-line) #password cisco
msk-donskaya-nabakulin-gw-1(config-line)#login
msk-donskaya-nabakulin-gw-1(config-line)#line console 0
msk-donskaya-nabakulin-gw-1(config-line) #password cisco
msk-donskaya-nabakulin-gw-1(config-line)#login
msk-donskaya-nabakulin-gw-1(config-line) #enable secret cisco
msk-donskaya-nabakulin-gw-1 (config) #service password-encryption
msk-donskaya-nabakulin-gw-1(config) #username admin privilege 1 secret cisco
msk-donskaya-nabakulin-gw-1(config)#ip domain-name donskaya.rudn.edu
msk-donskaya-nabakulin-gw-1(config)#crypto key generate rsa
The name for the keys will be: msk-donskaya-nabakulin-gw-1.donskaya.rudn.edu
Choose the size of the key modulus in the range of 360 to 2048 for your
  General Purpose Keys. Choosing a key modulus greater than 512 may take
  a few minutes.
How many bits in the modulus [512]:
% Generating 512 bit RSA keys, keys will be non-exportable...[OK]
msk-donskaya-nabakulin-gw-1(config)#line vty 0 4
*Mar 1 0:8:59.581: RSA key size needs to be at least 768 bits for ssh version 2
*Mar 1 0:8:59.581: %SSH-5-ENABLED: SSH 1.5 has been enabled
msk-donskaya-nabakulin-gw-1(config-line)#transport input ssh
```

Результаты выполнения

• Настроить статическую маршрутизацию VLAN.

```
msk-donskaya-nabakulin-gw-1#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
msk-donskaya-nabakulin-gw-1(config)#interface f0/0
msk-donskaya-nabakulin-gw-1(config-if)#no shutdown
msk-donskava-nabakulin-gw-1(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up
msk-donskaya-nabakulin-gw-1(config-if)#interface f0/0.2
msk-donskaya-nabakulin-gw-1(config-subif)#
%LINK-5-CHANGED: Interface FastEthernet0/0.2, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0.2, changed state to up
msk-donskaya-nabakulin-gw-1(config-subif)#encapsulation dot10 2
msk-donskaya-nabakulin-gw-1(config-subif)#ip address 10.128.1.1 255.255.255.0
msk-donskaya-nabakulin-gw-1(config-subif)#description management
msk-donskaya-nabakulin-gw-1(config-subif)#interface f0/0.3
msk-donskaya-nabakulin-gw-1(config-subif)#
%LINK-5-CHANGED: Interface FastEthernet0/0.3, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0.3, changed state to up
msk-donskaya-nabakulin-gw-1(config-subif)#encapsulation dot1Q 3
msk-donskaya-nabakulin-gw-1(config-subif)#ip address 10.128.0.1 255.255.255.0
msk-donskaya-nabakulin-gw-1(config-subif)#description servers
msk-donskaya-nabakulin-gw-1(config-subif)#interface f0/0.101
msk-donskaya-nabakulin-gw-1(config-subif)#
%LINK-5-CHANGED: Interface FastEthernet0/0.101, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0.101, changed state to up
msk-donskaya-nabakulin-gw-1(config-subif)#encapsulation dot1Q 101
msk-donskaya-nabakulin-gw-1(config-subif)#ip address 10.128.3.1 255.255.255.0
msk-donskava-nabakulin-gw-1(config-subif)#description dk
```

```
Cisco Packet Tracer PC Command Line 1.0
C:\>ping 10.128.3.202
Pinging 10.128.3.202 with 32 bytes of data:
Reply from 10.128.3.202: bytes=32 time=1ms TTL=128
Reply from 10.128.3.202: bytes=32 time<1ms TTL=128
Reply from 10.128.3.202: bytes=32 time<1ms TTL=128
Ping statistics for 10.128.3.202:
    Packets: Sent = 3, Received = 3, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 1ms, Average = 0ms
Control-C
C:\>ping 10.128.4.201
Pinging 10.128.4.201 with 32 bytes of data:
Request timed out.
Reply from 10.128.4.201: bytes=32 time<1ms TTL=127
Reply from 10.128.4.201: bytes=32 time<1ms TTL=127
Ping statistics for 10.128.4.201:
    Packets: Sent = 3, Received = 2, Lost = 1 (34% loss),
Approximate round trip times in milli-seconds:
   Minimum = 0ms, Maximum = 0ms, Average = 0ms
Control-C
```

Рис. 3

Результаты выполнения

• Настроить статическую маршрутизацию VLAN.

80	Simulation Panel		
Event List			
Vis.	Time(sec)	Last Device	At Device
	0.000		dk-nabakulin-donskaya-1
	0.001	dk-nabakulin-donskaya-1	msk-donskaya-nabakulin-sw-4
	0.002	msk-donskaya-nabakulin-sw-4	msk-donskaya-nabakulin-sw-1
	0.003	msk-donskaya-nabakulin-sw-1	msk-pavlovskaya-nabakulin-sw-1
	0.004	msk-pavlovskaya-nabakulin-sw-1	dk-nabakulin-pavlovskaya-1
	0.005	dk-nabakulin-pavlovskaya-1	msk-pavlovskaya-nabakulin-sw-1
	0.006	msk-pavlovskaya-nabakulin-sw-1	msk-donskaya-nabakulin-sw-1
	0.007	msk-donskaya-nabakulin-sw-1	msk-donskaya-nabakulin-sw-4
(9)	0.008	msk-donskaya-nabakulin-sw-4	dk-nabakulin-donskaya-1

80		Simulation Pane	Simulation Panel	
Event List				
Vis.	Time(sec)	Last Device	At Device	
	0.000		dk-nabakulin-donskaya-1	
	0.001	dk-nabakulin-donskaya-1	msk-donskaya-nabakulin-sw-4	
	0.002	msk-donskaya-nabakulin-sw-4	msk-donskaya-nabakulin-sw-1	
	0.003	msk-donskaya-nabakulin-sw-1	msk-donskaya-nabakulin-gw-1	
	0.004	msk-donskaya-nabakulin-gw-1	msk-donskaya-nabakulin-sw-1	
	0.005	msk-donskaya-nabakulin-sw-1	msk-donskaya-nabakulin-sw-4	
	0.006	msk-donskaya-nabakulin-sw-4	other-nabakulin-donskaya-1	
	0.007	other-nabakulin-donskaya-1	msk-donskaya-nabakulin-sw-4	
	0.008	msk-donskaya-nabakulin-sw-4	msk-donskaya-nabakulin-sw-1	
	0.009	msk-donskaya-nabakulin-sw-1	msk-donskaya-nabakulin-gw-1	
	0.010	msk-donskaya-nabakulin-gw-1	msk-donskaya-nabakulin-sw-1	
	0.011	msk-donskaya-nabakulin-sw-1	msk-donskaya-nabakulin-sw-4	
(9)	0.012	msk-donskaya-nabakulin-sw-4	dk-nabakulin-donskaya-1	

Рис. 5

Рис. 6




Рис. 7