

JPL Plugin 3.*

April 2021

JPL Plugin enables Panther developers to create and update Panthers' JPL source code within the Eclipse IDE.

In addition to creating Panther Projects, Panther Libraries and JPL files, the plugin also validates JPL syntax. The Content Assist feature enables the selection and insertion of existing JPL code elements to complete partially entered JPL code.

This document outlines features of the JPL Plugin

Features

- Create Panther Projects
- Create Panther Libraries
- * Import Panther Libraries
- * Export Panther Libraries
- Create JPL files
- JPL syntax validated for correctness
- Converts binary screens, reports and menus to ASCII
- * Search and Compare files
- * Content assist after "->", i.e. @widget("screen1")->title="Login Screen"
- Content assist after "_", i.e. " sm_" or " dm_"
- Hyperlinking for smart switching between call and procs
- Source Code Control Support

Software Requirements:

- Eclipse IDE (Neon/Oxygen/Release 2020-06 or any latest version):
 To install this plugin you must install Eclipse onto your system. You may download it from http://www.eclipse.org/downloads/eclipse-packages/
- 2. A suggested Eclipse Package is Eclipse IDE for Java Developers. The package should contain tools for JAVA EE and Web applications.

Note: - if you don't know which Eclipse version to select, just download Neon 3 from below link. https://www.eclipse.org/downloads/packages/release/neon/3

Installation Instructions:

Follow the step-by-step instructions to install the plugin.

Install JPL Editor Plugin

- 1. Download JPL Editor Plugin JPL Plugins.zip from GitHub https://github.com/ProlificsPanther/JPLPlugin/releases
- 2. Run eclipse.exe and create a workspace.
- 3. Once your workspace opens, go to the **Help** menu and select "**Install New Software**".




Fig 1




Fig 2

- 4. Click the Add button and choose Archive then Browse to the zip folder i.e. JPL Editor Plugin. Click Ok. [Fig 2]
- 5. Unselect 'Group items by category' in the Install window and select the check box 'JPL Plugin 3.*. Click Next. [Fig 3]




Fig 3

- 6. Choose the JPL Plugin 3.* then Press Next.
- 7. Next choose "I accept the terms of the license ..." radio button. Click Finish. You may ignore the Security Warning.
- 8. If you encounter any errors, redo Step 2 but this time choose Help->Install New Software and uncheck "Contact all update sites during install to find required software".
- 9. Restart Eclipse. The installation of JPL Editor Plugin is now complete. You may verify this in Eclipse's installation detail. You will see JPL Plugin 3.* appear in the list. Now, the very first thing to do is to create a new Panther Project.

Create a Panther Project

1. Please make sure SMBASE is set in your environment. It must point to the location of your Panther installation

SMBASE=C:\Prolifics\Panther553 (Windows)
SMBASE=/usr/develop/prolifics/panther553 (Linux)

- 2. From the Eclipse menu, click File-> New->Other->Panther -> Create Panther Project. [Fig 4]
- 3. Enter a Project name. For example "CurrDev2016" then press Finish.
- 4. If Eclipse requests that you add "Xtext nature" to your project, please click Yes.





Fig 4

Import a Panther Library

- 1. Your Panther library can contain screens, jpl, menus, reports, html, JavaScript, Java files etc. Right click on your newly created Panther project and select import from the context menu. [Fig 5]
- 2. Select Import Panther Library from the import wizard.[Fig 6] .Make sure your Panther library contains screens or jpl etc.
- 3. Click on Panther Library and then click on "Next".
- 4. Browse to your Panther library e.g. test.lib.
- 5. Click on "Finish".







Fig 5 Fig 6

6. All binary files are organized the <bin> folder and ASCII files are saved in the <src> folder [Fig 7]



Create a Panther Library

- 1. Right click on Project -> New -> Other -> Panther -> Create Panther Library. [Fig 8]
- It contains <src> and <bin> directories and one library.xml. You can change the
 extension of generated binaries by adding jpl/bin in the <jpl-binary-filename-extension>
 tag [Fig 9]




Fig 9

Create a New JPL File

- 1. Right-mouse click on the <src> folder in which you would like to create a jpl file in. Choose New -> Other -> Panther -> Create JPL File.[Fig 10]
- 2. The filename MUST have a ".jpl extension, then press Finish.
- 3. When making an update in any ASCII file, once you save your changes, the file is compiled to binary and stored in the <bi>bin> folder.




Fig 10

Sample Screen after installing plugin:

```
File Edit Navigate Search Project Run Window Help
✓ Panther Project Navigator №
                                                      😑 😘 🖁 📟 🔲 🗾 sp≤0079.jpl 💢
                                                                                                                                                                   WHEN LENGTH(zip_cd) > 9 AND zip_cd[6,6] = "-"

THEN zip_cd[1,5] || zip_cd[7,10]

WHEN LENGTH(zip_cd) > 9 AND zip_cd[1,3] IN("085","086")

AND st = "AZ"
⊿ 🧭 plugin test
                                                                                                                    32 //
33 //
34 //
35 //
36 //
37 //
38 //
40 //
41 //
42 //
43 //
45
    ⊿ ြ bin
             bin

bch1134,jpl

bch1134,jpl

bch1134,pjpl

bch1135,jpl

bch1135,pjpl

bch1136,pjpl

bch1136,pjpl

bch1136,pjpl

bch1136,pjpl

bch1136,pjpl

bch1136,pjpl

bch1140,pjpl

bch1140,pjpl

bch1140,pjpl

bch1140,pjpl

bch1140,pjpl

bch1140,pjpl
                                                                                                                                                                   THEN zip_cd(2,10)
WHEN LENGTH(zip_cd) > 9
THEN zip_cd(1,5)
ELSE TRIM(zip_cd)
g0079_zip
                                                                                                                                                  FROM address
                                                                                                                                         WHERE addr ser_nbr = :+g0079 addr_ser
DBMS WITH CURSOR g0079_c01 EXECUTE
DBMS CLOSE CURSOR g0079_c01
                                                                                                                                     if tmp_addr_ser != ""
                                                                                                                      469
             s bch140p.jpl
bch2522.jpl
bps0002b.jpl
bps015.jpl
bps141x.jpl
bps141x.jpl
bps141x.jpl
bps321tax.jpl
sps90078d.jpl
sps90078.jpl
sps90078b.jpl
                                                                                                                                           #If the address line 1 is too long, it must be reformatted or truncated
                                                                                                                                           call g0079_formatAddr(g0079_addr1, g0079_addr2)
receive bundle "g0079_formatAddr_bundle" data tmp_new_addr1,
tmp_new_addr2
                                                                                                                      518
                                                                                                                      52
53
54
55
56
57
58
                                                                                                                                           #Determine the formatted address and the 2-digit countr code as follows
                                                                                                                                           if g0079_st == "A2"
    tmp_country_cd = "US"
else if @length(g0079_country) == 2
             sps0078ix.jpl
sps0078j.jpl
sps0078k.jpl
sps0079.jpl
                                                                                                                                                 tmp_country_cd = g0079_country
                                                                                                                      62
63⊖
                                                                                                                                            else if g0079_st != ""
          ➢ src
☑ library.xml
                                                                                                                      64 //
                                                                                                                                                    DBMS DECLARE CURSOR g0079_c02 FOR
                                                                                                                                                         SELECT edit_cd_ind_1
                                                                                                                                                                                                            tmp_edit_ind1
    ▷ 🗁 test123.lib
                                                                                                                  ■ Console ⋈
                                                                                                                 JPL Console
```

Fig 11

Export a Panther Library

- 1. Right click on the Panther project library, for example Shazam.lib. [Fig 11]. Select export from the context menu.
- 2. Select Export Panther Library.
- 3. Then click on "Panther Library" and click on "Next".
- 4. Browse the destination directory. This is where you will export your Panther library to.
- 5. Click on "Finish" button.




Fig 12

NOTE: Due to a known defect, when exporting the library you must select both <src> and <bin> folders to be exported, or else the library file is not created. However, only files in the <bin> folder are ever included within the exported library, which is the intended behavior.

You may also add new files directly to the <bin> folder that should be added to the exported library.

YouTube Reference:

1. Installation:

https://www.youtube.com/watch?v=ymqthkjxJlc&t=41s&ab_channel=ProlificsPanther

2. JPL Plugin 3.2:

https://www.youtube.com/watch?v=ALmpeBqZTeQ&ab_channel=ProlificsPanther

Uninstalling the Plugin

- 1. If you need to remove an old JPL Plugin, uninstall it using Help->About Eclipse.
- 2. Click on Installation Details and select the "JPL Plugin Editor", press uninstall. Confirm that you would like to uninstall it. Then Restart Eclipse.