

Exercise 3.

```
1. fun Calculation (x, y, z: integer) return value: integer
2.   var i, j, t: integer
      value = 0
3.   For i = x to y do value = value + i efor
4.   If (value/(x+y)) <= 1 then return z
5.   Else
6.     t = x + ((y - x)/2)
7.     For i = x to y do
8.       For j = (3*x) to (3*y) do
9.         value = value + Minimum(i, j)
10.      efor
11.   efor
12.   value = value + 4 * Calculation(t, y, value)
13.   return value
14. eif
15. efun
```

Lines 1–2 (Declaration and Initialization):

- The function is defined, and variables are declared with the initial assignment $value = 0$.
- This initialization is an elementary operation with constant time complexity, $O(1)$

Line 3 (For Loop for Summation):

- The loop iterates from $i = x$ to y , summing each value into $value$.
- The number of iterations is roughly $n = y - x + 1$, which gives a cost of $O(n)$.

Line 4 (Conditional Statement):

- The condition $(value/(x+y)) \leq 1$ is evaluated.
- This evaluation takes constant time, $O(1)$.
- If the condition is true, the function immediately returns z , meaning the algorithm stops after the summation loop, resulting in an overall cost of $O(n)$ for this best-case scenario.

Lines 5–15 (Else Block – Recursive Case):

1. Line 6:

- The computation $t = x + ((y - x)/2)$ is an arithmetic operation, which is $O(1)$.

2. Lines 7–11 (Nested Loops):

- **Outer Loop (Line 7):** Iterates from $i = x$ to y , approximately $O(n)$ iterations.
- **Inner Loop (Line 8):** Iterates from $j = 3*x$ to $3*y$. The number of iterations remains $O(n)$.
- **Operation (Line 9):** Within the inner loop, the operation $value = value + Minimum(i, j)$ is assumed to be $O(1)$.
- **Total Cost of Nested Loops:** By applying the **Product Rule**, the cost is $O(n) \times O(n) = O(n^2)$.

3. Line 12 (Recursive Call):

- The algorithm updates $value$ by adding 4 times the result of a recursive call: $Calculation(t, y, value)$.
- **Recursive Parameter Reduction:** The parameter t is computed as $x + ((y - x)/2)$, meaning the new interval $[t, y]$ has size:
$$n' = y - t = y - (x + (y - x)/2) = (y - x) - (y - x)/2 = (y - x)/2 = 2/n$$

- This yields the recurrence relation for the worst-case scenario:

$$T(n) = T(n/2) + O(n^2)$$

4. Line 13:

– Returning the final *value* is an $O(1)$ operation.

The complexity of the algorithm is:

- $O(n)$ in the best case (when the condition on line 4 is satisfied).
- $O(n^2)$ in the worst case (when the recursive block and nested loops are executed).

Here, n represents the size of the interval $[n = y - x]$.

Exercise 7

Explanation:

First, we iterate through every number between 1 and N . For each of those numbers, we check if it's prime and/or perfect.

To check if it's prime, we go from 1 to the square root of the current number (*why the $\text{sqrt}(i)$? Because any number higher than $\text{sqrt}(i)$ must be paired with a smaller factor, therefore being irrelevant to check*) And check if any of those numbers are primes by making the division and checking its result.

To check if it's a perfect number we, first, start with a value of 1, as 1 is always a divisor, and then, we iterate from 2 to the $\text{sqrt}(i)$

Code:

```
1  from math import sqrt
2
3  # Input and validation
4  n = int(input("Enter a number: ")) # Get user input
5  Prime_n = 0 # Counter for prime numbers
6  Perfect_n = 0 # Counter for perfect numbers
7
8  # Ensure the number is positive
9  while n < 0:
10     print("Please enter a positive number")
11     n = int(input("Enter a number: "))
12
13 # Loop from 1 to N
14 for i in range(1, n+1):
15     # ----- Prime Number Check -----
16     is_prime = True # Assume number is prime
17     for num in range(2, int(sqrt(i)) + 1): # Check divisibility up to sqrt(i)
18         if i % num == 0:
19             is_prime = False # Not a prime
20             break # Stop checking further
21     if is_prime and i > 1: # If number is prime, increment count
22         Prime_n += 1
23
24     # ----- Perfect Number Check -----
25     sum_divisors = 1 # 1 is always a divisor (excluding itself)
26     for div in range(2, int(sqrt(i)) + 1): # Check divisibility up to sqrt(i)
27         if i % div == 0:
28             sum_divisors += div # Add divisor
29             if div != i // div: # Check if the paired divisor is not the same as div
30                 sum_divisors += i // div
31     if sum_divisors == i and i != 1: # Check if sum of divisors equals the number
32         Perfect_n += 1
33
34 # Output results
35 print("Number of prime numbers: ", Prime_n)
36 print("Number of perfect numbers: ", Perfect_n)
```

Test case:

Enter a number: 28

Number of prime numbers: 9

Number of perfect numbers: 2

Exercise 9

Explanation:

We initialize the sum to 1, then we check if the current number is 0 in order to exit correctly the function. If not 0, we sub the number to the factorization of the next lower one. At the end we reach 0 and the sum value is returned with the correct value.

Code:

```
1  n = int(input("Enter a number: "))
2
3  def fact_sum(n):
4      sum = 1 #initialize sum to 1
5      if n==0:
6          return sum #if n is 0, return the sum so we don't multiply by 0
7      else:
8          sum=n*fact_sum(n-1) #recursive call to multiply n by the sum of n-
9  1  return sum
10
11 print(fact_sum(n))
```

Test case:

Enter a number: 6

720