

Atlas-7 Espresso Machine · Service Manual

Model: Atlas-7 Dual Boiler (2026 revision C)

Manufacturer: Meridian Coffee Systems, Tacoma WA

1. OPERATING SPECIFICATIONS

The brew boiler operates at a pressure of 9.2 bar during extraction.

The steam boiler is maintained at 1.45 bar. The PID controller keeps brew water at 93.5 degrees Celsius with a tolerance of 0.4 degrees.

The vibratory pump is rated for 52 watts continuous duty.

2. MAINTENANCE SCHEDULE

Descaling must be performed every 60 days when water hardness exceeds 120 ppm. The group head gasket (part MG-311) should be replaced every 14 months. Backflushing with Cafiza detergent is recommended weekly.

Atlas-7 · Error Codes and Diagnostics

3. ERROR CODES

E11: Brew boiler thermistor open circuit. Replace sensor part TS-71.

E23: Steam boiler overpressure. Check the OPV calibration at 12 bar.

E42: Pump cavitation detected. Prime the pump by running 200 ml of water through the hot water wand, then power cycle the unit.

E57: Flow meter reports zero pulses. Clean the inlet mesh filter.

4. WARRANTY

The Atlas-7 carries a 36-month parts warranty. The warranty is void if third-party descaling agents containing citric acid above 8 percent concentration are used. Warranty claims require the serial number, which is engraved under the drip tray on the left rail.