

Tabel Kinerja MPPT — Pengujian 5 Pola Iradiasi (100 Detik Kontinu)

Pola	Iradiasi (W/m²)	Kondisi	Target GMPP (W)	Algoritma	tc (s)	Pavg (W)	ηtrack (%)	ΔP (W)
Pola 1	880 W/m²	Uniform High	122.30	WODE	1.093	122.76	100.38	1.85
Pola 1	880 W/m²	Uniform High	122.30	PNO	0.453	122.56	100.21	2.35
Pola 1	880 W/m²	Uniform High	122.30	WOA	2.007	122.05	99.80	2.31
Pola 1	880 W/m²	Uniform High	122.30	DE	0.000	123.02	100.59	1.55
Pola 2	660 W/m²	Medium Irradiance	92.18	WODE	2.469	91.45	99.21	1.97
Pola 2	660 W/m²	Medium Irradiance	92.18	PNO	0.928	90.41	98.08	3.66
Pola 2	660 W/m²	Medium Irradiance	92.18	WOA	2.364	89.61	97.21	3.46
Pola 2	660 W/m²	Medium Irradiance	92.18	DE	2.621	90.50	98.18	1.43
Pola 3	910 W/m²	Uniform Peak	126.13	WODE	0.988	126.63	100.40	2.04
Pola 3	910 W/m²	Uniform Peak	126.13	PNO	0.763	125.65	99.62	3.57
Pola 3	910 W/m²	Uniform Peak	126.13	WOA	2.261	125.74	99.69	2.69
Pola 3	910 W/m²	Uniform Peak	126.13	DE	0.000	126.96	100.66	1.63
Pola 4	460 W/m² (PSC)	Partial Shading	64.28	WODE	4.772	62.95	97.92	1.48
Pola 4	460 W/m² (PSC)	Partial Shading	64.28	PNO	4.389	47.86	74.46	17.06
Pola 4	460 W/m² (PSC)	Partial Shading	64.28	WOA	6.376	59.59	92.70	15.27
Pola 4	460 W/m² (PSC)	Partial Shading	64.28	DE	4.390	59.97	93.30	1.33
Pola 5	1000 W/m² (STC)	Full Irradiance (STC)	138.49	WODE	2.429	137.88	99.56	1.62
Pola 5	1000 W/m² (STC)	Full Irradiance (STC)	138.49	PNO	1.199	135.61	97.92	2.19
Pola 5	1000 W/m² (STC)	Full Irradiance (STC)	138.49	WOA	6.784	137.06	98.97	2.33
Pola 5	1000 W/m² (STC)	Full Irradiance (STC)	138.49	DE	4.005	136.74	98.74	1.52
Rata-rata	—	—	—	WODE	2.350	108.33	99.49	1.79
Rata-rata	—	—	—	PNO	1.546	104.42	94.06	5.77
Rata-rata	—	—	—	WOA	3.958	106.81	97.67	5.21
Rata-rata	—	—	—	DE	2.203	107.44	98.29	1.49