

# Homework 4 Solutions

February 22, 2013

## 1 TL13

a)


```
PROGRAM
  VAR ident AS INT SC
  VAR ident AS BOOL SC
BEGIN
  ident ASGN ident OP2 num OP3 boollit SC
  IF LP num OP4 num RP THEN
    WHILE num DO
      WRITEINT num SC
    END SC
  ELSE
    ident ASGN READINT SC
  END SC
  IF num THEN END SC
END
```

b)


```
program
  var A as int ;
  var B as bool ;
begin
  A := A * 0 + false ;
  if ( 0 = 0 ) then
    while 0 do
      writeInt 0 ;
    end ;
  else
    A := readInt ;
  end ;
  if 0 then end ;
end
```

c)






Add states and transitions for Kleene operator.



Concatenate NFA for 11 onto end:



b)

Initialization:

$$s_0 \leftarrow \varepsilon\text{-closure}(18) = \{18, 16, 0, 4, 8, 19, 12\}$$

Round 1:

$$s_1 \leftarrow \varepsilon\text{-closure}(\delta(s_0, 0)) = \{1, 9, 2, 10\}$$

$$s_2 \leftarrow \varepsilon\text{-closure}(\delta(s_0, 1)) = \{5, 13, 6, 14\}$$

Round 2:

$$s_3 \leftarrow \varepsilon\text{-closure}(\delta(s_1, 0)) = \{11, 17, 16, 0, 4, 8, 19, 12\}$$

$$s_4 \leftarrow \varepsilon\text{-closure}(\delta(s_1, 1)) = \{3, 17, 16, 0, 4, 8, 19, 12\}$$

$s_5 \leftarrow \varepsilon\text{-closure}(\delta(s_2, 0)) = \{7, 17, 16, 0, 4, 8, 19, 12\}$

$s_6 \leftarrow \varepsilon\text{-closure}(\delta(s_2, 1)) = \{15\}$

Round 3:

$\varepsilon\text{-closure}(\delta(s_3, 0)) = s_1$

$\varepsilon\text{-closure}(\delta(s_3, 1)) = s_2$

$\varepsilon\text{-closure}(\delta(s_4, 0)) = s_1$

$\varepsilon\text{-closure}(\delta(s_4, 1)) = s_2$


$\varepsilon\text{-closure}(\delta(s_5, 0)) = s_1$

$\varepsilon\text{-closure}(\delta(s_5, 1)) = s_2$

$\varepsilon\text{-closure}(\delta(s_6, 0)) = \emptyset$

$\varepsilon\text{-closure}(\delta(s_6, 1)) = \emptyset$

Worklist is now empty. The resulting DFA:



## 4 Direct Coded Scanner

```

fun ParseNum =
  if s.peak in [1..9]
    concatenate(s.next, ParseNum')
  else if s.next == 0
    ParseNum'',

```

```

fun ParseNum' =
  if s.peak in [0..9]
    concatenate(s.next, ParseNum')
  else if s.peak == empty
    empty
  else
    Error

```

```

fun ParseNum'' =

```

```
if s.peek == empty
    0
else
    Error
```

## 5 Make Grammar Unambiguous

$\langle \text{ALT} \rangle ::= \langle \text{ALT} \rangle \text{“} | \text{”} \langle \text{CON} \rangle \mid \langle \text{CON} \rangle$

$\langle \text{CON} \rangle ::= \langle \text{CON} \rangle \langle \text{CLO} \rangle \mid \langle \text{CLO} \rangle$

$\langle \text{CLO} \rangle ::= \langle \text{CLO} \rangle^* \mid \langle \text{PAR} \rangle$

$\langle \text{PAR} \rangle ::= (\langle \text{ALT} \rangle) \mid \langle \text{TERMSYM} \rangle$

$\langle \text{TERMSYM} \rangle ::= a \mid b \mid c \mid d \mid e \mid f \mid g \mid h \mid i \mid j$