How much of each description of a case is explained by its condition

Description	Cases	R^2 condition	R^2 given setting	R^2 labels shuffled	1-NN chance 0.05	1-NN labels shuffled	Silhouette	Pairs differing Holm, of 190	Closest pair R^2	Family P, two taxonomies
Text										
Narrative, words	600	**0.13**	0.11	0.032	**0.95**	0.04	0.04	190	HGG–IS 0.047	0.093 / 0.357
Narrative, meaning	600	**0.27**	0.23	0.035	**0.71**	0.05	−0.03	190	HGG–MS 0.054	0.080 / 0.323
Narrative, style	600	**0.15**	0.13	0.032	**0.59**	0.05	0.03	190	AE–BM 0.048	0.007 / 0.389
Tool reports, words	600	**0.32**	0.28	0.031	**0.99**	0.06	0.15	190	MA–SE 0.103	0.018 / 0.629
Tool reports, meaning	600	**0.45**	0.37	0.032	**0.95**	0.03	0.10	190	AE–SE 0.118	0.048 / 0.003
Work-up										
Required tools	600	**0.74**	0.60	0.024	**0.83**	0.04	0.39	189	AD–FTD 0.016	<0.001 / 0.034
Required studies	600	**0.60**	0.52	0.033	**0.98**	0.06	0.42	190	HE–MA 0.139	0.335 / 0.909
Required + recommended	600	**0.55**	0.47	0.032	**0.99**	0.04	0.34	190	HE–MA 0.153	0.199 / 0.948
Actions to avoid	600	**0.75**	0.64	0.032	**0.96**	0.04	0.53	190	HGG–TLE 0.260	0.157 / 0.462
Order, tool pairs	462	**0.76**	0.68	0.036	**0.84**	0.04	0.49	167	FND–VaD 0.037	0.027 / 0.861
Order, study pairs	465	**0.61**	0.54	0.039	**0.93**	0.04	0.55	171	HGG–SE 0.050	0.516 / 0.994
Order, full sequence	600	**0.85**	0.65	0.032	**0.82**	0.06	0.40	189	AD–FTD 0.037	0.002 / 0.053

600 cases, 20 conditions × 30. Each row is one distance between cases (Methods). R^2: PERMANOVA, 9999 permutations, $P < 0.001$ in every row, also within difficulty strata; given setting: partial R^2 after the encounter type (emergency, inpatient, outpatient). Labels shuffled: the same statistic with condition labels permuted (expected R^2 19/599 = 0.032). 1-NN: share of cases whose nearest other case has the same condition. Pairs differing: pairwise PERMANOVA between the 190 pairs of conditions, Holm-corrected. Family: within- versus across-family distance between conditions, permuting whole conditions, for the a-priori families of Methods and the groups of Fig. 2b. Order rows use the cases with at least one order constraint.