Calculation Sheet

PROVAL co.,Ltd

Calculation header

Identifier		*New calculation (1)*

Medium selection and state

State		*Vaporous*	
◉ Molar mass	M	*0.0*	g/mol

Operating data

☐ Safety-related application

	Maximum flow	Mean flow	Minimum flow	
t1	*0.0*	*0.0*	*0.0*	°C
p1	*0.3*	*0.0*	*0.0*	MPa(g)
◉ Δp	☒ *0.0*	☒ *0.0*	☒ *0.0*	MPa

Fluid operating data

	Maximum flow	Mean flow	Minimum flow	
ϱ1	☒ *0.0*	☒ *0.0*	☒ *0.0*	kg/m³
◉ η1	☒ *0.0*	☒ *0.0*	☒ *0.0*	mPa s
cF1	*0.0*	*0.0*	*0.0*	m/s
ϰ	*0.0*	*0.0*	*0.0*	-

Pipe downstream of valve

Size class downstream of valve	NPS2	*1/2"*
Schedule downstream	SCH2	*STD*

Valve configuration

Valve type	*Straight globe valve*
Trim type	*Contoured plug*
Flow direction	*FTC*
Valve performance class	*Multi stage valve*
Protection	*Non-hardened*
Low-noise design	*n.a.*

PROVAL co.,Ltd

Calculation Sheet

Valve data

Basic characteristic		*Equal percentage*	
☐ Lift stopper			
Selected valve size	NPS	*1/2"*	
Pressure class	class	*class 900*	
Maximum operating pressure	p,max	*157.0*	bar(a)
Valve modifier (Cv/Cv100 = 0.75)	FL^2	*0.791*	-
Valve modifier (Cv/Cv100 = 0.75)	xT	*0.734*	-
Valve style modifier (Cv/Cv100 = 1)	Fd	*0.41*	-

Load-dependent values

Noise calculation

Calculation standard (noise, gas)	*IEC 60534-8-3 (2010)*

Noise prediction data

Low-noise design	*n.a.*

Legend

☒ Errors