



Calculation Sheet

Calculation header

Identifier

New calculation (1)

Medium selection and state

State

Vaporous

M

X

0.0

g/mol

Operating data

Safety-related application

	Maximum flow	Mean flow	Minimum flow	
t1	0.0	0.0	0.0	°C
p1	X 0.0	X 0.0	X 0.0	bar(a)
Δp	X 0.0	X 0.0	X 0.0	bar
qv	X 0.0	X 0.0	X 0.0	m³/h

Fluid operating data

Pipe downstream of valve

Size class downstream of valve

NPS2

2"

Schedule downstream

SCH2

STD

Valve configuration

Valve type

Straight globe valve

Trim type

Contoured plug

Flow direction

FTC

Valve performance class

Multi stage valve

Protection

Non-hardened

Low-noise design

n.a.

Valve data

Basic characteristic

Linear

Lift stopper

Selected valve size

NPS

2"

Pressure class

class

class 600





Calculation Sheet

Maximum operating pressure	p,max	105.0	bar(a)
Valve modifier (Cv/Cv100 = 0.75)	FL ²	0.917	-
Valve modifier (Cv/Cv100 = 0.75)	xT	0.85	-
Valve style modifier (Cv/Cv100 = 1)	Fd	0.41	-

Load-dependent values

Noise calculation

Calculation standard (noise, gas) IEC 60534-8-3 (2010)

Noise prediction data

Low-noise design n.a.

Legend

 Errors

