



Calculation Sheet

Calculation header

Identifier *New calculation (1)*

Medium selection and state

State *Vaporous*
☒ Molar mass M *0.0* kg/kmol

Operating data

☐ Safety-related application

	Maximum flow	Mean flow	Minimum flow	
t1	<i>0.0</i>	<i>0.0</i>	<i>0.0</i>	°C
p1	☒ <i>0.0</i>	☒ <i>0.0</i>	☒ <i>0.0</i>	bar(a)
☒ Δp	☒ <i>0.0</i>	☒ <i>0.0</i>	☒ <i>0.0</i>	bar

Fluid operating data

	Maximum flow	Mean flow	Minimum flow	
ρ1	☒ <i>0.0</i>	☒ <i>0.0</i>	☒ <i>0.0</i>	kg/m³
☒ η1	☒ <i>0.0</i>	☒ <i>0.0</i>	☒ <i>0.0</i>	mPa s
κ	<i>0.0</i>	<i>0.0</i>	<i>0.0</i>	-

Pipe downstream of valve

Size class downstream of valve NPS2 *2"*
Schedule downstream SCH2 *STD*

Valve configuration

Valve type *Straight globe valve*
Trim type *Contoured plug*
Flow direction *FTC*
Valve performance class *Multi stage valve*
Protection *Non-hardened*
Low-noise design *n.a.*





Calculation Sheet

Valve data

Basic characteristic		Linear	
☐ Lift stopper			
Selected valve size	NPS	2"	
Pressure class	class	class 600	
Maximum operating pressure	p,max	105.0	bar(a)
Valve modifier (Cv/Cv100 = 0.75)	FL ²	0.917	-
Valve modifier (Cv/Cv100 = 0.75)	xT	0.85	-
Valve style modifier (Cv/Cv100 = 1)	Fd	0.41	-

Load-dependent values

Noise calculation

Calculation standard (noise, gas)	IEC 60534-8-3 (2010)
-----------------------------------	----------------------

Noise prediction data

Low-noise design	n.a.
------------------	------

Legend

 Errors

