



Calculation Sheet

Calculation header

Identifier New calculation (1)

Medium selection and state

State Vaporous
☒ Molar mass M ✖ 0.0 g/mol

Operating data

☐ Safety-related application

	Maximum flow	Mean flow	Minimum flow	
t1	0.0	0.0	0.0	°C
p1	0.0	0.0	0.0	MPa(g)
☒ Δp	✖ 0.0	✖ 0.0	✖ 0.0	MPa

Fluid operating data

Pipe downstream of valve

Size class downstream of valve NPS2 2"
Schedule downstream SCH2 STD

Valve configuration

Valve type Straight globe valve
Trim type Contoured plug
Flow direction FTC
Valve performance class Multi stage valve
Protection Non-hardened
Low-noise design n.a.

Valve data

Basic characteristic Linear
☐ Lift stopper
Selected valve size NPS 2"
Pressure class class class 600
Maximum operating pressure p,max 105.0 bar(a)





Calculation Sheet

Valve modifier (Cv/Cv100 = 0.75)	FL ²	0.917	-
Valve modifier (Cv/Cv100 = 0.75)	xT	0.85	-
Valve style modifier (Cv/Cv100 = 1)	Fd	0.41	-

Load-dependent values

Noise calculation

Calculation standard (noise, gas) IEC 60534-8-3 (2010)

Noise prediction data

Low-noise design n.a.

Legend

✖ Errors

