



Calculation Sheet

Calculation header

Identifier

*New calculation (1)***Medium selection and state**

State

Vaporous☒ Molar mass

M

0.0

kg/kmol

Operating data☐ Safety-related application**Maximum flow****Mean flow****Minimum flow**t1 *0.0**0.0**0.0*

°C

p1 *0.0**0.0**0.0*

MPa(g)

☒ Δp ☒ *0.0*☒ *0.0*☒ *0.0*

MPa

Fluid operating data**Maximum flow****Mean flow****Minimum flow**ρ1 ☒ *0.0*☒ *0.0*☒ *0.0*kg/m³☒ ν1 *0.0**0.0*mm²/sκ *0.0**0.0**0.0*

-

Pipe downstream of valve

Size class downstream of valve

NPS2

2"

Schedule downstream

SCH2

*STD***Valve configuration**

Valve type

Rotary plug valve

Trim type

Eccentric plug valve

Flow direction

FTC

Valve performance class

Multi stage valve

Protection

Non-hardened

Low-noise design

n.a.



Calculation Sheet

Valve data

Basic characteristic		Linear	
☐ Lift stopper			
Selected valve size	NPS	2"	
Pressure class	class	class 600	
Maximum operating pressure	p,max	105.0	bar(a)
Valve modifier (Cv/Cv100 = 0.75)	FL ²	0.906	-
Valve modifier (Cv/Cv100 = 0.75)	xT	0.841	-
Valve style modifier (Cv/Cv100 = 1)	Fd	0.44	-

Load-dependent values

Noise calculation

Calculation standard (noise, gas)	IEC 60534-8-3 (2010)
-----------------------------------	----------------------

Noise prediction data

Low-noise design	n.a.
------------------	------

Legend

 Errors

