



Calculation Sheet

Calculation header

Identifier

*New calculation (1)***Medium selection and state**

State

Vaporous☒ Molar massM ☒*0.0*

g/mol

Operating data☐ Safety-related application**Maximum flow****Mean flow****Minimum flow**t1 *0.0**0.0**0.0*

°C

p1 *0.0**0.0**0.0*

MPa(g)

☒ Δp ☒ *0.0*☒ *0.0*☒ *0.0*

MPa

Fluid operating data**Pipe downstream of valve**

Size class downstream of valve

NPS2

2"

Schedule downstream

SCH2

*STD***Valve configuration**

Valve type

Rotary plug valve

Trim type

Eccentric plug valve

Flow direction

FTC

Valve performance class

Multi stage valve

Protection

Non-hardened

Low-noise design

*n.a.***Valve data**

Basic characteristic

Linear☐ Lift stopper

Selected valve size

NPS

2"

Pressure class

class

class 600

Maximum operating pressure

p,max

105.0

bar(a)





Calculation Sheet

Valve modifier (Cv/Cv100 = 0.75)	FL ²	0.906	-
Valve modifier (Cv/Cv100 = 0.75)	xT	0.841	-
Valve style modifier (Cv/Cv100 = 1)	Fd	0.44	-

Load-dependent values

Noise calculation

Calculation standard (noise, gas) IEC 60534-8-3 (2010)

Noise prediction data

Low-noise design n.a.

Legend

✖ Errors

