



Calculation Sheet

Calculation header

Identifier

*New calculation (1)***Medium selection and state**

Medium

251127-01 Test 03

State

Vaporous☒ Molar mass

M

0.0

kg/kmol

Operating data☐ Safety-related application

	Maximum flow	Mean flow	Minimum flow	
t1	<i>40.0</i>	<i>40.0</i>	<i>40.0</i>	°C
p1	<i>30.0</i>	<i>20.0</i>	<i>1,000.0</i>	mmH2O(a)
☒ p2	<i>1.0</i>	<i>1.0</i>	<i>100.0</i>	mmH2O(a)
☐ Δp	<i>29.0</i>	<i>19.0</i>	<i>900.0</i>	mmH2O
☒ qm	<i>132.0</i>	<i>51.0</i>	<i>188.0</i>	kg/h
	<i>Choked flow!</i>	<i>Choked flow!</i>	<i>Choked flow!</i>	

Fluid operating data

	Maximum flow	Mean flow	Minimum flow	
ρ1	☒ <i>0.0</i>	☒ <i>0.0</i>	☒ <i>0.0</i>	kg/m ³
☒ η1	☒ <i>0.0</i>	☒ <i>0.0</i>	☒ <i>0.0</i>	mPa s
κ	<i>0.0</i>	<i>0.0</i>	<i>0.0</i>	-

Pipe downstream of valve

Size class downstream of valve

NPS2

2"

Schedule downstream

SCH2

*STD***Valve configuration**

Valve type

Straight globe valve

Trim type

Contoured plug

Flow direction

FTC

Valve performance class

Multi stage valve

Protection

Non-hardened

Calculation Sheet

Valve configuration (continued)

Low-noise design *n.a.*

Valve data

Basic characteristic *Linear*

☐ Lift stopper

Selected valve size NPS *2"*

Pressure class class *class 600*

Maximum operating pressure p,max *105.0* bar(a)

Valve modifier (Cv/Cv100 = 0.75) FL² *0.917* -

Valve modifier (Cv/Cv100 = 0.75) xT *0.85* -

Valve style modifier (Cv/Cv100 = 1) Fd *0.41* -

Load-dependent values**Noise calculation**

Calculation standard (noise, gas) *IEC 60534-8-3 (2010)*

Noise prediction data

Low-noise design *n.a.*

Legend

 Errors

