



Calculation Sheet

Calculation header

Identifier New calculation (1)

Medium selection and state

State Vaporous  
☒ Molar mass M ✖ 0.0 g/mol

Operating data

☐ Safety-related application

|                                     | Maximum flow                    | Mean flow                       | Minimum flow                    |        |
|-------------------------------------|---------------------------------|---------------------------------|---------------------------------|--------|
| t1                                  | <span>0.0</span>                | <span>0.0</span>                | <span>0.0</span>                | °C     |
| p1                                  | <span>0.0</span>                | <span>0.0</span>                | <span>0.0</span>                | MPa(g) |
| <input checked="" type="radio"/> Δp | <span>✖</span> <span>0.0</span> | <span>✖</span> <span>0.0</span> | <span>✖</span> <span>0.0</span> | MPa    |

Fluid operating data

Pipe downstream of valve

Size class downstream of valve NPS2 2"  
Schedule downstream SCH2 STD

Valve configuration

Valve type Rotary plug valve  
Trim type Eccentric plug valve  
Flow direction FTC  
Valve performance class Multi stage valve  
Protection Non-hardened  
Low-noise design n.a.

Valve data

Basic characteristic Linear  
☐ Lift stopper  
Selected valve size NPS 2"  
Pressure class class class 600  
Maximum operating pressure p,max 105.0 bar(a)





Calculation Sheet

|                                     |                 |       |   |
|-------------------------------------|-----------------|-------|---|
| Valve modifier (Cv/Cv100 = 0.75)    | FL <sup>2</sup> | 0.906 | - |
| Valve modifier (Cv/Cv100 = 0.75)    | xT              | 0.841 | - |
| Valve style modifier (Cv/Cv100 = 1) | Fd              | 0.44  | - |

**Load-dependent values**

**Noise calculation**

Calculation standard (noise, gas) *IEC 60534-8-3 (2010)*

**Noise prediction data**

Low-noise design *n.a.*

**Legend**

 Errors

