



Calculation Sheet

Calculation header

Identifier

*New calculation (1)***Medium selection and state**

Medium

Air

State

Gaseous

Gas

Gas, dry (Standard conditions)

Standard conditions

0°C, 1013.25 mbar☒ Molar mass

M

0.0

g/mol

Operating data☐ Safety-related application

	Maximum flow	Mean flow	Minimum flow	
t1	<i>0.0</i>	<i>0.0</i>	<i>0.0</i>	°C
p1	<i>0.0</i>	<i>0.0</i>	<i>0.0</i>	MPa(g)
☒ Δp	<i>0.0</i>	<i>0.0</i>	<i>0.0</i>	MPa

Fluid operating data

	Maximum flow	Mean flow	Minimum flow	
☒ v1	<i>0.0</i>		<i>0.0</i>	mm²/s
pv1	<i>37.85</i>	<i>37.85</i>	<i>37.85</i>	bar(a)
tv1	<i>-192.88</i>	<i>-192.88</i>	<i>-192.88</i>	°C
cF1	<i>0.0</i>	<i>0.0</i>	<i>0.0</i>	m/s
κ	<i>0.0</i>	<i>0.0</i>	<i>0.0</i>	-
Z1	<i>0.99894</i>	<i>0.99894</i>	<i>0.99894</i>	-

Pipe downstream of valve

Size class downstream of valve

NPS2

2"

Schedule downstream

SCH2

*STD***Valve configuration**

Valve type

Straight globe valve

Trim type

Contoured plug

Flow direction

FTC



Calculation Sheet

Valve configuration (continued)

Valve performance class

Multi stage valve

Protection

Non-hardened

Low-noise design

*n.a.***Valve data**

Basic characteristic

Linear☐ Lift stopper

Selected valve size

NPS

2"

Pressure class

class

class 600

Maximum operating pressure

p,max

105.0

bar(a)

Valve modifier (Cv/Cv100 = 0.75)

FL²*0.917*

-

Valve modifier (Cv/Cv100 = 0.75)

xT

0.85

-

Valve style modifier (Cv/Cv100 = 1)

Fd

0.41

-

Load-dependent values**Noise calculation**

Calculation standard (noise, gas)

*IEC 60534-8-3 (2010)***Noise prediction data**

Low-noise design

*n.a.***Legend**

Errors

